

Report for

City of Hamilton

CSO Facilities O&M Plan –
MECP Order Item 6

January 31, 2019



City of Hamilton
 CSO Facilities O&M Plan -
 MECP Order Item 6

Contact:
 Mark Stirrup - Principal Project Manager, Associate

Address:
 2265 Upper Middle Rd, Fifth Floor
 Oakville, Ontario, Canada L6H 0G5
 Tel: +1 (905) 486 0742
 www.hatch.com

January 31, 2019

| | | | | |
|--------------|-------------|---------------|----------------------------------|-----------------------------------|
| 01/31/19 | 1 | Final | Mark Stirrup, M.Eng., P.Eng. | Graeme Henderson, P.Eng., PMP |
| Date | Rev. | Status | Prepared By | Checked and Approved By |
| HATCH | | | | |

Table of Contents

| | |
|---|-----------|
| 1. Introduction and Background | 1 |
| 2. Discussion..... | 1 |
| 2.1 Greenhill CSO Tank #1 (HCS01)..... | 4 |
| 2.2 Bayfront Park CSO Tank (HCS02)..... | 6 |
| 2.3 James Street CSO Facility (HCS03 and HCG08) | 9 |
| 2.4 Main/King CSO Tank (HCS04) | 12 |
| 2.5 Eastwood Park CSO Tank (HCS05, HCG06 and HCG07)..... | 16 |
| 2.6 Greenhill CSO Tank #2 (HCS06)..... | 19 |
| 2.7 Red Hill Valley CSO Pipe Facility (HCS07)..... | 22 |
| 2.8 Royal Avenue CSO Tank (HCS08)..... | 25 |
| 2.9 McMaster CSO Tank (HCS09) | 28 |
| 2.10 Wentworth/Rosemary CSO Gate (HCG03)..... | 31 |
| 2.11 Brampton/Strathearne CSO Gate (HCG04)..... | 34 |
| 2.12 Wellington/Burlington CSO Gate (HCG14) | 36 |
| 2.13 Parkdale Burlington Wastewater Collection Station (HC001)..... | 39 |
| 3. References..... | 41 |
| Appendix A – Updated Standard Operating Procedures for CSO Facilities | |
| Appendix B – Updated Process Control Narrative for Main/King CSO Tank (HCS04) | |

1. Introduction and Background

On August 2, 2018, the Ministry of Environment, Conservation and Parks (MECP) issued Provincial Officer's Order #1-J25YB (hereinafter referred to as the Order) to the City in relation to the discharge of untreated wastewater to the environment.

The Facilities Assessment Report dated November 31, 2018 prepared by Hatch provided in response to MECP Order Items 4, 7, 8 and 9 (Hatch CSO Facilities Assessment Report, 2018) discussed the findings of the Combined Sewer Overflow (CSO) facility inspections and evaluation of the need for modifications to improve the monitoring, performance and reliability of each facility to minimize the potential for unapproved bypasses/overflows/spills from the facilities (Order Items 4, 7 and 8); and provided recommendations as required by Order Item 9.

Item 4 required the City to inspect all CSO facilities and inventory all critical valves (bypass gates) and control points (overflows) which can be a source of discharge to the natural environment and which would not be captured by existing flow monitoring equipment, including confirmation of manual and SCADA valve position correlation and local or remote control.

Item 7 required the City to evaluate the need for modification(s) to the Main/King CSO Facility, to improve monitoring, performance, reliability and to minimize bypasses/overflows/spills into the 2400 mm storm outfall from the (CSO tank) overflow trough and inlet chamber bypass.

Item 8 required the City to evaluate the need for modification(s) similar to those required by Item 7 above for all other CSO facilities within the Hamilton Wastewater Collection System to minimize bypasses/overflows/spills.

Item 9 required the City to prepare a written report which sets out the evaluation required by the Items 7 and 8 above, along with recommendations and timelines to implement these recommendations.

This current report addresses the requirements of Order Item 6, which requires the City to: using the information obtained from Item 4, and if applicable, Item 5 (updated CSO map), review and update drawings, Process Control Narratives (PCNs) and develop a written Operation and Maintenance Plan (O&M Plan) for each of the City's CSO facilities that identifies critical equipment and environmental discharge points, and shall include, but not be limited to: annual manual valve position checks of critical valves; monthly visual inspections of overflow structures at the CSO facilities equipped with station by-pass structures that discharge directly to the natural environment; and annual flow meter calibration.

The Hatch CSO Facilities Assessment Report (2018) already addressed the first requirement of Item 6, identifying critical equipment and potential environmental discharge points, and providing a number of recommendations to minimize the potential for such discharges in the future, including improved monitoring, control and inspection of the City's CSO facilities.

This report builds upon the information presented in the Hatch CSO Facilities Assessment Report (2018), providing a written O&M Plan for each of the City's CSO facilities and addressing whether updates are required to drawings and PCNs.

2. Discussion

The basis of the City's O&M Plan for each of the CSO facilities is their Standard Operating Procedure (SOP). The SOPs detail procedures for the safe and efficient operation of each facility, including the responsibilities of all levels of City staff involved in the operations and maintenance of the City's wastewater system, and in particular the CSO facilities; relevant safety notes and

procedures; procedures for the confined space entry into the underground CSO tanks and valve/gate chambers for the purposes of routine maintenance and inspection; an overview of the O&M process and equipment at each site; and specific procedures to be followed by City staff to safely operate and maintain each facility under all flow conditions, including annual and monthly inspection requirements.

The remaining components of the O&M Plan for each CSO facility include:

- The Process Control Narrative (PCN) for the facility, which describes how the facility is monitored and controlled by the City's Supervisory Control and Data Acquisition (SCADA) system
- Equipment Operation and Maintenance Manuals, which are typically provided by the Consultants and/or Contractors responsible for the construction and/or subsequent upgrades of each facility
- As-Built Drawings of each facility
- Additional formal procedures developed and employed by the City to operate and maintain the CSO facilities, including procedures for Confined Space Entry, Equipment Lock Out/Tagging, CSO Overflow Notification, and CSO Facility Inspection

This report summarizes the O&M Plan for each of the City's CSO facilities, including a brief description of the facility and any Critical Control Points (CCPs); an inventory of the key components of the plan, including the SOP, PCN, Equipment O&M Manuals, and As-Built Drawings; and appendices including the current updated SOPs and PCNs.

Copies of the updated SOPs can be found in Appendix A, and a copy of the updated PCN for the Main/King CSO Tank (HCS04) can be found in Appendix B. Copies of the remaining unchanged PCNs, equipment O&M manuals and as-built drawings are not provided here due their volume, but can be made available to the MECF.

The remainder of this report is broken down facility by facility, including a separate section for each of the City's existing CSO facilities, including the following locations:

- 1) Greenhill CSO Tank #1 (HCS01)
- 2) Bayfront Park CSO Tank (HCS02)
- 3) James Street CSO Tank (HCS03), including Ferrie-Mary CSO Regulator Gate (HCG03)
- 4) Main/King CSO Tank (HCS04)
- 5) Eastwood Park CSO Tank (HCS05), including Burlington-Ferguson and Ferrie-Ferguson CSO Regulator Gates (HCG06 and HCG07)
- 6) Greenhill CSO Tank #2 (HCS06)
- 7) Red Hill Storage Facility (HCS07), including Lawrence Road, Queenston Road and Barton Street Gates (HCS7A, HCS7B and HCS7C) and Lawrence/King CSO Gate (HCG05)
- 8) Royal Avenue CSO Tank (HCS08)
- 9) McMaster/Ewen CSO Tank (HCS09)
- 10) Wentworth/Rosemary CSO Gate (HCG03)
- 11) Brampton/Strathearne CSO Gate (HCG04)
- 12) Wellington/Burlington CSO Gate (HCG14)
- 13) Parkdale Burlington Wastewater Collection Station (HC001)

Additional details on each of the CSO facilities can be found in the Hatch CSO Facilities Assessment Report (2018), including a brief narrative description of each facility and its purpose; drawings/figures showing the location of the CCPs at each facility, and also indicating the potential for possible unapproved sewage discharges to the environment, colour coded to indicate criticality; and tables providing an inventory of all the CCPs at each facility, including their name; SCADA tag name (where applicable); size/capacity; whether they are manually operated or motorized; their purpose in terms of flow control; their default position (as per the facility's PCN and/or SOP); their potential for discharge to the environment under different flow conditions; and recommendations for improving the monitoring, performance, reliability of operation and minimizing the potential for unapproved bypasses/overflows/ spills into adjacent receiving waters.

The following sections of this current report provide a brief narrative description of each of the above CSO facilities and their purpose, and provide a summary of the key components of the O&M Plan for each facility, including a table providing an inventory of the key components of the plan, including the SOP, PCN, Equipment O&M Manuals, and As-Built Drawings; and appendices including the current updated SOPs and PCNs.

As noted above, additional details on each CSO facility can be found in the respective section of the Hatch CSO Facilities Assessment Report (2018). For the sake of brevity, the drawings/figures and tables presented in the Hatch CSO Facilities Assessment Report (2018) are not reproduced here in this report, but are referenced where applicable below.

2.1 Greenhill CSO Tank #1 (HCS01)

The original Greenhill CSO Tank (HCS01) is an underground reinforced concrete structure that provides approximately 83,500 m³ of CSO storage capacity, and was designed to capture the runoff from a 15 mm design storm. The storage volume is provided within a circular tank, which is approximately 54 m in diameter and 9 m deep, and includes two separate storage cells. The first cell provides approximately 13,900 m³ of storage, and if the first cell fills, the second cell provides approximately 69,600 m³ of additional storage.

Originally, HCS01 received sewage inflows directly from the combined trunk sewer running east along Greenhill Avenue, but with the addition of Greenhill CSO Tank #2 (HCS06), the original CSO tank now receives the overflows from the new CSO Tank #2 (HSC06). The combined operation of the two CSO tanks is discussed in more detail below in Section 2.6.

HCS01 is filled by gravity from the overflow from HCS06, and drained by motorized flow control gates over the discharges from the two storage cells, into the Red Hill Creek Sanitary Interceptor Sewer (RHCSI), which conveys flows to the Woodward Avenue Wastewater Treatment Plant (WWTP). The gates can be operated in either full Manual, SCADA Manual, or SCADA Auto modes. The default mode is SCADA Manual, with operation directed by Operators at the WWTP. A water spray nozzle system is provided to clean the floor of Cell 2.

Level transmitters are provided to monitor the level of sewage stored in each storage cell, and in the CSO tank outlet channel; and a flowmeter is provided to measure the rate and volume of any CSOs exiting the facility.

The facility is monitored and controlled via SCADA by Operators at the WWTP. The SCADA system includes a security system to advise of any unauthorized entries into the pumping station.

Figures 1A and 1B of the Hatch CSO Facilities Assessment Report (2018) showed the location of the CCPs at this facility, as well as potential for possible sewage discharges to the environment from each CCP, colour coded to indicate criticality; and Table 1 of the same report provided an inventory of all the CCPs at this facility, including the details described above; their potential for discharge to the environment under different flow conditions; and recommendations for improving the monitoring, performance, reliability of operation and minimizing the potential for unapproved bypasses/overflows/spills into adjacent receiving waters.

Table 1 provided below summarizes the key components of the O&M Plan for HCS01, including current versions of the SOP, PCN, Equipment O&M Manuals, and As-Built Drawings.

The SOP has been updated as part of this report (Issue #5, Jan 2019) to make the following changes: to clarify the description of the facilities; to provide consistency of format with all the other CSO facility SOPs, and to add a section on procedures for regular Inspection and Maintenance of the facility addressing the requirements of Order Item 6. No recent changes have been made, or are required, to the operation of the facility via SCADA, and therefore no changes have been made to the current version of the PCN (Version 2.4, Apr 2016). Similarly, no significant upgrades have been completed recently at this station, so there has also been no need to update the existing Equipment O&M Manuals and As-Built Drawings. These would be updated in the future, if and when any upgrades are completed. For example, the Hatch CSO Facilities Assessment Report (2018) recommended conducting an engineering study to determine the feasibility of adding redundant gate position sensors on the Cell 1 and 2 Drain Gates themselves, to back up the existing sensors on the gate stems; and the City has plans to investigate and possibly upgrade the performance of the existing tank cleaning system.

Table 1: Summary of O&M Plan for Greenhill CSO Tank #1 (HCS01)

| O&M Plan Component | Name of Document | Prepared By | Version # | Issue Date |
|------------------------------------|--|--|----------------|------------|
| Standard Operating Procedure (SOP) | Detailed Sewer System Operation – Greenhill CSO Tank #1 (HCS01) | Hamilton Water Hatch Ltd. | Issue #5 | Jan 2019 |
| Equipment O&M Manual | Operation and Maintenance Manual – Contract RHW-86-10 (S) – HCS01 | UMA Engineering Ltd. | N/A | 1986 |
| Equipment O&M Manual | Operation and Maintenance Manual for Odour Control System – HCS01 | McCullough Gibson Construction Ltd | N/A | Nov 1997 |
| Process Control Narrative (PCN) | Process Control Narrative – Greenhill Sewage Overflow Facility (HCS01) | Eramosa Engineering Inc. Westin Engineering Inc. XCG Consultants Ltd. R.E. Poisson Engineering Inc. | Version 2.4 | Apr 2016 |
| As-Built Drawings | Greenhill Avenue Storage Facility – Contract No. RHW-86-01 | UMA Engineering Ltd. | Dwg No. 807-13 | Dec 1985 |

2.2 Bayfront Park CSO Tank (HCS02)

The Bayfront Park CSO Tank (HCS02) covers an area of approximately 3,200 m², and is over 6 m deep, providing approximately 21,000 m³ of CSO storage capacity in two equally sized storage cells. A 4.0 m x 1.5 m box sewer (which later changes to 2,250 mm diameter) intercepts CSOs from the former Queen and Hess Street CSO outfalls and conveys them to the CSO tank. Flow into the tank is regulated by static CSO regulators at Queen/Barton, Stuart/Hess, and Stuart/Caroline, and by the Strachan Street Sewage Pumping Station (HC003). A flow regulating chamber is also provided upstream of the tank (near the CSO tank outfall), which includes three gates that can be operated to convey all flows into the CSO tank (in their default positions) or to provide a maintenance bypass of the tank (in their alternate positions). The operation of the gates is explained in more detail in the Hatch CSO Facilities Assessment Report (2018), and in the updated SOP found in Appendix A. The two Maintenance Bypass Gates are locked in the Fully Closed position to ensure all incoming sewage flows are conveyed into the CSO storage tank and eliminate the possibility of any dry weather sewage discharges to Hamilton Harbour at this location.

During Dry Weather Flow (DWF) conditions, all flow is directed to the WWTP via the CSO regulators and the three (3) dry pit pumps in the pumping station (3 x 180 L/s).

During Wet Weather Flow (WWF) conditions, excess flows from the three static CSO regulators overflow into the CSO tank. Cell 1 will fill first, and if it fills completely, will overflow into Cell 2. If Cell 2 also fills, CSOs are discharged to Hamilton Harbour via the outfall sewer that exits the north-west corner of the tank. Stainless steel underflow baffles are employed above the tank overflow in Cell 2 to retain floatable materials within the tank. If the tank fills completely, CSOs are conveyed via a 5,000 mm x 2,000 mm box sewer to the outfall that enters the Harbour at the east end of the inlet between the park and the railway lands.

Combined sewage retained in the tank during wet weather is subsequently returned to the Western Sanitary Interceptor (WSI) and conveyed to the WWTP for treatment during dry weather, when the plant can deal with the additional flow. The tank is drained by two (2) 200 L/s submersible pumps located in Cell 1. A flap gate between Cell 1 and Cell 2 allows the two cells to be emptied at the same time. The pumps discharge into a forcemain that connects to the WSI near Strachan and MacNab Streets. The rate of pumping from the tank can be controlled by Operators at the WWTP, based upon the current inflows at the WWTP. The pumps can be operated in either full Manual, SCADA Manual, or SCADA Auto modes. The default mode is SCADA Manual, with operation directed by Operators at the WWTP. Ten (10) sediment flushing tanks (SFTs) are provided to clean the floor of the two tank cells (5 SFTs in each cell).

Level transmitters are provided to monitor the level of sewage stored in each storage cell; a flowmeter is provided to measure the rate and volume of any CSOs exiting the facility; and two (2) automatic samplers are provided to collect grab and composite samples of both the influent and effluent (overflow) water quality.

The entire facility is monitored and controlled via SCADA by Operators at the WWTP. The SCADA system includes a security system to advise of any unauthorized entries into the pumping station. Stand-by power is provided for the sewage pumping station by a diesel power generator.

Figures 2A to 2C of the Hatch CSO Facilities Assessment Report (2018) showed the location of the CCPs at this facility, as well as potential for possible sewage discharges to the environment from each CCP, colour coded to indicate criticality; and Table 2 of the same report provided an inventory of all the CCPs at this facility, including the details described above; their potential for discharge to the environment under different flow conditions; and recommendations for improving the monitoring, performance, reliability of operation and minimizing the potential for unapproved bypasses/overflows/spills into adjacent receiving waters.

Table 2 provided below summarizes the key components of the O&M Plan for HCS02, including current versions of the SOP, PCN, Equipment O&M Manuals, and As-Built Drawings.

The SOP has been updated as part of this report (Issue #3, January 2019) to make the following changes: to clarify the description of the facilities; to provide consistency of format with all the other CSO facility SOPs; to note that the two Maintenance Bypass Gates have been locked in the Fully Closed position in December 2018; and to add a section on procedures for regular Inspection and Maintenance of the facility addressing the requirements of Order Item 6. No recent changes have been made, or are required, to the operation of the facility via SCADA, and therefore no changes have been made to the current version of the PCN (Version 1.3, April 2016). Similarly, no significant upgrades have been completed recently at this station, so there has also been no need to update the existing Equipment O&M Manuals and As-Built Drawings. These would be updated in the future, if and when any upgrades are completed.

Table 2: Summary of O&M Plan for Bayfront Park CSO Tank (HCS02)

| O&M Plan Component | Name of Document | Prepared By | Reference # | Issue Date |
|------------------------------------|--|--|-----------------|------------|
| Standard Operating Procedure (SOP) | Detailed Sewer System Operation – Bayfront CSO Tank (HCS02) | Hamilton Water Hatch Ltd. | Issue #3 | Jan 2019 |
| Process Control Narrative (PCN) | Process Control Narrative – CSO Facility HCS02 / Wastewater PS HC003 | Hamilton Water Eramosa Engineering Inc. Westin Engineering Inc. XCG Consultants Ltd. R.E. Poisson Engineering Inc. | Version 1.3 | Apr 2016 |
| Equipment O&M Manual | Operation and Maintenance Manual – Strachan Storage Tank – HCS02 | Matthews Contracting Inc. (General Contractor) Priestep Electric Limited (Electrical Contractor) | N/A | Mar 1993 |
| As-Built Drawings | Strachan Street (Bayfront Park) Storage Tank | Regional Municipality of Hamilton-Wentworth | Dwg No. 92-S-14 | Feb 1992 |

2.3 James Street CSO Facility (HCS03 and HCG08)

The James Street CSO Storage Facility (HCS03) incorporates both off-line and in-line storage components, which provide a total CSO storage capacity of approximately 3,200 m³.

The off-line storage tank is an underground, reinforced concrete structure, which resides beneath the parking lot of the Royal Hamilton Yacht Club, located at the north end of James Street. The rectangular tank covers an area of approximately 900 m², and is 0.8 to 2.1 m deep, providing approximately 1,400 m³ of CSO storage capacity.

The off-line storage capacity is augmented by 1,800 m³ of in-line storage, which is provided within the 1,400 mm diameter combined sewer downstream of the CSO tank. The additional in-line storage is created by the Ferrie-Mary CSO Regulator Gates (HCG08). The HCG08 sluice gates control the rate of flow from the James Street combined sewer system into the WSI at Ferrie and Mary Streets. These gates can be operated in either full Manual, SCADA Manual, or SCADA Auto modes. The default mode is SCADA Manual, with operation directed by Operators at the WWTP.

During DWF conditions, the gates are set to allow all flow to enter the WSI. During WWF conditions, the gates can be partially or completely closed to throttle the flow of combined sewage into the WSI, and begin filling the storage facilities. The rate of filling is determined by the position of the gates. The in-line storage pipe will fill first, and as levels in this pipe increase, the off-line storage tank will also begin to fill. If the tank fills completely, CSOs are discharged to Hamilton Harbour via the pre-existing 1,200 mm x 900 mm CSO outfall at the north end of the tank. Stainless steel underflow baffles are employed above the tank overflow to retain floatable materials within the tank.

Combined sewage retained in the tank during wet weather is subsequently returned to the WSI and conveyed to the WWTP for treatment during dry weather, when the plant can deal with the additional flow. The tank is drained by gravity as the in-line storage pipe empties. The rate of drainage from the in-line storage pipe and the off-line storage tank is determined by the position of the HCG08 gates, which can be controlled by Operators at the WWTP, based upon the current inflows at the WWTP. A water spray nozzle system is provided to clean the floor of the tank.

Level transmitters are provided to monitor the level of sewage stored in the off-line storage tank, and in the CSO tank overflow channel; and a flowmeter is provided to measure the rate and volume of any CSOs exiting the facility.

The facilities are monitored and controlled via SCADA by Operators at the WWTP.

Figures 3A to 3D of the Hatch CSO Facilities Assessment Report (2018) showed the location of the CCPs at this facility, as well as potential for possible sewage discharges to the environment from each CCP, colour coded to indicate criticality; and Table 3 of the same report provided an inventory of all the CCPs at this facility, including the details described above; their potential for discharge to the environment under different flow conditions; and recommendations for improving the monitoring, performance, reliability of operation and minimizing the potential for unapproved bypasses/overflows/spills into adjacent receiving waters.

Table 3 provided below summarizes the key components of the O&M Plan for HCS03, including current versions of the SOP, PCN, Equipment O&M Manuals, and As-Built Drawings.

The SOP has been updated as part of this report (Issue #4, January 2019) to make the following changes: to clarify the description of the facilities; to provide consistency of format with all the other CSO facility SOPs, and to add a section on procedures for regular Inspection and Maintenance of the facility addressing the requirements of Order Item 6. No recent changes have been made, or are required, to the operation of the facility via SCADA, and therefore no changes have been made to the current version of the PCN (Version 2.5, April 2016). Similarly, no significant upgrades have been completed recently at this station, so there has also been no need to update the existing Equipment O&M Manuals and As-Built Drawings. These would be updated in the future, if and when any upgrades are completed. For example, the Hatch CSO Facilities Assessment Report (2018) recommended conducting an engineering study to determine the feasibility of adding redundant gate position sensors on the HCG08 sluice gates themselves, to back up the existing sensors on the gate stems.

Table 3: Summary of O&M Plan for James Street CSO Facility (HCS03/HCG08)

| O&M Plan Component | Name of Document | Prepared By | Reference # | Issue Date |
|------------------------------------|---|--|-----------------|------------|
| Standard Operating Procedure (SOP) | Detailed Sewer System Operation – James Street CSO Tank (HCS03), Ferrie/Mary Sluice Gates (HCG08) | Hamilton Water Hatch Ltd. | Issue #4 | Jan 2019 |
| Process Control Narrative (PCN) | Process Control Narrative – James Street CSO Facility HCS03, Ferrie/Mary Sluice Gates (HCG08) | Hamilton Water Eramosa Engineering Inc. Westin Engineering Inc. XCG Consultants Ltd. R.E. Poisson Engineering Inc. | Version 2.5 | Apr 2016 |
| As-Built Drawings | James Street North Storage Tank – Contract RHW 92-78 (ST) | Regional Municipality of Hamilton-Wentworth | Dwg No. 92-S-45 | Sep 1992 |

2.4 Main/King CSO Tank (HCS04)

The Main/King CSO Tank (HCS04) covers an area of approximately 9,500 m², and is over 8 m deep, providing approximately 77,100 m³ of CSO storage capacity in two separate storage cells. The first cell provides approximately 23,300 m³ of storage, and the second provides a further 53,800 m³ of storage. The Main/King CSO Tank operates off-line, with combined sewage entering the tank during larger CSO events. Flow into the tank is regulated by three WWTP-controlled CSO regulators that were constructed in conjunction with the CSO tank. The Glen Road CSO Outfall, which is located at the east end of Glen Road on the west side of Hwy 403, was effectively eliminated by installing a new WWTP-controlled CSO regulator gate at Glen/Macklin (Chamber 1) and constructing a new 1,350 mm diameter sewer to convey CSOs underneath Hwy 403 and into the CSO tank. The former McKittrick CSO Outfall, which previously diverted CSOs from the 1,980 mm diameter combined sewer that conveys flows to the WSI, was eliminated by constructing a new WWTP-controlled CSO regulator (Chamber 4) to divert CSOs into the new tank. Flow from the 2,100 mm x 2,250 mm box sewer which runs along the south side of Main Street was diverted into the new tank by a bulkhead placed in the sewer and a new WWTP-controlled CSO regulator located at the south-east corner of the tank (Chamber 5). Downstream of the bulkhead, this sewer is used to convey the overflows which will still occur from the tank when its design capacity is exceeded.

During DWF conditions, flow is directed to the WWTP via the WSI. The gate in Chamber 4 (King Street Sewer) is set to be Fully Open; the gate in Chamber 5 (Interceptor Sewer) is set to 30% Open; and the gate in Chamber 1 (Glen Road Sewer) is always set at 35%. The Main Street Overflow Sewer, which maintains a base flow during dry weather due mainly to infiltration, is directed to the CSO tank's wet well and pumped into the interceptor sewer. The gate in Chamber 4 is currently without power or communications, and it is currently manually set to convey wet weather flow mainly to the CSO tank.

During WWF conditions, the pumps are taken out of auto mode and turned off; the opening of Gate 4 is reduced to 7%; and the opening of Gate 5 is reduced to 2%. Excess flow from the three regulators enters the pumping station wet well, which is located beneath the control building at the south-east corner of the facility. During dry weather and small storm events, the CSO tank's pumping station acts as a normal sewage pumping station. During larger storm events, two motorized sluice gates are opened to permit flow from the wet-well to enter the CSO tank. Cell 1 will fill first, and if it fills completely, will overflow into Cell 2. If Cell 2 also fills, CSOs are discharged into Chedoke Creek near the Main Street overpass, via the original 2,100 mm x 2,250 mm box sewer outfall. Stainless steel underflow baffles are employed above the tank overflow in Cell 2 to retain floatable materials within the tank.

The CSO tank's wet well includes an Influent Well Overflow Gate (CSO Maintenance Bypass Gate) that can be operated to convey all flows into the CSO tank and pumping station (when Closed) or to provide a maintenance bypass of the tank (when Open). Prior to November 2018, the PCN for HCS04 incorrectly indicated that during DWF conditions this gate should be 5% open, and during WWF conditions this gate should be 100% open. The default settings for the gate should actually be Fully Closed during both DWF and WWF conditions and the PCN was updated in November 2018 to reflect this.

Combined sewage retained in the tank during wet weather is subsequently returned to the Combined Sewer System (CSS) and conveyed by the WSI to the WWTP for treatment during dry weather, when the plant can deal with the additional flow. The tank is drained by three (3) 375 L/s submersible pumps located in the pumping station wet well. A flap gate between Cell 1 and Cell 2 allows the cells to be emptied at the same time. The pumps discharge into a forcemain that connects to the original 1,980 mm sewer, which in turn discharges into the WSI near Hunt Street. The rate of pumping from the tank can be controlled by Operators at the WWTP, based upon the current inflows at the WWTP. Thirty (30) sediment flushing tanks (SFTs) are provided to clean the floor of the two tank cells (10 in Cell 1 and 20 in Cell 2).

Level transmitters are provided to monitor the level of sewage stored in each storage cell; a flowmeter is provided to measure the rate and volume of any CSOs exiting the facility; and two (2) automatic samplers are provided to collect grab and composite samples of both the influent and effluent (overflow) water quality.

The facilities are all monitored and controlled via SCADA by Operators at the WWTP. The motorized gates and pumps can be operated in either full Manual, SCADA Manual, or SCADA Auto modes. The default mode is SCADA Manual, with operation directed by Operators at the WWTP. The SCADA system includes a security system to advise of any unauthorized entries into the control building.

Figures 4A to 4C of the Hatch CSO Facilities Assessment Report (2018) showed the location of the CCPs at this facility, as well as potential for possible sewage discharges to the environment from each CCP, colour coded to indicate criticality; and Table 4 of the same report provided an inventory of all the CCPs at this facility, including the details described above; their potential for discharge to the environment under different flow conditions; and recommendations for improving the monitoring, performance, reliability of operation and minimizing the potential for unapproved bypasses/overflows/spills into adjacent receiving waters.

Table 4 provided below summarizes the key components of the O&M Plan for HCS04, including current versions of the SOP, PCN, Equipment O&M Manuals, and As-Built Drawings.

The SOP has been updated as part of this report (Issue #4, January 2019) to reflect recent changes to the operation of HCS04. These included padlocking the Influent Well Overflow Gate (CSO Maintenance Bypass Gate) in the Fully Closed position, and removing access to this gate for control purposes from the SCADA system; and setting the position of the Chamber 1 sluice gate at Glen Road to 35% Open for all flow conditions. These changes are described further in the updated SOP. Other updates to SOP included clarifying the description of the facilities; to provide consistency of format with all the other CSO facility SOPs, and adding a section on procedures for regular Inspection and Maintenance of the facility addressing the requirements of Order Item 6.

The previous version of the PCN has been recently updated (Version 3.5, November 2018) to reflect the operational gate changes described above and incorporated in the updated SOP, and a copy of the updated SOP is included in Appendix B.

No significant upgrades have been completed recently at this station, so there has also been no need to update the existing Equipment O&M Manuals and As-Built Drawings. These would be updated in the future, if and when any upgrades are completed. For example, the Hatch CSO Facilities Assessment Report (2018) recommended conducting an engineering study to determine the feasibility of adding redundant gate position sensors on all the sluice gates associated with the facility, on the gates themselves, to back up the existing sensors on the gate stems; and to consider simplifying the operation of the sluice gates in Chamber 4 and 5. The City is evaluating options to investigate the feasibility of moving the existing flowmeter and automatic sampler on the CSO tank overflow, to a location downstream of the above-mentioned Influent Well Overflow Gate (CSO Maintenance Bypass Gate), to also capture any possible future flows through this gate; to relocate the CSO tank influent sampler to a better location not prone to high flows damaging the unit; and to investigate and upgrade portions of the existing tank cleaning system.

Table 4: Summary of O&M Plan for Main/King CSO Tank (HCS04)

| O&M Plan Component | Name of Document | Prepared By | Reference # | Issue Date |
|------------------------------------|---|--|-------------------------------|------------|
| Standard Operating Procedure (SOP) | Detailed Sewer System Operation – Main/King CSO Tank (HCS04) | Hamilton Water Hatch Ltd. | Issue #4 | Jan 2019 |
| Process Control Narrative (PCN) | Process Control Narrative – Wastewater PS / Main/King CSO Tank HCS04 | Hamilton Water Eramosa Engineering Inc. Westin Engineering Inc. XCG Consultants Ltd. R.E. Poisson Engineering Inc. | Version 3.5 | Nov 2018 |
| Equipment O&M Manual | Electrical O&M Manual – Contract RHW-94-75 (COIW) - HCS04 | Selectra Inc. (Electrical Contractor) Kenaidan Contracting Ltd (General Contractor) R.V. Anderson Associates (Consultant) | Shelf D-3, Doc No. 0000301 | 1998 |
| Equipment O&M Manual | Installation, Operating & Maintenance Manuals – Contract RHW-94-75 (COIW) – HCS04 | Bennett Mechanical Installations (Mech Contractor) Kenaidan Contracting Ltd (General Contractor) R.V. Anderson Associates (Consultant) | Shelf D-3, Doc No. 0000302 | 1998 |
| Equipment O&M Manual | Operations/Maintenance Manuals – Contract RHW-94-75 (COIW) – HCS04 | Kenaidan Contracting Ltd (General Contractor) R.V. Anderson Associates (Consultant) | Shelf D-3, Doc No. 0000520 | 1998 |
| Equipment O&M Manual | Electrical/I&C Instruction Manual J936 | Bristol Babcock (I&C Contractor) Kenaidan Contracting Ltd (General Contractor) R.V. Anderson Associates (Consultant) | Shelf D-3, Doc No. 0000521 | 1998 |
| As-Built Drawings | Main/King CSO Tank – Contract RHW-94-75 (COIW) – HCS04 | R.V. Anderson Associates Limited | Dwg No. 95-S-32 | 1998 |

2.5 Eastwood Park CSO Tank (HCS05, HCG06 and HCG07)

The Eastwood Park CSO Tank (HCS05) covers an area of approximately 4,000 m², and is over 6 m deep, providing approximately 27,350 m³ of CSO storage capacity in two separate storage cells. The first cell provides approximately 14,700 m³ of storage, and the second provides a further 12,650 m³ of storage. A sewer along Dock Service Road intercepts the CSOs from the two outfalls and conveys them to the CSO tank. The original Catharine Street (1,050 mm) and Ferguson Avenue (1,500 mm) CSO outfalls were left in place and are used to carry the overflow from the CSO tank on the infrequent occasions when the design capacity of the tank is exceeded. A flow splitter diverts the overflow from the tank between the two previously existing outfall sewers.

The Eastwood Park CSO Tank operates off-line, with combined sewage entering the tank only during larger CSO events. Flow into the tank is regulated by static CSO regulators at Catharine/Brock, Picton/Ferguson and MacAulay/Ferguson and by the two WWTP-controlled CSO regulators at Burlington/Ferguson and Ferrie/Ferguson.

During DWF conditions, the Burlington/Ferguson (HCG06) and Ferguson/Ferrie Streets (HCG07) sluice gates normally remain open, directing all flow to the WSI sewer and on to the WWTP.

During WWF conditions, excess flows from the Catharine/Brock CSO regulator and the two CSO regulators along Ferguson Avenue overflow into the tank. When rainfall occurs, the station is placed into Storm Mode and the pumps in the CSO tank are Off, and the HCG06 and HCG07 gates are fully closed, eliminating flow into the WSI at these locations. Cell 1 will fill first, and if it fills completely, will overflow into Cell 2. If Cell 2 also fills, CSOs are discharged to Hamilton Harbour through the Catharine Street and Ferguson Avenue CSO outfalls. Stainless steel underflow baffles are employed above the tank overflow in Cell 2 to retain floatable materials within the tank.

The CSO tank inlet chamber at the north-east corner of the tank includes three gates that can be operated to convey all flows into the CSO tank (in their default positions, with the CSO tank inlet gate open and the two CSO tank maintenance gates closed) or to provide a maintenance bypass of the tank (in their alternate positions). The operation of the gates is explained in more detail in the Hatch CSO Facilities Assessment Report (2018), and in the updated SOP found in Appendix A. The two Maintenance Bypass Gates are locked in the Fully Closed position to ensure all incoming sewage flows are conveyed into the CSO storage tank and eliminate the possibility of any dry weather sewage discharges to Hamilton Harbour at this location.

Combined sewage retained in the tank during wet weather is subsequently returned to the WSI and conveyed to the WWTP for treatment during dry weather, when the plant can deal with the additional flow. The tank is drained by two (2) 289 L/sec submersible pumps located in Cell 1. One pump is used as a duty pump and the other as a stand-by pump. A flap gate between Cell 1 and Cell 2 allows the cells to be emptied at the same time. The pumps discharge into a forcemain that connects to the 900 mm portion of the WSI downstream of HCG06. The rate of pumping from the tank can be controlled by Operators at the WWTP, based upon the current inflows at the WWTP. Fifteen (15) sediment flushing tanks (SFTs) are provided to clean the floor of the two tank cells (8 in Cell 1 and 7 in Cell 2).

Level transmitters are provided to monitor the level of sewage stored in each storage cell; a flowmeter is provided to measure the rate and volume of any CSOs exiting the facility; and two (2) automatic samplers are provided to collect grab and composite samples of both the influent and effluent (overflow) water quality.

The facilities are monitored and controlled via SCADA by Operators at the WWTP. The motorized gates and pumps can be operated in either full Manual, SCADA Manual, or SCADA Auto modes. The default mode is SCADA Manual, with operation directed by Operators at the WWTP. The SCADA system includes a security system to advise of unauthorized entries to the control building.

Figures 5A to 5D of the Hatch CSO Facilities Assessment Report (2018) showed the location of the CCPs at this facility, as well as potential for possible sewage discharges to the environment from each CCP, colour coded to indicate criticality; and Table 5 of the same report provided an inventory of all the CCPs at this facility, including the details described above; their potential for discharge to the environment under different flow conditions; and recommendations for improving the monitoring, performance, reliability of operation and minimizing the potential for unapproved bypasses/overflows/spills into adjacent receiving waters.

Table 5 provided below summarizes the key components of the O&M Plan for HCS05, including current versions of the SOP, PCN, Equipment O&M Manuals, and As-Built Drawings.

The SOP has been updated as part of this report (Issue #5, January 2019) to make the following changes: to clarify the description of the facilities; to provide consistency of format with all the other CSO facility SOPs; to note that the two Maintenance Bypass Gates have been locked in the Fully Closed position in December 2018; and to add a section on procedures for regular Inspection and Maintenance of the facility addressing the requirements of Order Item 6. No recent changes have been made, or are required, to the operation of the facility via SCADA, and therefore no changes have been made to the current version of the PCN (Version 2.2, April 2016). Similarly, no significant upgrades have been completed recently at this station, so there has also been no need to update the existing Equipment O&M Manuals and As-Built Drawings of the tank. These would be updated in the future, if and when any upgrades are completed. For example, the Hatch CSO Facilities Assessment Report (2018) recommended conducting an engineering study to determine the feasibility of adding redundant gate position sensors on the CSO Tank Inlet Gate and the HCG06 (Burlington/Ferguson) and HCG07 (Ferrie/Ferguson) sluice gates, on the gates themselves, to back up the existing sensors on the gate stems.

Table 5: Summary of O&M Plan for Eastwood Park CSO Tank (HCS05), Burlington/Ferguson Sluice Gate (HCG06) and Ferrie/Ferguson Sluice Gate (HCG07)

| O&M Plan Component | Name of Document | Prepared By | Reference # | Issue Date |
|------------------------------------|---|--|-------------------------------|------------|
| Standard Operating Procedure (SOP) | Detailed Sewer System Operation – Eastwood Park CSO Tank (HCS05), Burlington/Ferguson Sluice Gate (HCG06) and Ferrie/Ferguson Sluice Gate (HCG07) | Hamilton Water Hatch Ltd. | Issue #5 | Jan 2019 |
| Process Control Narrative (PCN) | Process Control Narrative – Eastwood Park CSO Facility HCS05 | Hamilton Water Eramosa Engineering Inc. Westin Engineering Inc. XCG Consultants Ltd. R.E. Poisson Engineering Inc. | Version 2.2 | Apr 2016 |
| Equipment O&M Manual | Electrical Maintenance Manuals – Contract RHW-96-03 (S) – HCS05 | Metric (Electrical Contractor) Granville (General Contractor) Thorburn Penny (Consultant) | Shelf D-3, Doc No. 0000303 | 1998 |
| Equipment O&M Manual | Operation and Maintenance Manuals – Contract RHW-96-03 (S) – HCS05 | Granville (General Contractor) Thorburn Penny Consulting Limited (Consultant) | Shelf D-3, Doc No. 0000307 | 1998 |
| Equipment O&M Manual | Operations Manual – Contract C13-09-12 – HCG06 and HCG07 | Stantec (Consultant) Newman Bros. Ltd (General Contractor) | Shelf D-5, Doc No. 0000639 | Sep 2012 |
| As-Built Drawings | Eastwood Park CSO Facility – Contract RHW-96-03 (S) – HCS05 | Thorburn Penny Consulting Limited | Dwg No. 96-S-29 | Oct 1995 |

2.6 Greenhill CSO Tank #2 (HCS06)

The second Greenhill CSO Tank (HCS06) is an underground reinforced concrete structure that was installed to augment the storage provided by the original Greenhill CSO Tank (HCS01). The rectangular tank covers an area of approximately 8,400 m², and is 7.5 to 8.3 m deep, providing approximately 66,750 m³ of CSO storage capacity in two equally sized storage cells. The new facility increased the combined CSO storage volume at the Greenhill site to approximately 150,250 m³.

HCS06 operates as an off-line facility, with combined sewage entering the tank only during larger CSO events. Flow into the storage tank is regulated by a WWTP-controlled CSO regulator located upstream of the tank. Cell 1 will fill first, and if it fills completely, excess flows overflow into Cell 2. If Cell 2 also fills, overflows will be conveyed into HCS01. Stainless steel underflow baffles are employed above the tank overflow in Cell 2 to retain floatable materials within the new tank and prevent them from entering HCS01.

HCS06 is drained by gravity into the RHCSI via a 1,200 mm diameter sewer. The rate of drainage is regulated by a WWTP-controlled gate, based upon the current inflows at the WWTP.

The facility includes a bypass chamber between HCS06 and HCS01 that can be used to isolate HCS01 for maintenance purposes. To operate this bypass, the manual stop gate in the chamber has to be physically removed from its default position and inserted in the alternate position across the overflow channel from HCS06 to HCS01 (thereby diverting flow to Red Hill Creek). Only one stop log is provided, making it impossible to block the flow of both sewers at the same time. Twenty (20) sediment flushing tanks (SFTs) are provided to clean the floor of the two tank cells (10 in each cell).

Level transmitters are provided to monitor the level of sewage stored in each storage cell; and a flowmeter is provided (at HCS01) to measure the rate and volume of any CSOs exiting the facility.

The facility is monitored and controlled via SCADA by Operators at the WWTP. The motorized gates can be operated in either full Manual, SCADA Manual, or SCADA Auto modes. The default mode is SCADA Manual, with operation directed by Operators at the WWTP. The SCADA system includes a security system to advise of any unauthorized entries into the control building.

HCS06 is also equipped with a biofilter odour control system to reduce the presence of unpleasant odours associated with the tank (possible when the tank is filling with sewage and air is being displaced from the tank).

Figures 6A to 6E of the Hatch CSO Facilities Assessment Report (2018) showed the location of the CCPs at this facility, as well as potential for possible sewage discharges to the environment from each CCP, colour coded to indicate criticality; and Table 6 of the same report provided an inventory of all the CCPs at this facility, including the details described above; their potential for discharge to the environment under different flow conditions; and recommendations for improving the monitoring, performance, reliability of operation and minimizing the potential for unapproved bypasses/overflows/spills into adjacent receiving waters.

Table 6 provided below summarizes the key components of the O&M Plan for HCS06, including current versions of the SOP, PCN, Equipment O&M Manuals, and As-Built Drawings.

The SOP has been updated as part of this report (Issue #3, January 2019) to make the following changes: to clarify the description of the facilities; to provide consistency of format with all the other CSO facility SOPs, and to add a section on procedures for regular Inspection and Maintenance of the facility addressing the requirements of Order Item 6. No recent changes have been made, or are required, to the operation of the facility via SCADA, and therefore no changes have been made to the current version of the PCN (Version 2.4, April 2016). Similarly, no significant upgrades have been completed recently at this station, so there has also been no need to update the existing Equipment O&M Manuals and As-Built Drawings. These would be updated in the future, if and when any upgrades are completed. For example, the Hatch CSO Facilities Assessment Report (2018) recommended conducting an engineering study to determine the feasibility of adding redundant gate position sensors on the Dry Flow Control Gate and CSO Drain Gate, on the gates themselves, to back up the existing sensors on the gate stems.

Table 6: Summary of O&M Plan for Greenhill CSO Tank #2 (HCS06)

| O&M Plan Component | Name of Document | Prepared By | Reference # | Issue Date |
|------------------------------------|--|--|-------------------------------|------------|
| Standard Operating Procedure (SOP) | Detailed Sewer System Operation – Greenhill CSO Tank #2 (HCS06) | Hamilton Water Hatch Ltd. | Issue #3 | Jan 2019 |
| Process Control Narrative (PCN) | Process Control Narrative – Greenhill #2 CSO Tank HCS06 | Hamilton Water Eramosa Engineering Inc. Westin Engineering Inc. XCG Consultants Ltd. R.E. Poisson Engineering Inc. | Version 2.4 | Apr 2016 |
| Equipment O&M Manual | Operating and Maintenance Manuals – Contract TOE-02-05 (CSO) – HCS06 | Bennett Contracting Millgrove Ltd General Contractor) | Shelf D-3, Doc No. 0000299 | N/A |
| As-Built Drawings | Greenhill CSO Tank #2 – Contract TOE-02-05 (CSO) – HCS06 | City of Hamilton | Dwg No. 01-S-23 | Jan 2002 |

2.7 Red Hill Valley CSO Pipe Facility (HCS07)

The Red Hill Valley CSO Pipe Facility (HCS07) captures and stores CSOs from the former Lawrence, Queenston and Melvin CSO outfalls to Red Hill Creek. The facility stores the CSO in an oversized pipe running parallel to the existing RHCSI and along the Red Hill Parkway. The oversized storage pipe ranges in size from 2,000 to 2,250 mm in diameter, and a series of four (4) motorized sluice gates are used to convey flows into and create temporary storage within the pipe during WWF conditions, and also to control the subsequent drainage of the facility to the WWTP for treatment during DWF conditions.

HCS07 comprises three (3) flow control structures: HCS7A at Lawrence Road; HCS7B at Queenston Road; and HCS7C at Barton Street; creating two (2) storage pipe cells providing a total storage volume of approximately 14,200 m³. Cell 1 consists of a 2,250 mm diameter pipe running between HCS7A and HCS7B; and Cell 2 consists of a 2,000 mm diameter pipe running between HCS7B and HCS7C. HCS7C includes an 1,800 mm diameter sanitary sewer to drain the storage facility, and a 2,250 mm diameter overflow sewer to Red Hill Creek that only becomes active if the design capacity of the facility is exceeded. The stored flow behind the gates can also be used to flush any sediments that may have settled at the bottom of the storage pipe cells during storage periods.

Level transmitters are provided to monitor the level of sewage at HCS7A/B/C (also giving the level of sewage stored in Cell 1 and 2); a flowmeter is provided at HCS7C at Barton Street to measure the rate and volume of any CSOs exiting the facility; and an automatic sampler is provided to collect grab and composite samples of effluent (overflow) water quality from the HCS7C overflow.

The facilities are all monitored and controlled via SCADA by Operators at the WWTP. The motorized gates can be operated in either full Manual, SCADA Manual, or SCADA Auto modes. The default mode is SCADA Manual, with operation directed by Operators at the WWTP. The SCADA system includes a security system to advise of any unauthorized entries into the control buildings.

Figures 7A to 7E of the Hatch CSO Facilities Assessment Report (2018) showed the location of the CCPs at this facility, as well as potential for possible sewage discharges to the environment from each CCP, colour coded to indicate criticality; and Table 7 of the same report provided an inventory of all the CCPs at this facility, including the details described above; their potential for discharge to the environment under different flow conditions; and recommendations for improving the monitoring, performance, reliability of operation and minimizing the potential for unapproved bypasses/overflows/spills into adjacent receiving waters.

Table 7 provided below summarizes the key components of the O&M Plan for HCS07, including current versions of the SOP, PCN, Equipment O&M Manuals, and drawings.

The SOP has been updated as part of this report (Issue #2, January 2019) to make the following changes: to clarify the description of the facilities; to provide consistency of format with all the other CSO facility SOPs, and to add a section on procedures for regular Inspection and Maintenance of the facility addressing the requirements of Order Item 6. No recent changes have been made, or are required, to the operation of the facility via SCADA, and therefore no changes have been to the current version of the HCS7A/B/C PCNs (Version 2.3, April 2016). Similarly, no significant upgrades have been completed recently at this station, so there has also been no need to update the existing Equipment O&M Manuals and drawings. These would be updated in the future, if and when any upgrades are completed. For example, the Hatch CSO Facilities Assessment Report (2018) recommended conducting an engineering study to determine the feasibility of adding redundant gate position sensors on all sluice gates associated with this facility, on the gates themselves, to back up the existing sensors on the gate stems.

Table 7: Summary of O&M Plan for Red Hill CSO Pipe Facility (HCS07, HCS7A/B/C)

| O&M Plan Component | Name of Document | Prepared By | Reference # | Issue Date |
|------------------------------------|--|--|-------------------------------|------------|
| Standard Operating Procedure (SOP) | Detailed Sewer System Operation – Red Hill CSO Pipe Facility (HCS07) | Hamilton Water Hatch Ltd. | Issue #2 | Jan 2019 |
| Process Control Narrative (PCN) | Process Control Narrative – Red Hill Valley CSO Pipe Facility HCS7A | Hamilton Water Eramosa Engineering Inc. Westin Engineering Inc. XCG Consultants Ltd. R.E. Poisson Engineering Inc. | Version 2.3 | Apr 2016 |
| Process Control Narrative (PCN) | Process Control Narrative – Red Hill Valley CSO Pipe Facility HCS7B | | Version 2.3 | Apr 2016 |
| Process Control Narrative (PCN) | Process Control Narrative – Red Hill Valley CSO Pipe Facility HCS7C | | Version 2.3 | Apr 2016 |
| Equipment O&M Manual | SCADA Operations Manual – Contract PW-04-239/241 (RHV) – HCS07 | Hatch Mott MacDonald (SCADA Consultant) Dufferin Construction Company (General Contractor) | Shelf D-2, Doc No. 0000570 | Feb 2009 |
| Equipment O&M Manual | Civil & Mechanical O&M Manual – Contract PW-04-239/241 (RHV) – HCS07 | Dufferin Construction Company (General Contractor) | Shelf D-2, Doc No. 0000571 | Feb 2009 |
| Equipment O&M Manual | PLC & WAN Panel O&M Manual – Contract PW-04-239/241 (RHV) – HCS07 | Hatch Mott MacDonald (SCADA Consultant) Dufferin Construction Company (General Contractor) | Shelf D-2, Doc No. 0000572 | Oct 2009 |
| Drawings | Red Hill Valley CSO Pipe Facility – Contract PW-04-239 (RHV) – HCS07 | AWS Engineers & Planners | Dwg No. 04-H-67 | Jul 2003 |

2.8 Royal Avenue CSO Tank (HCS08)

The Royal Avenue CSO Tank (HCS08) is an underground reinforced concrete structure that provides approximately 15,000 m³ of CSO storage capacity. The storage volume is provided within a rectangular tank, which is approximately 41 m long x 37 m wide x 10 m deep.

The site originally included a CSO Regulator chamber that employed a motorized sluice gate to dynamically control the rate of flow conveyed to the Woodward Avenue WWTP. This sluice gate was removed, and control of the flow conveyed to the WWTP and the CSO tank is accomplished passively by a 525 mm diameter drop pipe located in the diversion chamber at the east end of Royal Avenue. During dry weather and small storm events, the 525 mm drop pipe conveys all flow into the downstream 900 mm sanitary sewer and on to the WWTP. During larger storm events, the 525 mm drop pipe will fill to capacity and excess flows will be diverted to the CSO tank after passing through a coarse bar screen included in the CSO Tank Inlet Chamber. Filling of the CSO Tank occurs passively without any actions having to be initiated by the Operators at the WWTP.

CSOs are conveyed to the storage tank by a 2,400 mm x 2,400 mm step sewer. The inlet sewer is designed to operate under surcharge, dependent upon the level of the sewage in the CSO storage tank, which provides some additional storage volume.

The inlet chamber also includes provision to isolate the CSO storage tank in emergencies and during special maintenance activities, and a 2,400 mm wide x 2,000 mm deep box culvert is provided to divert flow to Chedoke Creek for those activities. The chamber includes two sets of guides for alternate placement of a single stop log to control the direction of flow. Under normal operation, the stop log will be inserted in the guides over the upstream end of the emergency bypass sewer, sending all excess WWF into the CSO tank. To operate the bypass, the stop log has to be physically removed from its default position and inserted in the alternate position over the upstream end of the CSO tank inlet sewer. Only one stop log is provided, making it impossible to block the flow of both sewers at the same time. A removable stainless-steel bar screen is provided at the upstream end of the CSO tank inlet sewer to capture debris to protect the sewage pumps in the storage tank.

Inside the storage tank, a stainless-steel baffle is provided along the length of the overflow weir, suspended from the roof of the tank, to retain floatables and oils inside the tank, so they can be subsequently pumped from the tank and conveyed to the Woodward WWTP for treatment. A 5,400 mm wide x 1,800 mm deep box culvert is provided at the northeast corner of the site to convey any overflows from the facility into Chedoke Creek.

Three (3) submersible pumps are provided to pump the contents of the storage tank back into the Combined Sewer System (CSS) in dry weather, for subsequent conveyance to the Woodward WWTP. The contents of the CSO tank will be drained and conveyed to the WWTP only during dry weather, when the capacity is available to treat these flows. Three (3) 250 L/s pumps are provided, but only one pump will run at any given time. The other 2 pumps are provided for redundancy, ensuring an extra pump is available even if one pump is out for maintenance or repairs. The flow from the pumps will be conveyed south via three (3) 400 mm diameter ductile iron forcemains into the relocated 900 mm sanitary sewer running east along the south wall of the tank. The pumps can be operated in either full Manual, SCADA Manual, or SCADA Auto modes. The default mode is SCADA Manual, with operation directed by Operators at the WWTP. Six (6) sediment flushing tanks (SFTs) are provided to clean the floor of the tank following each storm event.

Two (2) level transmitters are provided to monitor the level of sewage stored in the tank; and a flowmeter is provided to measure the rate and volume of any CSOs exiting the facility.

The facility is monitored and controlled via SCADA by Operators at the WWTP. The SCADA system includes a security system to advise of any unauthorized entries into the control building.

Figures 8A to 8C of the Hatch CSO Facilities Assessment Report (2018) showed the location of the CCPs at this facility, as well as potential for possible sewage discharges to the environment from each CCP, colour coded to indicate criticality; and Table 8 of the same report provided an inventory of all the CCPs at this facility, including the details described above; their potential for discharge to the environment under different flow conditions; and recommendations for improving the monitoring, performance, reliability of operation and minimizing the potential for unapproved bypasses/overflows/spills into adjacent receiving waters.

Table 8 provided below summarizes the key components of the O&M Plan for HCS08, including current versions of the SOP, PCN, Equipment O&M Manuals, and As-Built Drawings.

The SOP has been updated as part of this report (Issue #3, January 2019) to make the following changes: to clarify the description of the facilities; to provide consistency of format with all the other CSO facility SOPs, and to add a section on procedures for regular Inspection and Maintenance of the facility addressing the requirements of Order Item 6. No recent changes have been made, or are required, to the operation of the facility via SCADA, and therefore no changes have been made to the current version of the PCN (Version 1.3, April 2016). Similarly, no significant upgrades have been completed recently at this station, so there has also been no need to update the existing Equipment O&M Manuals and As-Built Drawings. These would be updated in the future, if and when any upgrades are completed.

Table 8: Summary of O&M Plan for Royal Avenue CSO Tank (HCS08)

| O&M Plan Component | Name of Document | Prepared By | Reference # | Issue Date |
|------------------------------------|---|--|-------------------------------|------------|
| Standard Operating Procedure (SOP) | Detailed Sewer System Operation – Royal Avenue CSO Tank (HCS08) | Hamilton Water Hatch Ltd. | Issue #3 | Jan 2019 |
| Process Control Narrative (PCN) | Process Control Narrative – Royal Avenue CSO Tank HCS08 | Hamilton Water Eramosa Engineering Inc. Westin Engineering Inc. XCG Consultants Ltd. R.E. Poisson Engineering Inc. | Version 1.3 | Apr 2016 |
| Equipment O&M Manual | SCADA O&M Manual – Contract PW-05-06 (CSO) – HCS08 | Hatch Mott MacDonald (Consultant) Genivar (General Contractor) | Shelf D-3, Doc No. 0000308 | Nov 2007 |
| As-Built Drawings | Royal Avenue CSO Storage Tank – Contract PW-05-06 (CSO) – HCS08 | Hatch Mott MacDonald / J&M Structural | Dwg No. 05-S-13 | Jan 2008 |

2.9 McMaster CSO Tank (HCS09)

The McMaster CSO Tank (HCS09) is an underground reinforced concrete structure that provides approximately 5,935 m³ of CSO storage capacity. The storage volume is provided within a rectangular tank, which is approximately 50 m long x 18 m wide x 6.6 m deep. When the tank is full, some additional CSO storage volume is provided within the upstream CSO tank inlet sewer.

A maintenance bypass is provided at the southwest corner of the storage tank, where the CSO inflow sewer enters the tank, to provide a means to bypass flows around the storage tank, to permit future isolation of the CSO storage tank in emergencies and during special maintenance activities.

Under normal operation, the CSO Tank Inlet Gate is Fully Open (it has been padlocked in this position) and the stop log over the end of the CSO tank overflow sewer is removed (sitting in guides above the end of the CSO tank overflow sewer), to allow all incoming flow to enter the tank, and the Operator does not have to do anything to allow the storage tank to fill. To operate the CSO tank bypass, in order to fully isolate the CSO tank from the CSO outfall pipe, the CSO Tank Inlet Gate must be fully closed and the stop log removed from its default position and inserted in the alternate guides provided over the end of the CSO tank overflow sewer. The CSO Tank Inlet Gate has recently been padlocked in the Fully Open position to ensure all incoming sewage flows are conveyed into the CSO storage tank and eliminate the possibility of any dry weather sewage discharges to Ancaster Creek.

Inside the storage tank, a stainless-steel underflow baffle is provided along the length of the overflow weir, suspended from the roof of the tank, to retain floatables and oils inside the CSO storage tank, so they can be subsequently pumped from the tank and conveyed to the WWTP for treatment. A 2,400 mm wide x 1,000 mm (sloped) overflow trough is provided at the northwest corner of the tank to safely convey any overflows from the facility into the 1,800 mm overflow sewer discharging to Lower Ancaster Creek

Three (3) 137 L/s submersible pumps are provided to pump the contents of the storage tank back into the CSS in dry weather, for subsequent conveyance to the Woodward WWTP. The contents of the CSO tank will be drained and conveyed to the WWTP only during DWF conditions, when capacity is available to treat these flows. Three pumps are provided, but only one pump will run at any given time. The other 2 pumps are provided for redundancy, ensuring an extra pump is available even if one pump is out for maintenance or repairs. The flow from the pumps is lifted via three (3) 200 mm diameter, ductile iron forcemains, which feed a single 350 mm diameter forcemain running around the east and south walls of the storage tank, then south through the City's easement within the Hydro One corridor, and finally east through the City's right-of-way at the west end of Sanders Boulevard, to connect to the gravity operated CSS along Sanders Boulevard. Three (3) sediment flushing tanks (SFTs) are provided to clean the floor of the tank following each storm event.

Two (2) level transmitters are provided to monitor the level of sewage stored in the tank; and a flowmeter is provided to measure the rate and volume of any CSOs exiting the facility.

The facility is monitored and controlled via SCADA by Operators at the WWTP. The motorized CSO tank inlet gate and the pumps can be operated in either full Manual, SCADA Manual, or SCADA Auto modes. The default mode is SCADA Manual, with operation directed by Operators at the WWTP. The SCADA system includes a security system to advise of any unauthorized entries into the control building.

Figures 9A and 9B of the Hatch CSO Facilities Assessment Report (2018) showed the location of the CCPs at this facility, as well as potential for possible sewage discharges to the environment from each CCP, colour coded to indicate criticality; and Table 9 of the same report provided an inventory of all the CCPs at this facility, including the details described above; their potential for discharge to the environment under different flow conditions; and recommendations for improving the monitoring, performance, reliability of operation and minimizing the potential for unapproved bypasses/overflows/spills into adjacent receiving waters.

Table 9 provided below summarizes the key components of the O&M Plan for HCS09, including current versions of the SOP, PCN, Equipment O&M Manuals, and As-Built Drawings.

A new SOP has been created for this facility as part of this report (Issue #1, January 2019) to: provide a description of the facilities; to provide consistency of format with all the other CSO facility SOPs, and include a section on procedures for regular Inspection and Maintenance of the facility addressing the requirements of Order Item 6. No recent changes have been made, or are required, to the operation of the facility via SCADA, and no therefore no changes have been made to the current version of the PCN (Version 1.4, April 2016). Similarly, no significant upgrades have been completed recently at this station, so there has also been no need to update the existing Equipment O&M Manuals and As-Built Drawings. These would be updated in the future, if and when any upgrades are completed.

Table 9: Summary of O&M Plan for McMaster CSO Tank (HCS09)

| O&M Plan Component | Name of Document | Prepared By | Reference # | Issue Date |
|------------------------------------|---|--|-------------------------------|------------|
| Standard Operating Procedure (SOP) | Detailed Sewer System Operation – McMaster CSO Tank (HCS09) | Hamilton Water Hatch Ltd. | Issue #1 | Jan 2019 |
| Process Control Narrative (PCN) | Process Control Narrative – McMaster CSO Tank HCS09 | Hamilton Water Eramosa Engineering Inc. Westin Engineering Inc. XCG Consultants Ltd. R.E. Poisson Engineering Inc. | Version 1.4 | Apr 2016 |
| Equipment O&M Manual | Electrical O&M Manual – Contract PW-08-13 (CSO) – HCS09 | Varcon (General Contractor) Selectra (Electrical Contractor) Hatch Mott MacDonald (Consultant) | Shelf D-3, Doc No. 0000528 | 2010 |
| Equipment O&M Manual | Mechanical O&M Manuals – Contract PW-08-13 (CSO) – HCS09 | Varcon (General Contractor) Hatch Mott MacDonald (Consultant) | Shelf D-3, Doc No. 0000603 | 2010 |
| As-Built Drawings | McMaster CSO Storage Tank – Contract PW-08-13 (CSO) – HCS09 | Hatch Mott MacDonald / J&M Structural | Dwg No. 08-S-38 | Sep 2010 |

2.10 Wentworth/Rosemary CSO Gate (HCG03)

HCG03 regulates the flow of combined sewage from a 266 ha drainage area served by a 1,220 mm x 1,525 mm combined sewer running north along Wentworth Street North. The gate is located in an underground chamber on the northeast corner of Wentworth Street North and Rosemary Avenue, near the entrance to the City's offices at 330 Wentworth Street North.

HCG03 is used to direct DWF and some WWF to the Burlington/Hillyard area where the flows enter the WSI North branch (WSIN) and are conveyed to the Woodward Avenue WWTP for treatment. The regulator also has the ability to isolate flows from the WSIN, where the gate is normally open but can be closed to direct flow to the Wentworth CSO outfall when the WSIN is surcharged.

During DWF conditions and small storms, a static overflow weir captures all flows and conveys them through the open gate in HCG03, into a 1,200 mm x 1,500 mm combined sewer which connects to the WSIN at the intersection of Hillyard Avenue and Burlington Street, and the WSIN conveys the flows east to the Woodward Avenue WWTP for treatment.

During larger storms, when the weir is overtopped, excess WWF is diverted to the Wentworth CSO Outfall via a 2,500 mm x 2,400 mm combined sewer on Wentworth Avenue.

During very large storms, every attempt is made to maximize the conveyance of combined sewage to the WWTP for treatment, however there will be circumstances where the Operator may need to close HCG03 to bypass combined sewage through the Wentworth CSO Outfall to protect the Influent Pump Station and biological treatment processes at the WWTP.

The gate can be operated in either full Manual, SCADA Manual, or SCADA Auto modes. The default mode is SCADA Auto, with operation directed by the Real Time Control (RTC) system, to maximize flow to the WWTP.

The Process Automation Controller (PAC), network equipment and gate actuator are powered by an Uninterruptable Power Supply (UPS). On a power failure, the gate is set to 30% Open.

The facility is monitored and controlled via SCADA by Operators at the WWTP. The SCADA system includes a security system to advise of any unauthorized entries into the control building.

Figure 10A of the Hatch CSO Facilities Assessment Report (2018) showed the location of the gate, as well as the potential for possible sewage discharges to the environment, colour coded to indicate criticality; and Table 10 of the same report provided an inventory of all the CCPs at this facility, including the details described above; their potential for discharge to the environment under different flow conditions; and recommendations for improving the monitoring, performance, reliability of operation and minimizing the potential for unapproved bypasses/overflows/spills into adjacent receiving waters.

Table 10 provided below summarizes the key components of the O&M Plan for HCG03, including current versions of the SOP, PCN, Equipment O&M Manuals, and As-Built Drawings.

The SOP has been updated as part of this report (Issue #4, January 2019) to make the following changes: to clarify the description of the facilities; to provide consistency of format with all the other CSO facility SOPs, and to add a section on procedures for regular Inspection and Maintenance of the facility addressing the requirements of Order Item 6. No recent changes have been made, or are required, to the operation of the facility via SCADA, and therefore no changes have been made to the current version of the PCN (Version 3.3, June 2012). Similarly, no significant upgrades have been completed recently at this station, so there has also been no need to update the existing Equipment O&M Manuals and As-Built Drawings. These would be updated in the future, if and when any upgrades are completed. For example, the Hatch CSO Facilities Assessment Report (2018) recommended conducting an engineering study to determine the feasibility of adding redundant gate position sensors on the gate itself, to back up the existing sensor on the gate stem.

Table 10: Summary of O&M Plan for Wentworth/Rosemary CSO Gate (HCG03)

| O&M Plan Component | Name of Document | Prepared By | Reference # | Issue Date |
|------------------------------------|---|---|-------------------------------|------------|
| Standard Operating Procedure (SOP) | Detailed Sewer System Operation – Wentworth/Rosemary CSO Gate (HCG03) | Hamilton Water Hatch Ltd. | Issue #4 | Jan 2019 |
| Process Control Narrative (PCN) | Process Control Narrative – 330 Wentworth St North Wastewater Regulator HCG03 | Hamilton Water BPR Eramosa Engineering Stantec | Version 3.3 | Jun 2012 |
| Equipment O&M Manual | Operations Manual – Contract C13-09-12 – HCG03 | Stantec (Consultant) Newman Bros. Ltd (General Contractor) | Shelf D-5, Doc No. 0000635 | 2010 |
| As-Built Drawings | Rosemary/Wentworth Regulator Upgrades – Contract C13-09-12 – HCG03 | Stantec | Not Provided | Jan 2013 |

2.11 Brampton/Strathearne CSO Gate (HCG04)

HCG04 regulates the flow of combined sewage from a 210 ha drainage area served by a 2,134 mm x 2,286 mm combined sewer running north along Strathearne Avenue. The gate is located in an underground chamber behind the Arcelor Mittal security guard house located just south of Brampton Street.

During DWF conditions and small storms, a static overflow weir captures all flows and conveys them through the open gate in HCG04, into a 1,050 mm combined sewer on Strathearne Avenue, which connects to the WSI at the intersection of Strathearne Avenue and Burlington Street, and the WSI conveys the flows east to the Woodward Avenue WWTP for treatment.

During larger storms, when the weir is overtopped, excess WWF is diverted to the Strathearne CSO Outfall via a second, 2,100 mm x 2,250 mm combined sewer on Strathearne Avenue.

During very large storms, every attempt is made to maximize the conveyance of combined sewage to the WWTP for treatment, however there will be circumstances where the Operator may need to close HCG04 to bypass combined sewage through the Strathearne CSO Outfall to protect the Influent Pump Station and biological treatment processes at the WWTP.

The gate can be operated in either full Manual, SCADA Manual, or SCADA Auto modes. The default mode is SCADA Manual, with operation directed by Operators at the WWTP, to maximize flow to the WWTP.

The facility is monitored and controlled via SCADA by Operators at the WWTP. The SCADA system includes a security system to advise of any unauthorized entries into the control building.

Figure 11A of the Hatch CSO Facilities Assessment Report (2018) showed the location of the gate, as well as the potential for possible sewage discharges to the environment, colour coded as described in the report to indicate criticality; and Table 11 of the same report provided an inventory of all the CCPs at this facility, including the details described above; their potential for discharge to the environment under different flow conditions; and recommendations for improving the monitoring, performance, reliability of operation and minimizing the potential for unapproved bypasses/overflows/spills into adjacent receiving waters.

Table 11 provided below summarizes the key components of the O&M Plan for HCG04, including current versions of the SOP, PCN, Equipment O&M Manuals, and drawings.

The SOP has been updated as part of this report (Issue #4, January 2019) to make the following changes: to clarify the description of the facilities; to provide consistency of format with all the other CSO facility SOPs, and to add a section on procedures for regular Inspection and Maintenance of the facility addressing the requirements of Order Item 6. No recent changes have been made, or are required, to the operation of the facility via SCADA, and therefore no changes have been made to the current version of the PCN (Version 1.2, April 2016). Similarly, no significant upgrades have been completed recently at this station, so there has also been no need to update the existing Equipment O&M Manuals and drawings. These would be updated in the future, if and when any upgrades are completed. For example, the Hatch CSO Facilities Assessment Report (2018) recommended conducting an engineering study to determine the feasibility of adding redundant gate position sensors on the gate itself, to back up the existing sensor on the gate stem.

Table 11: Summary of O&M Plan for Brampton/Strathearne CSO Gate (HCG04)

| O&M Plan Component | Name of Document | Prepared By | Reference # | Issue Date |
|------------------------------------|---|--|-------------------------------|------------|
| Standard Operating Procedure (SOP) | Detailed Sewer System Operation – Brampton/Strathearne CSO Gate (HCG04) | Hamilton Water Hatch Ltd. | Issue #4 | Jan 2019 |
| Process Control Narrative (PCN) | Process Control Narrative – Brampton/Strathearne Regulator HCG04 | Hamilton Water Eramosa Engineering Inc. Westin Engineering Inc. XCG Consultants Ltd. R.E. Poisson Engineering Inc. | Version 1.2 | Apr 2016 |
| Equipment O&M Manual | Operating and Maintenance Manuals – Contract C11-85-07 – HCG04 | Procon (General Contractor) Hydromantis, Inc. (Consultant) | Shelf D-5, Doc No. 0000635 | 2010 |
| Drawings | Strathearne/Brampton CSO Gate Replacement – Contract C11-85-07 – HCG04 | Hydromantis, Inc. | Not Provided | Mar 2007 |

2.12 Wellington/Burlington CSO Gate (HCG14)

HCG14 is located at the intersection of Wellington Street North and Burlington Street East, where the Wellington CSO Outfall sewer crosses the WSIN. The purpose of HCG14 is to capture and divert combined sewage from the Wellington CSO Outfall sewer into the WSIN for conveyance to the Woodward Avenue WWTP for treatment.

HCG14 is equipped with a modulation slide gate and back-up isolation slide gate, which are operated automatically by the City's Real Time Control (RTC) system based on level measurements on the receiving WSIN, the Wellington CSO Outfall sewer, and the regulator chamber itself. The modulation gate controls the flow into the WSIN and the isolation gate facilitates maintenance of the modulation gate (when required) and provides redundancy for the modulation gate to control flow into the WSIN. Two passive flap gates are also located just downstream of the flow diversion channel to the regulator to prevent water from Hamilton Harbour from flowing back into the sewer system.

During DWF conditions, the modulation gate remains fully closed and the isolation gate remains fully open. During WWF conditions, upon detection of a threshold flow depth in either the Wellington CSO Outfall sewer or in the WSI North Branch, the site is automatically switched to wet conditions strategy operation, which causes the isolation gate to remain open and the modulation gate to be placed in a partially open position according to the output from a proportional-integral-derivative (PID) controller. The PID controller will then cause the gate to modulate with the objective of attaining and then maintaining the flow level in the WSIN at a specified setpoint. Once the flow levels in the WSIN and the Wellington CSO Outfall sewer fall below the wet conditions strategy trigger levels, the site operation will revert back to the dry conditions strategy. A number of fail-safe and degraded operation conditions features are built into the process control logic in order to ensure the robust and safe operation of the site in the event of a variety of equipment failures (e.g. gate motors, level sensors, etc), all of which are detailed further within the PCN for the site.

The gates can be operated in either full Manual, SCADA Manual, or SCADA Auto modes. The default mode is SCADA Auto, with operation directed by the RTC system, to maximize flow to the WWTP.

The facility is monitored and controlled via SCADA by Operators at the WWTP. The SCADA system includes a security system to advise of any unauthorized entries into the control building.

Figure 12A of the Hatch CSO Facilities Assessment Report (2018) showed the location of the gates, as well as the potential for possible sewage discharges to the environment, colour coded to indicate criticality; and Table 12 of the same report provided an inventory of all the CCPs at this facility, including the details described above; their potential for discharge to the environment under different flow conditions; and recommendations for improving the monitoring, performance, reliability of operation and minimizing the potential for unapproved bypasses/overflows/spills into adjacent receiving waters.

Table 12 provided below summarizes the key components of the O&M Plan for HCG14, including current versions of the SOP, PCN, Equipment O&M Manuals, and As-Built Drawings.

The SOP has been updated as part of this report (Issue #2, January 2019) to make the following changes: to clarify the description of the facilities; to provide consistency of format with all the other CSO facility SOPs, and to add a section on procedures for regular Inspection and Maintenance of the facility addressing the requirements of Order Item 6. No recent changes have been made, or are required, to the operation of the facility via SCADA, and therefore no changes have been made to the current version of the PCN (Version 1.7, January 2012). Similarly, no significant upgrades have been completed recently at this station, so there has also been no need to update the existing Equipment O&M Manuals and As-Built Drawings. These would be updated in the future, if and when any upgrades are completed. For example, the Hatch CSO Facilities Assessment Report (2018) recommended conducting an engineering study to determine the feasibility of adding redundant gate position sensors on the gates themselves, to back up the existing sensors on the gate stems.

Table 12: Summary of O&M Plan for Wellington/Burlington CSO Gate (HCG14)

| O&M Plan Component | Name of Document | Prepared By | Reference # | Issue Date |
|------------------------------------|---|---|-------------------------------|------------|
| Standard Operating Procedure (SOP) | Detailed Sewer System Operation – Wellington/Burlington CSO Gate (HCG14) | Hamilton Water Hatch Ltd. | Issue #2 | Jan 2019 |
| Process Control Narrative (PCN) | Process Control Narrative – Wastewater Regulator (221 Burlington St.) HCG14 | Hamilton Water BPR Eramosa Engineering Stantec | Version 1.7 | Jan 2012 |
| Equipment O&M Manual | Operations Manual, Volume 1 of 2 – Contract C13-09-12 – HCG14 | Stantec (Consultant) Newman Bros. Ltd (General Contractor) | Shelf D-5, Doc No. 0000637 | Sep 2012 |
| Equipment O&M Manual | Operations and Maintenance Manual, Volume 2 of 2 – Contract C13-09-12 – HCG14 | Newman Bros. Ltd (General Contractor) Stantec (Consultant) | Shelf D-5, Doc No. 0000638 | Sep 2012 |
| As-Built Drawings | Wellington/Burlington Regulator Upgrades – Contract C13-09-12 – HCG14 | Stantec | Not Provided | Mar 2013 |

2.13 Parkdale Burlington Wastewater Collection Station (HC001)

Wastewater Pumping Station HC001 is located on the northwest corner of the intersection of Parkdale Avenue and Burlington Street East. The purpose of the station is to lift CSOs from the combined sewer coming from Leaside Road and Woodward Avenue (and separate stormwater from the storm sewer on the north side of Burlington Street between Strathearne Avenue and Parkdale Avenue), which are too deep to be conveyed by gravity to the Parkdale CSO Outfall at the north end of Parkdale Avenue.

The station is equipped with five (5) active pumps, with two (2) 150 L/s pumps employed to handle normal flow conditions, and three (3) more 600 L/s pumps employed to handle high flow conditions. There is also a diesel engine driven pump, but it is currently out of service and not available for operation.

The pumps can be operated in either full Manual, SCADA Manual, or SCADA Auto modes. The default mode of operation involves monitoring of the wet well level via SCADA by Operators at the WWTP, with operation of the pumps in SCADA Auto mode, and only required when the Leaside/Woodward combined sewer and/or Burlington storm sewer are active. The SCADA system includes a security system to advise of any unauthorized entries into the control building.

Figure 13A of the Hatch CSO Facilities Assessment Report (2018) showed the location of the pumps, as well as the potential for possible sewage discharges to the environment, colour coded to indicate criticality; and Table 13 of the same report provided an inventory of all the CCPs at this facility, including the details described above; their potential for discharge to the environment under different flow conditions; and recommendations for improving the monitoring, performance, reliability of operation and minimizing the potential for unapproved bypasses/overflows/spills into adjacent receiving waters.

Table 13 provided below summarizes the key components of the O&M Plan for HC001, including current versions of the SOP, PCN, Equipment O&M Manuals, and As-Built Drawings.

The SOP has been updated as part of this report (Issue #5, January 2019) to make the following changes: to clarify the description of the facilities; to provide consistency of format with all the other CSO facility SOPs, and to add a section on procedures for regular Inspection and Maintenance of the facility addressing the requirements of Order Item 6. No formal changes have been made to the operation of the facility via SCADA, and therefore no changes have been made to the current version of the PCN (Version 2.4, June 2015), although as noted in the SOP, some possible changes are being reviewed. Similarly, no significant upgrades have been completed recently at this station, so there has also been no need to update the existing Equipment O&M Manuals and As-Built Drawings. These would be updated in the future, if and when any upgrades are completed.

Table 13: Summary of O&M Plan for Parkdale Burlington Wastewater Collection Station (HC001)

| O&M Plan Component | Name of Document | Prepared By | Reference # | Issue Date |
|------------------------------------|--|--|----------------|------------|
| Standard Operating Procedure (SOP) | Detailed Sewer System Operation – Parkdale Wastewater Collection Station (HC001) | Hamilton Water Hatch Ltd. | Issue #5 | Jan 2019 |
| Process Control Narrative (PCN) | Process Control Narrative – Parkdale/Burlington Wastewater PS HC001 | Hamilton Water Eramosa Engineering Inc. Westin Engineering Inc. XCG Consultants Ltd. R.E. Poisson Engineering Inc. | Version 2.4 | Jun 2015 |
| As-Built Drawings | Parkdale Sewage Pumping Station – HC001 | City of Hamilton | Plan No. P-138 | 1955 |

3. References

Hatch Corporation (2018). Report – CSO Facilities Assessment – MECP Order Items 4, 7, 8 and 9. Report prepared for the City of Hamilton, November 2018.

Appendix A

Updated Standard Operating Procedures for CSO Facilities

| | | | |
|-------------------|--|-----------------------|---------------|
| Title: | Detailed Sewer System Operation – Greenhill CSO Tank #1 (HCS01) | | |
| Document # | PW-WW-PO-P-011- HCS01-1004-001 | Document Level | Sectional (4) |
| Issue #: | 5 | Issue Date: | January 2019 |

1 PURPOSE

To provide procedures for the safe and efficient operation of the first Greenhill CSO Storage Tank (HCS01).

2 SCOPE

This procedure applies to all operations staff including: Plant Operators, Process Supervisors, Maintenance staff and Superintendents involved in operations of the wastewater systems.

3 DEFINITIONS

| | |
|-------|--|
| BCOS | Beyond Compliance Operating System |
| CS | Confined Space |
| CSO | Combined Sewer Overflow |
| DWQMS | Drinking Water Quality Management System |
| MLD | Mega Litres per Day |
| PO | Plant Operations |
| PW | Public Works |
| RHCSI | Red Hill Creek Sanitary Interceptor |
| SCADA | Supervisory Control and Data Acquisition |
| SFT | Sediment Flushing Tank |
| SG | Sluice Gate |
| WW | Wastewater |
| WWTP | Wastewater Treatment Plant |

4 RESPONSIBILITY

4.1 Manager, Plant Operations / Manager, Plant Maintenance & Technical Services

- Overall responsibility to ensure compliance with this procedure
- Ensure that, at all times, the facilities and related equipment and appurtenances used to achieve the compliance with this procedure are properly operated and maintained

| | | | |
|-------------------|--|-----------------------|---------------|
| Title: | Detailed Sewer System Operation – Greenhill CSO Tank #1 (HCS01) | | |
| Document # | PW-WW-PO-P-011- HCS01-1004-001 | Document Level | Sectional (4) |
| Issue #: | 5 | Issue Date: | January 2019 |

4.2 Superintendent, Wastewater Treatment Process

- Update this procedure as required to ensure its accuracy
- Ensure that staff are trained on and follow this procedure
- Ensure that all operations staff follow this procedure and respond to alarms

4.3 Process Supervisor

- Immediately report suspected problems and issues to Superintendent, Wastewater Process and Superintendent of Operations
- Work with Superintendent, Wastewater Treatment Process to develop a corrective action plan and to implement it to resolve any issues

4.4 Operators

- Follow this procedure and respond to alarms
- Immediately report suspected problems and issues to the Process Supervisor
- Work with Superintendent, Wastewater Treatment Process and Process Supervisor to develop a corrective action plan and implement it to resolve any issues
- Thoroughly document with time all aspects of any incident including the identification of a potential problem, consultations, assessments, actions taken, corrective action plan, implementation of corrective actions, and actions required to prevent reoccurrence of problems

4.5 Maintenance Staff

- Follow this procedure
- Immediately report suspected problems and issues to your Supervisor

5 PROCEDURE

The Greenhill CSO Tank #1 (HCS01) is located at the east end of Greenhill Avenue behind Rosseau Road, north of Rosedale Arena.

The HCS01 tank functions as a second CSO storage facility to capture overflows from the HCS06 tank. This document identifies procedures for the normal operation of HCS01, as well as operation of HCS01 if HCS06 is taken offline.

There is no backup power available at this station. In the event of a power failure, a portable 100 kW (600 V, 3PH) generator must be mobilized to the site.

Hydro Services to this station are provided by Alectra Utilities (905-522-6611).

| | | | |
|------------|--|----------------|---------------------|
| Title: | Detailed Sewer System Operation – Greenhill CSO Tank #1 (HCS01) | | |
| Document # | PW-WW-PO-P-011-HCS01-1004-001 | Document Level | Sectional (4) |
| Issue #: | 5 | Issue Date: | January 2019 |

5.1 Safety Notes and Procedures


- 5.1.1 Ensure all applicable City of Hamilton policies and procedures are understood and followed. Refer to BCOS or PO Workspace.
- 5.1.2 The area inside the Greenhill CSO Tank is considered a confined space (CS).
- 5.1.3 Ensure the City of Hamilton policy on Confined Space Entry (Confined Space Program PW-WW-P-019-001) is understood and followed before entry is attempted.
- 5.1.4 Ensure that the Confined Space Hazard Assessment (Confined Space Hazard Assessment Form Template PW-WW-PO-F-019-002) is completed before entry.
- 5.1.5 Ensure the CS Entry Plan (Confined Space Plan PW-WW-PO-F-019-001) and CS Entry Permit (Confined Space Entry Permit PW-WW-PO-F-019-003) are filled out prior to entry.
- 5.1.6 Ensure any lockout points are identified and locked according to Lock Out/Tag procedure (Lock Out/Tagging PW-WW-PO-P-019-003).
- 5.1.7 Use of a portable gas detector, lifeline/extraction, and two-way radios are mandatory. Fully charged breathing apparatus should be on site at all times in case of an emergency.

5.2 Procedure for Tank Entry: Routine Minor Maintenance and Inspection

NOTE: A Hazard Assessment and a Project Specific Entry Procedure must be written for Construction, Major Maintenance, or for Entry by more than One Person.

- 5.2.1 Fill out and execute a Confined Space Entry Permit (Confined Space Entry Permit PW-WW-PO-F-019-003) and notify the Process Supervisor at the Woodward Avenue Wastewater Treatment Plant (WWTP) (905-546-2424 Ext 1086 or Cell 905-570-6124) of your intent to enter the tank. Ensure that there is no impending rain in the weather forecast, the upstream HCS06 tank cells are empty, that the HCS01 tank cells have been cleaned and are empty, and that the washing system is turned off/isolated.
- 5.2.2 Sluice Gates: Ensure that no flow will be detained in the tank by placing gates SG1 and SG2 in the fully “Open” position. This will convey all flow directly into the Red Hill Creek Sanitary Interceptor (RHCSI) sewer. Contact the Process Supervisor and ensure that the gates are in the fully “Open” position. Place both gates in the Hand/Local mode to ensure the gates positions cannot be changed remotely via SCADA. The control panel is located in the building above the tank. Use the door on the north side of the building. Shut off the intrusion alarm.


| | | | |
|------------|--|----------------|---------------------|
| Title: | Detailed Sewer System Operation – Greenhill CSO Tank #1 (HCS01) | | |
| Document # | PW-WW-PO-P-011- HCS01-1004-001 | Document Level | Sectional (4) |
| Issue #: | 5 | Issue Date: | January 2019 |



Disarm the Intrusion

Open Sluice Gates 1&2 then place in "Hand" mode

5.2.3 When entering the tank, ensure that the tank has been flushed, and that the flushing system has been switched to "Station" mode.



Switch Washdown System Control to

- 5.2.4 The CSO tank cells have no mechanical/electrical ventilation system. Access to both cells of HCS01 is through access doors located in the main building on the south perimeter of the tank. Stairs on the north side lead into Cell 1, and on the south side, into Cell 2. There are no access hatches to open on either cell for ventilation. There is a buried access port atop Cell 2. Exercise care when entering the tank, as the steps can be slippery.
- 5.2.5 Personnel entering the tank shall carry a two-way radio; wear a chemical suit, breathing apparatus, fall arrest, personnel extraction equipment, and chemical protective gloves. Intrinsically safe portable lighting and a fully charged flashlight is necessary for lighting.
- 5.2.6 At least one person in full gear, equipped with a two-way radio and flashlight should remain outside the tank at all times, holding the lifeline, maintaining the Confined Space Entry Permit and communicating with the person/persons inside the tank via a two-way radio.

| | | | |
|-------------------|--|-----------------------|---------------|
| Title: | Detailed Sewer System Operation – Greenhill CSO Tank #1 (HCS01) | | |
| Document # | PW-WW-PO-P-011- HCS01-1004-001 | Document Level | Sectional (4) |
| Issue #: | 5 | Issue Date: | January 2019 |

- 5.2.7 The outside person should initiate contact with the person in the tank every 10 minutes via two-way radio. If there is no response, attempt to contact a second time, and if there is no response again, initiate emergency measures.
- 5.2.8 After all personnel have vacated the tank, secure all hatches.
- 5.2.9 Notify the Process Supervisor that the tank entry has been completed.

5.3 Process and Equipment Overview

5.3.1 The older parts of the City of Hamilton are served by combined sewers, where a single sewer system conveys both sanitary sewage and stormwater runoff. During dry weather and light rainfall, the combined sewers convey all flows to the Woodward Avenue Wastewater Treatment Plant (WWTP). During heavy rainstorms, flows that exceed the capacity of the sewer system and/or the WWTP are diverted to local receiving waters. These combined sewer overflows (CSOs) are necessary in order to minimize basement flooding and overloading of the WWTP. In some areas, the CSOs are captured by underground detention storage tanks that store the sewage during wet weather. The CSO tanks are filled by gravity, and when flows subside after a rainstorm, their liquid contents are drained and/or pumped back into the combined sewer system and conveyed the WWTP where they receive treatment. Floating debris is retained in the tanks by a system of underflow baffles, and large volumes of solids settle to the bottom of the tanks while the sewage is detained in them. After the liquid contents of the tanks are conveyed to the WWTP, these solids remain on the bottom of the tanks. To reduce odours from the CSO tanks, the solids are washed from the tank floors by sediment flushing tanks (SFTs), commonly referred to as tipping buckets, or by high-pressure water spray nozzles (as is the case for HCS01).

NOTE: HCS01 cannot be washed out by the spray nozzle system and must be washed manually with fire hoses.


5.3.2 The Greenhill CSO Tank #1 (HCS01) is an underground reinforced concrete structure, which provides approximately 83,500 m³ of CSO storage capacity, which was designed to capture the runoff from generated by a 15 mm design storm. The storage volume is provided within a circular tank, which is approximately 54 m in diameter and 9 m deep, and includes two separate storage cells. The first cell provides approximately 13,900 m³ of storage. If the first cell fills, the second cell provides approximately 69,600 m³ of additional storage. Normally, HCS01 will receive the overflow from HCS06 and act as a secondary CSO storage facility. When HCS06 is out of service, flow from the tank into the Red Hill Creek Sanitary Interceptor (RHCSI) is regulated by two motorized sluice gates, which can be controlled from the Woodward Avenue WWTP to regulate the rate of flow from the two storage cells. The first gate is typically set to allow sanitary sewage to flow straight through Cell 1 and into the RHCSI, which in turn conveys the sewage directly to the WWTP. Only when

| | | | |
|-------------------|--|-----------------------|---------------|
| Title: | Detailed Sewer System Operation – Greenhill CSO Tank #1 (HCS01) | | |
| Document # | PW-WW-PO-P-011-HCS01-1004-001 | Document Level | Sectional (4) |
| Issue #: | 5 | Issue Date: | January 2019 |

the inflows to the tank exceed the threshold of this gate, does the storage tank begin to fill; first Cell 1, and then Cell 2. If Cell 2 also fills, CSOs from the tank are discharged to the Red Hill Creek via an outfall sewer located on the east side of the tank. Stainless steel underflow baffles are employed above the tank overflow in Cell 2 to retain floatable materials within the tank, and these are subsequently conveyed to the WWTP via the RHCSI.

- 5.3.3 Combined sewage retained in the tank during wet weather is subsequently drained by gravity into the RHCSI and conveyed to the WWTP for treatment during dry weather, when the plant can deal with the additional flow. The rate of drainage from the tank is regulated by the two WWTP-controlled gates, based upon the current inflows at the WWTP.
- 5.3.4 The entire facility is monitored and controlled via SCADA by plant operations staff. The SCADA system includes a security system to advise of any unauthorized entries into the control building.

5.4 Greenhill CSO Tank #1 (HCS01) SCADA Screen



5.5 Dry Weather Operation

- 5.5.1 During normal dry weather operation, HCS01 receives the overflow from HCS06 and both of the sluice gates are normally closed. During dry weather operation with HCS06 out of service, the sluice gates are normally completely open.

| | | | |
|------------|--|----------------|---------------------|
| Title: | Detailed Sewer System Operation – Greenhill CSO Tank #1 (HCS01) | | |
| Document # | PW-WW-PO-P-011- HCS01-1004-001 | Document Level | Sectional (4) |
| Issue #: | 5 | Issue Date: | January 2019 |

5.5.2 To set the opening of Sluice Gate 1 (SG1) to 100% via the SCADA system:

1. Go to the HCS01 screen
2. Select “SG1” and enter a gate position set point of 100%

5.5.3 To set the opening of Sluice Gate 2 (SG2) to 100% via the SCADA system:

1. Go to the HCS01 screen
2. Select “SG2” and enter a gate position set point of 100%

Typically, the Outlet Chamber Level during dry weather is in the 0.10-0.30 m range.

5.6 Wet Weather Operation

5.6.1 CSO enters the storage tanks by gravity, but the rate of filling of the tanks can be increased by closing the motorized gates at HCS01 and HCS06. This wet weather operation mode begins at the Greenhill CSO Tanks, and is initiated when:

- The flow rate into the Woodward Avenue WWTP exceeds 370 MLD; and
- The wet well level at the Woodward Avenue WWTP exceeds 66 m

5.6.2 To fill the tank, the sluice gates must be at least partially closed. This standard operating procedure is to completely close the gates, to provide maximum protection of the Woodward Avenue WWTP, and the maximum rate of filling of HCS01.

NOTE: If HCS01 overflows to the Red Hill Creek, a pop up will appear on the SCADA screen directing the Operator to a CSO Overflow Notification List (PW-WW-PO-L-011-004) which outlines specific instructions to be followed for this CSO overflow.

5.6.3 To close Sluice Gate 1 (SG1) to 0% via the SCADA system:

1. Go to the HCS01 SCADA screen
2. Select “SG1” and set gate position to 0% Open

5.6.4 To close Sluice Gate 2 (SG2) to 0% via the SCADA system:

1. Go to the HCS01 SCADA screen
2. Select “SG2” and set gate position to 0% Open

5.7 Emptying the Tank following a Rainfall Event

5.7.1 The CSO tank drains entirely by gravity. The decision to begin draining the tank is based upon the wet well level at the Woodward Avenue WWTP and/or the flow rate into the plant. Drainage begins when plant inflows drops below 350 MLD.

5.7.2 Following a storm, the Greenhill tanks are emptied first. Drain HCS06 before draining HCS01

5.7.3 Begin by opening SG1 to 5% and once Cell 1 has emptied, empty Cell 2.

| | | | |
|-------------------|--|-----------------------|----------------------|
| Title: | Detailed Sewer System Operation – Greenhill CSO Tank #1 (HCS01) | | |
| Document # | PW-WW-PO-P-011-HCS01-1004-001 | Document Level | Sectional (4) |
| Issue #: | 5 | Issue Date: | January 2019 |

- 5.7.4 Set the opening of Sluice Gate 1 (SG1) to 5% via the SCADA system:
1. Go to the HCS01 SCADA screen
 2. Select “SG1” and set gate position to 5% Open
- 5.7.5 When Cell 1 is empty, set the opening of Sluice Gate 2 (SG2) to 5% via the SCADA system:
1. Go to the HCS01 SCADA screen
 2. Select “SG2” and set gate position to 5% Open
- 5.7.6 As flow to the WWTP subsides, the gates can be opened up in increments of 5% but be sure to monitor the CSO outlet chamber level and not let it exceed 0.60 m in order to control flow to the WWTP.

6 INSPECTION & MAINTENANCE

6.1 Annual Inspections

- 6.1.1 An Annual Inspection of the facilities should be conducted, as outlined in the City’s O-M1 Wastewater Station Inspections (CSO Stations) Operations Procedure, where applicable including but not limited to:
- Health and Safety, including fire extinguishers
 - General Facility, including lighting, heating and ventilation, and general condition of the premises (building, grounds, doors, etc)
 - Sewage Pumps, including pump run tests and checking of pumps for bearing/motor heat/noise and air locks, and checking of breakers
 - Sluice Gates, including exercising of gates to confirm proper operation, only where the gates can be exercised without risk of sewage discharges to the environment
 - Wet Well, including well level controls, signs of scum/debris accumulation, piping and valves, ventilation and lighting
 - Bar Screens, visual inspection to confirm not blocked by debris
 - Flushing System, including testing of system in SCADA Auto mode, verifying SFTs are tipping and emptying properly, checking valve chambers for leaks, and reporting any abnormalities
 - Water Quality Samplers, including testing to confirm proper operation
 - Documenting any significant Odours noticed outside the station
 - Other Operational Checks, including control panels, SCADA alarms, backflow preventers, electric hoists, hatch covers, well level controls



| | | | |
|-------------------|--|-----------------------|----------------------|
| Title: | Detailed Sewer System Operation – Greenhill CSO Tank #1 (HCS01) | | |
| Document # | PW-WW-PO-P-011-HCS01-1004-001 | Document Level | Sectional (4) |
| Issue #: | 5 | Issue Date: | January 2019 |

- 6.1.2 Specific to HCS01, annual position checks and exercising of all sluice gates associated with the facility to confirm they are in proper working order.
- 6.1.3 Specific to HCS01, annual calibration of CSO Tank Overflow flow metering system.

7 ASSOCIATED DOCUMENTS

- Lock Out / Tagging – PW-WW-PO-P-019-003
- Confined Space Procedure – PW-WW-PO-P-019-001
- Confined Space Program – WW Level III - PW-WW-P-019-001
- Confined Space Hazard Assessment Form – PO Level IV - PW-WW-PO-F-019-002
- Confined Space Entry Permit – PO Level IV - PW-WW-PO-F-019-003
- CSO Overflow Notification List – PO Level IV - PW-WW-PO-L-011-004
- Greenhill No. 1 CSO Tank (HCS01) Process Control Narrative, Version 2.4
- O-M1 Wastewater Station Inspections (CSO Stations) Procedure

BCOS software tracks the revision history of document.

| | | | |
|-------------------|---|-----------------------|---------------|
| Title: | Detailed Sewer System Operation – Bayfront Park CSO Tank (HCS02) | | |
| Document # | PW-WW-PO-P-011- HCS02-1004-002 | Document Level | Sectional (4) |
| Issue #: | 3 | Issue Date: | January 2019 |

1 PURPOSE

To provide procedures for the safe and efficient operation of the Bayfront Park (Strachan Street) CSO Storage Tank (HCS02).

2 SCOPE

This procedure applies to all operations staff including: Plant Operators, Process Supervisors, Maintenance Staff and Superintendents involved in operations of the wastewater systems.

3 DEFINITIONS

| | |
|-------|---|
| BCOS | Beyond Compliance Operating System |
| CS | Confined Space |
| CSO | Combined Sewer Overflow |
| ECA | Environmental Compliance Approval |
| MECP | Ministry of Environment, Conservation and Parks |
| MLD | Mega Litres per Day |
| ORO | Overall Responsible Operator |
| PO | Plant Operations |
| PW | Public Works |
| SCADA | Supervisory Control and Data Acquisition |
| SFT | Sediment Flushing Tank |
| WSI | Western Sanitary Interceptor |
| WW | Wastewater |
| WWTP | Wastewater Treatment Plant |

4 RESPONSIBILITY

4.1 Manager, Plant Operations / Manager, Plant Maintenance and Technical Services

- Overall responsibility to ensure compliance with this procedure
- Ensure that, at all times, the facilities and related equipment and appurtenances used to achieve the compliance with this procedure are properly operated and maintained

| | | | |
|-------------------|---|-----------------------|----------------------|
| <i>Title:</i> | Detailed Sewer System Operation – Bayfront Park CSO Tank (HCS02) | | |
| <i>Document #</i> | <i>PW-WW-PO-P-011-</i> <i>HCS02-1004-002</i> | <i>Document Level</i> | <i>Sectional (4)</i> |
| <i>Issue #:</i> | 3 | <i>Issue Date:</i> | January 2019 |

4.2 **Superintendent, Wastewater Treatment Process**

- Update this procedure as required to ensure its accuracy
- Ensure that staff are trained on and follow this procedure
- Ensure that all operations staff follow this procedure and respond to alarms

4.3 **Process Supervisor**

- Immediately report suspected problems and issues to Superintendent, Wastewater Process and Superintendent of Operations
- Work with Superintendent, Wastewater Treatment Process to develop a corrective action plan and to implement it to resolve any issues

4.4 **Operators**

- Follow this procedure and respond to alarms
- Immediately report suspected problems and issues to the Process Supervisor
- Work with Superintendent, Wastewater Treatment Process and Process Supervisor to develop a corrective action plan and implement it to resolve any issues
- Thoroughly document with time all aspects of any incident including the identification of a potential problem, consultations, assessments, actions taken, corrective action plan, implementation of corrective actions, and actions required to prevent reoccurrence of problems

4.5 **Maintenance Staff**

- Follow this procedure
- Immediately report suspected problems and issues to your Supervisor

5 **PROCEDURE**

The Bayfront Park CSO Tank (HCS02) is located at Bayfront Park, off Harbour Front Drive, at the west end of Strachan Street.

This document identifies procedures for the normal operation of HCS02, as well as procedures for confined space entry into the underground storage tank.

Hydro services to this station are provided by Alectra Utilities (905-522-6611).

| | | | |
|-------------------|---|-----------------------|----------------------|
| Title: | Detailed Sewer System Operation – Bayfront Park CSO Tank (HCS02) | | |
| Document # | <i>PW-WW-PO-P-011-HCS02-1004-002</i> | Document Level | <i>Sectional (4)</i> |
| Issue #: | 3 | Issue Date: | January 2019 |

5.1 Safety Notes and Procedures

- 5.1.1 Ensure all applicable City of Hamilton policies and procedures are understood and followed. Refer to BCOS or PO Workspace.
- 5.1.2 The area inside the Bayfront Park CSO Tank is considered a confined space (CS).
- 5.1.3 Smoking is not permitted inside the tank, the adjoining HC003 control building, or the influent and effluent sampling huts.
- 5.1.4 Ensure the City of Hamilton policy on Confined Space Entry (Confined Space Program PW-WW-P-019-001) is understood and followed before entry is attempted.
- 5.1.5 Ensure that the Confined Space Hazard Assessment (Confined Space Hazard Assessment Form Template PW-WW-PO-F-019-002) is completed before entry.
- 5.1.6 Ensure the CS Entry Plan (Confined Space Plan PW-WW-PO-F-019-001) and CS Entry Permit (Confined Space Entry Permit PW-WW-PO-F-019-003) are filled out prior to entry.
- 5.1.7 Ensure any lockout points are identified and locked according to Lock Out/Tag procedure (Lock Out/Tagging PW-WW-PO-P-019-003).
- 5.1.8 Two persons trained and certified in confined space entry must be present at all times (one inside and one outside), and confined space entry protocol must be followed.
- 5.1.9 Use of a portable gas detector, lifeline/extraction, and two-way radios are mandatory. Fully charged breathing apparatus should be on site at all times in case of an emergency.

5.2 Procedure for Tank Entry: Routine Minor Maintenance and Inspection

NOTE: A Hazard Assessment and a Project Specific Entry Procedure must be written for Construction, Major Maintenance, or for Entry by More Than One Person.

- 5.2.1 Fill out and execute a Confined Space Entry Permit (Confined Space Entry Permit PW-WW-PO-F-019-003) and notify the Process Supervisor at the Woodward Avenue Wastewater Treatment Plant (WWTP) (905-546-2424 Ext 1086 or Cell 905-570-6124) of your intent to enter the tank. Ensure that there is no impending rain in the weather forecast, the tank has been cleaned and is empty, the pumps are turned on, and the washing system is turned off.

| | | | |
|-------------------|---|-----------------------|---------------|
| Title: | Detailed Sewer System Operation – Bayfront Park CSO Tank (HCS02) | | |
| Document # | PW-WW-PO-P-011- HCS02-1004-002 | Document Level | Sectional (4) |
| Issue #: | 3 | Issue Date: | January 2019 |

5.2.2 When entering the control room, shut off the intrusion alarm. Press the “Washdown Stop” button to ensure the washdown cycle has not been initiated.




5.2.3 **Maintenance Bypass:** A Maintenance Bypass of the CSO Tank is provided at Manhole HG06E052, where the influent sewer and CSO tank outfall sewer connect. Closing the Tank Inlet Gate on the east wall of the manhole (located just to the north of the influent sampling chamber) and opening the two Maintenance Bypass Gates on the north wall of the same manhole, diverts any flow in the upstream sewer to the CSO tank outfall sewer. The gates in this manhole should only be operated in this manner when tank entry is absolutely necessary during wet weather conditions. Proper authorities must be notified of any plans to employ such by-pass, and spill notification procedures should be followed.

NOTE: The two Maintenance Bypass Gates are locked in the Full Closed position to ensure all incoming sewage flows are conveyed into the CSO storage tank and eliminate the possibility of any dry weather sewage discharges to Hamilton Harbour at the is location. They should only be opened for maintenance purposes with the approval of the Overall Responsible Operator (ORO) and notification to the Ministry of Environment, Conservation and Parks (MECP) as per the Environmental Compliance Approval (ECA) for the facility.

| | | | |
|-------------------|---|-----------------------|----------------------|
| Title: | Detailed Sewer System Operation – Bayfront Park CSO Tank (HCS02) | | |
| Document # | PW-WW-PO-P-011- HCS02-1004-002 | Document Level | Sectional (4) |
| Issue #: | 3 | Issue Date: | January 2019 |

- 5.2.4 Ensure minimum flow will enter the tank by turning all pumps to “Auto” (3 pumps in the Strachan Street Pumping Station (HC003) and 2 pumps in the CSO tank) at the control panel. Initiate tank pump out by pressing the tank pump out “Start” button.



- 5.2.5 The CSO tank has no mechanical/electrical ventilation or lighting. Ventilation is provided by opening the access hatches above the sediment flushing tanks (SFTs). Open all SFT access hatches to the storage cell or cells you are going to enter (10 hatches on the west side for Cell 1, and 10 hatches on the east side for Cell 2). Also open the hatches to all secondary accesses (i.e. manholes in the northwest corner of Cell 1 and northeast corner of Cell 2). The tank’s primary access points are the staircases on either side of the centre wall of the tank, beginning at the east wall. The south set of stairs accesses Cell 1, and the north set accesses Cell 2. Exercise care when entering the tank, as the steps can be slippery. The person **inside the tank** should carry a fully charged flashlight.
- 5.2.6 At least one person equipped with a two-way radio and flashlight should remain outside the tank at all times, holding the lifeline, maintaining the Confined Space Entry Permit and communicating with the person inside the tank via a two-way radio. All personnel should wear long sleeves, long pants, safety boots, gloves, safety vest and hardhat at all times.
- 5.2.7 The outside person should initiate contact with the person in the tank every 10 minutes via two-way radio. If there is no response, attempt to contact a second time, and if there is no response again, initiate emergency measures.
- 5.2.8 A portable gas detector should be used to determine if the air inside the tank is safe for entry. The gas detector should remain with the person/persons inside the tank and should be turned on at all times. If the gas detector alarm sounds at any time, all personnel inside the tank should exit immediately. Re-entry should only be attempted using fully charged breathing apparatus.
- 5.2.9 After all personnel have vacated the tank, secure all access hatches.

| | | | |
|-------------------|---|-----------------------|----------------------|
| Title: | Detailed Sewer System Operation – Bayfront Park CSO Tank (HCS02) | | |
| Document # | <i>PW-WW-PO-P-011- HCS02-1004-002</i> | Document Level | <i>Sectional (4)</i> |
| Issue #: | 3 | Issue Date: | January 2019 |

- 5.2.10 At the control panel, reset the controls for the washing system and pumps to the “Remote” mode. Reinststate the intrusion alarm and secure the door.
- 5.2.11 Notify the Process Supervisor that the tank entry has been completed.

5.3 PROCESS AND EQUIPMENT OVERVIEW


- 5.3.1 The older parts of the City of Hamilton are served by combined sewers, where a single sewer system conveys both sanitary sewage and storm water runoff. During dry weather and light rainfall, the combined sewers convey all flows to the Woodward Avenue Wastewater Treatment Plant (WWTP). During heavy rainstorms, flows that exceed the capacity of the sewer system and/or the WWTP are diverted to local receiving waters. These combined sewer overflows (CSOs) are necessary in order to minimize basement flooding and overloading of the WWTP. In some areas, the CSOs are captured by underground detention storage tanks that store the sewage during wet weather. The CSO tanks are filled by gravity, and when flows subside after a rainstorm, their liquid contents are drained and/or pumped back into the combined sewer system and conveyed the WWTP where they receive treatment. Floating debris is retained in the tanks by a system of underflow baffles, and large volumes of solids settle to the bottom of the tanks while the sewage is detained in them. After the liquid contents of the tanks are conveyed to the WWTP, these solids remain on the bottom of the tanks. To reduce odours from the CSO tanks, the solids are washed from the tank floors by sediment flushing tanks (SFTs), commonly referred to as tipping buckets, or by high-pressure water spray nozzles. HCS02 employs SFTs for tank cleaning.
- 5.3.2 The Bayfront Park CSO Tank (HCS02) covers an area of approximately 3,200 m², and is over 6 m deep, providing approximately 21,000 m³ of CSO storage capacity in two equally sized storage cells. A new 4.0 m x 1.5 m box sewer (which later changes to 2250 mm) was constructed to intercept the CSOs from the former Queen and Hess Street CSO outfalls and convey them to the CSO tank. The two outfalls were replaced by a single outfall to carry the overflow from the CSO tank on the infrequent occasions when the tank is filled. The new outfall discharges to the Harbour at the east end of the inlet which separates the park and the railway lands. The Bayfront Park CSO Tank operates off-line, meaning that combined sewage is only diverted into the facility during larger CSO events. This reduces the potential for odours and reduces tank cleaning costs. Flow into the tank is regulated by static CSO regulators at Queen/Barton, Stuart/Hess, and Stuart/Caroline, and by the Strachan Street Sewage Pumping Station (HC003). During dry weather, all flow is directed to the WWTP via the CSO regulators and the three (3) dry pit pumps in the pumping station (1 x 394 L/s and 2 x 1,232 L/s).

| | | | |
|-------------------|---|-----------------------|----------------------|
| Title: | Detailed Sewer System Operation – Bayfront Park CSO Tank (HCS02) | | |
| Document # | <i>PW-WW-PO-P-011- HCS02-1004-002</i> | Document Level | <i>Sectional (4)</i> |
| Issue #: | 3 | Issue Date: | January 2019 |

- 5.3.3 During wet weather, excess flows from the three CSO regulators overflow into the CSO tank. Cell 1 will fill first, and if it fills completely, will overflow into Cell 2. If Cell 2 also fills, CSOs are discharged to Hamilton Harbour via the new outfall sewer that exits the north-west corner of the tank. Stainless steel underflow baffles are employed above the tank overflow in Cell 2 to retain floatable materials within the tank. Combined sewage retained in the tank during wet weather is subsequently returned to the Western Sanitary Interceptor (WSI) and conveyed to the WWTP for treatment during dry weather, when the plant can deal with the additional flow. The tank is drained by two (2) 200 L/sec submersible pumps located in Cell 1. A flap gate between Cell 1 and Cell 2 allows the two cells to be emptied at the same time. The pumps discharge into a forcemain that connects to the WSI near Strachan and MacNab Streets. The rate of pumping from the tank can be controlled by Operators at the WWTP, based upon the current inflows at the WWTP. Solids that settle from the combined sewage detained in the CSO tank, and floatable materials retained in the tank by the underflow baffles, are washed from the floor by ten (10) SFTs. The SFTs are large stainless steel buckets, which are suspended above and along the west wall of the CSO tank, about 6 m above the floor. The SFTs are filled with potable water, and when full, they tip and empty their contents down the back walls of the tank. The flush water continues down the sloped floor of the tank at a high velocity and washes the solids from the floor. Washwater from the SFTs is collected in a trough at the bottom of the tank and is also pumped back into the combined sewer system and conveyed to the WWTP for treatment.
- 5.3.4 Two automatic water quality samplers are provided to sample the influent and effluent from the CSO tank, as per its Certificate of Approval/Environmental Compliance Approval. The influent sampler collects its samples from Manhole 3, where the incoming box sewer changes from 4.0 m x 1.5 m to 2250 mm. The effluent sampler collects its samples from the tank overflow channel at the north end of Cell 2. The samplers are housed in above ground huts located adjacent to each sampling location.
- 5.3.5 The entire facility is monitored and controlled via SCADA by plant operations staff. The SCADA system includes a security system to advise of any unauthorized entries into the pumping station. Stand by power is provided for the sewage pumping station by a diesel power generator.

| | | | |
|-------------------|---|-----------------------|----------------------|
| Title: | Detailed Sewer System Operation – Bayfront Park CSO Tank (HCS02) | | |
| Document # | PW-WW-PO-P-011- HCS02-1004-002 | Document Level | Sectional (4) |
| Issue #: | 3 | Issue Date: | January 2019 |

5.4 Bayfront Park (Strachan St.) CSO Tank (HCS02) SCADA Screen



5.5 Dry Weather Operation

5.5.1 Set pumps at the Bayfront Park Pumping Station to “Enable/Dry” mode through the SCADA system:

1. Go to the HCS02 SCADA screen
2. Select Pumping Station System Control “Enable/Dry”

5.5.2 Set pumps in the tank to “Start/Dry” through the SCADA system:

1. Go to the HCS02 SCADA screen
2. Select CSO Pumps System Control “Start/Dry”

5.6 Wet Weather Operation

5.6.1 CSO enters the storage tank cells by gravity, but the rate of filling of the tank cells can be increased by closing motorized gates and/or disabling pumps at each of the facilities. This wet weather operation mode begins at the Greenhill CSO Tank, and is initiated when:

- The Woodward Avenue WWTP exceeds 66 m, and
- The flow rate into the Woodward Avenue WWTP exceeds 370 MLD

| | | | |
|-------------------|---|-----------------------|----------------------|
| Title: | Detailed Sewer System Operation – Bayfront Park CSO Tank (HCS02) | | |
| Document # | <i>PW-WW-PO-P-011- HCS02-1004-002</i> | Document Level | <i>Sectional (4)</i> |
| Issue #: | 3 | Issue Date: | January 2019 |

As the flow rate at the plant increases, filling rates at other facilities are also increased.

5.6.2 And set the pumps in the CSO tank to “Stop/Storm” via the SCADA system:

1. Go to the HCS02 SCADA screen
2. Select CSO Pumps System Control “Stop/Storm”

5.7 Emptying the Tank Following a Rainfall Event

5.7.1 Following a storm, when the Woodward Avenue WWTP can accept more flow, the James Street and Greenhill CSO tanks are emptied first. When Gate 1 at the Greenhill facility is 10% open, the remaining tanks are emptied in this order: Main/King, Bayfront Park, and then Eastwood Park.

5.7.2 For the Bayfront Park CSO Tank, set the pumps at the Strachan Street Sewage Pumping Station (HC003) to “Enable/Dry” mode via the SCADA system:

1. Go to the HCS02 SCADA screen
2. Select Pumping Station System Control “Enable/Dry”

5.7.3 And set the pumps in the CSO tank to “Start/Dry” through the SCADA system:

1. Go to the HCS02 SCADA screen
2. Select CSO Pumps System Control “Start/Dry”

5.8 Washing the Tank Following a Rainfall Event

5.8.1 Ensure all pumps are on. When the level in the tank drops below 1.5m, tank washing may commence via the SCADA system:

1. Go to the HCS02 SCADA screen
2. Select “Start Wash” from the CSO Wash Tank box

If excessive sediment buildup has occurred due to the tank not being flushed between storms or the contents of the tank being detained for an extended period of time, a second flushing is recommended.

6 INSPECTION & MAINTENANCE

6.1 Annual Inspections

6.1.1 An Annual Inspection of the facilities should be conducted, as outlined in the City’s O-M1 Wastewater Station Inspections (CSO Stations) Procedure, where applicable including but not limited to:

- Health and Safety, including fire extinguishers

| | | | |
|-------------------|---|-----------------------|----------------------|
| Title: | Detailed Sewer System Operation – Bayfront Park CSO Tank (HCS02) | | |
| Document # | <i>PW-WW-PO-P-011- HCS02-1004-002</i> | Document Level | <i>Sectional (4)</i> |
| Issue #: | 3 | Issue Date: | January 2019 |

- General Facility, including lighting, heating and ventilation, and general condition of the premises (building, grounds, doors, etc)
- Sewage Pumps, including pump run tests and checking of pumps for bearing/motor heat/noise and air locks, and checking of breakers
- Sluice Gates, including exercising of gates to confirm proper operation, only where the gates can be exercised without risk of sewage discharges to the environment
- Wet Well, including well level controls, signs of scum/debris accumulation, piping and valves, ventilation and lighting
- Bar Screens, visual inspection to confirm not blocked by debris
- Flushing System, including testing of system in SCADA Auto mode, verifying SFTs are tipping and emptying properly, checking valve chambers for leaks, and reporting any abnormalities
- Water Quality Samplers, including testing to confirm proper operation
- Documenting any significant Odours noticed outside the station
- Other Operational Checks, including control panels, SCADA alarms, backflow preventers, electric hoists, hatch covers, well level controls

6.1.2 Specific to HCS02, annual position checks and exercising of all sluice gates associated with the facility to confirm they are in proper working order (except the Influent Well Overflow Gate, which has been padlocked in the Fully Closed position).

6.1.3 Specific to HCS02, annual calibration of CSO Tank Overflow flow metering system.

6.2 Monthly Inspections

6.2.1 Specific to HCS02, monthly inspections of the Tank Inlet Gate and two Maintenance Bypass Gates in the chamber near the end of the CSO Tank Outfall channel to confirm the Tank Inlet Gate is the Fully Open position and that the two Maintenance Bypass Gates are both in the Fully Closed Position and that no sewage is leaking through these gates. The latter can be accomplished by visual inspection of the CSO Tank Outfall Channel on the north side of the gates, which can be viewed from above by opening the access hatch cover on top of the inlet/bypass chamber. Additional lighting may be required to see well enough to confirm no flow is passing through the bypass gates.

| | | | |
|-------------------|---|-----------------------|----------------------|
| <i>Title:</i> | Detailed Sewer System Operation – Bayfront Park CSO Tank (HCS02) | | |
| <i>Document #</i> | <i>PW-WW-PO-P-011-</i> <i>HCS02-1004-002</i> | <i>Document Level</i> | <i>Sectional (4)</i> |
| <i>Issue #:</i> | 3 | <i>Issue Date:</i> | January 2019 |

7 ASSOCIATED DOCUMENTS

- Lock Out / Tagging – PW-WW-PO-P-019-003
- Confined Space Procedure – PW-WW-PO-P-019-001
- Confined Space Program – WW Level III - PW-WW-P-019-001
- Confined Space Hazard Assessment Form – PO Level IV - PW-WW-PO-F-019-002
- Confined Space Entry Permit – PO Level IV - PW-WW-PO-F-019-003
- CSO Overflow Notification List – PO Level IV - PW-WW-PO-L-011-004
- Strachan St. (Bayfront Park) CSO Facility (HCS02) and WWPS (HC003) Process Control Narrative, Version 1.3
- O-M1 Wastewater Station Inspection (CSO Stations) Procedure

BCOS software tracks the revision history of document.

| | | | |
|-------------------|--|-----------------------|---------------|
| Title: | Detailed Sewer System Operation – James Street CSO Tank (HCS03), Ferrie/Mary Sluice Gates (HCG08) | | |
| Document # | PW-WW-PO-P-011- HCS03-1004-003 | Document Level | 4 (Sectional) |
| Issue #: | 4 | Issue Date: | January 2019 |

1 PURPOSE

To provide procedures for the safe and efficient operation of the James Street CSO Storage Tank (HCS03) and Ferrie/Mary Sluice Gates (HCG08).

2 SCOPE

This procedure applies to all operations staff including: plant operators, process supervisors, maintenance staff and superintendents involved in operations of wastewater systems.

3 DEFINITIONS

| | |
|-------|--|
| BCOS | Beyond Compliance Operating System |
| CS | Confined Space |
| CSO | Combined Sewer Overflow |
| EME | Environmental Monitoring and Enforcement |
| MLD | Mega Litres per Day |
| PO | Plant Operations |
| PW | Public Works |
| RTC | Real Time Control |
| SCADA | Supervisory Control and Data Acquisition |
| WSI | Western Sanitary Interceptor |
| WW | Wastewater |
| WWTP | Wastewater Treatment Plant |

4 RESPONSIBILITY

4.1 Manager, Plant Operations / Manager, Plant Maintenance & Technical Services

- Overall responsibility to ensure compliance with this procedure
- Ensure that, at all times, the facilities and related equipment and appurtenances used to achieve the compliance with this procedure are properly operated and maintained

| | | | |
|-------------------|--|-----------------------|----------------------|
| Title: | Detailed Sewer System Operation – James Street CSO Tank (HCS03), Ferrie/Mary Sluice Gates (HCG08) | | |
| Document # | PW-WW-PO-P-011- HCS03-1004-003 | Document Level | 4 (Sectional) |
| Issue #: | 4 | Issue Date: | January 2019 |

4.2 Superintendent, Wastewater Treatment Process

- Update this procedure as required to ensure its accuracy
- Ensure that staff are trained on and follow this procedure
- Ensure that all the operations staff follow this procedure and respond to alarms

4.3 Process Supervisor

- Immediately report suspected problems and issues to the Superintendent, Wastewater Treatment Process
- Work with the Superintendent, Wastewater Treatment Process to develop a corrective action plan and implement it to resolve any issues

4.4 Operators

- Follow this procedure and respond to alarms
- Immediately report suspected problems and issues to the Process Supervisor
- Work with Superintendent, Wastewater Treatment Process and Process Supervisor to develop corrective action plan and to implement it to resolve the issues
- Thoroughly document with time all aspects of any incident including the identification of a potential problem, consultations, assessments, actions taken, corrective action plan, implementation of corrective actions, and actions required to prevent reoccurrence of problems

4.5 Maintenance Staff

- Follow this procedure
- Immediately report suspected problems and issues to your Supervisor

5 PROCEDURE

The James Street CSO Tank (HCS03) is located at the north end of James Street North, at Guise Street. The off-line storage tank is augmented by additional in-line storage created within the combined sewer downstream of the tank, by the Mary/Ferrie Sluice Gates (HCG08) located at the intersection of Mary/Ferrie Streets.

This document identifies procedures for the normal operation of HCS03 and HCG08, as well as procedures for confined space entry into the underground storage tank and sluice gate chamber.

Hydro services to this station are provided by Alectra Utilities (905-522-6611).

| | | | |
|-------------------|--|-----------------------|----------------------|
| Title: | Detailed Sewer System Operation – James Street CSO Tank (HCS03), Ferrie/Mary Sluice Gates (HCG08) | | |
| Document # | PW-WW-PO-P-011-HCS03-1004-003 | Document Level | 4 (Sectional) |
| Issue #: | 4 | Issue Date: | January 2019 |

5.1 Safety Notes and Procedures

- 5.1.1 Ensure all applicable City of Hamilton policies and procedures are understood and followed. Refer to BCOS or PO Workspace.
- 5.1.2 The area inside the off-line storage tank and the underground chamber that contains the Ferrie/Mary sluice gates are both considered a confined space (CS).
- 5.1.3 Smoking is not permitted inside the CSO tank or the Mary/Ferrie sluice gate chamber.
- 5.1.4 Ensure the City of Hamilton policy on Confined Space Entry (Confined Space Program PW-WW-P-019-001) is understood and followed before entry is attempted.
- 5.1.5 Ensure that the Confined Space Hazard Assessment (Confined Space Hazard Assessment Form Template PW-WW-PO-F-019-002) is completed before entry.
- 5.1.6 Ensure that the CS Entry Plan (Confined Space Plan PW-WW-PO-F-019-001) and CS Entry Permit (Confined Space Entry Permit PW-WW-PO-F-019-003) are filled out prior to entry.
- 5.1.7 Ensure any lockout points are identified and locked according to Lock Out/Tag procedure (Lock Out / Tagging PW-WW-PO-P-019-003).
- 5.1.8 Use of a portable gas detector, lifeline/extraction, and two-way radios are mandatory. Fully charged breathing apparatus should be on site at all times in case of an emergency.

5.2 Process and Equipment Overview

- 5.2.1 The older parts of the City of Hamilton are served by combined sewers, where a single sewer system conveys both sanitary sewage and stormwater runoff. During dry weather and light rainfall, the combined sewers convey all flows to the Woodward Avenue Wastewater Treatment Plant (WWTP). During heavy rainstorms, flows that exceed the capacity of the sewer system and/or the WWTP are diverted to local receiving waters. These combined sewer overflows (CSOs) are necessary in order to minimize basement flooding and overloading of the WWTP. In some areas, the CSOs are captured by underground detention storage tanks that store the sewage during wet weather. The CSO tanks are filled by gravity, and when flows subside after a rainstorm, their liquid contents are drained and/or pumped back into the combined sewer system and conveyed the WWTP where they receive treatment. Floating debris is retained in the tanks by a system of underflow baffles, and large volumes of solids settle to the bottom of the tanks while the sewage is detained in them. After the liquid contents of the tanks are conveyed to the WWTP, these solids remain on the bottom of the tanks. To reduce odours from the CSO tanks, the solids are washed from the tank floors by sediment flushing tanks (SFTs), commonly referred to as tipping

| | | | |
|-------------------|--|-----------------------|---------------|
| Title: | Detailed Sewer System Operation – James Street CSO Tank (HCS03), Ferrie/Mary Sluice Gates (HCG08) | | |
| Document # | PW-WW-PO-P-011- HCS03-1004-003 | Document Level | 4 (Sectional) |
| Issue #: | 4 | Issue Date: | January 2019 |

buckets, or by high-pressure water spray nozzles. HCS03 employs water spray nozzles for tank cleaning.


- 5.2.2 The James Street CSO Storage Facility (HCS03) incorporates both off-line and in-line storage components, which provide a total CSO storage capacity of approximately 3,200 m³. The off-line storage tank is an underground, reinforced concrete structure, which resides beneath the parking lot of the Royal Hamilton Yacht Club, located at the north end of James Street. The rectangular tank covers an area of approximately 900 m², and is 0.8 to 2.1 m deep, providing approximately 1,500 m³ of CSO storage capacity. The off-line storage capacity is augmented by 1,800 m³ of in-line storage, which is provided within the 1500 mm diameter combined sewer downstream of the CSO tank. The additional in-line storage is created by the Mary/Ferrie CSO Sluice Gates (HCG08). The Mary/Ferrie sluice gates control the rate of flow from the James combined sewer system into the Western Sanitary Interceptor (WSI) at Mary and Ferrie Streets. In dry weather, the gate is set to allow all flow to enter the WSI.

NOTE: When in auto mode the Mary/Ferrie Sluice Gates (HCG08) function as part of the Real Time Control (RTC) system, and will automatically close the isolation gate when the southern branch of the Western Sanitary Interceptor (WSI) reaches a high level.

- 5.2.3 During wet weather, the gates can be partially or completely closed to throttle the flow of combined sewage into the WSI, and begin filling the storage facilities. The rate of filling is determined by the position of the gate. The in-line storage pipe will fill first, and as levels in this pipe increase, the off-line storage tank will also begin to fill. If the tank fills completely, CSOs are discharged to Hamilton Harbour via the pre-existing 1200 mm x 900 mm CSO outfall at the north end of the tank. Stainless steel underflow baffles are employed above the tank overflow to retain floatable materials within the tank. Combined sewage retained in the tank during wet weather is subsequently returned to the WSI and conveyed to the WWTP for treatment during dry weather, when the plant can deal with the additional flow. The tank is drained by gravity as the in-line storage pipe empties. The rate of drainage from the in-line storage pipe and the off-line storage tank is determined by the position of the Mary/Ferrie gates, which can be controlled by Operators at the WWTP, based upon the current inflows at the WWTP.
- 5.2.4 Solids that settle from the combined sewage detained in the CSO tank, and floatable materials retained in the tank by the underflow baffles, are washed from the floor by high-pressure water spray nozzles located around the perimeter of the tank, and are also conveyed to the WWTP for treatment.
- 5.2.5 The entire facility is monitored and controlled via SCADA by plant operations staff.

| | | | |
|------------|--|----------------|---------------|
| Title: | Detailed Sewer System Operation – James Street CSO Tank (HCS03), Ferrie/Mary Sluice Gates (HCG08) | | |
| Document # | PW-WW-PO-P-011- HCS03-1004-003 | Document Level | 4 (Sectional) |
| Issue #: | 4 | Issue Date: | January 2019 |

5.3 James Street CSO Tank (HCS03) and Ferrie/Mary Sluice Gates (HCG08) SCADA Screen



5.4 Dry Weather Operation (Manual)

Manually open the Mary/Ferrie Sluice Gate (HCG08) via the SCADA system:

1. Go to the HCG08 screen on SCADA
2. Switch station control to manual
3. Select “HCG08 Isolation Gate” and set to “Open”

5.5 Wet Weather Operation

NOTE: When in Auto mode the HCG08 Mary/Ferrie sluice gates function as part of the Real Time Control (RTC) system and will automatically close the isolation gate when the southern branch of the WSI reaches a high level.

- 5.5.1 When three (3) pumps are operating at the Woodward Avenue WWTP during an extreme storm and bypassing is imminent (Flow > 614MLD), set the Mary/Ferrie Sluice Gate (HCG08) to “Closed” via the SCADA system:

| | | | |
|-------------------|--|-----------------------|---------------|
| Title: | Detailed Sewer System Operation – James Street CSO Tank (HCS03), Ferrie/Mary Sluice Gates (HCG08) | | |
| Document # | PW-WW-PO-P-011- HCS03-1004-003 | Document Level | 4 (Sectional) |
| Issue #: | 4 | Issue Date: | January 2019 |

1. Go to the HCG08 screen on SCADA
2. Switch station control to manual
3. Select “HCG08 Isolation Gate” and set to “Closed”

NOTE: When putting the CSO tank in service, notification must be given to the Supervisor of Environmental Monitoring and Enforcement (EME) at Extension 5678. When the CSO tank overflows, refer to the CSO Overflow Notification list (CSO Overflow Notification List PW-WW-PO-L-011-004).

5.6 Emptying the Tank Following a Rainfall Event

- 5.6.1 The CSO tank drains entirely by gravity. The decision to begin draining the tank is based upon the wet well level at the Woodward Avenue WWTP and/or the flow rate into the plant. Drainage begins when plant inflows drop below 350 MLD.
- 5.6.2 Emptying the tank can be done by either placing HCG08 station control to Auto or manually opening the Mary/Ferrie Sluice Gate (HCG08) via the SCADA system:
1. Go to the HCG08 screen on SCADA
 2. Switch station control to manual
 3. Select “HCG08 Isolation Gate” and set to “Open”

5.7 Washing the Tank Following a Rainfall Event

- 5.7.1 The CSO tank should be cleaned after each use. When the sewage level in the tank has dropped below 0.1 m, tank washing may commence via the SCADA system:
1. Go to the HCG08 screen on SCADA
 2. Select Start on the Wash Tank icon

6 INSPECTION & MAINTENANCE

6.1 Annual Inspections

- 6.1.1 An Annual Inspection of the facilities should be conducted, as outlined in the City’s O-M1 Wastewater Station Inspections (CSO Stations) Procedure, where applicable including but not limited to:
- Health and Safety, including fire extinguishers
 - General Facility, including lighting, heating and ventilation, and general condition of the premises (building, grounds, doors, etc)
 - Sewage Pumps, including pump run tests and checking of pumps for bearing/motor heat/noise and air locks, and checking of breakers

| | | | |
|-------------------|--|-----------------------|----------------------|
| Title: | Detailed Sewer System Operation – James Street CSO Tank (HCS03), Ferrie/Mary Sluice Gates (HCG08) | | |
| Document # | PW-WW-PO-P-011-HCS03-1004-003 | Document Level | 4 (Sectional) |
| Issue #: | 4 | Issue Date: | January 2019 |

- Sluice Gates, including exercising of gates to confirm proper operation, only where the gates can be exercised without risk of sewage discharges to the environment
- Wet Well, including well level controls, signs of scum/debris accumulation, piping and valves, ventilation and lighting
- Bar Screens, visual inspection to confirm not blocked by debris
- Flushing System, including testing of system in SCADA Auto mode, verifying SFTs are tipping and emptying properly, checking valve chambers for leaks, and reporting any abnormalities
- Water Quality Samplers, including testing to confirm proper operation
- Documenting any significant Odours noticed outside the station
- Other Operational Checks, including control panels, SCADA alarms, backflow preventers, electric hoists, hatch covers, well level controls

6.1.2 Specific to HCS03, annual position checks and exercising of all sluice gates associated with the facility to confirm they are in proper working order.

6.1.3 Specific to HCS03, annual calibration of CSO Tank Overflow flow metering system.

7 ASSOCIATED DOCUMENTS

- CSO Overflow Notification List PW-WW-PO-L-011-004
- Lock Out / Tagging PW-WW-PO-P-019-003
- Confined Space Procedure – Plant Operations Section PW-WW-PO-P-019-001
- Confined Space Program PW-WW-P-019-001
- Confined Space Hazard Assessment Form Template- Plant Operations - Level IV - PW-WW-PO-F-019-002
- Confined Space Entry Permit – Plant Operations Level IV PW-WW-PO-F-019-003
- Confined Space Plan PW-WW-PO-F-019-001
- James Street CSO Facility (HCS03) Process Control Narrative, Version 2.5
- O-M1 Wastewater Station Inspections (James CSO) Procedure

BCOS software tracks the revision history of document.

| | | | |
|-------------------|---|-----------------------|--------------|
| Title: | Detailed Sewer System Operation – Main/King CSO Tank (HCS04) | | |
| Document # | PW-WW-PO-P-011- HCS04-1004-004 | Document Level | 4 Sectional |
| Issue #: | 7 | Issue Date: | January 2019 |

1 PURPOSE

To provide procedures for the safe and efficient operation of the Main/King CSO Storage Tank (HCS04).

2 SCOPE

This procedure applies to all operations staff including: Plant Operators, Process Supervisors, Maintenance staff and Superintendents involved in operations of wastewater systems.

3 DEFINITIONS

| | |
|-------|--|
| BCOS | Beyond Compliance Operating System |
| CS | Confined Space |
| CSO | Combined Sewer Overflow |
| MLD | Mega Litres per Day |
| PO | Plant Operations |
| PW | Public Works |
| RTC | Real Time Control |
| SCADA | Supervisory Control and Data Acquisition |
| SG | Sluice Gate |
| SFT | Sediment Flushing Tank |
| WSI | Western Sanitary Interceptor |
| WW | Wastewater |
| WWPS | Wastewater Pumping Station |
| WWTP | Wastewater Treatment Plant |

4 RESPONSIBILITY

4.1 Manager, Plant Operations / Manager, Plant Maintenance & Technical Services

- Overall responsibility to ensure compliance with this procedure
- Ensure that, at all times, the facilities and related equipment and appurtenances used to achieve the compliance with this procedure are properly operated and maintained

| | | | |
|------------|---|----------------|---------------------|
| Title: | Detailed Sewer System Operation – Main/King CSO Tank (HCS04) | | |
| Document # | PW-WW-PO-P-011- HCS04-1004-004 | Document Level | 4 Sectional |
| Issue #: | 7 | Issue Date: | January 2019 |

4.2 Superintendent, Wastewater Treatment Process

- Update this procedure as required to ensure its accuracy
- Ensure that staff are trained on and follow this procedure
- Ensure that all the operations staff follow this procedure and respond to alarms

4.3 Process Supervisor

- Immediately report suspected problems and issues to the Superintendent, Wastewater Treatment Process
- Work with the Superintendent, Wastewater Treatment Process to develop a corrective action plan and implement it to resolve any issues

4.4 Operators

- Follow this procedure and respond to alarms
- Immediately report suspected problems and issues to the Process Supervisor
- Work with Superintendent, Wastewater Treatment Process and Process Supervisor to develop corrective action plan and to implement it to resolve the issues
- Thoroughly document with time all aspects of any incident including the identification of a potential problem, consultations, assessments, actions taken, corrective action plan, implementation of corrective actions, and actions required to prevent reoccurrence of problems

4.5 Maintenance Staff

- Follow this procedure
- Immediately report suspected problems and issues to your Supervisor

5 PROCEDURE

The Main/King CSO Tank (HCS04) is located in Cathedral Park, in the area bounded by King Street/Dundurn Street/Main Street/Highway 403. Inflows to the CSO tank are regulated by three external sluice gates, installed in Chamber 1 (on Glen Road), Chamber 4 (near the northwest corner of the tank) and Chamber 5 (just outside the control building).

This document identifies procedures for the normal operation of HCS04 (and the gates in Chambers 1, 4 and 5), as well as procedures for confined space entry into the underground storage tank and sluice gate chambers.

Hydro services to this station are provided by Alectra Utilities (905-522-6611).

| | | | |
|------------|---|----------------|---------------------|
| Title: | Detailed Sewer System Operation – Main/King CSO Tank (HCS04) | | |
| Document # | PW-WW-PO-P-011- HCS04-1004-004 | Document Level | 4 Sectional |
| Issue #: | 7 | Issue Date: | January 2019 |

5.1 Safety Notes and Procedures

- 5.1.1 Ensure all applicable City of Hamilton policies and procedures are understood and followed. Refer to BCOS or PO Workspace.
- 5.1.2 The area inside the storage tank and the underground gate chambers are all considered a confined space (CS).
- 5.1.3 Smoking is not permitted inside the CSO tank or the sluice gate chambers.
- 5.1.4 Ensure the City of Hamilton policy on Confined Space Entry (Confined Space Program PW-WW-P-019-001) is understood and followed before entry is attempted.
- 5.1.5 Ensure that the Confined Space Hazard Assessment (Confined Space Hazard Assessment Form Template PW-WW-PO-F-019-002) is completed before entry.
- 5.1.6 Ensure the CS Entry Plan (Confined Space Plan PW-WW-PO-F-019-001) and CS Entry Permit (Confined Space Entry Permit PW-WW-PO-F-019-003) are filled out prior to entry.
- 5.1.7 Ensure any lockout points are identified and locked according to Lock Out/Tag procedure (Lock Out / Tagging PW-WW-PO-P-019-003).
- 5.1.8 Use of a portable gas detector, lifeline/extraction, and two-way radios are mandatory. Fully charged breathing apparatus should be on site at all times in case of an emergency.

5.2 Procedure for Tank Entry: Routine Minor Maintenance and Inspection

NOTE: A Hazard Assessment and Project Specific Entry Procedure must be written for Construction, Major Maintenance, or for Entry by more than One Person.


- 5.2.1 Fill out and execute a Confined Space Entry Permit and notify the Process Supervisor at the Woodward Avenue Wastewater Treatment Plant (WWTP) (905-546-2424 Ext 1086 or cell phone 905-570-6124) of your intent to enter the tank. Ensure that there is no impending rain in the weather forecast, the tank floor has been cleaned and is empty, and the washing system is turned off. The tank may have some liquid in it. Entry can be made so long as gas levels are within acceptable levels.

| | | | |
|-------------------|---|-----------------------|--------------|
| Title: | Detailed Sewer System Operation – Main/King CSO Tank (HCS04) | | |
| Document # | PW-WW-PO-P-011- HCS04-1004-004 | Document Level | 4 Sectional |
| Issue #: | 7 | Issue Date: | January 2019 |

- 5.2.2 When entering the control room, shut off the intrusion alarm. Exhaust fans and lights should be turned on from the panel prior to entering the tank.



- 5.2.3 When entering either storage cell, ensure that the tank has been flushed and the flushing system has been locked out. Ensure that no flow will enter the tank in dry weather by placing Gates 4 and 5 in the fully open position and maintaining the opening for Gate 1 at 35%, which will direct dry weather flow into the Western Sanitary Interceptor sewer. Lock out of gates 4 and 5 is not needed unless you are entering the chambers for each. Gates should be confirmed to be in open position with Process Supervisor before entry is done. The tank cannot be washed every time there is an entry. Gas testing will determine if the tank needs to be washed. If there is no gas, then there is no need to wash the tank.



- 5.2.4 Leave all pumps in “Auto” position to ensure that any flow into the tank is pumped out.
- 5.2.5 Exercise care when entering the tank, as the steps can be slippery.
- 5.2.6 Do not enter if the portable Methane Detection System does not register “OK”. Personnel inside the tank should carry and use a portable gas detector.

| | | | |
|-------------------|---|-----------------------|--------------|
| Title: | Detailed Sewer System Operation – Main/King CSO Tank (HCS04) | | |
| Document # | PW-WW-PO-P-011- HCS04-1004-004 | Document Level | 4 Sectional |
| Issue #: | 7 | Issue Date: | January 2019 |

- 5.2.7 At least one person equipped with a two-way radio and flashlight should remain outside the tank at all times, maintaining the “Confine Space Entry Permit” and communicating with the person inside the tank via a two-way radio. All personnel should wear long sleeves, long pants, safety boots, gloves, safety vest and hardhat at all times.
- 5.2.8 The person outside the tank should initiate contact with the person in the tank every 10 minutes via two-way radio. If there is no response, attempt to contact a second time, and if there is no response again, initiate emergency measures.
- 5.2.9 Notify the process supervisor when leaving the site. Remove all lockouts and return all gates to “Remote” mode. Shut off all lights and exhaust fans. Reinstate the intrusion alarm and secure all doors.

5.3 Process and Equipment Overview

- 5.3.1 The older parts of the City of Hamilton are served by combined sewers, where a single sewer system conveys both sanitary sewage and stormwater runoff. During dry weather and light rainfall, the combined sewers convey all flows to the Woodward Avenue Wastewater Treatment Plant (WWTP). During heavy rainstorms, flows that exceed the capacity of the sewer system and/or the WWTP are diverted to local receiving waters. These combined sewer overflows (CSOs) are necessary in order to minimize basement flooding and overloading of the WWTP. In some areas, the CSOs are captured by underground detention storage tanks that store the sewage during wet weather. The CSO tanks are filled by gravity, and when flows subside after a rainstorm, their liquid contents are drained and/or pumped back into the combined sewer system and conveyed the WWTP where they receive treatment. Floating debris is retained in the tanks by a system of underflow baffles, and large volumes of solids settle to the bottom of the tanks while the sewage is detained in them. After the liquid contents of the tanks are conveyed to the WWTP, these solids remain on the bottom of the tanks. To reduce odours from the CSO tanks, the solids are washed from the tank floors by sediment flushing tanks (SFTs), commonly referred to as tipping buckets, or by high-pressure water spray nozzles. HCS04 employs SFTs for tank cleaning.
- 5.3.2 The Main/King CSO Tank (HCS04) covers an area of approximately 9,500 m², and is over 8 m deep, providing approximately 77,100 m³ of CSO storage capacity in two separate storage cells. The first cell provides approximately 23,300 m³ of storage, and the second provides a further 53,800 m³ of storage. The Main-King CSO Tank operates off-line, with combined sewage entering the tank during larger CSO events. Flow into the tank is regulated by three WWTP-controlled CSO regulators which were constructed in conjunction with the CSO tank. The former Glen Road CSO Outfall, which was located at the east end of Glen Road on the west side of Hwy 403, was eliminated by installing a new WWTP-controlled CSO regulator gate at Glen/Macklin

| | | | |
|------------|---|----------------|---------------------|
| Title: | Detailed Sewer System Operation – Main/King CSO Tank (HCS04) | | |
| Document # | PW-WW-PO-P-011- HCS04-1004-004 | Document Level | 4 Sectional |
| Issue #: | 7 | Issue Date: | January 2019 |

(Chamber 1) and constructing a new 1350 mm diameter sewer to convey CSOs underneath Hwy 403 and into the new CSO tank. The former McKittrick CSO Outfall, which previously diverted CSOs from the 1980 mm diameter combined sewer which runs along the north side of the Main Street, was eliminated by constructing a new WWTP-controlled CSO regulator (Chamber 4) to divert CSOs into the new tank. Flow from the 2100 mm x 2250 mm box sewer which runs along the south side of Main Street was diverted into the new tank by a bulkhead placed in the sewer and a new WWTP-controlled CSO regulator located at the south-east corner of the tank (Chamber 5). Downstream of the bulkhead, this sewer is used to convey the overflows which will still occur from the tank when its design capacity is exceeded.

5.3.3 During dry weather, flow is directed to the WWTP via the interceptor sewer. The gate in Chamber 4 (King Street Sewer) should be 100% opened and Chamber 5 (Interceptor Sewer) at 30% and Chamber 1 (Glen Road Sewer) is always set at 35%. The Main Street Overflow Sewer, which maintains a base flow during dry weather due mainly to infiltration, is directed to the tank’s wet well and pumped into the Western Sanitary Interceptor (WSI) sewer.

NOTE: The gate in Chamber 4 is presently without power and communication with SCADA. The gate has been manually set to divert wet weather flows mainly to the CSO tank.

5.3.4 The CSO tank wet well includes an Influent Well Overflow Gate that can be operated to convey all flows into the CSO tank and pumping station (when Closed) or to provide a maintenance bypass of the tank (when Open). Under normal operating conditions, this gate should remain Fully Closed at all times, under all flow conditions.

NOTE: The Influent Well Overflow Gate has been closed and padlocked in the Fully Closed position to ensure all incoming sewage flows are conveyed into the CSO storage tank and eliminate the possibility of any dry weather sewage discharges to Chedoke Creek. Access to the gate for control purposes has also been removed from the SCADA system.



5.3.5 During wet weather, the pumps are taken out of auto mode and turned off; the opening of Gate 4 is reduced to 7%; and the opening of Gate 5 is reduced to 2%. Excess flows from the three regulators enters the pumping station wet-well, which is located beneath the control building at the south-east corner of the facility. During dry weather and small storm events, the CSO tank’s pumping station acts as a normal sewage pumping station. During larger storm events, two motorized sluice gates are opened to permit flow from the wet-well to enter the CSO tank. Cell 1 will fill first, and if it fills completely, will overflow into Cell 2. If Cell 2 also fills, CSOs are discharged into Chedoke Creek near the Main Street overpass, via the remaining 2100 mm x 2250 mm box culvert. Stainless steel underflow baffles are employed above the tank

| | | | |
|-------------------|---|-----------------------|--------------|
| Title: | Detailed Sewer System Operation – Main/King CSO Tank (HCS04) | | |
| Document # | PW-WW-PO-P-011- HCS04-1004-004 | Document Level | 4 Sectional |
| Issue #: | 7 | Issue Date: | January 2019 |

overflow in Cell 2 to retain floatable materials within the tank. Combined sewage retained in the tank during wet weather is subsequently returned to the CSS and conveyed by the WSI to the WWTP for treatment during dry weather, when the plant can deal with the additional flow. The tank is drained by three (3) 375 L/sec submersible pumps located in the pumping station wet-well. A flap gate between Cell 1 and Cell 2 allows the cells to be emptied at the same time. The pumps discharge into a forcemain that connects to the original 1980 mm sewer, which in turn discharges into the WSI near Hunt Street. The rate of pumping from the tank can be controlled by Operators at the WWTP, based upon the current inflows at the WWTP.

- 5.3.6 Solids that settle from the combined sewage detained in the CSO tank, and floatable materials retained in the tank by the underflow baffles, are washed from the floor by a series of 30 SFTs, and also conveyed to the WWTP for treatment. The SFTs are large stainless steel buckets, which are suspended above and along the west wall of the CSO tank, about 8 m above the floor. The SFTs are filled with potable water, and when full, they tip and empty their contents down the back walls of the tank. The flush water continues down the sloped floor of the tank at a high velocity and washes the solids from the floor. Washwater from the SFTs is collected in a trough at the bottom of the tank and is also pumped back into the combined sewer system and conveyed to the WWTP for treatment.
- 5.3.7 The entire facility is monitored and controlled via SCADA by plant operations staff. The SCADA system includes a security system to advise of any unauthorized entries into the pumping station.

5.4 Main/King CSO Tank (HCS04) SCADA Screen



| | | | |
|-------------------|---|-----------------------|--------------|
| Title: | Detailed Sewer System Operation – Main/King CSO Tank (HCS04) | | |
| Document # | PW-WW-PO-P-011-HCS04-1004-004 | Document Level | 4 Sectional |
| Issue #: | 7 | Issue Date: | January 2019 |

5.5 Dry Weather Operation

5.5.1 In Normal mode, during dry weather operation, HCS04 operates as a typical wet well pumping station, with the pump station isolated from the CSO storage tank.

5.5.2 The gates in Chambers 1, 4 and 5 should be in the following positions:

- Chamber 1 Gate = 35% Open
- Chamber 4 Gate = 100% Open
- Chamber 5 Gate = 30% Open

5.5.3 And the gates in the pump station should be in the following positions:

- PS Inlet Gate = 100% Open
- CSO Tank Inlet Gate = 50% Open
- CSO Tank Outlet Gate = 100% Open

NOTE: The gate in Chamber 1 (Glen Road) should always be set to 35% Open, in all flow conditions, and should never be opened more than 35%.

5.6 Wet Weather Operation

5.6.1 To fill the Main/King CSO Tank, the various sluice gates should be placed in the following positions:

- Chamber 1 Gate = 35% Open
- Chamber 4 Gate = 7% Open
- Chamber 5 Gate = 2% Open
- PS Inlet Gate = 100% Open
- CSO Tank Inlet Gate = 100% Open
- CSO Tank Outlet Gate = 100% Open

5.7 Emptying the Tank following a Rainfall Event

5.7.1 The Main/King CSO Tank drains entirely by gravity, through the CSO Tank Influent Well and Pump Station Wet Well, and then back through Chamber 5, from which point the drained flows are conveyed by gravity via the Western Sanitary Interceptor (WSI) to the Woodward Avenue WWTP. The decision to begin draining the tank is based upon the wet well level at the Woodward Avenue WWTP and/or the flow rate into the plant. Drainage begins when plant inflows drops below 320 MLD.

| | | | |
|-------------------|---|-----------------------|---------------------|
| Title: | Detailed Sewer System Operation – Main/King CSO Tank (HCS04) | | |
| Document # | PW-WW-PO-P-011- HCS04-1004-004 | Document Level | 4 Sectional |
| Issue #: | 7 | Issue Date: | January 2019 |

- 5.7.2 Following a storm, the James Street and Greenhill tanks are emptied first. When Gate 1 at the Greenhill facility is 10% open, the remaining tanks are emptied in this order: Main/King, Bayfront Park, and then Eastwood Park.
- 5.7.3 As flow to the plant subsides, the gates can be opened up in increments of 5%. When the openings of the Greenhill Sluice Gates are both 10%, drainage of the other CSO tanks may begin.
- 5.7.4 To begin emptying the Main/King CSO Tank, when the Wet Well level is between 9.9-10.3 m, the various sluice gates should be placed in the following positions:
- Chamber 1 Gate = 35% Open
 - Chamber 4 Gate = 7% Open
 - Chamber 5 Gate = 10% Open
 - PS Inlet Gate = 100% Open
 - CSO Tank Inlet Gate = 100% Open
 - CSO Tank Outlet Gate = 100% Open
- 5.7.5 When the Wet Well level is between 9.7-9.9 m, the various sluice gates should be placed in the following positions:
- Chamber 1 Gate = 35% Open
 - Chamber 4 Gate = 100% Open
 - Chamber 5 Gate = 10% Open
 - PS Inlet Gate = 100% Open
 - CSO Tank Inlet Gate = 100% Open
 - CSO Tank Outlet Gate = 100% Open
- 5.7.6 When the Wet Well level falls to 9.05 m, the system flips back to Normal pump station mode and the Duty 1 and Duty 2 sewage lift pumps are started to drain the rest of the Wet Well and CSO Tank.
- 5.8 Washing the Tank following a Rainfall Event**
- 5.8.1 Washing of the floors of the Main/King CSO Tank is done remotely via SCADA:
1. Go to the HCS04 screen on SCADA
 2. Check that the CSO Tank Backwash is set to “Run” and in “Remote” mode
 3. Select Cell 1 “Start”
 4. When Cell 1 is complete, Select Cell 2 “Start”
 5. Note: Cell 2 will not wash if the CSO Tank Cells Outlet Gate in the wet well is less than 10% open

| | | | |
|------------|---|----------------|---------------------|
| Title: | Detailed Sewer System Operation – Main/King CSO Tank (HCS04) | | |
| Document # | PW-WW-PO-P-011- HCS04-1004-004 | Document Level | 4 Sectional |
| Issue #: | 7 | Issue Date: | January 2019 |

6 INSPECTION & MAINTENANCE

6.1 Annual Inspections

6.1.1 An Annual Inspection of the facilities should be conducted, as outlined in the City's O-M1 Wastewater Station Inspections (CSO Stations) Procedure, where applicable including but not limited to:

- Health and Safety, including fire extinguishers
- General Facility, including lighting, heating and ventilation, and general condition of the premises (building, grounds, doors, etc)
- Sewage Pumps, including pump run tests and checking of pumps for bearing/motor heat/noise and air locks, and checking of breakers
- Sluice Gates, including exercising of gates to confirm proper operation, only where the gates can be exercised without risk of sewage discharges to the environment
- Wet Well, including well level controls, signs of scum/debris accumulation, piping and valves, ventilation and lighting
- Flushing System, including testing of system in SCADA Auto mode, verifying SFTs are tipping and emptying properly, checking valve chambers for leaks, and reporting any abnormalities
- Water Quality Samplers, including testing to confirm proper operation
- Documenting any significant Odours noticed outside the station
- Other Operational Checks, including control panels, SCADA alarms, backflow preventers, electric hoists, hatch covers, well level controls

6.1.2 Specific to HCS04, annual position checks and exercising of all sluice gates associated with the facility to confirm they are in proper working order (except the Influent Well Overflow Gate, which has been padlocked in the Fully Closed position).

6.1.3 Specific to HCS04, annual calibration of CSO Tank Overflow flow metering system.

6.2 Monthly Inspections

6.2.1 Specific to HCS04, monthly inspections of the Influent Well Overflow Gate to confirm that it is in the Fully Closed Position, and that no sewage is leaking through the gate. The latter can be accomplished by visual inspection of the Overflow Chamber on the downstream side of the gate, which can be viewed from above by opening the access hatch cover on top of the Overflow Chamber. Additional lighting may be required to see down to the floor of the chamber on the downstream side of the gate and confirm no flow is passing through the gate.

| | | | |
|-------------------|---|-----------------------|---------------------|
| Title: | Detailed Sewer System Operation – Main/King CSO Tank (HCS04) | | |
| Document # | PW-WW-PO-P-011- HCS04-1004-004 | Document Level | 4 Sectional |
| Issue #: | 7 | Issue Date: | January 2019 |

7 ASSOCIATED DOCUMENTS

- Lock Out / Tagging – PW-WW-PO-P-019-003
- Confined Space Procedure – PW-WW-PO-P-019-001
- Confined Space Program – WW Level III - PW-WW-PO-F-019-001
- Confined Space Hazard Assessment Form – PO Level IV - PW-WW-PO-F-019-002
- E2 Confined Space Plan – PW-WW-PO-F-019-014
- HCS04-01 Confined Space Plan – WW Level IV - PW-WW-PO-F-019-01-096
- WWPS HCS04 (Main/King CSO Tank), Process Control Narrative, Version 3.5
- O-M1 Wastewater Station Inspections (CSO Stations) Procedure

BCOS software tracks the revision history of document.

| | | | |
|-------------------|---|-----------------------|---------------------|
| Title: | Detailed Sewer System Operation – Eastwood Park CSO Tank (HCS05), Burlington/Ferguson Sluice Gate (HCG06), Ferrie/Ferguson Sluice Gate (HCG07) | | |
| Document # | PW-WW-PO-P-011- HSC05-1004-005 | Document Level | 4 (Sectional) |
| Issue #: | 5 | Issue Date: | January 2019 |

1 PURPOSE

To provide procedures for the safe and efficient operation of the Eastwood Park CSO Storage Tank (HCS05), Burlington/Ferguson Sluice Gate (HCG06), and Ferrie/Ferguson Sluice Gate (HCG07).

2 SCOPE

This procedure applies to all operations staff including: Plant Operations, Process Supervisors, Maintenance staff and Superintendents involved in operations of the wastewater systems.

3 DEFINITIONS

| | |
|-------|---|
| BCOS | Beyond Compliance Operating System |
| CS | Confined Space |
| CSO | Combined Sewer Overflow |
| EME | Environmental Monitoring and Enforcement |
| MECP | Ministry of Environment, Conservation and Parks |
| MLD | Mega Litres per Day |
| ORO | Overall Responsible Operator |
| PO | Plant Operations |
| PW | Public Works |
| SCADA | Supervisory Control and Data Acquisition |
| WSI | Western Sanitary Interceptor |
| WW | Wastewater |
| WWTP | Wastewater Treatment Plant |
| SFT | Sediment Flushing Tank |

4 RESPONSIBILITY

4.1 Manager, Plant Operations / Manager, Plant Maintenance & Technical Services

- Overall responsibility to ensure compliance with this procedure

| | | | |
|-------------------|---|-----------------------|---------------------|
| Title: | Detailed Sewer System Operation – Eastwood Park CSO Tank (HCS05), Burlington/Ferguson Sluice Gate (HCG06), Ferrie/Ferguson Sluice Gate (HCG07) | | |
| Document # | PW-WW-PO-P-011- HSC05-1004-005 | Document Level | 4 (Sectional) |
| Issue #: | 5 | Issue Date: | January 2019 |

- Ensure that, at all times, the facilities and related equipment and appurtenances used to achieve the compliance with this procedure are properly operated and maintained

4.2 Superintendent, Wastewater Treatment Process

- Update this procedure as required to ensure its accuracy
- Ensure that staff are trained on and follow this procedure
- Ensure that all the operations staff follow this procedure and respond to alarms

4.3 Process Supervisor

- Immediately report suspected problems and issues to the Superintendent, Wastewater Treatment Process
- Work with the Superintendent, Wastewater Treatment Process to develop a corrective action plan and implement it to resolve any issues

4.4 Operators

- Follow this procedure and respond to alarms
- Immediately report suspected problems and issues to the Process Supervisor
- Work with Superintendent, Wastewater Treatment Process and Process Supervisor to develop corrective action plan and to implement it to resolve the issues
- Thoroughly document with time all aspects of any incident including the identification of a potential problem, consultations, assessments, actions taken, corrective action plan, implementation of corrective actions, and actions required to prevent reoccurrence of problems

4.5 Maintenance Staff

- Follow this procedure
- Immediately report suspected problems and issues to your Supervisor

5 PROCEDURE

The Eastwood Park CSO Tank (HCS05) is located at 113 Burlington Street East in Eastwood Park, on the northwest corner of Burlington Street East and Ferguson Avenue North. Inflows to the tank are regulated by two upstream CSO regulators: the Burlington/Ferguson Sluice Gate (HCG06) and Ferrie/Ferguson Sluice Gate (HCG07).

| | | | |
|-------------------|---|-----------------------|---------------------|
| Title: | Detailed Sewer System Operation – Eastwood Park CSO Tank (HCS05), Burlington/Ferguson Sluice Gate (HCG06), Ferrie/Ferguson Sluice Gate (HCG07) | | |
| Document # | PW-WW-PO-P-011- HSC05-1004-005 | Document Level | 4 (Sectional) |
| Issue #: | 5 | Issue Date: | January 2019 |

This document identifies procedures for the normal operation of HCS05 (and HCG06 and HCG07), as well as procedures for confined space entry into the underground storage tank and sluice gate chambers.

There is no backup power available at this station. In the event of a power failure a portable 350 kW (600 V, 3PH) generator must be mobilized to the site.

Hydro services to this station are provided by Alectra Utilities (905-522-6611).

5.1 Safety Notes and Procedures

- 5.1.1 Ensure all applicable City of Hamilton policies and procedures are understood and followed. Refer to BCOS or PO Workspace.
- 5.1.2 The area inside the storage tank and the underground gate chambers are all considered a confined space (CS).
- 5.1.3 Smoking is not permitted inside the CSO tank, sampling huts, or sluice gate chambers.
- 5.1.4 Ensure the City of Hamilton policy on Confined Space Entry (Confined Space Program PW-WW-P-019-001) is understood and followed before entry is attempted.
- 5.1.5 Ensure that the Confined Space Hazard Assessment (Confined Space Hazard Assessment Form Template PW-WW-PO-F-019-002) is completed before entry.
- 5.1.6 Ensure that the CS Entry Plan (Confined Space Plan PW-WW-PO-F-019-001) and CS Entry Permit (Confined Space Entry Permit PW-WW-PO-F-019-003) are filled out prior to entry.
- 5.1.7 Ensure any lockout points are identified and locked according to Lock Out/Tag procedure (Lock Out / Tagging PW-WW-PO-P-019-003).
- 5.1.8 Two persons trained and certified in confined space entry must be present at all times (one inside and one outside), and confined space entry protocol must be followed.
- 5.1.9 Use of a portable gas detector, lifeline/extraction, and two-way radios are mandatory. Fully charged breathing apparatus should be on site at all times in case of an emergency.

5.2 Procedure for Tank Entry: Routine Minor Maintenance and Inspection

NOTE: A hazard assessment and a project specific entry procedure must be written for Construction, Major Maintenance, or for Entry by more than One Person. Only pump the pump well down to the level of the bend in the suction pipe, i.e. do not air lock the pumps.

| | | | |
|------------|---|----------------|---------------------|
| Title: | Detailed Sewer System Operation – Eastwood Park CSO Tank (HCS05), Burlington/Ferguson Sluice Gate (HCG06), Ferrie/Ferguson Sluice Gate (HCG07) | | |
| Document # | PW-WW-PO-P-011- HSC05-1004-005 | Document Level | 4 (Sectional) |
| Issue #: | 5 | Issue Date: | January 2019 |

- 5.2.1 Fill out and execute a Confined Space Entry Permit and notify the Process Supervisor at the Woodward Avenue Wastewater Treatment Plant (WWTP) (905-546-2424 Ext 1086 or cell phone 905-570-6124) of your intent to enter the tank. Ensure that there is no impending rain in the weather forecast, the tank floor has been cleaned and is empty, and the washing system is turned off. The tank may have some liquid in it. Entry can be made so long as gas levels are within acceptable levels.
- 5.2.2 Burlington/Ferguson (HCG06) and Ferrie/Ferguson (HCG07) Sluice Gates: Ensure that no flow will enter the tank in dry weather, by placing the HCG06 and HCG07 sluice gates in the fully Open position, directing all flow to the Western Sanitary Interceptor (WSI) sewer. Contact the Process Supervisor and ensure that the gates are in the Open position. Lock out the power to both gates in the Open position. The control panels are located on the side of the road near each gate.
- 5.2.2.1 Ferrie/Ferguson Sluice Gate (HCG06): Open the gate and then lock out power to the actuator at the disconnect.




- 5.2.2.2 Burlington/Ferguson Sluice Gate (HCG07): Open the gate and lock out power to the actuator at the disconnect.



| | | | |
|------------|---|----------------|---------------------|
| Title: | Detailed Sewer System Operation – Eastwood Park CSO Tank (HCS05), Burlington/Ferguson Sluice Gate (HCG06), Ferrie/Ferguson Sluice Gate (HCG07) | | |
| Document # | PW-WW-PO-P-011- HSC05-1004-005 | Document Level | 4 (Sectional) |
| Issue #: | 5 | Issue Date: | January 2019 |

5.2.3 Eastwood Park Tank Control Panel: Contact the Process Supervisor to ensure that the tank floor has been flushed, and that the flushing system is not currently operating. Ensure that the pumps are in the Auto position. Notify the Process Supervisor of your intent to enter the Control Room. When entering the Control Room, which is located on the south side of the Pavilion (replica of a tugboat), shut off the intrusion alarm (lower right corner of the control panel). Press the green button labelled “Tank Pump Out” Start. This will pump out the wet well. Place the flushing system in “Local” mode on the control panel. Ensure that the pumps are left in the “Auto” position.

5.2.3.1 Eastwood Park CSO Tank Control Panel and Pump Controls



5.2.4 The CSO tank has no mechanical/electrical ventilation or lighting. Ventilation is provided by opening the access hatches above the sediment flushing tanks (SFTs). Open all SFT access hatches to the cell or cells you are going to enter (14 hatches on the east side for Cell 1, and 16 hatches on the west side for Cell 2). Also open the hatch above the submersible pumps at the southeast corner of the tank. The tank’s primary access points are the entrance staircase to Cell1, which is located along the east wall of the tank and begins at the northeast corner of the tank, and the entrance ladder to Cell 2, which is located at the northwest corner of the tank. Exercise care

| | | | |
|-------------------|---|-----------------------|---------------------|
| Title: | Detailed Sewer System Operation – Eastwood Park CSO Tank (HCS05), Burlington/Ferguson Sluice Gate (HCG06), Ferrie/Ferguson Sluice Gate (HCG07) | | |
| Document # | PW-WW-PO-P-011- HSC05-1004-005 | Document Level | 4 (Sectional) |
| Issue #: | 5 | Issue Date: | January 2019 |

when entering the tank, as the steps can be slippery. The person inside the tank should carry intrinsically safe portable lighting and a fully charged flashlight.

- 5.2.5 At least one person equipped with a two-way radio and flashlight should remain outside the tank at all times, holding the lifeline, maintaining the Confined Space Entry Permit and communicating with the person inside the tank via a two-way radio. All personnel should wear long sleeves, long pants, safety boots, gloves, safety vest and hardhat at all times.
- 5.2.6 The outside person should initiate contact with the person in the tank at least every 10 minutes via two-way radio. If there is no response, attempt to contact a second time, and if there is no response again, initiate emergency measures.
- 5.2.7 A portable gas detector should be used to determine if the air inside the tank is safe for entry. The gas detector should remain with the person/persons inside the tank and should be turned on at all times. If the gas detector alarm sounds at any time, all personnel inside the tank should exit immediately. Re-entry should only be attempted using fully charged breathing apparatus.
- 5.2.8 After all personnel have vacated the tank, secure all access hatches.
- 5.2.9 At the control panel, reset the controls for the washing system and pumps to the “Remote” mode. Reinstate the intrusion alarm and secure the door.
- 5.2.10 Reinstate power to the HCG06 and HCG07 sluice gates.
- 5.2.11 Notify the Process Supervisor that the tank entry has been completed, and the lockouts have been removed.

5.3 Process and Equipment Overview

- 5.3.1 The older parts of the City of Hamilton are served by combined sewers, where a single sewer system conveys both sanitary sewage and stormwater runoff. During dry weather and light rainfall, the combined sewers convey all flows to the WWTP. During heavy rainstorms, flows that exceed the capacity of the sewer system and/or the WWTP are diverted to local receiving waters. These combined sewer overflows are necessary in order to minimize basement flooding and overloading of the WWTP. In some areas, the CSOs are captured by underground detention storage tanks that store the sewage during wet weather. The CSO tanks are filled by gravity, and when flows subside after a rainstorm, their liquid contents are drained and/or pumped back into the combined sewer system and conveyed the WWTP where they receive treatment. Floating debris is retained in the tanks by a system of underflow baffles, and large volumes of solids settle to the bottom of the tanks while the sewage is detained in them. After the liquid contents of the tanks are conveyed to the WWTP, these solids remain on the bottom of the tanks. To reduce odours from the CSO tanks,

| | | | |
|-------------------|---|-----------------------|---------------------|
| Title: | Detailed Sewer System Operation – Eastwood Park CSO Tank (HCS05), Burlington/Ferguson Sluice Gate (HCG06), Ferrie/Ferguson Sluice Gate (HCG07) | | |
| Document # | PW-WW-PO-P-011- HSC05-1004-005 | Document Level | 4 (Sectional) |
| Issue #: | 5 | Issue Date: | January 2019 |

the solids are washed from the tank floors by sediment flushing tanks, commonly referred to as tipping buckets, or by high-pressure water spray nozzles. HCS05 employs SFTs for tank cleaning.

- 5.3.2 The Eastwood Park CSO Tank (HCS05) covers an area of an area of approximately 4,000 m², and is over 6 m deep, providing approximately 27,350 m³ of CSO storage capacity in two separate storage cells. The first cell provides approximately 14,700 m³ of storage, and the second provides a further 12,650 m³ of storage. A new sewer was constructed along Dock Service Road to intercept the CSOs from the two outfalls and convey them to the CSO tank. The original Catharine Street (1050 mm) and Ferguson Avenue (1500 mm) CSO outfalls were left in place and are still used to carry the overflow from the CSO tank on the infrequent occasions when the tank is filled. A flow splitter diverts the overflow from the tank between the two previously existing outfall sewers.
- 5.3.3 The Eastwood Park CSO Tank operates off-line, with combined sewage entering the tank only during larger CSO events. Flow into the tank is regulated by static CSO regulators at Caroline/Brock, Picton/Ferguson and McAulay/Ferguson and by the two WWTP-controlled CSO regulators at Burlington/Ferguson and Ferrie/Ferguson. During dry weather, the Burlington/Ferguson (HCG06) and Ferrie/Ferguson (HCG07) sluice gates normally remain open, directing all flow to the Western Sanitary Interceptor (WSI) sewer.
- 5.3.4 Maintenance Bypass: A Maintenance Bypass of the CSO Tank is provided in the CSO Tank Inlet Chamber at the northeast corner of the tank. Closing the CSO Tank Inlet Gate on the south wall of the chamber and opening the two Maintenance Bypass Gates on the north wall of the same chamber, diverts any flow in the upstream sewer to the CSO tank outfall sewer. The gates in this chamber should only be operated in this manner when tank entry is absolutely necessary during wet weather conditions. Proper authorities must be notified of any plans to employ such by-pass, and spill notification procedures should be followed.


NOTE: The two Maintenance Bypass Gates are locked in the Full Closed position to ensure all incoming sewage flows are conveyed into the CSO storage tank and eliminate the possibility of any dry weather sewage discharges to Hamilton Harbour at the is location. They should only be opened for maintenance purposes with the approval of the Overall Responsible Operator (ORO) and notification to the Ministry of Environment, Conservation and Parks (MECP) as per the Environmental Compliance Approval (ECA) for the facility.

| | | | |
|-------------------|---|-----------------------|---------------------|
| Title: | Detailed Sewer System Operation – Eastwood Park CSO Tank (HCS05), Burlington/Ferguson Sluice Gate (HCG06), Ferrie/Ferguson Sluice Gate (HCG07) | | |
| Document # | PW-WW-PO-P-011- HSC05-1004-005 | Document Level | 4 (Sectional) |
| Issue #: | 5 | Issue Date: | January 2019 |

- 5.3.5 During wet weather, excess flows from the Catharine/Brock CSO regulator and the five CSO regulators along Ferguson Avenue overflow into the tank. When rainfall occurs, the pumps in the CSO tank are taken out of auto “DRY” mode and turned off, and gates HCG06 and HCG07 are fully closed, eliminating flow into the WSI at these locations. Cell 1 will fill first, and if it fills completely, will overflow into Cell 2. If Cell 2 also fills, CSOs are discharged to Hamilton Harbour through either the Catharine Street or Ferguson Avenue CSO outfalls. Stainless steel underflow baffles are employed above the tank overflow in Cell 2 to retain floatable materials within the tank. Combined sewage retained in the tank during wet weather is subsequently returned to the WSI and conveyed to the WWTP for treatment during dry weather, when the plant can deal with the additional flow. The tank is drained by two (2) 289 L/sec submersible pumps located in Cell 1. One pump is used as a duty pump and the other as a stand-by pump. A flap gate between Cell 1 and Cell 2 allows the cells to be emptied at the same time. The pumps discharge into a forcemain that connects to the 900 mm portion of the WSI downstream of the HCG06 sluice gate. The rate of pumping from the tank can be controlled by Operators at the WWTP, based upon the current inflows at the WWTP.
- 5.3.6 Solids that settle from the combined sewage detained in the CSO tank, and floatable materials retained in the tank by the underflow baffles, are washed from the floor by fifteen (15) SFTs. The SFTs are large stainless steel buckets, which are suspended above and along the west wall of the CSO tank, about 6 m above the floor. The SFTs are filled with potable water, and when full, they tip and empty their contents down the back walls of the tank. The flush water continues down the sloped floor of the tank at a high velocity and washes the solids from the floor. Washwater from the SFTs is collected in a trough at the bottom of the tank and is also pumped back into the combined sewer system and conveyed to the WWTP for treatment.
- 5.3.7 Two automatic water quality samplers are provided to sample the influent and effluent from the CSO tank, as per its Certificate of Approval. The influent sampler collects its samples from the inlet chamber at the northeast corner of the tank, and the effluent sampler collects its samples from the overflow channel at the northwest corner of the tank. The samplers are housed in above ground huts and collected by the Environmental Monitoring and Enforcement (EME) sample technicians.
- 5.3.8 The entire facility is monitored and controlled via SCADA by plant operations staff. The SCADA system includes a security system to advise of any unauthorized entries into the pumping station.

| | | | |
|------------|---|----------------|---------------------|
| Title: | Detailed Sewer System Operation – Eastwood Park CSO Tank (HCS05), Burlington/Ferguson Sluice Gate (HCG06), Ferrie/Ferguson Sluice Gate (HCG07) | | |
| Document # | PW-WW-PO-P-011- HSC05-1004-005 | Document Level | 4 (Sectional) |
| Issue #: | 5 | Issue Date: | January 2019 |

5.4 Eastwood Park CSO Tank (HCS05), Burlington/Ferguson Sluice Gate (HCG06), Ferrie/Ferguson Sluice Gate (HCG07) SCADA Screen



5.5 Dry Weather Operation

5.5.1 During normal dry weather operation HCS05 receives very little sanitary flow with the HCG06 and HCG07 sluice gates in their normal Open position and the pumps cycling as a lift station would.

5.5.2 Set to “Dry” Mode, to run pumps automatically via the SCADA system:

1. Go to the HCS05 SCADA screen
2. Select “Dry” in the CSO Wash Tank box to set the pumps to “Dry” Mode

Ensure that the duty pump is rotated to provide equal operating time on both pumps.

5.5.3 Set the Burlington/Ferguson Sluice Gate (HCG06) to 100% Open via the SCADA system:

1. Go to the HCS05 SCADA screen
2. Select “HCG06 Sluice Gate” and set to 100% Open

5.5.4 Set the Ferrie/Ferguson Sluice Gate (HCG07) to 100% Open via the SCADA system:

1. Go to the HCS05 SCADA Screen
2. Select “HCG07 Sluice Gate” and set to 100% Open

| | | | |
|-------------------|---|-----------------------|---------------------|
| Title: | Detailed Sewer System Operation – Eastwood Park CSO Tank (HCS05), Burlington/Ferguson Sluice Gate (HCG06), Ferrie/Ferguson Sluice Gate (HCG07) | | |
| Document # | PW-WW-PO-P-011- HSC05-1004-005 | Document Level | 4 (Sectional) |
| Issue #: | 5 | Issue Date: | January 2019 |

5.6 Wet Weather Operation

5.6.1 CSO enters the storage tanks by gravity, but the rate of filling of the tanks can be increased by closing motorized gates and/or disabling pumps at each of the facilities. This wet weather operation mode begins with the Greenhill CSO Tank first, and is initiated when:

- The wet well level at the Woodward Avenue WWTP exceeds 66 m, and
- The flow rate into the Woodward Avenue WWTP exceeds 370 MLD

As the flow rate at the plant increases, filling rates at other facilities are also increased.

5.6.2 For the Eastwood Park CSO Tank (HCS05), set pumps to “Storm” mode via the SCADA system:

1. Go to the HCS05 SCADA screen
2. Select “Storm” mode from the CSO Wash Tank box

The pumps will not operate without intervention. Ensure that the pumps are set back to “Dry” mode following a rainfall event.

5.6.3 Set the opening of the Burlington/Ferguson Sluice Gate (HCG06) to 0% Open (i.e. gate fully closed) via the SCADA system:

1. Go to the HCS05 SCADA screen
2. Select “HCG06 Sluice Gate” and set to 0% Open (i.e. gate fully closed)

Set the opening of the Ferrie/Ferguson Sluice Gate (HCG07) to 0% Open (i.e. gate fully closed) via the SCADA system:

1. Go to the HCS05 SCADA screen
2. Select “HCG07 Sluice Gate” and set to 0% Open (i.e. gate fully closed)

5.7 Emptying the Tank Following a Rainfall Event

5.7.1 Following a storm, when the Woodward Avenue WWTP can accept more flow, the James Street and Greenhill CSO tanks are emptied first. The decision to begin draining the tanks is based upon the wet well level at the Woodward Avenue WWTP and/or the flow rate into the plant. The CSO tanks that are overflowing should be drained first. Priority should then be given to tanks that are approaching overflow.

| | | | |
|-------------------|---|-----------------------|---------------------|
| Title: | Detailed Sewer System Operation – Eastwood Park CSO Tank (HCS05), Burlington/Ferguson Sluice Gate (HCG06), Ferrie/Ferguson Sluice Gate (HCG07) | | |
| Document # | PW-WW-PO-P-011- HSC05-1004-005 | Document Level | 4 (Sectional) |
| Issue #: | 5 | Issue Date: | January 2019 |

5.7.2 The Eastwood Park CSO Tank (HCS05) is drained by pumping. Re-open gates HCG06 and HCG07 (refer to Dry Weather Operation).

Start up pumps. Set pumps to “Dry” mode via the SCADA system:

1. Go to the HCS05 screen
2. Select “Dry” mode from the CSO Tank Wash box

5.8 Washing the Tank following a Rainfall Event

5.8.1 Ensure that the pumps are enabled to dry weather mode. When the level in the tank drops below 2.0 m, tank washing may commence via the SCADA system:

1. Go to the HCS05 SCADA screen
2. Select “Storm” Condition from the CSO Tank Wash box
3. Select “TK1 Wash. This will initiate flushing of both storage tank cells

5.8.2 If excessive sediment buildup has occurred due to the tank not being flushed between storms or the contents of the tank being detained for an extended period of time, a second flushing is recommended.

6 INSPECTION & MAINTENANCE

6.1 Annual Inspections

6.1.1 An Annual Inspection of the facilities should be conducted, as outlined in the City’s O-M1 Wastewater Station Inspections (CSO Stations) Procedure, where applicable including but not limited to:

- Health and Safety, including fire extinguishers
- General Facility, including lighting, heating and ventilation, and general condition of the premises (building, grounds, doors, etc)
- Sewage Pumps, including pump run tests and checking of pumps for bearing/motor heat/noise and air locks, and checking of breakers
- Sluice Gates, including exercising of gates to confirm proper operation, only where the gates can be exercised without risk of sewage discharges to the environment
- Wet Well, including well level controls, signs of scum/debris accumulation, piping and valves, ventilation and lighting
- Bar Screens, visual inspection to confirm not blocked by debris
- Flushing System, including testing of system in SCADA Auto mode, verifying SFTs are tipping and emptying properly, checking valve chambers for leaks, and reporting any abnormalities

| | | | |
|-------------------|---|-----------------------|---------------------|
| Title: | Detailed Sewer System Operation – Eastwood Park CSO Tank (HCS05), Burlington/Ferguson Sluice Gate (HCG06), Ferrie/Ferguson Sluice Gate (HCG07) | | |
| Document # | PW-WW-PO-P-011- HSC05-1004-005 | Document Level | 4 (Sectional) |
| Issue #: | 5 | Issue Date: | January 2019 |

- Water Quality Samplers, including testing to confirm proper operation
- Documenting any significant Odours noticed outside the station
- Other Operational Checks, including control panels, SCADA alarms, backflow preventers, electric hoists, hatch covers, well level controls

6.1.2 Specific to HCS05, annual position checks and exercising of all sluice gates associated with the facility to confirm they are in proper working order.

6.1.3 Specific to HCS05, annual calibration of CSO Tank Overflow flow metering system.

6.2 Monthly Inspections

6.2.1 Specific to HCS05, monthly inspections of the CSO Tank Inlet Gate and two Maintenance Bypass Gates in the chamber at the northeast corner of the tank to confirm the CSO Tank Inlet Gate is in the Fully Open position, and that the two Maintenance Bypass Gates are both in the Fully Closed position and that no sewage is leaking through these gates.

7 ASSOCIATED DOCUMENTS

- Safe Entry and Exit from Stations – PW-WW-PO-P-011-002
- Lock Out / Tagging – PW-WW-PO-P-019-003
- Confined Space Procedure – PW-WW-PO-P-019-001
- Confined Space Program – WW Level III - PW-WW-PO-F-019-001
- Confined Space Entry Permit – PW-WW-PO-F-019-003
- Confined Space Hazard Assessment Form – PO Level IV - PW-WW-PO-F-019-002
- BCOS + DWQMS - Log Book and Record Keeping Procedure
- Eastwood Park CSO Tank (HCS05) Process Control Narrative, Version 2.2
- O-M1 Wastewater Station Inspections (CSO Stations) Procedure

BCOS software tracks the revision history of document.

| | | | |
|------------|--|----------------|---------------------|
| Title: | Detailed Sewer System Operation – Greenhill CSO Tank #2 (HCS06) | | |
| Document # | PW-WW-PO-P-011- HCS06-1004-001 | Document Level | Sectional (4) |
| Issue #: | 3 | Issue Date: | January 2019 |

1 PURPOSE

To provide procedures for the safe and efficient operation of the Greenhill CSO Storage Tank (HCS06).

2 SCOPE

This procedure applies to all operations staff including: Plant Operators, Process Supervisors, Maintenance staff and Superintendents involved in operations of the wastewater systems.

3 DEFINITIONS

| | |
|-------|--|
| BCOS | Beyond Compliance Operating System |
| CS | Confined Space |
| CSO | Combined Sewer Overflow |
| MCC | Motor Control Centre |
| MLD | Mega Litres per Day |
| PO | Plant Operations |
| PW | Public Works |
| RHCSI | Red Hill Creek Sanitary Interceptor |
| PLC | Programmable Logic Controller |
| RTC | Real Time Control |
| SCADA | Supervisory Control and Data Acquisition |
| SG | Sluice Gate |
| SFT | Sediment Flushing Tank |
| WW | Wastewater |
| WWTP | Wastewater Treatment Plant |

| | | | |
|------------|--|----------------|---------------------|
| Title: | Detailed Sewer System Operation – Greenhill CSO Tank #2 (HCS06) | | |
| Document # | PW-WW-PO-P-011- HCS06-1004-001 | Document Level | Sectional (4) |
| Issue #: | 3 | Issue Date: | January 2019 |

4 RESPONSIBILITIES

4.1 Manager, Plant Operations / Manager, Plant Maintenance & Technical Services

- Overall responsibility to ensure compliance with this procedure
- Ensure that, at all times, the facilities and related equipment and appurtenances used to achieve the compliance with this procedure are properly operated and maintained

4.2 Superintendent, Wastewater Treatment Process

- Update this procedure as required to ensure its accuracy
- Ensure that staff are trained on and follow this procedure
- Ensure that all the operations staff follow this procedure and respond to alarms

4.3 Process Supervisor

- Immediately report suspected problems and issues to the Superintendent, Wastewater Treatment Process
- Work with the Superintendent, Wastewater Treatment Process to develop a corrective action plan and implement it to resolve any issues

4.4 Operators

- Follow this procedure and respond to alarms
- Immediately report suspected problems and issues to the Process Supervisor
- Work with Superintendent, Wastewater Treatment Process and Process Supervisor to develop corrective action plan and to implement it to resolve the issues
- Thoroughly document with time all aspects of any incident including the identification of a potential problem, consultations, assessments, actions taken, corrective action plan, implementation of corrective actions, and actions required to prevent reoccurrence of problems

4.5 Maintenance Staff

- Follow this procedure
- Immediately report suspected problems and issues to your Supervisor

| | | | |
|------------|--|----------------|---------------------|
| Title: | Detailed Sewer System Operation – Greenhill CSO Tank #2 (HCS06) | | |
| Document # | PW-WW-PO-P-011-HCS06-1004-001 | Document Level | Sectional (4) |
| Issue #: | 3 | Issue Date: | January 2019 |

5 PROCEDURE

The Greenhill CSO Tank #2 (HCS06) is located at 100 Greenhill Avenue in Hamilton, behind Rosedale Arena. HCS06 operates in conjunction with Greenhill CSO Tank #1 (HCS01), which functions as a second CSO storage facility to capture overflows from the HCS06 tank. The two facilities include a number of sluice gate and stop-log chambers to control the flow to the storage tanks, including bypassing of either of the tanks for major maintenance activities, should they be required.

This document identifies procedures for the normal operation of HCS06, as well as procedures for confined space entry into the underground storage tank and associated flow control gate and stop-log chambers.

Hydro services to this station are provided by Alectra Utilities (905-522-6611).

5.1 Safety Notes and Procedures

- 5.1.1 Ensure all applicable City of Hamilton policies and procedures are understood and followed. Refer to BCOS or PO Workspace.
- 5.1.2 The area inside the storage tank and the underground sluice gate and stop-log chambers are all considered a confined space (CS).
- 5.1.3 Smoking is not permitted in the control building or inside the tank.
- 5.1.4 Ensure the City of Hamilton policy on Confined Space Entry (Confined Space Program PW-WW-P-019-001) is understood and followed before entry is attempted.
- 5.1.5 Ensure that the Confined Space Hazard Assessment (Confined Space Hazard Assessment Form Template PW-WW-PO-F-019-002) is completed before entry.
- 5.1.6 Ensure the CS Entry Plan (Confined Space Plan PW-WW-PO-F-019-001) and CS Entry Permit (Confined Space Entry Permit PW-WW-PO-F-019-003) are filled out prior to entry.
- 5.1.7 Ensure any lockout points are identified and locked according to Lock Out/Tag procedure (Lock Out/Tagging PW-WW-PO-P-019-003).
- 5.1.8 Use of a portable gas detector, lifeline/extraction, and two-way radios are mandatory. Fully charged breathing apparatus should be on site at all times in case of an emergency.

5.2 Procedure for Tank Entry: Routine Minor Maintenance and Inspection

- 5.2.1 Fill out and execute a Confined Space Entry Permit and notify the Process Supervisor at the Woodward Avenue Wastewater Treatment Plant (WWTP) (905-546-2424 Ext 1086 or cell phone 905-570-6124) of your intent to enter the tank. Ensure that there is

| | | | |
|------------|--|----------------|---------------------|
| Title: | Detailed Sewer System Operation – Greenhill CSO Tank #2 (HCS06) | | |
| Document # | PW-WW-PO-P-011- HCS06-1004-001 | Document Level | Sectional (4) |
| Issue #: | 3 | Issue Date: | January 2019 |

no impending rain in the weather forecast, the tank has been cleaned and is empty, and the washing system is turned off.

- 5.2.2 Sluice Gates: Ensure that no flow will be detained in the tank by placing gates SG3 in the fully “Open” position and SG4 in the fully “Closed” position. This will convey all flow directly into the Red Hill Creek Sanitary Interceptor (RHCSI) sewer. Contact the Process Supervisor and ensure that the gates are in the fully “Open” position. Place both gates in the “Hand” mode to ensure the gates positions cannot be changed remotely via SCADA and lock-out conforming to lock out procedure PW-WW-PO-P-019-003. The control panel is located in the building above the tank. Use the door on the north side of the building. Shut off the intrusion alarm.
- 5.2.3 When entering the tank, ensure that the tank has been flushed, and that the flushing system has been switched to “Station” mode
- 5.2.4 There are five supply fans, SF-1 to SF-5, to ventilate the gallery and service areas. They can be operated locally at the CSO Tank's electrical room or automatically controlled by programmable logic controller (PLC). The Local/Remote control is operator selectable at the MCC panel. If methane gas reaches a level of 20% L.E.L, the PLC shall initiate the Hi gas alarm and turn on the supply fans (the selector switches are left on “Remote). If the methane gas is still rising up to 40% L.E.L., the RPU shall initiate the Hi-Hi gas alarm. The supply fans shall stay on until the methane gas is back to normal.
- NOTE: The electrical control panel alarm annunciator horn will continue sounding 5 seconds after the alarm has been acknowledged
- 5.2.5 Personnel entering the tank shall carry a two-way radio; wear a chemical suit, breathing apparatus, fall arrest, personnel extraction equipment, and chemical protective gloves. Intrinsically safe portable lighting and a fully charged flashlight is necessary for lighting.
- 5.2.6 At least one person in full gear, equipped with a two-way radio and flashlight should remain outside the tank at all times, holding the lifeline, maintaining the Confined Space Entry Permit and communicating with the person/persons inside the tank via a two-way radio.
- 5.2.7 The outside person should initiate contact with the person in the tank every 10 minutes via two-way radio. If there is no response, attempt to contact a second time, and if there is no response again, initiate emergency measures.
- 5.2.8 After all personnel have vacated the tank, secure all hatches.
- 5.2.9 Notify the Process Supervisor that the tank entry has been completed.


| | | | |
|------------|--|----------------|---------------------|
| Title: | Detailed Sewer System Operation – Greenhill CSO Tank #2 (HCS06) | | |
| Document # | PW-WW-PO-P-011- HCS06-1004-001 | Document Level | Sectional (4) |
| Issue #: | 3 | Issue Date: | January 2019 |

5.3 Process and Equipment Overview

- 5.3.1 The total storage capacity is 66,000 m³ (divided evenly into two 33,000 m³ cells). Each cell has 20 washdown lanes and sediment flushing tanks (SFTs) to thoroughly wash down the tank after each use. Both cells can be drained by the motorized sluice gate SG-4 that is controlled remotely by the Operators at the Woodward Avenue WWTP or locally by panel door mounted pushbuttons.
- 5.3.2 The 3.0 m X 3.0 m inlet box sewer will divert the existing Greenhill Avenue trunk sewer flow to the rectangular storage tank HCS06. All dry weather flow will by-pass the storage tank discharging to the existing Red Hill Creek sanitary trunk sewer and then to the Woodward WWTP. The dry weather flow is diverted into the 900 mm diameter sewer by the drop structure and the opened motorized sluice gate SG-3.
- 5.3.3 During a storm event, sluice gate SG-3 should be closed, causing all flows to be diverted into HCS06 Cell 1, and if HCS06 Cell 1 fills, then into HCS06 Cell 2.
- 5.3.4 If HCS06 Cell 2 is filled, excess wet weather flows will overflow into HCS01 Cell 1, and if HCS01 Cell 1 fills, then into HCS01 Cell 2. Overflows to Red Hill Creek will only occur if HCS01 Cell 2 is filled.
- 5.3.5 There are three flow control gates and two stop-gates, whose functions are as follows:
- 5.3.5.1 SG-1 (Sluice Gate #1): This motorized sluice gate should normally remain Fully Open directing all inflow into HCS06, with the manual Stop Gate #1 (located in the same chamber) in its default Closed position sending all flow towards HCS06. SG-1 should never closed with the stop gate in its default position, since this could cause sewage to backup in the incoming trunk sewer on Greenhill Avenue and cause basement flooding upstream. To prevent this from happening, SG-1 is locally padlocked in the fully “Open” position, with no remote control possible from the Woodward Avenue WWTP; i.e. **there is no PC Manual Control allowed for sluice gate SG-1.**
- 5.3.5.2 Stop Gate #1: This manual stop gate should normally remain Fully Closed. It is used only to bypass flows around HCS06 for maintenance purposes (and only with a pre-approved bypass plan in place). When bypassing HCS06 for maintenance, Stop Gate #1 would be opened and SG-1 would be closed. Removal of Stop Gate #1 from its default Fully Closed position would require a boom truck or crane.
- 5.3.5.3 SG-3 (Sluice Gate #3): This motorized sluice gate provides dry weather flow control, controlling how much flow is conveyed directly into the RHCSI and on to the Woodward Avenue WWTP. Open the gate. The normal setting of this gate is approximately 20% Open.
- 5.3.5.4 SG-4 (Sluice Gate #4): This motorized sluice gate is also referred to as the Outflow Sluice Gate, which is opened to drain both cells of the HCS06 storage tank. The percentage of opening will be based on the measured outlet chamber level at HCS01.

| | | | |
|------------|--|----------------|---------------------|
| Title: | Detailed Sewer System Operation – Greenhill CSO Tank #2 (HCS06) | | |
| Document # | PW-WW-PO-P-011-HCS06-1004-001 | Document Level | Sectional (4) |
| Issue #: | 3 | Issue Date: | January 2019 |

5.4 Greenhill CSO Tank #2 (HCS06) SCADA Screen



5.5 Control Modes

In general, there are two control modes available for operation of the equipment at HCS06: LOCAL Manual and PC Manual (PC standing for Personal Computer).

5.5.1 Local Manual

5.5.1.1 Equipment can be controlled locally by the operator using the “ON-OFF” or “START-STOP” or “OPEN-CLOSE” switch on the local panel.

5.5.1.2 First, the panel hand switch must be in LOCAL, and then the operator can operate the equipment locally.

5.5.1.3 When the panel switch is in LOCAL position, the equipment is not available for control by either the RPU or the SCADA system.

5.5.1.4 Each gate is provided with manual controls incorporated within the actuator. These allow the operator to open and close the gates directly from the gate.

5.5.2 PC Manual.

5.5.2.1 Equipment can be controlled remotely from one of the SCADA PCs at the Woodward Avenue WWTP.

5.5.2.2 First, the “LOCAL-REMOTE” switch must be in REMOTE.

| | | | |
|------------|--|----------------|---------------------|
| Title: | Detailed Sewer System Operation – Greenhill CSO Tank #2 (HCS06) | | |
| Document # | PW-WW-PO-P-011-HCS06-1004-001 | Document Level | Sectional (4) |
| Issue #: | 3 | Issue Date: | January 2019 |

- 5.5.2.3 The SCADA system is then on-line for process control. With the SCADA system set to MANUAL, an operator may operate equipment manually from one of the SCADA PCs.
- 5.5.2.4 Each gate is provided with a means of selecting LOCAL or REMOTE mode directly from the actuator. The gate must be selected to REMOTE mode to allow the SCADA system to control the gate. Similarly, REMOTE mode must be selected to allow the electrical room gate push-buttons to control the gate.

5.6 Washing the HCS06 Tank following a Rainfall Event

- 5.6.1 The tank can be cleaned (backwashed) locally at the station via push-buttons located on the electrical room control panel or remotely from the SCADA system. Note that the solenoid valves and the proximity switches (c/w intrinsic safety barriers) supplied and installed for the backwash system are intrinsically safe; therefore, the tank can be backwashed even under high methane gas alarms.
- 5.6.2 There are 20 solenoid valves to control the flow of water for filling the sediment flushing tanks (SFTs) used to clean the tank. Valves 1 to 10 (WLL01SV01-WLL01SV10) are for washing Cell 1, and valves 11 to 20 (WLL02SV11-WLL02SV20) are for washing Cell 2.
- 5.6.3 Forty (40) SFTs are employed to clean the tank. SFTs # 1-20 are used to backwash Cell 1 and SFTs # 21-40 are used to wash Cell 2. The solenoid valves will provide potable water to fill the SFTs as programmed in SCADA. Solenoid Valve #1 fills SFTs # 1&2, Valve #2 fills SFTs # 3&4, and so on. After each pair of SFTs are filled, they will tip backwards by gravity and release their water volume down the back wall and then along the floor of the tank to wash the tank. SFTs (which are also referred as flushing buckets (FB)) are numbered 00000FB01 to 00000FB40 in SCADA.
- 5.6.4 Flushing Sequence

To Flush Cell 1¹:

1. Open Solenoid Valve #1 to fill SFTs # 1 & 2.
2. SFTs # 1 & 2 are filled and tipped; upon receiving signals that the SFTs have tipped, close Valve #1 and start 30-second delay timer.
3. After 30 seconds timeout, open Valve #6 to fill SFTs # 11 & 12.
4. SFTs # 11 & 12 are filled and tipped; upon receiving signals that SFTs # 11 & 12 have tipped, close Valve #6 and start 30-second delay timer.
5. After 30 seconds timeout, open Valve #2 to fill SFTs # 3 & 4.
6. SFTs # 3 & 4 are filled and tipped; upon receiving signals that SFTs # 3 & 4 have tipped, close Valve #2 and start 30-second delay timer.
7. After 30 seconds timeout, open Valve #7 to fill SFTs # 13 & 14.

¹ Due to possible low water pressure, a 30-Seconds Delay Timer is added in the program between water valves operation.

| | | | |
|------------|--|----------------|---------------------|
| Title: | Detailed Sewer System Operation – Greenhill CSO Tank #2 (HCS06) | | |
| Document # | PW-WW-PO-P-011-HCS06-1004-001 | Document Level | Sectional (4) |
| Issue #: | 3 | Issue Date: | January 2019 |

8. SFTs # 13 & 14 are filled and tipped; upon receiving signals that SFTs # 13 & 14 have tipped, close Valve #7 and start 30-second delay timer.
9. After 30 seconds timeout, open Valve #3 to fill SFTs # 5 & 6.
10. SFTs # 5 & 6 are filled and tipped; upon receiving signals that SFTs # 5 & 6 have tipped, close Valve #3 and start 30-second delay timer.
11. After 30 seconds timeout, open Valve #8 to fill SFTs # 15 & 16.
12. SFTs # 15 & 16 are filled and tipped; upon receiving signals that SFTs # 15 & 16 have tipped, close Valve #8 and start 30-second delay timer.
13. After 30 seconds timeout, open Valve #4 to fill water in SFTs # 7 & 8.
14. SFTs # 7 & 8 are filled and tipped; upon receiving signals that SFTs # 7 & 8 have tipped, close Valve #4 and start 30-second delay timer.
15. After 30 seconds timeout, open Valve #9 to fill SFTs # 17 & 18.
16. SFTs # 17 & 18 are filled and tipped; upon receiving signals that SFTs # 17 & 18 have tipped, then close Valve #9 and start 30-second delay timer.
17. After 30 seconds timeout, open Valve #5 to fill SFTs # 9 & 10.
18. SFTs # 9 & 10 are filled and tipped; upon receiving both signals that SFTs # 9 & 10 have tipped, close Valve #5 and start 30-second delay timer.
19. After 30 seconds timeout, open Valve #10 for SFTs # 19 & 20.
20. SFTs # 19 & 20 are filled and tipped; upon receiving both signals that SFTs # 19 & 20 have tipped, then close Valve #10.

This completes the flushing of Cell 1.

To Flush Cell 2:

1. Open Solenoid Valve #20 to fill SFTs # 40 & 39.
2. SFTs # 40 & 39 are filled and tipped; upon receiving signals that SFTs # 40 & 39 have tipped, close Valve #20 and start 30-second delay timer.
3. After 30 seconds timeout, open Valve #15 to fill SFTs # 30 & 29.
4. SFTs # 30 & 29 are filled and tipped; upon receiving signals that SFTs # 30 & 29 have tipped, then close Valve #15 and start 30-second delay timer.
5. After 30 seconds timeout, open Valve #19 to fill SFTs # 38 & 37.
6. SFTs # 38 & 37 are filled and tipped; upon receiving signals that SFTs # 38 & 37 have tipped, close Valve #19 and start 30-second delay timer.
7. After 30 seconds timeout, open Valve #14 to fill SFTs # 28 & 27.
8. SFTs # 28 & 27 are filled and tipped; upon receiving signals that SFTs # 28 & 27 have tipped, close Valve #14 and start 30-second delay timer.
9. After 30 seconds timeout, open Valve #18 to fill SFTs # 36 & 35.
10. SFTs # 36 & 35 are filled and tipped; upon receiving signals that SFTs # 36 & 35 have tipped, close Valve #18 and start 30-second delay timer.
11. After 30 seconds timeout, open Valve# 13 to fill SFTs # 26 & 25.
12. SFTs # 26 & 25 are filled and tipped; upon receiving signals that SFTs # 26 & 25 have tipped, close Valve #13 and start 30-second delay timer.
13. After 30 seconds timeout, open Valve# 17 to fill SFTs # 34 & 33.
14. SFTs # 34 & 33 are filled and tipped; upon receiving signals that SFTs # 34 & 33 have tipped, close Valve #17 and start 30-second delay timer.
15. After 30 seconds timeout, open Valve# 12 to fill SFTs # 24 & 23.
16. SFTs # 24 & 23 are filled and tipped; upon receiving signals that SFTs # 24 & 23 have tipped, close Valve #12 and start 30-second delay timer.
17. After 30 seconds timeout, open Valve# 16 to fill SFTs # 32 & 31.

| | | | |
|------------|--|----------------|---------------------|
| Title: | Detailed Sewer System Operation – Greenhill CSO Tank #2 (HCS06) | | |
| Document # | PW-WW-PO-P-011- HCS06-1004-001 | Document Level | Sectional (4) |
| Issue #: | 3 | Issue Date: | January 2019 |

18. SFTs # 32 & 31 are filled and tipped; upon receiving signals that SFTs # 32 & 31 have tipped, close Valve #16 and start 30-second delay timer.
19. After 30 seconds timeout, open Valve #11 to fill SFTs # 23 & 22.
20. SFTs # 22 & 21 are filled and tipped; upon receiving signals that SFTs # 22 & 21 have tipped, close Valve #11.

This completes the flushing of Cell 2.

- 5.6.5 A timer (6 minutes) is set up in the PLC programs so that if a solenoid water valve fails to actuate or the proximity switch to indicate the buckets have tipped is broken, the program will automatically advance to the next pair of valves/SFTs. This value is not adjustable from the SCADA screen.

6 INSPECTION & MAINTENANCE

6.1 Annual Inspections

- 6.1.1 An Annual Inspection of the facilities should be conducted, as outlined in the City's O-M1 Wastewater Station Inspections (CSO Stations) Procedure, where applicable including but not limited to:

- Health and Safety, including fire extinguishers
- General Facility, including lighting, heating and ventilation, and general condition of the premises (building, grounds, doors, etc)
- Sewage Pumps, including pump run tests and checking of pumps for bearing/motor heat/noise and air locks, and checking of breakers
- Sluice Gates, including exercising of gates to confirm proper operation, only where the gates can be exercised without risk of sewage discharges to the environment
- Wet Well, including well level controls, signs of scum/debris accumulation, piping and valves, ventilation and lighting
- Flushing System, including testing of system in SCADA Auto mode, verifying SFTs are tipping and emptying properly, checking valve chambers for leaks, and reporting any abnormalities
- Water Quality Samplers, including testing to confirm proper operation
- Documenting any significant Odours noticed outside the station
- Other Operational Checks, including control panels, SCADA alarms, backflow preventers, electric hoists, hatch covers, well level controls

| | | | |
|------------|--|----------------|---------------------|
| Title: | Detailed Sewer System Operation – Greenhill CSO Tank #2 (HCS06) | | |
| Document # | PW-WW-PO-P-011-HCS06-1004-001 | Document Level | Sectional (4) |
| Issue #: | 3 | Issue Date: | January 2019 |

6.1.2 Specific to HCS06, annual position checks and exercising of all motorized sluice gates associated with the facility to confirm they are in proper working order.

6.2 Monthly Inspections

6.2.1 Specific to HCS06, monthly inspections of the CSO Tank Inlet Gate to confirm it is in the Fully Open position.

6.2.2 Specific to HCS06, monthly inspections of the Manual Stop Gate in the CSO Tank Inlet Chamber to confirm it is in its correct default position, diverting all flow towards HCS06, and that no sewage is leaking around the edges of the stop gate. The latter can be accomplished by visual inspection of the chamber/pipe on the downstream side of the stop gate, which can be viewed from above by opening the access hatch cover on top of the stop gate. The air pressure of the inflatable bladder around the outside of the stop gate (which provides the seal around the gate) should be checked to ensure the seal is tight to prevent any possibility of sewage discharge downstream of the gate (which would in any case continue into HCS01, so would not discharge directly to the environment).

6.2.3 Specific to HCS06, monthly inspections of the Manual Stop Gate in the Overflow Gate and Chamber on the overflow channel running from HCS06 to HCS01 to confirm it is in its correct default position, diverting all flow towards HCS01, and that no sewage is leaking around the edges of the stop gate into Red Hill Creek. The latter can be accomplished by visual inspection of the chamber/pipe on the downstream side of the stop gate, which can be viewed from above by opening the access hatch cover on top of the chamber. The air pressure of the inflatable bladder around the outside of the stop gate (which provides the seal around the gate) should be checked to ensure the seal is tight to prevent any possibility of sewage discharge directly into Red Hill Creek.

7 ASSOCIATED DOCUMENTS

- Lock Out / Tagging – PW-WW-PO-P-019-003
- Confined Space Procedure – PW-WW-PO-P-019-001
- Confined Space Program – WW Level III - PW-WW-P-019-001
- Confined Space Hazard Assessment Form – PO Level IV - PW-WW-PO-F-019-002
- Confined Space Entry Permit – PO Level IV - PW-WW-PO-F-019-003
- CSO Overflow Notification List – PO Level IV - PW-WW-PO-L-011-004
- Greenhill No. 2 CSO Tank (HCS06) Process Control Narrative, Version 2.4
- O-M1 Wastewater Station Inspections (CSO Stations) Procedure

BCOS software tracks the revision history of document.

| | | | |
|-------------------|---|-----------------------|---------------|
| Title: | Detailed Sewer System Operation - Red Hill CSO Pipe Facility (HCS07) | | |
| Document # | PW-WW-PO-P-011- HCS07-1004-001 | Document Level | 4 (Sectional) |
| Issue #: | 2 | Issue Date: | January 2019 |

1 PURPOSE

To provide procedures for the safe and efficient operation of the Red Hill CSO Pipe Facility (HCS07), including Chambers HCS7A/B/C.

2 SCOPE

This procedure applies to all operations staff including: Plant Operators, Process Supervisors, Maintenance staff and Superintendents involved in operations of wastewater systems.

3 DEFINITIONS

| | |
|-------|--|
| BCOS | Beyond Compliance Operating System |
| CS | Confined Space |
| CSO | Combined Sewer Overflow |
| EME | Environmental Monitoring and Enforcement |
| MLD | Mega Litres per Day |
| PO | Plant Operations |
| PW | Public Works |
| SCADA | Supervisory Control and Data Acquisition |
| SG | Sluice Gate |
| WSI | Western Sanitary Interceptor |
| WW | Wastewater |
| WWTP | Wastewater Treatment Plant |

4 RESPONSIBILITY

4.1 Manager, Plant Operations / Manager, Plant Maintenance & Technical Services

- Overall responsibility to ensure compliance with this procedure
- Ensure that, at all times, the facilities and related equipment and appurtenances used to achieve the compliance with this procedure are properly operated and maintained

| | | | |
|------------|---|----------------|---------------------|
| Title: | Detailed Sewer System Operation - Red Hill CSO Pipe Facility (HCS07) | | |
| Document # | PW-WW-PO-P-011- HCS07-1004-001 | Document Level | 4 (Sectional) |
| Issue #: | 2 | Issue Date: | January 2019 |

4.2 Superintendent, Wastewater Treatment Process

- Update this procedure as required to ensure its accuracy
- Ensure that staff are trained on and follow this procedure
- Ensure that all the operations staff follow this procedure and respond to alarms

4.3 Process Supervisor

- Immediately report suspected problems and issues to the Superintendent, Wastewater Treatment Process
- Work with the Superintendent, Wastewater Treatment Process to develop a corrective action plan and implement it to resolve any issues

4.4 Operators

- Follow this procedure and respond to alarms
- Immediately report suspected problems and issues to the Process Supervisor
- Work with Superintendent, Wastewater Treatment Process and Process Supervisor to develop corrective action plan and to implement it to resolve the issues
- Thoroughly document with time all aspects of any incident including the identification of a potential problem, consultations, assessments, actions taken, corrective action plan, implementation of corrective actions, and actions required to prevent reoccurrence of problems

4.5 Maintenance Staff

- Follow this procedure
- Immediately report suspected problems and issues to your Supervisor

5 PROCEDURE

The Red Hill CSO Pipe Facility (HCS07) captures and stores CSOs from the former Lawrence, Queenston and Melvin CSO outfalls to Red Hill Creek. The facility stores the CSO in an oversized pipe running parallel to the existing Red Hill Creek Sanitary Interceptor (RHCSI) sewer and along the Red Hill Parkway. The oversized pipe ranges in size from 2,000 to 2,250 mm in diameter, and a series of four (4) motorized sluice gates are used to convey flows into and create temporary storage within the pipe during wet weather flow conditions, and also to control the subsequent drainage of the facility to the Woodward Avenue Wastewater Treatment Plant (WWTP) for treatment during dry weather flow conditions.

| | | | |
|------------|---|----------------|---------------------|
| Title: | Detailed Sewer System Operation - Red Hill CSO Pipe Facility (HCS07) | | |
| Document # | PW-WW-PO-P-011- HCS07-1004-001 | Document Level | 4 (Sectional) |
| Issue #: | 2 | Issue Date: | January 2019 |

HCS07 comprises three (3) flow control structures: HCS7A at Lawrence Road; HCS7B at Queenston Road; and HCS7C at Barton Street; creating two (2) storage pipe cells providing a total storage volume of approximately 14,200 m³. Cell 1 consists of a 2,250 mm diameter pipe running between HCS7A and HCS7B; and Cell 2 consists of a 2,000 mm diameter pipe running between HCS7B and HCS7C. HCS7C includes an 1,800 mm diameter sanitary sewer to drain the storage facility, and a 2,250 mm diameter overflow sewer to Red Hill Creek that only becomes active if the design capacity of the facility is exceeded.

The stored flow behind the gates can also be used to flush any sediments that may have settled at the bottom of the storage pipe cells during storage periods.

This document identifies procedures for the normal operation of HCS07 (including Chambers HCS7A, HCS7B and HCS7C), as well as procedures for confined space entry into the sluice gate chambers.

Hydro services to this station are provided by Alectra Utilities (905-522-6611).

5.1 Safety Notes and Procedures

- 5.1.1 Ensure all applicable City of Hamilton policies and procedures are applicable and followed. Refer to BCOS or PO Workspace.
- 5.1.2 The area inside the CSO storage pipe and the HCS7A, HCS7B and HCS7C sluice gate chambers are each considered a confined space (CS).
- 5.1.3 Ensure the City of Hamilton policy on Confined Space Entry (Confined Space Program PW-WW-P-019-001) is understood and followed before entry is attempted.
- 5.1.4 Ensure that the Confined Space Hazard Assessment (Confined Space Hazard Assessment Form Template PW-WW-PO-F-019-002), is completed before entry.
- 5.1.5 Ensure the CS Entry Plan (Confined Space Plan PW-WW-PO-F-019-001) and CS Entry Permit (Confined Space Entry Permit PW-WW-PO-F-019-003) are filled out prior to entry.
- 5.1.6 Ensure any lockout points are identified and locked according to Lock Out/Tag procedure (Lock Out/Tagging PW-WW-PO-P-019-003).
- 5.1.7 Use of a portable gas detector, lifeline/extraction, and two-way radios are mandatory. Fully charged breathing apparatus should be on site at all times in case of an emergency.

5.2 Procedure for Facility Entry: Routine Minor Maintenance and Inspection

NOTE: A Hazard Assessment and Project Specific Entry Procedure must be written for Construction, Major Maintenance, or for Entry by more than One Person.

| | | | |
|------------|---|----------------|---------------------|
| Title: | Detailed Sewer System Operation - Red Hill CSO Pipe Facility (HCS07) | | |
| Document # | PW-WW-PO-P-011- HCS07-1004-001 | Document Level | 4 (Sectional) |
| Issue #: | 2 | Issue Date: | January 2019 |

- 5.2.1 Fill out and execute a Confined Space Entry Permit and notify the Process Supervisor at the Woodward Avenue Wastewater Treatment Plant (WWTP) (905-546-2424 Ext 1086 or cell phone 905-570-6124) of your intent to enter HCS7A, HCS7B or HCS7C. Ensure that there is no impending rain in the weather forecast, and that all CSO pipe inflow gates are closed and locked out in the closed position, so all sewage flow is in the RCHSI, and none in HCS07.
- 5.2.2 Do not enter if the portable Methane Detection System does not register "OK". Personnel inside the chambers should carry and use a portable gas detector.
- 5.2.3 At least one person equipped with a two-way radio and flashlight should remain outside the chambers at all times, maintaining the "Confine Space Entry Permit" and communicating with the person inside the chamber via a two-way radio. All personnel should wear long sleeves, long pants, safety boots, gloves, safety vest and hardhat at all times.
- 5.2.4 The person outside the chamber should initiate contact with the person in the chamber every 10 minutes via two-way radio. If there is no response, attempt to contact a second time, and if there is no response again, initiate emergency measures.
- 5.2.5 Notify the process supervisor when leaving the site. Remove all lockouts and return all gates to "Remote" mode. Shut off all lights and exhaust fans. Reinstate the intrusion alarm and secure all doors.

5.3 Process and Equipment Overview


- 5.3.1 The older parts of the City of Hamilton are served by combined sewers, where a single sewer system conveys both sanitary sewage and stormwater runoff. During dry weather and light rainfall, the combined sewers convey all flows to the Woodward Avenue Wastewater Treatment Plant (WWTP). During heavy rainstorms, flows that exceed the capacity of the sewer system and/or the WWTP are diverted to local receiving waters. These combined sewer overflows (CSOs) are necessary in order to minimize basement flooding and overloading of the WWTP. Nearly 200 diversion structures regulate the amount of flow reaching the WWTP. The vast majority of these structures are static flow regulators where the volume of overflow is simply dependent upon the level of sewage entering the structure. Static flow regulators cannot be quickly or easily manipulated, if at all, to control the volume of flow entering the interceptors. However, the Combined Sewer System also employs a number of motorized sluice gates which can be opened or closed by operators at the Woodward Avenue WWTP to dynamically regulate the amount of flow entering the sanitary interceptors. These gates are required to reduce inflows to the WWTP Main Pumphouse during extreme storm events, in order to ensure that the WWTP is not overloaded. Centralized control of the gates is made possible via the Supervisory Control and Data Acquisition (SCADA) system.

| | | | |
|-------------------|---|-----------------------|---------------|
| Title: | Detailed Sewer System Operation - Red Hill CSO Pipe Facility (HCS07) | | |
| Document # | PW-WW-PO-P-011- HCS07-1004-001 | Document Level | 4 (Sectional) |
| Issue #: | 2 | Issue Date: | January 2019 |


- 5.3.2 The Red Hill CSO Pipe Facility (HCS07) captures and stores CSOs from the former Lawrence, Queenston and Melvin CSO outfalls to Red Hill Creek. The facility stores the CSO in an oversized pipe running parallel to the existing Red Hill Creek Sanitary Interceptor (RHCSI) sewer and along the Red Hill Parkway. The oversized pipe ranges in size from 2,000 to 2,250 mm in diameter, and a series of four (4) motorized sluice gates are used to convey flows into and create temporary storage within the pipe during wet weather flow conditions, and also to control the subsequent drainage of the facility to the Woodward Avenue Wastewater Treatment Plant (WWTP) for treatment during dry weather flow conditions.
- 5.3.3 HCS07 comprises three (3) flow control structures: HCS7A at Lawrence Road (Manhole #1); HCS7B at Queenston Road (Manhole #8); and HCS7C at Barton Street (Manhole #16); creating two (2) storage pipe cells providing a total storage volume of approximately 14,200 m³. Cell 1 consists of a 2,250 mm diameter pipe running between HCS7A and HCS7B; and Cell 2 consists of a 2,000 mm diameter pipe running between HCS7B and HCS7C.
- 5.3.4 HCS7C includes an 1,800 mm diameter sanitary sewer to drain the storage facility, and a 2,250 mm diameter overflow sewer to Red Hill Creek that only becomes active if the design capacity of the facility is exceeded.
- 5.3.5 The stored flows are drained from the facility during dry weather, when capacity is available at the Woodward Avenue WWTP to treat the flows, by opening the sluice gates in Chambers HCS7B and HCS7C.
- 5.3.6 The stored flow behind the gates can also be used to flush any sediments that may have settled at the bottom of the storage pipe cells during storage periods.

5.4 Red Hill CSO Pipe (HCS07) SCADA Screens


5.4.1 HCS07 Main SCADA Screen




5.4.2 HCS7A SCADA Screen



5.4.3 HCS7B SCADA Screen



5.4.4 HCS7C SCADA Screen



| | | | |
|-------------------|---|-----------------------|---------------|
| Title: | Detailed Sewer System Operation - Red Hill CSO Pipe Facility (HCS07) | | |
| Document # | PW-WW-PO-P-011- HCS07-1004-001 | Document Level | 4 (Sectional) |
| Issue #: | 2 | Issue Date: | January 2019 |

5.5 Dry Weather Operation

- 5.5.1 HCS7A at Lawrence Road (Manhole #1A SG-1): This gate is normally Open directing inflow to the storage pipe. It is only closed when maintenance is required on the existing 1650 mm diameter RHCSI upstream of this manhole, or while flushing the storage pipe.
- 5.5.2 HCS7A at Lawrence Road (Manhole #1A SG-2): This gate is normally Closed. It is only opened for backwashing/flushing of the CSO storage pipe.
- 5.5.3 HCG05, adjacent to HCS7A at Lawrence Road: This gate is normally Open allowing flow into the 1650 mm diameter RHCSI downstream of this gate. This gate can also be closed to reduce the flow into the RCHSI and divert that flow into the CSO storage pipe.
- 5.5.4 HCS7B at Queenston Road (Manhole #8 SG-1): This gate is normally 5% Open during dry weather allowing flow to enter the RHCSI for conveyance to the WWTP. During a wet weather event, and if the WWTP cannot handle any additional flow, the gate shall be closed with flows diverted into Cell # 1 of the CSO storage pipe.
- 5.5.5 HCS7C at Barton Street (Manhole #16 SG-1): This gate is normally 5% Open during dry weather allowing flow to enter the RHCSI for conveyance to the WWTP. During a wet weather event, and if the Woodward WWTP cannot handle any additional flow, the gate shall be closed with flows diverted into Cell 2 of the CSO storage pipe.

HCS7B Chamber #8 SG-1 and HCS7C Chamber #16 SG-1 are setpoint limited, only up to 20% Open from the Local Operator Interface, to safely control the rate of drainage of the CSO storage pipe into the RHCSI and on to the WWTP.

5.6 Wet Weather Operation - Filling of the CSO Storage Pipe

- 5.6.1 The control gates at HCS7B and HCS7C (Manholes #8 and #16) are normally 5% Open during dry weather and when there is no CSO overflowing into the storage facility. During a wet weather event, and if the Woodward WWTP cannot handle any additional flow, these two control gates shall be closed to begin filling the CSO storage pipe. Cell #1 (between HCS7A and HCS7B) fills first, followed by Cell #2 (between HCS7B and HCS7C) after Cell #1 is filled.

The liquid level in the CSO storage pipe is monitored by level sensors installed in storage Cell #1 and Cell #2.

NOTE: When putting the CSO storage pipe into service, notification must be given to the Supervisor of Environmental Monitoring and Enforcement (EME) at Ext 5678. If the CSO storage pipe overflows (at Barton Street) refer to the CSO Overflow Notification list (CSO Overflow Notification List PW-WW-PO-L-011-004) for instructions on reporting.

| | | | |
|------------|---|----------------|---------------------|
| Title: | Detailed Sewer System Operation - Red Hill CSO Pipe Facility (HCS07) | | |
| Document # | PW-WW-PO-P-011- HCS07-1004-001 | Document Level | 4 (Sectional) |
| Issue #: | 2 | Issue Date: | January 2019 |

5.7 Emptying the CSO Storage Pipe following a Rainfall Event

5.7.1 After the storm event, and when Woodward WWTP has capacity available to treat the stored flows, Cell #2 shall be drained first by opening the sluice gate at HCS7C (Manhole #16) gradually in 5% increments (5%, 10%, 15%, etc), at a flow rate that can be safely accommodated for treatment at the Woodward Avenue WWTP. After Cell 2 has been drained, Cell 1 shall be drained in the same manner until it is empty.

5.8 Flushing the CSO Storage Pipe following a Rainfall Event

5.8.1 The gates at HCS7A (Manhole #1A) can be used for maintenance and flushing purposes. Two sluice gates are installed at this structure, SG-1 and SG-2.

Gate SG-1 at HCS7A (Manhole #1A) is normally Open. It should only be Closed when maintenance is required on the existing 1650 mm diameter RHCSI upstream of this manhole, or during backwashing/flushing of the CSO storage pipe.

Gate SG-2 at HCS7A (Manhole #1A) is normally Closed. It should only be Opened for backwashing/flushing of the CSO storage pipe.

Gates SG-1 at HCS7B and HCS7C (Manholes #8 and #16) shall be set to Fully Open for flushing the storage pipe.

The storage pipe can also be scheduled to be washed down in conjunction with drainage of the Greenhill CSO tanks (HCS01 and HCS06), where the flows drained from the upstream CSO tanks will provide more flow that can also be temporarily diverted into the CSO storage pipe to provide increased flushing power.

To Flush the CSO Storage Pipe:

- Set Gate SG-1 at HCS7A (Manhole #1A) to Fully Closed (0% Open)
- Set Gate SG-2 at HCS7A (Manhole #1A) to Fully Open (100% Open)
- Set Gate SG-1 at HCS7B (Manhole #8) to Fully Open (100% Open)
- Set Gate SG-1 at HCS7C (Manhole #16) to Fully Open (100% Open)

5.8.2 Auto Sampler

The automatic water quality sampler on the CSO storage pipe overflow is located at HCS7C (Manhole #16) at Barton Street, and is set up to take a sample automatically every time the level in the chamber at HCS7C (Manhole #16) tops the elevation of the overflow weir crest @ 7.7 meters above the chamber invert.

| | | | |
|-------------------|---|-----------------------|----------------------|
| Title: | Detailed Sewer System Operation - Red Hill CSO Pipe Facility (HCS07) | | |
| Document # | PW-WW-PO-P-011- HCS07-1004-001 | Document Level | 4 (Sectional) |
| Issue #: | 2 | Issue Date: | January 2019 |

6 INSPECTION & MAINTENANCE

6.1 Annual Inspections

6.1.1 An Annual Inspection of the facilities should be conducted, as outlined in the City's O-M1 Wastewater Station Inspections (CSO Stations) Procedure, where applicable including but not limited to:

- Health and Safety, including fire extinguishers
- General Facility, including lighting, heating and ventilation, and general condition of the premises (building, grounds, doors, etc)
- Sewage Pumps, including pump run tests and checking of pumps for bearing/motor heat/noise and air locks, and checking of breakers
- Sluice Gates, including exercising of gates to confirm proper operation, only where the gates can be exercised without risk of sewage discharges to the environment
- Wet Well, including well level controls, signs of scum/debris accumulation, piping and valves, ventilation and lighting
- Bar Screens, visual inspection to confirm not blocked by debris
- Flushing System, including testing of system in SCADA Auto mode, verifying SFTs are tipping and emptying properly, checking valve chambers for leaks, and reporting any abnormalities
- Water Quality Samplers, including testing to confirm proper operation
- Documenting any significant Odours noticed outside the station
- Other Operational Checks, including control panels, SCADA alarms, backflow preventers, electric hoists, hatch covers, well level controls

6.1.2 Specific to HCS07, annual position checks and exercising of all sluice gates associated with the facility to confirm they are in proper working order.

6.1.3 Specific to HCS07, annual calibration of CSO Pipe Overflow flow metering system at Chamber HCS7C at Barton Street.

| | | | |
|-------------------|---|-----------------------|----------------------|
| Title: | Detailed Sewer System Operation - Red Hill CSO Pipe Facility (HCS07) | | |
| Document # | PW-WW-PO-P-011- HCS07-1004-001 | Document Level | 4 (Sectional) |
| Issue #: | 2 | Issue Date: | January 2019 |

7 ASSOCIATED DOCUMENTS

- Lock Out / Tagging – PW-WW-PO-P-019-003
- Confined Space Procedure – PW-WW-PO-P-019-001
- Confined Space Program – WW Level III - PW-WW-P-019-001
- Confined Space Hazard Assessment Form – PO Level IV - PW-WW-PO-F-019-002
- Confined Space Entry Permit – PO Level IV - PW-WW-PO-F-019-003
- Confined Space Plan – PW-WW-PO-F-019-001
- CSO Overflow Notification List – PW-WW-PO-L-011-004
- Red Hill Valley CSO Pipe Facility (HCS07) Process Control Narrative, Version 4.2a
- Red Hill Valley CSO Facility (HCS7A) Process Control Narrative, Version 2.3
- Red Hill Valley CSO Facility (HCS7B) Process Control Narrative, Version 2.3
- Red Hill Valley CSO Facility (HCS7C) Process Control Narrative, Version 2.3
- O-M1 Wastewater Station Inspections (Red Hill CSO) Procedure

BCOS software tracks the revision history of document.

| | | | |
|-------------------|--|-----------------------|---------------|
| Title: | Detailed Sewer System Operation – Royal Avenue CSO Tank (HCS08) | | |
| Document # | PW-WW-PO-P-011- HCS08-1004-001 | Document Level | 4 (Sectional) |
| Issue #: | 3 | Issue Date: | January 2019 |

1 PURPOSE

To provide procedures for the safe and efficient operation of the Royal Avenue CSO Storage Tank (HCS08).

2 SCOPE

This procedure applies to all operations staff including: Plant Operators, Process Supervisors, Maintenance staff and Superintendents involved in operations of wastewater systems.

3 DEFINITIONS

| | |
|-------|--|
| BCOS | Beyond Compliance Operating System |
| CS | Confined Space |
| CSO | Combined Sewer Overflow |
| MLD | Mega Litres per Day |
| PO | Plant Operations |
| PLC | Programable Logic Controller |
| PW | Public Works |
| SCADA | Supervisory Control and Data Acquisition |
| SFT | Sediment Flushing Tank |
| WW | Wastewater |
| WWTP | Wastewater Treatment Plant |

4 RESPONSIBILITY

4.1 Manager, Plant Operations / Manager, Plant Maintenance & Technical Services

- Overall responsibility to ensure compliance with this procedure
- Ensure that, at all times, the facilities and related equipment and appurtenances used to achieve the compliance with this procedure are properly operated and maintained

| | | | |
|-------------------|--|-----------------------|---------------------|
| Title: | Detailed Sewer System Operation – Royal Avenue CSO Tank (HCS08) | | |
| Document # | PW-WW-PO-P-011- HCS08-1004-001 | Document Level | 4 (Sectional) |
| Issue #: | 3 | Issue Date: | January 2019 |

4.2 Superintendent, Wastewater Treatment Process

- Update this procedure as required to ensure its accuracy
- Ensure that staff are trained on and follow this procedure
- Ensure that all the operations staff follow this procedure and respond to alarms

4.3 Process Supervisor

- Immediately report suspected problems and issues to the Superintendent, Wastewater Treatment Process
- Work with the Superintendent, Wastewater Treatment Process to develop a corrective action plan and implement it to resolve any issues

4.4 Operators

- Follow this procedure and respond to alarms
- Immediately report suspected problems and issues to the Process Supervisor
- Work with Superintendent, Wastewater Treatment Process and Process Supervisor to develop corrective action plan and to implement it to resolve the issues
- Thoroughly document with time all aspects of any incident including the identification of a potential problem, consultations, assessments, actions taken, corrective action plan, implementation of corrective actions, and actions required to prevent reoccurrence of problems

4.5 Maintenance Staff

- Follow this procedure
- Immediately report suspected problems and issues to your Supervisor

5 PROCEDURE

The Royal Avenue CSO Tank (HCS08) is located in Stroud Road Park at the east end of Royal Avenue. Inflows to the tank are regulated by a passive overflow structure (Inlet Chamber) located at the southwest corner of the park, which also provides a manual stop log that can be moved to bypass the CSO storage tank if required for maintenance purposes.

This document identifies procedures for the normal operation of HCS08, as well as procedures for confined space entry into the underground storage tank and inlet chamber.

Hydro services to this station are provided by Alectra Utilities (905-522-6611).

| | | | |
|------------|--|----------------|---------------------|
| Title: | Detailed Sewer System Operation – Royal Avenue CSO Tank (HCS08) | | |
| Document # | PW-WW-PO-P-011- HCS08-1004-001 | Document Level | 4 (Sectional) |
| Issue #: | 3 | Issue Date: | January 2019 |

5.1 Safety Notes and Procedures

- 5.1.1 Ensure all applicable City of Hamilton policies and procedures are understood and followed. Refer to BCOS or PO Workspace.
- 5.1.2 The area inside the storage tank and inlet chamber are both considered to be a confined space (CS).
- 5.1.3 Smoking is not permitted inside the CSO tank, inlet chamber, or effluent flow monitoring chamber.
- 5.1.4 Ensure the City of Hamilton policy on Confined Space Entry (Confined Space Program PW-WW-P-019-001) is understood and followed before entry is attempted.
- 5.1.5 Ensure the Confined Space Hazard Assessment (Confined Space Hazard Assessment Form Template PW-WW-PO-F-019-002) is completed before entry.
- 5.1.6 Ensure the CS Entry Plan (Confined Space Plan PW-WW-PO-F-019-001) and CS Entry Permit (Confined Space Entry Permit PW-WW-PO-F-019-003) are filled out prior to entry.
- 5.1.7 Ensure any lockout points are identified and locked according to Lock Out/Tag procedure (Lock Out/Tagging PW-WW-PO-P-019-003).
- 5.1.8 Use of a portable gas detector, lifeline/extraction, and two-way radios are mandatory. Fully charged breathing apparatus should be on site at all times in case of an emergency.

5.2 Procedure for Tank Entry: Routine Minor Maintenance and Inspection

NOTE: A Hazard Assessment and Project Specific Entry Procedure must be written for Construction, Major Maintenance, or for Entry by more than One Person.

- 5.2.1 Fill out and execute a Confined Space Entry Permit and notify the Process Supervisor at the Woodward Avenue Wastewater Treatment Plant (WWTP) (905-546-2424 Ext 1086 or cell phone 905-570-6124) of your intent to enter the tank. Ensure that there is no impending rain in the weather forecast, the tank floor has been cleaned and is empty, and the washing system is turned off. The tank may have some liquid in it. Entry can be made so long as gas levels are within acceptable levels.
- 5.2.2 When entering the control room, shut off the intrusion alarm.
- 5.2.3 When entering the tank, ensure that it has been flushed and the flushing system has been locked out. The tank may not need to be washed every time there is an entry. Gas testing will determine if the tank needs to be washed. If there is no gas, then there is no need to wash the tank.
- 5.2.4 Leave all pumps in “Auto” position to ensure that any flow into the tank is pumped out.
- 5.2.5 Exercise care when entering the tank, as the steps can be slippery.

Printed copies (unless noted) are uncontrolled. Do Not Photocopy.

Page 3 of 10

| | | | |
|-------------------|--|-----------------------|---------------|
| Title: | Detailed Sewer System Operation – Royal Avenue CSO Tank (HCS08) | | |
| Document # | PW-WW-PO-P-011- HCS08-1004-001 | Document Level | 4 (Sectional) |
| Issue #: | 3 | Issue Date: | January 2019 |

- 5.2.6 Do not enter if the portable Methane Detection System does not register “OK”. Personnel inside the tank should carry and use a portable gas detector.
- 5.2.7 At least one person equipped with a two-way radio and flashlight should remain outside the tank/chamber at all times, maintaining the Confined Space Entry Permit and communicating with the person inside the tank via a two-way radio. All personnel should wear long sleeves, long pants, safety boots, gloves, safety vest and hardhat at all times.
- 5.2.8 The person outside the tank/chamber should initiate contact with the person in the tank every 10 minutes via two-way radio. If there is no response, attempt to contact a second time, and if there is no response again, initiate emergency measures.
- 5.2.9 Notify the process supervisor when leaving the site. Remove all lockouts and return all gates to “Remote” mode. Shut off all lights and exhaust fans. Reinstate the intrusion alarm and secure all doors.

5.3 Process and Equipment Overview

- 5.3.1 The City has constructed a 15,000 m³ CSO detention storage tank to control existing CSOs discharging to Chedoke Creek at the Royal CSO outfall. The CSO tank is located in the northeast corner of the City-owned parkland on the northeast corner of Royal Avenue and Stroud Road. The underground storage tank will capture CSO prior to discharge and store it during wet weather. During dry weather, the captured CSO will be pumped back into the collection system and conveyed to the Woodward Avenue Wastewater Treatment Plant (WWTP) for full treatment. Settled solids that remain in the tanks after the liquid contents are emptied will be washed from the floor of the tanks and also conveyed to the WWTP. Floating debris will be contained in the tank by underflow baffles located over the CSO tank overflow weir. All equipment at the facilities, including flow control gates, floor cleaning system, pumps, monitoring devices and status indicator alarms is connected to the City’s Supervisory Control and Data Acquisition (SCADA) system, so that operators at the Woodward WWTP can monitor and operate all equipment at the tanks remotely. The control building, located at the northeast corner of the storage tank, includes two separate rooms; one to house the electrical controls, and another to house the water valves that control the distribution of water to the sediment flushing buckets and the influent and effluent water quality samplers.
- 5.3.2 The site originally included a CSO Regular chamber that employed a motorized sluice gate to dynamically control the rate of flow conveyed to the Woodward WWTP. This sluice gate has been removed, and control of the flow conveyed to the WWTP and the new CSO tank is now accomplished passively by a 525 mm drop pipe located in the new diversion chamber at the east end of Royal Avenue. During dry weather and small storm events, the drop pipe will convey all flow into the downstream 900mm

| | | | |
|------------|--|----------------|---------------------|
| Title: | Detailed Sewer System Operation – Royal Avenue CSO Tank (HCS08) | | |
| Document # | PW-WW-PO-P-011- HCS08-1004-001 | Document Level | 4 (Sectional) |
| Issue #: | 3 | Issue Date: | January 2019 |

sanitary sewer and on to the WWTP. During larger storm events, the drop pipe will fill to capacity and excess flows will be diverted to the CSO tank after passing through a coarse bar screen. Filling of the CSO Tank will occur passively without any actions having to be initiated by the Operators or the SCADA screen.

- 5.3.3 The rectangular storage tank is approximately 41 m long x 37 m wide x 10 m deep. Inside the tank, three (3) submersible pumps are provided to empty the tank, and six (6) sediment flushing tanks (SFTs) are provided to clean the floor of the tank after each use. The primary access/regress in/out of the storage tank is provided via a permanent stairway located along the west wall of the storage tank, and the access to the stairs is covered by a large hatch at the ground surface. A secondary access/regress is provided via a manhole located at the northeast corner of the tank, which includes multiple landing areas and guides for fall-arrest equipment. Additional access hatches are provided above the submersible pumps in the southwest corner of the tank to facilitate the removal and installation of each pump for maintenance or repairs as required. Multiple access hatches for the sediment flushing tanks are provided along a concrete pad running the length of the north wall of the tank. A 200 mm diameter vent, located at the northeast corner of the tank, and disguised as a flagpole, provides a means for air to exit the tank as it is displaced by incoming sewage. However, the majority of the air will exit the tank via the CSO tank overflow sewer, where it will then flow into the existing box culvert at the northeast corner of the site.
- 5.3.4 CSO is conveyed to the storage tank by a 2400 mm x 2400 mm step sewer. The inlet sewer is designed to operate under surcharge, dependent upon the level of the sewage in the CSO storage tank, and air relief is provided along the roof of the sewer to prevent flow from choking due to air pockets that may form after the level of sewage in the storage tank rises above the obvert of the downstream end of the sewer, where it enters the tank. A removable stainless steel bar screen is provided at the upstream end of the CSO tank inlet sewer to capture debris to protect the sewage pumps in the storage tank. The bars have a spacing of 100 mm, and area inclined at an angle of 45° with the floor of the sewer. The bars span the width of the inlet sewer, but extend only 600 mm up from the floor of the sewer to ensure they cannot become plugged and cause upstream flooding. An emergency bypass is provided at the upstream end of the CSO tank inlet sewer to permit future isolation of the CSO storage tank in emergencies and during special maintenance activities, and a 2400 mm wide x 2000 mm deep box culvert is provided to divert flow to the Chedoke Creek in such special circumstances. The chamber located at the intersection of the incoming box sewer and outgoing CSO tank inlet and emergency bypass sewers includes two sets of guides for alternate placement of a single stop log to control the direction of flow. Under normal operation, the stop log will be inserted in the guides over upstream end of the emergency bypass sewer, sending all excess wet weather flow to the CSO storage tank. To operate the emergency bypass, the stop log will have to be physically

| | | | |
|-------------------|--|-----------------------|----------------------|
| Title: | Detailed Sewer System Operation – Royal Avenue CSO Tank (HCS08) | | |
| Document # | PW-WW-PO-P-011- HCS08-1004-001 | Document Level | 4 (Sectional) |
| Issue #: | 3 | Issue Date: | January 2019 |


removed and inserted in the guides over the upstream end of the CSO tank inlet sewer. Only one stop log is provided, making it impossible to block the flow of both sewers at the same time.

- 5.3.5 Inside the storage tank, a stainless steel baffle is provided along the length of the overflow weir, suspended from the roof of the tank, to retain floatables and oils inside the CSO storage tank, so they can be subsequently pumped from the tank and conveyed to the Woodward WWTP for treatment. A 5400 mm wide x 1800 mm deep box culvert is provided at the northeast corner of the site. A flow meter and water quality sampler are installed in the CSO tank overflow sewer to monitor the future performance of the facility. A 300 mm high, stainless steel weir, with a 150 mm high square-notch, is installed in the overflow sewer to improve the measurement of smaller overflow rates.
- 5.3.6 Three (3) 250 L/sec submersible pumps are provided to pump the contents of the storage tank back into the combined sewer system in dry weather, for subsequent conveyance to the Woodward WWTP. The contents of the CSO tank will be drained and conveyed to the WWTP only during dry weather, when the capacity is available to treat these flows. Three (3) pumps are provided, but only one pump will run at any given time. The other 2 pumps are provided for redundancy, ensuring an extra pump is available even if one pump is out for maintenance or repairs. The flow from the pumps will be conveyed south via three (3) 400 mm diameter, ductile iron forcemains into the relocated 900 mm sanitary sewer running east along the south wall of the tank.
- 5.3.7 Six (6) stainless steel sediment flushing tanks (SFTs) are employed to clean the floor of the storage tank following each use. The SFTs are suspended above the floor along the back (north) wall of the storage tank. The SFTs will be filled with potable water, and when full, they will tip and empty their contents down the back wall of the storage tank. The flush water will continue down the sloped floor of the storage tank at a high velocity and wash the solids from the floor. The floor of the tank is sloped, and small containment walls are provided along the floor of the tank between each flushing bay to maintain the momentum and velocity of the flow from the flushing buckets. A 2400 mm wide x 1500 mm deep trough along the south wall of the tank will collect the wash water and channel it to the submersible pumps used to drain the storage tank. The wash water collection trough is sloped toward the sump containing the sewage pumps to reduce the possibility of sediment remaining on the trough slopes. A 150 mm diameter water line is provided from the 150 mm watermain on Stroud Road to supply the water to fill the sediment flushing buckets. The water line terminates inside the control building at the northeast corner of the tank, which houses the valves employed to distribute the water to the flushing buckets.
- 5.3.8 All equipment at the Royal Avenue CSO Tank, including the submersible sewage pumps; the sediment flushing tanks and the valves that deliver water to them; sewage

| | | | |
|-------------------|--|-----------------------|---------------------|
| Title: | Detailed Sewer System Operation – Royal Avenue CSO Tank (HCS08) | | |
| Document # | PW-WW-PO-P-011- HCS08-1004-001 | Document Level | 4 (Sectional) |
| Issue #: | 3 | Issue Date: | January 2019 |

level sensors; flow-meters; water quality samplers; and numerous other devices and status indicators and alarms; are connected to a programmable logic controller (PLC) in the control building, which records and stores information from these devices, and provides a means of locally operating the sewage pumps and cleaning system. The PLC is connected to the City’s SCADA system, which provides the capability to control the storage tank remotely from the Woodward WWTP.

5.4 Royal Avenue CSO Tank (HCS08) SCADA Screen



5.5 Dry Weather Operation (Manual)

5.5.1 Set pumps in the CSO tank to “Start/Dry” via the SCADA system:

1. Go to the HCS08 screen on SCADA
2. Select CSO Pumps System Control “Start/Dry”

5.6 Wet Weather Operation

5.6.1 CSO enters the City’s storage tanks by gravity, but the rate of filling of the tanks can be increased by closing motorized gates and/or disabling pumps at each of the facilities. This wet weather operation mode begins at the Greenhill CSO Tank, and is initiated when:

- The wet well level at the Woodward Avenue WWTP exceeds 66 m, and
- The flow rate into the Woodward Avenue WWTP exceeds 350 MLD

| | | | |
|-------------------|--|-----------------------|---------------|
| Title: | Detailed Sewer System Operation – Royal Avenue CSO Tank (HCS08) | | |
| Document # | PW-WW-PO-P-011- HCS08-1004-001 | Document Level | 4 (Sectional) |
| Issue #: | 3 | Issue Date: | January 2019 |

5.6.2 As the flow rate at the plant increases, filling rates at other facilities are also increased. The Royal Avenue CSO Tank (HCS08) fills passively by gravity, when the capacity of the 525 mm dry weather flow drop pipe in the tank inlet chamber at the southwest corner of the park is exceeded.

5.6.3 For the Royal Avenue CSO Tank (HCS08), set the pumps in the tank to “Stop/Storm” via the SCADA system.

1. Go to the HCS08 screen on SCADA
2. Select CSO Pumps System Control “Stop/Storm”

NOTE: When putting the CSO tank into wet weather mode, notification must be given to the Supervisor of Environmental Monitoring and Enforcement (EME) at Ext 5678. When the CSO tank overflows, refer to the CSO Overflow Notification List (CSO Overflow Notification List PW-WW-PO-L-011-004).

5.7 Emptying the Tank following a Rainfall Event

5.7.1 Following a storm, when the Woodward Avenue WWTP can accept more flow, the James Street and Greenhill tanks are emptied first. CSO Tanks should be emptied based on priority given to tanks that are closest to overflowing.

5.7.2 For the Royal Avenue CSO Tank, set the pumps in the CSO tank to “Start/Dry” through the SCADA system:

1. Bring up the MAP screen
2. Select CSO Pumps System Control “Start/Dry”

5.8 Washing the Tank following a Rainfall Event

5.8.1 The CSO tank should be cleaned after each use. When the sewage level in the tank has dropped below 1.1 m, tank washing may commence via the SCADA system:

1. Go to the HCS08 screen on SCADA
2. Select Start on the “Wash Tank” icon

6 INSPECTION & MAINTENANCE

6.1 Annual Inspections

6.1.1 An Annual Inspection of the facilities should be conducted, as outlined in the City’s O-M1 Wastewater Station Inspections (CSO Stations) Procedure, where applicable including but not limited to:

- Health and Safety, including fire extinguishers
- General Facility, including lighting, heating and ventilation, and general condition of the premises (building, grounds, doors, etc)

| | | | |
|-------------------|--|-----------------------|---------------------|
| Title: | Detailed Sewer System Operation – Royal Avenue CSO Tank (HCS08) | | |
| Document # | PW-WW-PO-P-011- HCS08-1004-001 | Document Level | 4 (Sectional) |
| Issue #: | 3 | Issue Date: | January 2019 |

- Sewage Pumps, including pump run tests and checking of pumps for bearing/motor heat/noise and air locks, and checking of breakers
- Sluice Gates, including exercising of gates to confirm proper operation, only where the gates can be exercised without risk of sewage discharges to the environment
- Wet Well, including well level controls, signs of scum/debris accumulation, piping and valves, ventilation and lighting
- Bar Screens, visual inspection to confirm not blocked by debris
- Flushing System, including testing of system in SCADA Auto mode, verifying SFTs are tipping and emptying properly, checking valve chambers for leaks, and reporting any abnormalities
- Water Quality Samplers, including testing to confirm proper operation
- Documenting any significant Odours noticed outside the station
- Other Operational Checks, including control panels, SCADA alarms, backflow preventers, electric hoists, hatch covers, well level controls

6.1.2 Specific to HCS08, annual calibration of CSO Tank Overflow flow metering system.

6.2 Monthly Inspections

6.2.1 Specific to HCS08, monthly inspections of the Manual Stop Log in the CSO Tank Inlet Chamber to confirm that it is in its default Fully Closed Position, and that no sewage is leaking around the Stop Log. The latter can be accomplished by visual inspection of the Inlet Chamber on the downstream side of the stop gate, which can be viewed from above by opening the access hatch cover on the south side of the chamber. The air pressure of the inflatable bladder around the outside of the stop gate (which provides the seal around the gate) should be checked to ensure the seal is tight to prevent any possibility of sewage discharge to Chedoke Creek.

| | | | |
|-------------------|--|-----------------------|----------------------|
| Title: | Detailed Sewer System Operation – Royal Avenue CSO Tank (HCS08) | | |
| Document # | PW-WW-PO-P-011- HCS08-1004-001 | Document Level | 4 (Sectional) |
| Issue #: | 3 | Issue Date: | January 2019 |

7 ASSOCIATED DOCUMENTS

- CSO Overflow Notification List – PW-WW-PO-L-011-004
- Lock Out / Tagging – PW-WW-PO-P-019-003
- Confined Space Plan – PW-WW-PO-F-019-001
- Confined Space Procedure – PW-WW-PO-P-019-001
- Confined Space Program – WW Level III - PW-WW-P-019-001
- Confined Space Hazard Assessment Form – PO Level IV - PW-WW-PO-F-019-002
- Confined Space Entry Permit – PO Level IV - PW-WW-PO-F-019-003
- Royal Ave. CSO Tank (HCS08) Process Control Narrative, Version 1.3
- O-M1 Wastewater Station Inspections (CSO Stations) Procedure

BCOS software tracks the revision history of document.

| | | | |
|-------------------|--|-----------------------|---------------|
| Title: | Detailed Sewer System Operation – McMaster CSO Tank (HCS09) | | |
| Document # | PW-WW-PO-P-011- HCS08-1004-001 | Document Level | 4 (Sectional) |
| Issue #: | 1 | Issue Date: | January 2019 |

1 PURPOSE

To provide procedures for the safe and efficient operation of the McMaster CSO Storage Tank (HCS09).

2 SCOPE

This procedure applies to all operations staff including: Plant Operators, Process Supervisors, Maintenance staff and Superintendents involved in operations of wastewater systems.

3 DEFINITIONS

| | |
|-------|--|
| BCOS | Beyond Compliance Operating System |
| CS | Confined Space |
| CSO | Combined Sewer Overflow |
| EME | Environmental Monitoring and Enforcement |
| MLD | Mega Litres per Day |
| PO | Plant Operations |
| PLC | Programable Logic Controller |
| PW | Public Works |
| SCADA | Supervisory Control and Data Acquisition |
| SFT | Sediment Flushing Tank |
| WW | Wastewater |
| WWTP | Wastewater Treatment Plant |

4 RESPONSIBILITY

4.1 Manager, Plant Operations / Manager, Plant Maintenance & Technical Services

- Overall responsibility to ensure compliance with this procedure
- Ensure that, at all times, the facilities and related equipment and appurtenances used to achieve the compliance with this procedure are properly operated and maintained

| | | | |
|-------------------|--|-----------------------|----------------------|
| Title: | Detailed Sewer System Operation – McMaster CSO Tank (HCS09) | | |
| Document # | PW-WW-PO-P-011- HCS08-1004-001 | Document Level | 4 (Sectional) |
| Issue #: | 1 | Issue Date: | January 2019 |

4.2 Superintendent, Wastewater Treatment Process

- Update this procedure as required to ensure its accuracy
- Ensure that staff are trained on and follow this procedure
- Ensure that all the operations staff follow this procedure and respond to alarms

4.3 Process Supervisor

- Immediately report suspected problems and issues to the Superintendent, Wastewater Treatment Process
- Work with the Superintendent, Wastewater Treatment Process to develop a corrective action plan and implement it to resolve any issues

4.4 Operators

- Follow this procedure and respond to alarms
- Immediately report suspected problems and issues to the Process Supervisor
- Work with Superintendent, Wastewater Treatment Process and Process Supervisor to develop corrective action plan and to implement it to resolve the issues
- Thoroughly document with time all aspects of any incident including the identification of a potential problem, consultations, assessments, actions taken, corrective action plan, implementation of corrective actions, and actions required to prevent reoccurrence of problems

4.5 Maintenance Staff

- Follow this procedure
- Immediately report suspected problems and issues to your Supervisor

5 PROCEDURE

The McMaster CSO Tank (HCS09) is located at McMaster University in the far southwest corner of their Zone M (lower) parking lot on the west side of Cootes Drive.

Wet weather inflows to the tank are regulated by a passive CSO weir at Ewen Road and Main Street West. The CSO tank includes a motorized sluice gate (CSO Tank Inlet Gate) at the southwest corner of the tank that controls flow into the tank, which is normally left in the Fully Open position to allow all flow to enter the storage tank.

The CSO Tank Inlet Gate (if Fully Closed) can also be used to provide a bypass of the storage tank in emergencies or during special maintenance activities, and a manual stop log provided inside the CSO Tank Overflow Chamber can be used to further

| | | | |
|-------------------|--|-----------------------|----------------------|
| Title: | Detailed Sewer System Operation – McMaster CSO Tank (HCS09) | | |
| Document # | PW-WW-PO-P-011- HCS08-1004-001 | Document Level | 4 (Sectional) |
| Issue #: | 1 | Issue Date: | January 2019 |

isolate the CSO storage tank for special maintenance activities to be conducted within the tank itself. The stop log is normally in a resting position above the CSO Tank Overflow so it does not affect the normal hydraulic operation of the tank.

NOTE: The CSO Tank Inlet Gate has been padlocked in the Fully Open position to ensure all incoming sewage flows are conveyed into the CSO storage tank and eliminate the possibility of any dry weather sewage discharges to Ancaster Creek.

This document identifies procedures for the normal operation of HCS09, as well as procedures for confined space entry into the underground storage tank, inlet and overflow chambers, and maintenance bypass channel.

Hydro services to this station are provided by Alectra Utilities (905-522-6611).

5.1 Safety Notes and Procedures

- 5.1.1 Ensure all applicable City of Hamilton policies and procedures are understood and followed. Refer to BCOS or PO Workspace.
- 5.1.2 The area inside the storage tank and inlet chamber are both considered to be a confined space (CS).
- 5.1.3 Smoking is not permitted inside the CSO tank, inlet and overflow chambers, or the maintenance bypass channel.
- 5.1.4 Ensure the City of Hamilton policy on Confined Space Entry (Confined Space Program PW-WW-P-019-001) is understood and followed before entry is attempted.
- 5.1.5 Ensure the Confined Space Hazard Assessment (Confined Space Hazard Assessment Form Template PW-WW-PO-F-019-002) is completed before entry.
- 5.1.6 Ensure the CS Entry Plan (Confined Space Plan PW-WW-PO-F-019-001) and CS Entry Permit (Confined Space Entry Permit PW-WW-PO-F-019-003) are filled out prior to entry.
- 5.1.7 Ensure any lockout points are identified and locked according to Lock Out/Tag procedure (Lock Out/Tagging PW-WW-PO-P-019-003).
- 5.1.8 Use of a portable gas detector, lifeline/extraction, and two-way radios are mandatory. Fully charged breathing apparatus should be on site at all times in case of an emergency.

| | | | |
|-------------------|--|-----------------------|---------------|
| Title: | Detailed Sewer System Operation – McMaster CSO Tank (HCS09) | | |
| Document # | PW-WW-PO-P-011- HCS08-1004-001 | Document Level | 4 (Sectional) |
| Issue #: | 1 | Issue Date: | January 2019 |

5.2 Procedure for Tank Entry: Routine Minor Maintenance and Inspection

NOTE: A Hazard Assessment and Project Specific Entry Procedure must be written for Construction, Major Maintenance, or for Entry by more than One Person.

- 5.2.1 Fill out and execute a Confined Space Entry Permit and notify the Process Supervisor at the Woodward Avenue Wastewater Treatment Plant (WWTP) (905-546-2424 Ext 1086 or cell phone 905-570-6124) of your intent to enter the tank. Ensure that there is no impending rain in the weather forecast, the tank floor has been cleaned and is empty, and the washing system is turned off. The tank may have some liquid in it. Entry can be made so long as gas levels are within acceptable levels.
- 5.2.2 When entering the control room, shut off the intrusion alarm.
- 5.2.3 When entering the tank, ensure that it has been flushed and the flushing system has been locked out. The tank may not need to be washed every time there is an entry. Gas testing will determine if the tank needs to be washed. If there is no gas, then there is no need to wash the tank.
- 5.2.4 Leave all pumps in “Auto” position to ensure that any flow into the tank is pumped out.
- 5.2.5 Exercise care when entering the tank, as the steps can be slippery.
- 5.2.6 Do not enter if the portable Methane Detection System does not register “OK”. Personnel inside the tank should carry and use a portable gas detector.
- 5.2.7 At least one person equipped with a two-way radio and flashlight should remain outside the tank/chamber at all times, maintaining the Confined Space Entry Permit and communicating with the person inside the tank via a two-way radio. All personnel should wear long sleeves, long pants, safety boots, gloves, safety vest and hardhat at all times.
- 5.2.8 The person outside the tank/chamber should initiate contact with the person in the tank every 10 minutes via two-way radio. If there is no response, attempt to contact a second time, and if there is no response again, initiate emergency measures.
- 5.2.9 Notify the process supervisor when leaving the site. Remove all lockouts and return all gates to “Remote” mode. Shut off all lights and exhaust fans. Reinstate the intrusion alarm and secure all doors.

5.3 Process and Equipment Overview

- 5.3.1 The McMaster CSO Tank (HCS09) is an underground reinforced concrete structure that provides approximately 5,935 m³ of CSO storage capacity. The storage volume is provided within a rectangular tank, which is approximately 50 m long x 18 m wide x 6.6 m deep. When the tank is full, some additional CSO storage volume is provided within the upstream CSO tank inlet sewer.

| | | | |
|-------------------|--|-----------------------|---------------|
| Title: | Detailed Sewer System Operation – McMaster CSO Tank (HCS09) | | |
| Document # | PW-WW-PO-P-011- HCS08-1004-001 | Document Level | 4 (Sectional) |
| Issue #: | 1 | Issue Date: | January 2019 |

5.3.2 A maintenance bypass is provided at the southwest corner of the storage tank, where the CSO inflow sewer enters the tank, to provide a means to bypass flows around the storage tank, to permit future isolation of the CSO storage tank in emergencies and during special maintenance activities.

5.3.3 Under normal operation, the CSO Tank Inlet Gate is Fully Open and the manual stop log over the end of the CSO tank overflow sewer is removed (sitting in guides above the end of the CSO tank overflow sewer), to allow all incoming flow to enter the tank.

NOTE: The CSO Tank Inlet Gate has been padlocked in the Fully Open position to ensure all incoming sewage flows are conveyed into the CSO storage tank and eliminate the possibility of any dry weather sewage discharges to Ancaster Creek.

5.3.4 To operate the CSO tank bypass, in order to fully isolate the CSO tank from the CSO outfall pipe, the CSO Tank Inlet Gate must be Fully Closed and the manual stop log has to be physically removed from its default position and inserted into the alternate guides provided over the end of the CSO tank overflow sewer.

5.3.5 Inside the storage tank, a stainless-steel underflow baffle is provided along the length of the overflow weir, suspended from the roof of the tank, to retain floatables and oils inside the CSO storage tank, so they can be subsequently pumped from the tank and conveyed to the WWTP for treatment. A 2400 mm wide x 1000 mm (sloped) overflow trough is provided at the northwest corner of the tank to safely convey any overflows from the facility into the 1800 mm overflow sewer discharging to Lower Ancaster Creek

5.3.6 Three (3) 137 L/sec submersible pumps are provided to pump the contents of the storage tank back into the combined sewer system in dry weather, for subsequent conveyance to the Woodward WWTP. The contents of the CSO tank will be drained and conveyed to the WWTP only during dry weather flow conditions, when capacity is available to treat these flows. Three pumps are provided, but only one pump will run at any given time. The other 2 pumps are provided for redundancy, ensuring an extra pump is available even if one pump is out for maintenance or repairs. The flow from the pumps is lifted via three (3) 200 mm diameter, ductile iron forcemains, which feed a single 350 mm diameter forcemain running around the east and south walls of the storage tank, then south through the City’s easement within the Hydro One corridor, and finally east through the City’s right-of-way at the west end of Sanders Boulevard, to connect to the gravity operated CSS along Sanders Boulevard.


5.3.7 Three (3) stainless steel sediment flushing tanks (SFTs) are employed to clean the floor of the storage tank following each use. The SFTs are suspended above the floor along the back (north) wall of the storage tank. The SFTs are filled with potable water, and when full, they will tip and empty their contents down the back wall of the storage

| | | | |
|-------------------|--|-----------------------|----------------------|
| Title: | Detailed Sewer System Operation – McMaster CSO Tank (HCS09) | | |
| Document # | PW-WW-PO-P-011- HCS08-1004-001 | Document Level | 4 (Sectional) |
| Issue #: | 1 | Issue Date: | January 2019 |

tank. The flush water continues down the sloped floor of the storage tank at a high velocity and wash the solids from the floor. The floor of the tank is sloped, and small containment walls are provided along the floor of the tank between each flushing bay to maintain the momentum and velocity of the flow from the flushing buckets.

- 5.3.8 A 2400 mm wide x 600-1000 mm deep trough along the east wall of the tank collects the wash water and channels it to the submersible pumps used to drain the storage tank. The wash water collection trough is sloped toward the sump containing the sewage pumps to reduce the possibility of sediment remaining on the trough slopes. A 100 mm diameter water line is provided from the watermain on Sanders Boulevard to supply the water to fill the SFTs. The water line terminates inside the control building at the southwest corner of the tank, which houses the valves employed to distribute the water to the SFTs.
- 5.3.9 The facility is monitored and controlled via the City's Supervisory Control and Data Acquisition (SCADA) system by Operators at the WWTP. The motorized CSO tank inlet gate and the pumps can be operated in either full Manual, SCADA Manual, or SCADA AUTO modes. The default mode is SCADA Manual, with operation directed by Operators at the WWTP. The SCADA system includes a security system to advise of any unauthorized entries into the control building.
- 5.3.10 All equipment at the McMaster CSO Tank, including the CSO Tank Inlet Gate, the submersible sewage pumps; the sediment flushing tanks and the valves that deliver water to them; sewage level sensors; flow-meters; water quality samplers; and numerous other devices and status indicators and alarms; are connected to a programable logic controller (PLC) in the control building, which records and stores information from these devices, and provides a means of locally operating the sewage pumps and cleaning system. The PLC is connected to the City's SCADA system, which provides the capability to control the storage tank remotely from the Woodward WWTP.

5.4 McMaster CSO Tank (HCS09) SCADA Screen



5.5 Dry Weather Operation (Manual)

5.5.1 Set pumps in the CSO tank to “Start/Dry” via the SCADA system:

1. Go to the HCS09 screen on SCADA
2. Select CSO Pumps System Control “Start/Dry”

5.6 Wet Weather Operation

5.6.1 CSO enters the City’s storage tanks by gravity, but the rate of filling of the tanks can be increased by closing motorized gates and/or disabling pumps at each of the facilities. This wet weather operation mode begins at the Greenhill CSO Tank, and is initiated when:

- The wet well level at the Woodward Avenue WWTP exceeds 66 m, and
- The flow rate into the Woodward Avenue WWTP exceeds 350 MLD

5.6.2 As the flow rate at the plant increases, filling rates at other facilities are also increased. The McMaster CSO Tank (HCS09) fills passively by gravity, when the capacity of the CSO regulator (overflow weir) at Ewen Road and Main Street West is exceeded.

5.6.3 For the McMaster CSO Tank (HCS09), set the pumps in the tank to “Stop/Storm” via the SCADA system.

| | | | |
|-------------------|--|-----------------------|----------------------|
| Title: | Detailed Sewer System Operation – McMaster CSO Tank (HCS09) | | |
| Document # | PW-WW-PO-P-011- HCS08-1004-001 | Document Level | 4 (Sectional) |
| Issue #: | 1 | Issue Date: | January 2019 |

1. Go to the HCS09 screen on SCADA
2. Select CSO Pumps System Control “Stop/Storm”

NOTE: When putting the CSO tank into wet weather mode, notification must be given to the Supervisor of Environmental Monitoring and Enforcement (EME) at Ext 5678. When the CSO tank overflows, refer to the CSO Overflow Notification List (CSO Overflow Notification List PW-WW-PO-L-011-004).

5.7 Emptying the Tank following a Rainfall Event

- 5.7.1 Following a storm, when the Woodward Avenue WWTP can accept more flow, the James Street and Greenhill tanks are emptied first. CSO Tanks should be emptied based on priority given to tanks that are closest to overflowing.
- 5.7.2 For the McMaster CSO Tank, set the pumps in the CSO tank to “Start/Dry” through the SCADA system:
 1. Go to the HCS09 screen on SCADA
 2. Select CSO Pumps System Control “Start/Dry”

5.8 Washing the Tank following a Rainfall Event

- 5.8.1 The CSO tank should be cleaned after each use. When the sewage level in the tank has dropped below 1.0 m, tank washing may commence via the SCADA system:
 1. Go to the HCS09 screen on SCADA
 2. Select Start on the “Wash Tank” icon

6 INSPECTION & MAINTENANCE

6.1 Annual Inspections

- 6.1.1 An Annual Inspection of the facilities should be conducted, as outlined in the City’s O-M1 Wastewater Station Inspections (CSO Stations) Procedure, where applicable including but not limited to:
 - Health and Safety, including fire extinguishers
 - General Facility, including lighting, heating and ventilation, and general condition of the premises (building, grounds, doors, etc)
 - Sewage Pumps, including pump run tests and checking of pumps for bearing/motor heat/noise and air locks, and checking of breakers
 - Sluice Gates, including exercising of gates to confirm proper operation, only where the gates can be exercised without risk of sewage discharges to the environment
 - Wet Well, including well level controls, signs of scum/debris accumulation, piping and valves, ventilation and lighting

| | | | |
|-------------------|--|-----------------------|----------------------|
| Title: | Detailed Sewer System Operation – McMaster CSO Tank (HCS09) | | |
| Document # | PW-WW-PO-P-011-HCS08-1004-001 | Document Level | 4 (Sectional) |
| Issue #: | 1 | Issue Date: | January 2019 |

- Bar Screens, visual inspection to confirm not blocked by debris
- Flushing System, including testing of system in SCADA Auto mode, verifying SFTs are tipping and emptying properly, checking valve chambers for leaks, and reporting any abnormalities
- Water Quality Samplers, including testing to confirm proper operation
- Documenting any significant Odours noticed outside the station
- Other Operational Checks, including control panels, SCADA alarms, backflow preventers, electric hoists, hatch covers, well level controls

6.1.2 Specific to HCS09, annual calibration of CSO Tank Overflow flow metering system.

6.2 Monthly Inspections

6.2.1 Specific to HCS09, monthly inspections of the CSO Tank Inlet Gate to confirm that it is in the Fully Open position (it should be, since it has been padlocked in this position).

7 ASSOCIATED DOCUMENTS

- CSO Overflow Notification List – PW-WW-PO-L-011-004
- Lock Out / Tagging – PW-WW-PO-P-019-003
- Confined Space Plan – PW-WW-PO-F-019-001
- Confined Space Procedure – PW-WW-PO-P-019-001
- Confined Space Program – WW Level III - PW-WW-P-019-001
- Confined Space Hazard Assessment Form – PO Level IV - PW-WW-PO-F-019-002
- Confined Space Entry Permit – PO Level IV - PW-WW-PO-F-019-003
- McMaster CSO Tank (HCS09) Process Control Narrative, Version 1.4
- O-M1 Wastewater Station Inspections (CSO Stations) Procedure

BCOS software tracks the revision history of document.

| | | | |
|-------------------|---|-----------------------|---------------|
| Title: | Detailed Sewer System Operation – Wentworth/Rosemary Sluice Gate (HCG03) | | |
| Document # | PW-WW-PO-P-011- HCG03-1004-053 | Document Level | 4 (Sectional) |
| Issue #: | 4 | Issue Date: | January 2019 |

1 PURPOSE

To provide procedures for the safe and efficient operation of the Wentworth/Rosemary Sluice Gate (HCG03).

2 SCOPE

This procedure applies to all operations staff including: Plant operators, Process Supervisors, Maintenance staff and Superintendents involved in operations of wastewater systems.

3 DEFINITIONS

| | |
|-------|--|
| BCOS | Beyond Compliance Operating System |
| CS | Confined Space |
| CSO | Combined Sewer Overflow |
| MLD | Mega Litres per Day |
| PO | Plant Operations |
| PW | Public Works |
| RTC | Real Time Control |
| SCADA | Supervisory Control and Data Acquisition |
| WSI | Western Sanitary Interceptor |
| WW | Wastewater |
| WWTP | Wastewater Treatment Plant |

4 RESPONSIBILITY

4.1 Manager, Plant Operations / Manager, Plant Maintenance & Technical Services

- Overall responsibility to ensure compliance with this procedure
- Ensure that, at all times, the facilities and related equipment and appurtenances used to achieve the compliance with this procedure are properly operated and maintained

| | | | |
|-------------------|---|-----------------------|---------------|
| Title: | Detailed Sewer System Operation – Wentworth/Rosemary Sluice Gate (HCG03) | | |
| Document # | PW-WW-PO-P-011- HCG03-1004-053 | Document Level | 4 (Sectional) |
| Issue #: | 4 | Issue Date: | January 2019 |

4.2 Superintendent, Wastewater Treatment Process

- Update this procedure as required to ensure its accuracy
- Ensure that staff are trained on and follow this procedure
- Ensure that all the operations staff follow this procedure and respond to alarms

4.3 Process Supervisor

- Immediately report suspected problems and issues to the Superintendent, Wastewater Treatment Process
- Work with the Superintendent, Wastewater Treatment Process to develop a corrective action plan and implement it to resolve any issues

4.4 Operators

- Follow this procedure and respond to alarms
- Immediately report suspected problems and issues to the Process Supervisor
- Work with Superintendent, Wastewater Treatment Process and Process Supervisor to develop corrective action plan and to implement it to resolve the issues
- Thoroughly document with time all aspects of any incident including the identification of a potential problem, consultations, assessments, actions taken, corrective action plan, implementation of corrective actions, and actions required to prevent reoccurrence of problems

4.5 Maintenance Staff

- Follow this procedure
- Immediately report suspected problems and issues to your Supervisor

5 PROCEDURE

The Wentworth/Rosemary Sluice Gate (HCG03) is located in Manhole HJ06E002 at the intersection of Wentworth Street North and Rosemary Avenue.

The CSO gate regulates flows from the combined sewer on Wentworth Street North, controlling the amount of flow conveyed to the Woodward Avenue Wastewater Treatment Plant (WWTP) and/or Wentworth Street CSO Outfall Sewer in wet weather.

This document identifies procedures for the normal operation of the gate in both dry and wet weather flow, as well as procedures for confined space entry into the underground gate chamber.

Hydro services to this station are provided by Alectra Utilities (905-522-6611).

| | | | |
|-------------------|---|-----------------------|---------------|
| Title: | Detailed Sewer System Operation – Wentworth/Rosemary Sluice Gate (HCG03) | | |
| Document # | PW-WW-PO-P-011- HCG03-1004-053 | Document Level | 4 (Sectional) |
| Issue #: | 4 | Issue Date: | January 2019 |

5.1 Safety Notes and Procedure

- 5.1.1 Ensure all applicable City of Hamilton policies and procedures are understood and followed. Refer to BCOS or PO Workspace.
- 5.1.2 The area inside the chamber that contains the sluice gate and overflow weir is considered a confined space (CS).
- 5.1.3 Smoking is not permitted inside the control building or sluice gate chamber.
- 5.1.4 Ensure the City of Hamilton policy on Confined Space Entry (Confined Space Program PW-WW-P-019-001) is understood and followed before entry is attempted.
- 5.1.5 Ensure that the Confined Space Hazard Assessment (Confined Space Hazard Assessment Form Template PW-WW-PO-F-019-002), is completed before entry.
- 5.1.6 Ensure the CS Entry Plan (Confined Space Plan PW-WW-PO-F-019-001) and CS Entry Permit (Confined Space Entry Permit PW-WW-PO-F-019-003) are filled out prior to entry.
- 5.1.7 Ensure any lockout points are identified and locked according to Lock Out/Tag procedure (Lock Out/Tagging PW-WW-PO-P-019-003).

5.2 Procedure for Tank Entry: Routine Minor Maintenance and Inspection

NOTE: A Hazard Assessment and Project Specific Entry Procedure must be written for Construction, Major Maintenance, or for Entry by more than One Person.

- 5.2.1 Fill out and execute a Confined Space Entry Permit and notify the Process Supervisor at the Woodward Avenue Wastewater Treatment Plant (WWTP) (905-546-2424 Ext 1086 or cell phone 905-570-6124) of your intent to enter the sluice gate chamber. Ensure that there is no impending rain in the weather forecast. The chamber may have some flow passing through it. Entry can be made so long as gas levels are within acceptable levels.
- 5.2.2 When entering the control room/building, shut off the intrusion alarm.
- 5.2.3 Make sure the sluice gate is Open so sewage continues to enter the downstream interceptor sewer and cannot back up inside the chamber.
- 5.2.4 Do not enter the gate chamber if the portable Methane Detection System does not register “OK”. Personnel inside the tank should carry and use a portable gas detector.
- 5.2.5 At least one person equipped with a two-way radio and flashlight should remain outside the chamber at all times, maintaining the “Confine Space Entry Permit” and communicating with the person inside the chamber via a two-way radio. All personnel should wear long sleeves, long pants, safety boots, gloves, safety vest and hardhat at all times.

| | | | |
|-------------------|---|-----------------------|---------------|
| Title: | Detailed Sewer System Operation – Wentworth/Rosemary Sluice Gate (HCG03) | | |
| Document # | PW-WW-PO-P-011- HCG03-1004-053 | Document Level | 4 (Sectional) |
| Issue #: | 4 | Issue Date: | January 2019 |

- 5.2.6 The person outside the chamber should initiate contact with the person in the chamber every 10 minutes via two-way radio. If there is no response, attempt to contact a second time, and if there is no response again, initiate emergency measures.
- 5.2.7 Notify the process supervisor when leaving the site. Remove all lockouts and return all gates to “Remote” mode. Shut off all lights and exhaust fans. Reinstate the intrusion alarm and secure all doors.

5.3 Process and Equipment Overview

- 5.3.1 The older parts of the City of Hamilton are served by combined sewers, where a single sewer system conveys both sanitary sewage and stormwater runoff. During dry weather and light rainfall, the combined sewers convey all flows to the Woodward Avenue Wastewater Treatment Plant (WWTP). During heavy rainstorms, flows that exceed the capacity of the sewer system and/or the WWTP are diverted to local receiving waters. These combined sewer overflows (CSOs) are necessary in order to minimize basement flooding and overloading of the WWTP. Nearly 200 diversion structures regulate the amount of flow reaching the WWTP. The vast majority of these structures are static flow regulators where the volume of overflow is simply dependent upon the level of sewage entering the structure. Static flow regulators cannot be quickly or easily manipulated, if at all, to control the volume of flow entering the interceptors. However, the Combined Sewer System also employs a number of motorized sluice gates which can be opened or closed by operators at the Woodward Avenue WWTP to dynamically regulate the amount of flow entering the sanitary interceptors. These gates are required to reduce inflows to the WWTP Main Pump house during extreme storm events, in order to ensure that the WWTP is not overloaded. Centralized control of the gates is made possible via the Supervisory Control and Data Acquisition (SCADA) system.
- 5.3.2 The Wentworth/Rosemary Sluice Gate regulates the flow of combined sewage from a 266 ha area. The gate is located in Manhole HJ06E002 at the intersection of Wentworth Street North and Rosemary Avenue. During dry weather and small storms, a static overflow weir captures all flows and conveys them through the open gate and into the Western Sanitary Interceptor (WSI) via a 900 mm sewer on Hillyard Street. This sewer connects to the WSI at the intersection of Hillyard and Burlington Streets, and the WSI conveys the flows east to the WWTP. During larger storms, when the weir is overtopped, excess flows are diverted to the Wentworth Street CSO outfall via a 2500 mm x 2400 mm sewer on Wentworth Street North. During an emergency or where an extreme storm event requires operation of more than three (3) pumps in the WWTP Main Pump house and plant by-passing at the is imminent (Flow > 614MLD), the Process Supervisor may elect to close this sluice gate to by-pass all combined sewage through the Wentworth Street CSO Outfall. Bypassing these excess flows at

| | | | |
|-------------------|---|-----------------------|---------------|
| Title: | Detailed Sewer System Operation – Wentworth/Rosemary Sluice Gate (HCG03) | | |
| Document # | PW-WW-PO-P-011- HCG03-1004-053 | Document Level | 4 (Sectional) |
| Issue #: | 4 | Issue Date: | January 2019 |

their source provides additional protection of the WWTP and reduces the pumping of flows at the plant that would not be provided treatment in any case.

NOTE: When in Auto mode this station functions as part of the Real Time Control (RTC) system and will automatically close the isolation gate when the Western Sanitary Interceptor (WSI) reaches a high level measured at HCG14.

5.4 Dry Weather Operation (Manual)

Manually set the Wentworth/Rosemary Sluice Gate (HCG03) to “Open” via the SCADA system:

1. Go to the HCG03 screen on SCADA
2. Select “HCG03 Isolation Gate” and set to “Open”


5.5 Wet Weather Operation

When three (3) pumps are operating at the Woodward Avenue WWTP during an extreme storm and bypassing is imminent (Flow > 614 MLD), set the Wentworth/Rosemary Sluice Gate (HCG03) to “Closed” via the SCADA system:

1. Go to the HCG03 screen on SCADA
2. Select “HCG03 Isolation Gate” and set to “Closed”

| | | | |
|-------------------|---|-----------------------|---------------|
| Title: | Detailed Sewer System Operation – Wentworth/Rosemary Sluice Gate (HCG03) | | |
| Document # | PW-WW-PO-P-011- HCG03-1004-053 | Document Level | 4 (Sectional) |
| Issue #: | 4 | Issue Date: | January 2019 |

5.6 Wentworth/Rosemary Sluice Gate (HCG03) SCADA Screen



6 INSPECTION & MAINTENANCE

6.1 Annual Inspections

6.1.1 An Annual Inspection of the facilities should be conducted, as outlined in the City's O-M1 Wastewater Station Inspections (CSO Stations) Procedure, where applicable including but not limited to:

- Health and Safety, including fire extinguishers
- General Facility, including lighting, heating and ventilation, and general condition of the premises (building, grounds, doors, etc)
- Sluice Gates, including exercising of gates to confirm proper operation, only where the gates can be exercised without risk of sewage discharges to the environment
- Documenting any significant Odours noticed outside the station
- Other Operational Checks, including control panels, SCADA alarms, electric hoists, hatch covers

| | | | |
|-------------------|---|-----------------------|---------------|
| Title: | Detailed Sewer System Operation – Wentworth/Rosemary Sluice Gate (HCG03) | | |
| Document # | PW-WW-PO-P-011- HCG03-1004-053 | Document Level | 4 (Sectional) |
| Issue #: | 4 | Issue Date: | January 2019 |

6.1.2 Specific to HCG03, annual position checks and exercising of the sluice gate to confirm it is in proper working order.

7 ASSOCIATED DOCUMENTS

- Lock Out / Tagging – PW-WW-PO-P-019-003
- Confined Space Procedure – PW-WW-PO-P-019-001
- Confined Space Program – WW Level III - PW-WW-P-019-001
- Confined Space Hazard Assessment Form – PO Level IV - PW-WW-PO-F-019-002
- Confined Space Entry Permit – PO Level IV - PW-WW-PO-F-019-003
- Wentworth/Rosemary Regulator (HCG03) Process Control Narrative, Version 3.3
- O-M1 Wastewater Station Inspections (CSO Stations) Procedure

BCOS software tracks the revision history of document.

| | | | |
|-------------------|---|-----------------------|---------------|
| Title: | Detailed Sewer System Operation - Brampton/Strathearne Sluice Gate (HCG04) | | |
| Document # | PW-WW-PO-P-011- HCG04-1004-054 | Document Level | 4 (Sectional) |
| Issue #: | 4 | Issue Date: | January 2019 |

1 PURPOSE

To provide procedures for the safe and efficient operation of the Brampton/Strathearne Sluice Gate (HCG04).

2 SCOPE

This procedure applies to all operations staff including: Plant Operators, Process Supervisors, Maintenance staff and Superintendents involved in operations of wastewater systems.

3 DEFINITIONS

| | |
|-------|--|
| BCOS | Beyond Compliance Operating System |
| CS | Confined Space |
| CSO | Combined Sewer Overflow |
| PO | Plant Operations |
| PW | Public Works |
| RTC | Real Time Control |
| SCADA | Supervisory Control and Data Acquisition |
| WSI | Western Sanitary Interceptor |
| WW | Wastewater |
| WWTP | Wastewater Treatment Plant |

4 RESPONSIBILITY

4.1 Plant Manager / Manager, Plant Maintenance & Technical Services

- Overall responsibility to ensure compliance with this procedure
- Ensure that, at all times, the facilities and related equipment and appurtenances used to achieve the compliance with this procedure are properly operated and maintained

4.2 Superintendent, Wastewater Treatment Process

- Update this procedure as required to ensure its accuracy
- Ensure that staff are trained on and follow this procedure
- Ensure that all the operations staff follow this procedure and respond to alarms

| | | | |
|------------|---|----------------|---------------|
| Title: | Detailed Sewer System Operation - Brampton/Strathearne Sluice Gate (HCG04) | | |
| Document # | PW-WW-PO-P-011- HCG04-1004-054 | Document Level | 4 (Sectional) |
| Issue #: | 4 | Issue Date: | January 2019 |

4.3 Process Supervisor

- Immediately report suspected problems and issues to Superintendent, Wastewater Treatment Process
- Work with Superintendent, Wastewater Treatment Process to develop corrective action plan and to implement it to resolve the issues

4.4 Operators

- Follow this procedure and respond to alarms
- Immediately report suspected problems and issues to the Process Supervisor
- Work with Superintendent, Wastewater Treatment Process and Process Supervisor to develop corrective action plan and to implement it to resolve the issues
- Thoroughly document with time all aspects of any incident including the identification of a potential problem, consultations, assessments, actions taken, corrective action plan, implementation of corrective actions, and actions required to prevent reoccurrence of problems.

4.5 Maintenance Staff

- Follow this procedure
- Immediately report suspected problems and issues to your Supervisor

5 PROCEDURE

The Brampton/Strathearne Sluice Gate (HCG04) is located in Manhole HO06E003 on Strathearne Avenue, just south of Brampton Street behind the Dofasco security guard house.

This CSO gate regulates flows from the combined sewer on Strathearne Avenue, controlling the amount of flow conveyed to the Woodward Avenue WWTP and/or Strathearne Avenue CSO Outfall Sewer in wet weather.

This document identifies procedures for the normal operation of the gate in both dry and wet weather flow, as well as procedures for confined space entry into the underground gate chamber.

5.1 Safety Notes and Procedure

- 5.1.1 Ensure all applicable City of Hamilton policies and procedures are understood and followed. Refer to BCOS or PO Workspace.
- 5.1.2 The area inside the chamber that contains the sluice gate and overflow weir is considered a confined space (CS).

| | | | |
|------------|---|----------------|---------------|
| Title: | Detailed Sewer System Operation - Brampton/Strathearne Sluice Gate (HCG04) | | |
| Document # | PW-WW-PO-P-011-HCG04-1004-054 | Document Level | 4 (Sectional) |
| Issue #: | 4 | Issue Date: | January 2019 |

- 5.1.3 Smoking is not permitted inside the control building or sluice gate chamber.
- 5.1.4 Ensure the company policy on Confined Space Entry (Confined Space Program PW-WW-P-019-001) is understood and followed before entry is attempted.
- 5.1.5 Ensure that the Confined Space Hazard Assessment (Confined Space Hazard Assessment Form Template PW-WW-PO-F-019-002), is completed before entry.
- 5.1.6 Ensure the CS Entry Plan (Confined Space Plan PW-WW-PO-F-019-001) and CS Entry Permit (Confined Space Entry Permit PW-WW-PO-F-019-003) are filled out prior to entry.
- 5.1.7 Ensure any lockout points are identified and locked according to Lock Out/Tag procedure (Lock Out / Tagging PW-WW-PO-P-019-003).

5.2 Procedure for Tank Entry: Routine Minor Maintenance and Inspection

NOTE: A Hazard Assessment and Project Specific Entry Procedure must be written for Construction, Major Maintenance, or for Entry by more than One Person.

- 5.2.1 Fill out and execute a Confined Space Entry Permit and notify the Process Supervisor at the Woodward Avenue Wastewater Treatment Plant (WWTP) (905-546-2424 Ext 1086 or cell phone 905-570-6124) of your intent to enter the sluice gate chamber. Ensure that there is no impending rain in the weather forecast. The chamber may have some flow passing through it. Entry can be made so long as gas levels are within acceptable levels.
- 5.2.2 When entering the control room/building, shut off the intrusion alarm.
- 5.2.3 Make sure the sluice gate is Open so sewage continues to enter the downstream interceptor sewer and cannot back up inside the chamber.
- 5.2.4 Do not enter the gate chamber if the portable Methane Detection System does not register "OK". Personnel inside the tank should carry and use a portable gas detector.
- 5.2.5 At least one person equipped with a two-way radio and flashlight should remain outside the chamber at all times, maintaining the "Confine Space Entry Permit" and communicating with the person inside the chamber via a two-way radio. All personnel should wear long sleeves, long pants, safety boots, gloves, safety vest and hardhat at all times.
- 5.2.6 The person outside the chamber should initiate contact with the person in the chamber every 10 minutes via two-way radio. If there is no response, attempt to contact a second time, and if there is no response again, initiate emergency measures.
- 5.2.7 Notify the process supervisor when leaving the site. Remove all lockouts and return all gates to "Remote" mode. Shut off all lights and exhaust fans. Reinstate the intrusion alarm and secure all doors.

| | | | |
|------------|---|----------------|---------------|
| Title: | Detailed Sewer System Operation - Brampton/Strathearne Sluice Gate (HCG04) | | |
| Document # | PW-WW-PO-P-011- HCG04-1004-054 | Document Level | 4 (Sectional) |
| Issue #: | 4 | Issue Date: | January 2019 |

5.3 Process and Equipment Overview

5.3.1 The older parts of the City of Hamilton are served by combined sewers, where a single sewer system conveys both sanitary sewage and stormwater runoff. During dry weather and light rainfall, the combined sewers convey all flows to the Woodward Avenue Wastewater Treatment Plant (WWTP). During heavy rainstorms, flows that exceed the capacity of the sewer system and/or the WWTP are diverted to local receiving waters. These combined sewer overflows (CSOs) are necessary in order to minimize basement flooding and overloading of the WWTP. Nearly 200 diversion structures regulate the amount of flow reaching the WWTP. The vast majority of these structures are static flow regulators where the volume of overflow is simply dependent upon the level of sewage entering the structure. Static flow regulators cannot be quickly or easily manipulated, if at all, to control the volume of flow entering the interceptors. However, the Combined Sewer System also employs a number of motorized sluice gates which can be opened or closed by operators at the Woodward Avenue WWTP to dynamically regulate the amount of flow entering the sanitary interceptors. These gates are required to reduce inflows to the WWTP Main Pumphouse during extreme storm events, in order to ensure that the WWTP is not overloaded. Centralized control of the gates is made possible via the Supervisory Control and Data Acquisition (SCADA) system.

5.3.2 The Brampton/Strathearne Sluice Gate regulates the flow of combined sewage from a 210 ha area. The gate is located in manhole HO06E003 on Strathearne Avenue, just south of Brampton Street behind the Dofasco security guard house. During dry weather and small storms, a static overflow weir captures all flows and conveys them through the open gate and into the Western Sanitary Interceptor (WSI) via a 1050 mm sewer on Strathearne Avenue. This sewer connects to the WSI at the intersection of Strathearne Avenue and Burlington Street, and the WSI conveys the flows east to the WWTP. During larger storms, when the weir is overtopped, excess flows are diverted to the Strathearne CSO outfall via a 2100 mm x 2250 mm sewer on Strathearne Avenue. During an emergency, where an extreme storm event requires operation of five (5) or more pumps in the WWTP Main Pump House, the Process Supervisor may elect to close this sluice gate to by-pass all combined sewage through the Strathearne Avenue CSO Outfall. Bypassing these excess flows at their source provides additional protection of the WWTP, and reduces the pumping of flows at the plant that would not be provided treatment in any case.

5.4 Dry Weather Operation (Manual)

Manually set the Brampton/Strathearne Sluice Gate (HCG04) to “Open” via the SCADA system:

1. Go to the HCG04 SCADA screen
2. Select “HCG04 Isolation Gate” and set to “Open” or alternatively enter 100% Open setpoint


| | | | |
|------------|---|----------------|---------------|
| Title: | Detailed Sewer System Operation - Brampton/Strathearne Sluice Gate (HCG04) | | |
| Document # | PW-WW-PO-P-011- HCG04-1004-054 | Document Level | 4 (Sectional) |
| Issue #: | 4 | Issue Date: | January 2019 |

5.5 Wet Weather Operation

When five (5) pumps are operating at the Woodward Avenue WWTP during an extreme storm event, set the Brampton/Strathearne Sluice Gate (HCG04) to “Closed” via the SCADA system:

1. Go to the HCG04 SCADA screen
2. Select “HCG04 Isolation Gate” and set to “Closed” or alternatively enter 0% Open setpoint

5.6 Brampton/Strathearne Sluice Gate (HCG04) SCADA Screen:



6 INSPECTION & MAINTENANCE

6.1 Annual Inspections

6.1.1 An Annual Inspection of the facilities should be conducted, as outlined in the City’s O-M1 Wastewater Station Inspections (CSO Stations) Procedure, where applicable including but not limited to:

- Health and Safety, including fire extinguishers
- General Facility, including lighting, heating and ventilation, and general condition of the premises (building, grounds, doors, etc)
- Sluice Gates, including exercising of gates to confirm proper operation, only where the gates can be exercised without risk of sewage discharges to the environment

| | | | |
|-------------------|---|-----------------------|---------------|
| Title: | Detailed Sewer System Operation - Brampton/Strathearne Sluice Gate (HCG04) | | |
| Document # | PW-WW-PO-P-011- HCG04-1004-054 | Document Level | 4 (Sectional) |
| Issue #: | 4 | Issue Date: | January 2019 |

- Documenting any significant Odours noticed outside the station
- Other Operational Checks, including control panels, SCADA alarms, electric hoists, hatch covers

6.1.2 Specific to HCG04, annual position checks and exercising of the sluice gate to confirm it is in proper working order.

7 ASSOCIATED DOCUMENTS

- Lock Out / Tagging – PW-WW-PO-P-019-003
- Confined Space Procedure – PW-WW-PO-P-019-001
- Confined Space Program – WW Level III - PW-WW-P-019-001
- Confined Space Hazard Assessment Form – PO Level IV - PW-WW-PO-F-019-002
- Confined Space Entry Permit – PO Level IV - PW-WW-PO-F-019-003
- Brampton/Strathearne Regulator (HCG04) Process Control Narrative, Version 1.2
- O-M1 Wastewater Station Inspections (CSO Stations) Procedure

BCOS software tracks the revision history of document.

| | | | |
|-------------------|---|-----------------------|---------------------|
| Title: | Detailed Sewer System Operation – Wellington/Burlington Sluice Gates (HCG14) | | |
| Document # | PW-WW-PO-P-011- HCG14-1004-056 | Document Level | 4 (Sectional) |
| Issue #: | 2 | Issue Date: | January 2019 |

1 PURPOSE

To provide procedures for the safe and efficient operation of the Wellington/Burlington Sluice Gates (HCG14).

2 SCOPE

This procedure applies to all operations staff including: plant operators, process supervisors, maintenance staff and superintendents involved in operations of wastewater systems.

3 DEFINITIONS

| | |
|-------|---|
| BCOS | Beyond Compliance Operating System |
| CS | Confined Space |
| CSO | Combined Sewer Overflow |
| DWF | Dry Weather Flow |
| PCN | Process Control Narrative |
| PID | Proportional-Integral-Derivative Controller |
| PO | Plant Operations |
| PW | Public Works |
| PLC | Programmable Logic Controller |
| RTC | Real Time Control |
| SCADA | Supervisory Control and Data Acquisition |
| WW | Wastewater |
| WWF | Wet Weather Flow |
| WWTP | Wastewater Treatment Plant |
| WSIN | West Sewer Interceptor, North Branch |

4 RESPONSIBILITY

4.1 Manager, Plant Operations / Manager, Plant Maintenance & Technical Services

- Overall responsibility to ensure compliance with this procedure

| | | | |
|-------------------|---|-----------------------|---------------------|
| Title: | Detailed Sewer System Operation – Wellington/Burlington Sluice Gates (HCG14) | | |
| Document # | PW-WW-PO-P-011- HCG14-1004-056 | Document Level | 4 (Sectional) |
| Issue #: | 2 | Issue Date: | January 2019 |

- Ensure that, at all times, the facilities and related equipment and appurtenances used to achieve the compliance with this procedure are properly operated and maintained

4.2 Superintendent, Wastewater Treatment Process

- Update this procedure as required to ensure its accuracy
- Ensure that staff are trained on and follow this procedure
- Ensure that all the operations staff follow this procedure and respond to alarms

4.3 Process Supervisor

- Immediately report suspected problems and issues to the Superintendent, Wastewater Treatment Process
- Work with the Superintendent, Wastewater Treatment Process to develop a corrective action plan and implement it to resolve any issues

4.4 Operators

- Follow this procedure and respond to alarms
- Immediately report suspected problems and issues to the Process Supervisor
- Work with Superintendent, Wastewater Treatment Process and Process Supervisor to develop corrective action plan and to implement it to resolve the issues
- Thoroughly document with time all aspects of any incident including the identification of a potential problem, consultations, assessments, actions taken, corrective action plan, implementation of corrective actions, and actions required to prevent reoccurrence of problems

4.5 Maintenance Staff

- Follow this procedure
- Immediately report suspected problems and issues to your Supervisor

5 PROCEDURE

The Wellington/Burlington Sluice Gates (HCG14) is located on the north side of Burlington Street, just west of Wellington Street.

This CSO gates regulate flows from the combined sewer on Wellington Street, controlling the amount of flow conveyed to the Woodward Avenue WWTP and/or Wellington CSO Outfall Sewer in wet weather.

| | | | |
|-------------------|---|-----------------------|---------------------|
| Title: | Detailed Sewer System Operation – Wellington/Burlington Sluice Gates (HCG14) | | |
| Document # | PW-WW-PO-P-011- HCG14-1004-056 | Document Level | 4 (Sectional) |
| Issue #: | 2 | Issue Date: | January 2019 |

This document identifies procedures for the normal operation of HCG14 in both dry and wet weather flow, as well as procedures for confined space entry into the underground gate chamber.

Hydro services to this station are provided by Alectra Utilities (905-522-6611).

5.1 Safety Notes and Procedure

- 5.1.1 Ensure all applicable City of Hamilton policies and procedures are understood and followed. Refer to BCOS or PO Workspace.
- 5.1.2 The area inside the chamber that contains the sluice gate and overflow weir is considered a confined space.
- 5.1.3 Ensure the company policy on Confined Space Entry (Confined Space Program PW-WW-P-019-001) is understood and followed before entry is attempted.
- 5.1.4 Ensure that the Confined Space Hazard Assessment (Confined Space Hazard Assessment Form Template- Plant Operations - Level IV - PW-WW-PO-F-019-002), is completed before entry.
- 5.1.5 Ensure the CS Entry Plan (Confined Space Plan PW-WW-PO-F-019-001) and CS Entry Permit (Confined Space Entry Permit – Plant Operations Level IV PW-WW-PO-F-019-003) are filled out prior to entry.
- 5.1.6 Ensure any lockout points are identified and locked according to Lock Out/Tag procedure (Lock Out / Tagging PW-WW-PO-P-019-003).

5.2 Process and Equipment Overview

- 5.2.1 The older parts of the City of Hamilton are served by combined sewers, where a single sewer system conveys both sanitary sewage and stormwater runoff. During dry weather and light rainfall, the combined sewers convey all flows to the Woodward Avenue Wastewater Treatment Plant (WWTP). During heavy rainstorms, flows that exceed the capacity of the sewer system and/or the WWTP are diverted to local receiving waters. These combined sewer overflows (CSOs) are necessary in order to minimize basement flooding and overloading of the WWTP. Nearly 200 diversion structures regulate the amount of flow reaching the WWTP. The vast majority of these structures are static flow regulators where the volume of overflow is simply dependent upon the level of sewage entering the structure. Static flow regulators cannot be quickly or easily manipulated, if at all, to control the volume of flow entering the interceptors. However, the Combined Sewer System also employs a number of motorized sluice gates which can be opened or closed by operators at the Woodward Avenue WWTP to dynamically regulate the amount of flow entering the sanitary interceptors. These gates are required to reduce inflows to the WWTP Main Pumpouse during extreme storm events, in order to ensure that the WWTP is not

| | | | |
|-------------------|---|-----------------------|---------------------|
| Title: | Detailed Sewer System Operation – Wellington/Burlington Sluice Gates (HCG14) | | |
| Document # | PW-WW-PO-P-011- HCG14-1004-056 | Document Level | 4 (Sectional) |
| Issue #: | 2 | Issue Date: | January 2019 |

overloaded. Centralized control of the gates is made possible via the Supervisory Control and Data Acquisition (SCADA) system.

NOTE: The facility is monitored and controlled via SCADA by Operators at the WWTP. The SCADA system includes a security system to advise of any unauthorized entries into the control building.

- 5.2.2 The Wellington-Burlington Regulator (SCADA tag HCG14), went into service in the year 2012, at the intersection of Wellington Street North and Burlington Street East where the Wellington CSO crosses the West Sewer Interceptor (WSIN). The purpose of this site is to capture combined sewage from the Wellington CSO and to convey it to the WSIN for conveyance to the Woodward Avenue WWTP for treatment.
- 5.2.3 HCG14 is equipped with a modulation slide gate and back-up isolation slide gate, which are operated automatically by the City’s Real Time Control (RTC) system based on level measurements on the receiving WSIN, the Wellington CSO Outfall sewer, and the regulator chamber itself. The modulation gate controls the flow into the WSIN and the isolation gate facilitates maintenance of the modulation gate (when required) and provides redundancy for the modulation gate to control flow into the WSIN. Two passive flap gates are also located just downstream of the flow diversion channel to the regulator to prevent water from Hamilton Harbour from flowing back into the sewer system.
- 5.2.4 During dry weather flow (DWF) conditions, both gates remain fully closed. During wet weather flow (WWF) conditions, upon detection of a threshold flow depth in either the Wellington CSO Outfall sewer or in the WSIN, the site is automatically switched to wet conditions strategy operation, which causes the isolation gate to open and the modulation gate to be placed in a partially open position according to the output from a proportional-integral-derivative (PID) controller. The PID controller will then cause the gate to modulate with the objective of attaining and then maintaining the flow level in the WSIN at a specified set-point. Once the flow levels in the WSIN and the Wellington CSO Outfall sewer fall below the wet conditions strategy trigger levels, the site operation will revert back to the dry conditions strategy. A number of fail-safe and degraded operation conditions features are built into the process control logic in order to ensure the robust and safe operation of the site in the event of a variety of equipment failures (e.g. gate motors, level sensors, etc.), all of which are detailed further within the process control narrative (PCN) for the site.
- 5.2.5 The gates can be operated in either full Manual, SCADA Manual, or SCADA Auto modes. The default mode is SCADA Auto, with operation directed by the RTC system, to maximize flow to the WWTP.
- 5.2.6 The Control Building at 221 Burlington Street East contains the electrical, control, communications equipment and UPS back-up power for isolation slide gate emergency operation in the event of power failure

| | | | |
|------------|---|----------------|---------------------|
| Title: | Detailed Sewer System Operation – Wellington/Burlington Sluice Gates (HCG14) | | |
| Document # | PW-WW-PO-P-011- HCG14-1004-056 | Document Level | 4 (Sectional) |
| Issue #: | 2 | Issue Date: | January 2019 |

5.3 Dry Weather Operation (Manual)

Manually set the Wellington/Burlington Sluice Gate (HCG14) to “Open” via the SCADA system:


1. Go to the HCG14 SCADA screen
2. Select “HCG14 Isolation Gate” and set to “Open”

5.4 Wet Weather Operation (Manual)

When three (3) pumps are operating at the Woodward Avenue WWTP during an extreme storm and bypassing is imminent (Flow > 614 MLD), set the Wellington/Burlington Sluice Gate (HCG14) to “Closed” via the SCADA system:

1. Go to the HCG14 SCADA screen
2. Select “HCG14 Isolation Gate” and set to “Closed”

5.5 SCADA Screen for HCG14 WWTP-Controlled Sluice Gates



| | | | |
|-------------------|---|-----------------------|---------------------|
| Title: | Detailed Sewer System Operation – Wellington/Burlington Sluice Gates (HCG14) | | |
| Document # | PW-WW-PO-P-011- HCG14-1004-056 | Document Level | 4 (Sectional) |
| Issue #: | 2 | Issue Date: | January 2019 |

6 INSPECTION & MAINTENANCE

6.1 Annual Inspections

6.1.1 An Annual Inspection of the facilities should be conducted, as outlined in the City's O-M1 Wastewater Station Inspections (CSO Stations) Procedure, where applicable including but not limited to:

- Health and Safety, including fire extinguishers
- General Facility, including lighting, heating and ventilation, and general condition of the premises (building, grounds, doors, etc)
- Sluice Gates, including exercising of gates to confirm proper operation, only where the gates can be exercised without risk of sewage discharges to the environment
- Documenting any significant Odours noticed outside the station
- Other Operational Checks, including control panels, SCADA alarms, electric hoists, hatch covers

6.1.2 Specific to HCG14, annual position checks and exercising of the sluice gates to confirm they are in proper working order.

7 ASSOCIATED DOCUMENTS

- Lock Out / Tagging PW-WW-PO-P-019-003
- Confined Space Procedure – Plant Operations Section PW-WW-PO-P-019-001
- Confined Space Program PW-WW-P-019-001
- Confined Space Hazard Assessment Form Template- Plant Operations - Level IV- PW-WW-PO-F-019-002
- Confined Space Entry Permit – Plant Operations Level IV PW-WW-PO-F-019-003
- Wastewater Regulator (HCG14) Process Control Narrative, Version 1.7
- O-M1 Wastewater Station Inspections (CSO Stations)

BCOS software tracks the revision history of document.

| | | | |
|-------------------|--|-----------------------|---------------|
| Title: | Detailed Sewer System Operation - Parkdale Burlington Wastewater Collection Station (HC001) | | |
| Document # | PW-WW-PO-P-011- HC051-1001-051 | Document Level | 4 (Sectional) |
| Issue #: | 5 | Issue Date: | January 2019 |

1 PURPOSE

To provide procedures for the safe and efficient operation of the Parkdale Burlington Wastewater Collection Station (HC001).

2 SCOPE

This procedure applies to all operations staff including: Plant Operators, Process Supervisors, Maintenance staff and Superintendents involved in operations of wastewater systems.

3 DEFINITIONS

| | |
|-------|--|
| BCOS | Beyond Compliance Operating System |
| DWQMS | Drinking Water Quality Management System |
| PO | Plant Operations |
| PW | Public Works |
| SCADA | Supervisory Control and Data Acquisition |
| PLC | Programmable Logic Controller |
| WW | Wastewater |
| WWTP | Wastewater Treatment Plant |

4 RESPONSIBILITY

4.1 Manager, Plant Operations / Manager, Plant Maintenance & Technical Services

- Overall responsibility to ensure compliance with this procedure
- Ensure that, at all times, the facilities and related equipment and appurtenances used to achieve the compliance with this procedure are properly operated and maintained

4.2 Superintendent, Wastewater Treatment Process

- Update this procedure as required to ensure its accuracy

4.3 Superintendent, Plant Operations

- Ensure that all the operations staff follow this procedure and respond to alarms

| | | | |
|------------|--|----------------|---------------------|
| Title: | Detailed Sewer System Operation - Parkdale Burlington Wastewater Collection Station (HC001) | | |
| Document # | PW-WW-PO-P-011- HC051-1001-051 | Document Level | 4 (Sectional) |
| Issue #: | 5 | Issue Date: | January 2019 |

4.4 Process Supervisor

- Immediately report suspected problems and issues to the Superintendent, Wastewater Treatment Process and Superintendent, Plant Operations
- Work with the Superintendent, Wastewater Treatment Process to develop a corrective action plan and implement it to resolve any issues

4.5 Operators

- Follow this procedure and respond to alarms
- Immediately report suspected problems and issues to the Process Supervisor
- Work with Superintendent, Wastewater Treatment Process and Process Supervisor to develop a corrective action plan and to implement it to resolve any issues
- Thoroughly document with time all aspects of any incident including the identification of a potential problem, consultations, assessments, actions taken, corrective action plan, implementation of corrective actions, and actions required to prevent reoccurrence of problems

4.6 Maintenance Staff

- Follow this procedure
- Immediately report suspected problems and issues to your Supervisor


5 PROCEDURE

5.1 General Overview

- 5.1.1 This collection station is located on the northwest corner of Parkdale Avenue North and Nicola Tesla Boulevard in Hamilton.
- 5.1.2 This station is equipped with 5 pumps - 2 each rated at 150 L/s, and 3 each rated at 600 L/s.
- 5.1.3 This station is used for high flow bypass during rainstorms by allowing the wet well to fill and then pumping it out to Hamilton Harbour.

NOTE: This procedure is currently under review. Currently, pumps are kept on standby until the HI HI level is reached in the wet well.

5.2 Parkdale Burlington Wastewater Collection Station (HC001) SCADA Screen



5.3 Normal Operation

- 5.3.1 Under normal operating conditions, HC001 is monitored and controlled automatically through the City's SCADA system located in the control room of the Woodward Avenue Wastewater Treatment Plant (WWTP) and can also be monitored from several other remote locations. The level relays from the wet well ultrasonic transmitter are used to start and stop each of the pumps.
- 5.3.2 When the operation of the pumps is in Auto Control mode, the units start and stop according to the following set points programmed within the station's programmable logic controller (PLC). These set points open and close relays within each of the five pumps, which in turn start and stop the pumps:

| Milltronics Control | Starting | Stopping |
|---------------------|----------|----------|
| Pump #1 | 0.9 m | 0.2 m |
| Pump #3 | 1.1 m | 0.27 m |
| Pump #4 | 3.2 m | 0.9 m |
| Pump #5 | 4.3 m | 1.0 m |
| Pump #6 | 4.6 m | 1.25 m |

| | | | |
|-------------------|--|-----------------------|---------------|
| Title: | Detailed Sewer System Operation - Parkdale Burlington Wastewater Collection Station (HC001) | | |
| Document # | PW-WW-PO-P-011- HC051-1001-051 | Document Level | 4 (Sectional) |
| Issue #: | 5 | Issue Date: | January 2019 |

NOTE: The wet well has been sealed off due to safety concerns about the entry walls.

5.4 Manual Operation at the Control Panel in Station

To operate the station, manually perform the following:

- Ensure all discharge and suction valves are open.
- Turn the MAN-OFF-AUTO Selector Switch for each pump to the OFF position.
- Turn the MAN-OFF-AUTO Selector Switch for each pump to the MAN position.
- Push the start button for the selected pump.
- The pumps will start and run continuously.

NOTE: There is no level control system when the system is operated manually.

- Only pump the wet well down to the level of the bend in the suction pipe, i.e. Do not air lock the pumps.
- Switch the station back to automatic mode when required.

5.5 Local Operation at the Control Panel in Station

To operate the station manually, perform the following:

- Turn the HAND-OFF-AUTO Selector Switch for each pump to the OFF position.
- Turn the HAND-OFF-AUTO Selector Switch for each pump to the HAND position.
- The pumps will start and run continuously.

NOTE: There is no level control system when the system is operated manually.

- Only pump the wet well down to low level, i.e. Do not air lock the pumps.
- Switch the station back to automatic mode when required.

5.6 Resetting the Pump(s)

- Turn the MAN-OFF-AUTO Selector Switch for each pump to the OFF position.
- Reset pump breaker, located in the electrical panel on south wall of station.
- Turn the MAN-OFF-AUTO Selector Switch for each pump to the AUTO position.
- The pump will start. If it does not, call maintenance.

| | | | |
|-------------------|--|-----------------------|----------------------|
| Title: | Detailed Sewer System Operation - Parkdale Burlington Wastewater Collection Station (HC001) | | |
| Document # | PW-WW-PO-P-011- HC051-1001-051 | Document Level | 4 (Sectional) |
| Issue #: | 5 | Issue Date: | January 2019 |

6 INSPECTION & MAINTENANCE

6.1 Annual Inspections

6.1.1 An Annual Inspection of the facilities should be conducted, as outlined in the City's O-M1 Wastewater Station Inspections Procedure, where applicable including but not limited to:

- Health and Safety, including fire extinguishers
- General Facility, including lighting, heating and ventilation, and general condition of the premises (building, grounds, doors, etc)
- Sewage Pumps, including pump run tests and checking of pumps for bearing/motor heat/noise and air locks, and checking of breakers
- Sluice Gates, including exercising of gates to confirm proper operation, only where the gates can be exercised without risk of sewage discharges to the environment
- Wet Well, including well level controls, signs of scum/debris accumulation, piping and valves, ventilation and lighting
- Documenting any significant Odours noticed outside the station
- Other Operational Checks, including control panels, SCADA alarms, backflow preventers, electric hoists, hatch covers, well level controls

7 ASSOCIATED DOCUMENTS

- Safe Entry and Exit from Stations PW-WW-PO-P-011-002
- BCOS + DWQMS - Log Book and Record Keeping Procedure
- Parkdale Burlington WWCS (HC001) Process Control Narrative, Version 2.4
- O-M1 Wastewater Station Inspections Procedure

BCOS software tracks the revision history of document.

Appendix B

Updated Process Control Narrative for Main/King CSO Tank (HCS04)



Hamilton



**WASTEWATER PUMPING STATION HCS04
(Main St. / King St.)**

PROCESS CONTROL NARRATIVE

Version 3.5

(Narrative format: SCADA Standards Version 5.0)

Prepared by:

Eramosa Engineering Inc.

Westin Engineering Inc.

XCG Consultants Ltd.

R.E. Poisson Engineering Inc.

November 2018

Table of Contents

| | | |
|----------|---|-------------------------------------|
| 1 | FACILITY DESCRIPTION | 1 |
| 1.1 | FACILITY OVERVIEW | 1 |
| 1.1.1 | Main Process..... | 1 |
| 1.1.2 | Demo Backwashing Sequence..... | Error! Bookmark not defined. |
| 1.1.3 | Influent and Overflow Sampler Modes..... | Error! Bookmark not defined. |
| 1.1.4 | Sampling..... | 3 |
| 1.1.5 | CSO Tank Overflow | 3 |
| 1.1.6 | Backup Power..... | 3 |
| 1.2 | SCADA SYSTEM OVERVIEW..... | 4 |
| 1.3 | FACILITY DRAWINGS | 5 |
| 2 | EQUIPMENT & INSTRUMENTATION..... | 5 |
| 2.1 | MECHANICAL EQUIPMENT | 5 |
| 2.2 | INSTRUMENTATION..... | 7 |
| 2.3 | I/O LISTING..... | 8 |
| 3 | COMPLIANCE WITH HAMILTON SCADA STANDARDS | 8 |
| 4 | CONTROL MODES..... | 8 |
| 4.1.1 | Station Control Mode..... | 9 |
| 5 | STATION CONTROL | 11 |
| 5.1 | GENERAL DESCRIPTION | 11 |
| 5.1.1 | Main Process..... | 11 |
| 5.1.2 | CSO Sampling System Description | 11 |
| 5.1.3 | CSO Tank Flushing System..... | 14 |
| 5.1.4 | CSO Tank Lighting System..... | 15 |
| 5.1.5 | CSO Tank Supply Fan System | 15 |
| 5.2 | SUMMARY OF RELATED DEVICES | 15 |
| 5.3 | PROCESS CONTROL LOGIC | 15 |
| 5.3.1 | Equipment Starting/Opening | 15 |
| 5.3.2 | Equipment Running/Positioning | 16 |
| 5.3.3 | Equipment Stopping/Closing..... | 17 |
| 5.4 | MAJOR EQUIPMENT CONTROL LOGIC | 18 |
| 5.4.1 | Control Modes | 18 |
| 5.4.2 | Hardwired Interlocks | 19 |
| 5.4.3 | Backup Control System | 20 |
| 5.4.4 | Software Interlocks..... | 20 |
| 5.4.5 | Program Variables & Internal Software Parameters..... | 21 |
| 5.4.6 | Calculated Variables | 21 |
| 5.4.7 | Normal Operating Conditions | 22 |
| 5.4.8 | Normal Backwashing Sequence | 22 |
| 5.4.9 | Demo Backwashing Sequence..... | 23 |
| 5.4.10 | Influent and Overflow Sampler Modes | 23 |
| 5.4.11 | SCADA Auto Starting/Stopping Conditions | 24 |
| 5.4.12 | Automatic Duty Rotation Modes..... | 25 |
| 6 | WASTEWATER EVENT MANAGEMENT | 26 |
| 7 | FAULT RESPONSE AND ALARMS | 27 |
| 7.1 | FAULT RESPONSE OPERATION | 27 |

| | | |
|---|---|-----------|
| 7.1.1 | Power Failure..... | 27 |
| 7.1.2 | SCADA Communication Failure..... | 27 |
| 7.1.3 | PAC Failure..... | 27 |
| 7.1.4 | Wetwell Level Transmitter Failure..... | 27 |
| 7.1.5 | Flow Transmitter Failure..... | 28 |
| 7.1.6 | Sluice Gate Failure..... | 28 |
| 7.1.7 | Sampler Unresponsive..... | 28 |
| 7.1.8 | Sewage Lift Pump Failure..... | 28 |
| 7.2 | ALARMS..... | 28 |
| 7.2.1 | Sewage Lift Pump Virtual Alarm Auto-Acknowledge..... | 29 |
| 7.2.2 | HMI - Red Screen..... | 29 |
| 7.2.3 | Pilot Lights..... | 29 |
| 7.2.4 | Alarm Horn..... | 29 |
| 7.3 | ENVIRONMENTAL COMPLIANCE APPROVAL OR OTHER REGULATORY REQUIREMENTS..... | 29 |
| 7.4 | TRENDING OF INPUTS..... | 29 |
| 7.5 | REPORTING..... | 31 |
| 7.6 | LOCAL LOGGING..... | 32 |
| 8 | MISCELLANEOUS..... | 33 |
| 8.1 | ELECTRICAL EQUIPMENT AND STANDBY POWER..... | 33 |
| 8.2 | HVAC..... | 33 |
| 8.3 | HAZARDOUS GASES..... | 34 |
| 8.4 | STATION FLOOD..... | 34 |
| 8.5 | STATION SECURITY..... | 34 |
| 8.6 | PRECIPITATION (RAINFALL) MONITORING..... | 34 |
| 8.7 | STATION LIGHTING..... | 34 |
| APPENDIX A – SCADA I/O LISTING BY DEVICE..... | | A |
| APPENDIX B – SCADA I/O LISTING BY CARD ASSIGNMENT..... | | B |
| APPENDIX C – SCADA HMI SCREENS AND P&IDS..... | | C |
| APPENDIX D – HISTORIAN REPORT..... | | D |
| APPENDIX E – ALARM TABLE..... | | E |
| APPENDIX F – MESSAGE TABLE..... | | F |
| APPENDIX G – PROGRAM VARIABLES & INTERNAL SOFTWARE PARAMETERS..... | | G |
| APPENDIX H – REFERENCE SITE PHOTOS..... | | H |
| APPENDIX I – FLOOR PLAN..... | | I |

List of Tables

| | |
|--|----|
| Table 1-1: HCS04 Station Details | 1 |
| Table 1-2: HCS04 Overflow Summary | 3 |
| Table 1-3: HCS04 Communications | 4 |
| Table 1-4: HCS04 Network Equipment Summary | 5 |
| Table 2-1: HCS04 SCADA Mechanical Equipment Summary | 5 |
| Table 2-2: HCS04 Mechanical Equipment Summary | 6 |
| Table 2-3: HCS04 Pump Capacity Summary | 6 |
| Table 2-4: HCS04 Wetwell Capacity Summary | 7 |
| Table 2-5: HCS04 Instrumentation Summary | 7 |
| Table 3-1: HCS04 Standards Deviation | 8 |
| Table 4-1: HCS04 Standard Control Modes | 8 |
| Table 4-2: HCS04 Station Control Modes | 9 |
| Table 5-1: HCS04 Influent Sampler Key Parameters | 12 |
| Table 5-2: HCS04 Influent Sampler Programming Parameters | 12 |
| Table 5-3: HCS04 Effluent Sampler Key Parameters | 14 |
| Table 5-4: HCS04 Effluent Sampler Programming Parameters | 14 |
| Table 5-5: HCS04 Related Devices Summary | 15 |
| Table 5-6: HCS04 Mechanical Equipment Modes of Operation | 18 |
| Table 5-7: HCS04 Hardwired Interlocks by Device | 20 |
| Table 5-8: HCS04 Software Interlocks By Device | 20 |
| Table 5-9: HCS04 Calculated Values | 21 |
| Table 5-10: HCS04 Sampler Modes | 23 |
| Table 5-11: HCS04 Duty Rotation Modes | 25 |
| Table 6-1: HCS04 Wastewater Event Management | 26 |
| Table 7-1: HCS04 Trending Points | 30 |
| Table 7-2: HCS04 Reporting Variables List | 31 |
| Table 7-3: HCS04 Local Logging | 32 |
| Table 8-1: HCS04 Electrical Equipment Summary | 33 |
| Table 8-2: HCS04 Generator Summary | 33 |

List of Figures

| | |
|---|----|
| Figure 1-1: HCS04 Simplified Network Layout | 4 |
| Figure 5-1: HCS04 Normal Operating Levels | 25 |

Revision History

| Version | Date | Description Of Revisions |
|---------|------------------|--|
| 1.0 | 16 November 2010 | Original Version |
| 2.0 | 11 January 2011 | Reconciled with final I/O list |
| 3.0 | January 2012 | Released with SCADA Standards Version 4.2 and updated to address City comments |
| 3.1 | January 2013 | Released with SCADA Standards Version 4.3 |
| 3.2 | October 2013 | Released with SCADA Standards Version 4.4 |
| 3.3 | February 2014 | Control Variable Setpoints Update |
| 3.4 | August 2017 | Updated to SCADA Standards V5.0 |
| 3.5 | November 2018 | PCN Update |

Definitions Glossary

| Term | Definition |
|-----------------|--|
| ADSL | Asymmetric Digital Subscriber Line (ADSL) is a method of communication that allows data transmission over telephone lines. |
| AI | Analog Input (AI). Incoming signals (inputs) that are modulating in nature (i.e. 4-20mA or 0-5VDC). |
| AO | Analog Output (AO). Outgoing setpoint signals (outputs) that are modulating in nature (i.e. 4-20mA or 0-5VDC). |
| ATS | Automatic Transfer Switch (ATS). A device which automatically transfers normal power to emergency power in the event of disruption in normal or quality of normal power feed. |
| BOD | Biochemical Oxygen Demand (BOD) is the amount of dissolved oxygen needed by aerobic biological organisms in a body of water to break down organic material present in a given water sample at certain temperature over a specific time period. |
| CEPT | Chemically Enhanced Primary Treatment (CEPT). Additional wastewater treatment of bypass flows, polymer addition and possible increase of ferric sulphate dosing, during wet weather (storm) events. |
| DI | Digital Input (DI). Incoming signals (inputs) that are on/off in nature. |
| DO | Digital Output (DO). Outgoing command signals (outputs) that are on/off in nature. |
| HLP | High Lift Pump (HLP). |
| HMI | Human Machine Interface (HMI) is the user interface in a process control system. It provides a graphics-based visualization of an industrial control and monitoring system. An HMI typically resides in an office-based Windows computer that communicates with programmable logic controllers throughout the plant. |
| HVAC | Heating, Ventilation, and Air Conditioning (HVAC). |
| I/O | Input/Output (I/O). |
| ISR | Intrinsically Safe Relay (ISR). This is a relay that provides an 'intrinsically safe' barrier between circuits. Typically used when interfacing signals sourced from hazardous environments. |
| MCC | Motor Control Centre (MCC). |
| MOE | The Ministry of Environment (MOE) is the government agency responsible for the enforcement of water quality standards in Canada. |
| NAC | Network Access Closet (NAC). A cabinet that houses the WAN equipment. |
| OIT | Operator Interface Terminal (OIT). This is a local display which allows operations staff to view process and alarming as well as enter setpoints and control equipment without using a SCADA workstation. Typically it is mounted on the control panel enclosure doors at remote stations or on vendor panels. |
| P&ID | Process and Instrumentation Diagram (P&ID) – A diagram illustrating all of the process equipment, interconnecting piping and instrumentation, including the connections to the process control system. |

| Term | Definition |
|--------------------|---|
| PAC | Process Automation Controller (PAC) – A microprocessor-controlled device to which all of the process and instrumentation I/O is connected and which contains the process control logic. Functionally identical, and for the purposes of the process narrative, the same as, a PLC (programmable logic controller) or RPU (remote processing unit). |
| PCN | Process Control Narrative (PCN). |
| PLC | Programmable Logic Controller (PLC). This is a programmable field controller. |
| PRV | Pressure Reducing Valve (PRV). A valve that will automatically open when a pre-set pressure is reached then close automatically when the pressure is relieved. |
| SCADA | Supervisory Control and Data Acquisition (SCADA) refers to an industrial control system; a computer system monitoring and controlling a process. |
| SCADA Tag | The term ‘SCADA Tag’ or ‘code’ refers to the 18-character code that is defined within this standard. The code is used to define the physical location of the equipment within the City’s water and wastewater system. It also defines functionality within the SCADA system when using Fragment 8 to expand upon specifics of the location tag defined in the first 15 characters of the coding system. |
| SNMP | Simple Network Management Protocol (SNMP). Internet-standard protocol for managing devices on IP networks. |
| TSS | Total Suspended Solids (TSS) is a filter residue measurement to determine water quality. |
| UPS | Uninterruptible Power Supply (UPS). A power supply device which provides emergency power to the supplied device, for a limited period of time, from battery power during a power failure/quality event. |
| VAC | Voltage in Alternating Current (VAC). A unit of voltage. |
| VDC | Voltage Direct Current (VDC). A unit of voltage. |
| VFD | Variable Frequency Drive (VFD). This is a motor starter unit which utilizes a solid state (electronic) starter control which allows dynamic/adjustable motor speed control. |
| WAN | Wide Area Network (WAN) is a geographically dispersed telecommunications network. The term distinguishes a broader telecommunication structure from a local area network (LAN). |
| WAO | Work Area Outlet (WAO). A set of Ethernet jacks to connect to the SCADA system. |
| WET WEATHER | Wet weather (storm) conditions/events are classified as flows greater than 614MLD into the Woodward WWTP. |
| WTP | Water Treatment Plant (WTP). |
| WWTP | Wastewater Treatment Plant (WWTP). |

1 FACILITY DESCRIPTION

1.1 FACILITY OVERVIEW

The Main St. and King St. Combined Sewage Overflow (CSO) facility is located in the park between Main and King Streets, adjacent to Hwy 403. The station consists of a single-story control building, a Wetwell, and two below-ground cells within a CSO Tank.

The following table lists important information about the site:

Table 1-1: HCS04 Station Details

| Station | Detail |
|----------------------|-----------------------------------|
| Civic Address | 707 King St. W, Hamilton, Ontario |
| Site Phone Number | 905-777-1125 |
| Hydro Account Number | 24468-709 (Alectra) |
| Hydro Meter Number | TBD |

1.1.1 Main Process

During dry weather the station collects wastewater in a Wetwell and automatically pumps it to the Woodward WWTP.

There are three (3) sewage lift pumps (duty 1, duty 2 and standby) available, each with a rated capacity of 375 L/s. Refer to “For a backwash sequence to start, the level in both CSO tanks must be below 1m. Once the sequence is started the following sequence is followed.

Backwash CSO Tank Cell No.1:

1. Flush bucket fill valve no.1 is opened for a time period sufficient to tipping flush buckets no.1 & 2;
2. Flush buckets no.1 & 2 are full and tilted then flush bucket fill valve no.1 is closed;
3. Flush bucket fill valve 2 is opened for a time period sufficient to tipping flush buckets no.3 & 4;
4. Flush buckets no.3 & 4 are full and tilted then flush bucket fill valve no.2 is closed;
5. Flush bucket fill valve 3 is opened for a time period sufficient to tipping flush buckets no.5 & 6;
6. Flush buckets no.5 & 6 are full and tilted then flush bucket fill valve no.3 is closed;
7. Flush bucket fill valve 4 is opened for a time period sufficient to tipping flush buckets no.7 & 8;
8. Flush buckets no.7 & 8 are full and tilted then flush bucket fill valve no.4 is closed;
9. Flush bucket fill valve 5 is opened for a time period sufficient to tipping flush buckets no.9 & 10;
10. Flush buckets no.9 & 10 are full and tilted then flush bucket fill valve no.5 is closed.
11. CSO Tank Cell no.1 backwash is completed.

Backwash CSO Tank Cell No.2:

1. Flush bucket fill valve no.6 is opened for a time period sufficient to tipping flush buckets no.11 & 12;
2. Flush buckets no.11 & 12 are full and tilted then flush bucket fill valve no.6 is closed;
3. Flush bucket fill valve no.7 is opened for a time period sufficient to tipping flush buckets no.13 & 14;
4. Flush buckets no.13 & 14 are full and tilted then flush bucket fill valve no.7 is closed;
5. Flush bucket fill valve no.8 is opened for a time period sufficient to tipping flush buckets no.15 & 16;
6. Flush buckets no.15 & 16 are full and tilted then flush bucket fill valve no.8 is closed;
7. Flush bucket fill valve no.9 is opened for a time period sufficient to tipping flush buckets no.17 & 18;
8. Flush buckets no.17 & 18 are full and tilted then flush bucket fill valve no.9 is closed;
9. Flush bucket fill valve no.10 is opened for a time period sufficient to tipping flush buckets no.19 & 20;
10. Flush buckets no.19 & 20 are full and tilted then flush bucket fill valve no.10 is closed;
11. Flush bucket fill valve no.11 is opened for a time period sufficient to tipping flush buckets no.21 & 22;

12. Flush buckets no.21 & 22 are full and tilted then flush bucket fill valve no.11 is closed;
13. Flush bucket fill valve no.12 is opened for a time period sufficient to tipping flush buckets no.23 & 24;
14. Flush buckets no.23 & 24 are full and tilted then flush bucket fill valve no.12 is closed;
15. Flush bucket fill valve no.13 is opened for a time period sufficient to tipping flush buckets no.25 & 26;
16. Flush buckets no.25 & 26 are full and tilted then flush bucket fill valve no.13 is closed;
17. Flush bucket fill valve no.14 is opened for a time period sufficient to tipping flush buckets no.27 & 28;
18. Flush buckets no. 27 & 28 are full and tilted then flush bucket fill valve no.14 is closed;
19. Flush bucket fill valve no.15 is opened for a time period sufficient to tipping flush buckets no.29 & 30;
20. Flush buckets no.29 & 30 are full and tilted then flush bucket fill valve no.15 is closed.
21. CSO Tank Cell no.2 backwash is completed.

After the backwash cycle is complete, flush bucket fill valve no.16 is activated for two minutes to flush the trough. Should any flush bucket fill valve fail to open when commanded as determined by the city water pressure transmitter (no pressure drop), an alarm is annunciated on the SCADA HMI and the next tipping flush buckets fill in the sequence until the entire sequence is complete. Should three (3) or more flush bucket fill valves fail to close when commanded as determined by the city water pressure transmitter (no pressure increase) an alarm is annunciated on the SCADA HMI, the main flushing water line shut-off line is commanded to close and the flush sequence is terminated.

1.1.2 Demo Backwashing Sequence

The DEMO mode is a short cycle, used to demonstrate the backwashing process.

When the DEMO mode is selected from the SCADA HMI, flush bucket fill valve no.1 opens for a time period sufficient to fill tipping flush buckets no. 1 and 2. When full, the flush buckets tip, flush bucket fill valve no.1 closes, and flush bucket fill valve no.2 opens to fill tipping flush buckets no.3 and 4. When full, the flush buckets tip, flush bucket fill valve no.2 closes, and the cycle repeats until the timers set for both flush bucket fill valves time out.

1.1.3 Influent and Overflow Sampler Modes

Table 5-10: HCS04 Sampler Modes

| Sampler Mode | Description |
|--|---|
| 1. Inactive | No samples are taken and sampler pumps remain off |
| 2. Time Paced Sample | Time Paced Sampling begins when the level increases above the sampler pump start setpoint. Samples are taken at defined intervals until bottle change (24 samples). The influent sampler uses an intervals of 60 seconds while the overflow sampler uses an interval of 180 seconds. |
| 3. Volume Paced Sample (Influent Sampler only) | After 24 samples have been taken in time paced mode the Influent Sampler is put in volume paced sample mode. A sample is taken for every 4390 m3 of volume in the CSO tanks. See Calculated Variables for volume paced calculations. |
| 4. Hourly Samples | After 24 samples have been taken by the Overflow Sampler, the Overflow Sampler is put into Hourly Samples mode. The Influent sample is issued a command to finish its current bottle and then sync with the Overflow Sampler. Once synchronized, samples are taken every hour for 24 hours. After 24 samples are taken both samplers are moved to the Inactive state. They will then move to Time Paced Mode if the start conditions are met. |

| Sampler Mode | Description |
|------------------|--|
| 5. Finish Bottle | When in Finish Bottle mode, samples will be taken at the minimum allowed interval until the current bottle is finished (24 samples). The Influent Sampler has a minimum sample interval of 60 seconds while the Overflow Sampler has a minimum sample interval of 180 seconds. After the finish bottle sequence is complete the sample event ends. |
| 6. Overflow Sync | When Overflow Hourly Sample Mode begins it moves the Influent Sampler into Finish Bottle mode in order to synchronize the Influent Sampler with the Overflow Sampler. Once synchronized with the Overflow Sampler, the Influent sampler will remain in Overflow Sync Mode until the Overflow Sampler has completed its sequence. |

SCADA Auto Starting/Stopping Conditions” in Section 5.4 for detailed sewage lift pump duty arrangements.

During periods of heavy precipitation, a.k.a. wet weather, when flows exceed the treatment capacity of the Woodward WWTP, this facility stores the excess influent in the onsite CSO Tank.

Storm water enters the Wetwell and flows into Cell No.1 during a storm event from four separate interceptor chambers:

- Main Street overflow via Chamber No. 6A
- Interceptor sewer via Chamber No.5
- King Street sewer via Chamber No.4
- Glen Road sewer via Chamber No. 1

Storm flows exceeding the storage volume of Cell No.1 overflow a weir into Cell No.2. Storm water exceeding the capacity of Cell No.2 overflows a second weir in Cell No.1 and discharges into Cootes Paradise at the mouth of Chedoke Creek.

After flows return to normal, the sewage lift pumps are used to dewater the CSO Tank. A tank flush system is present at this station for removal of accumulated solids from the CSO Tank floor after it has drained.

1.1.4 Sampling

There is both influent and overflow sampling at this station. Influent sampling occurs when the level in the Wetwell reaches a preset height. Overflow sampling occurs when the level in the overflow channel reaches a preset height.

1.1.5 CSO Tank Overflow

Storm flows exceeding the storage volume of Cell No.1 overflow a weir into Cell No.2. Storm water exceeding the capacity of Cell No.2 overflows a second weir in Cell No.1 and Cell No. 2 and discharges into Cootes Paradise at the mouth of Chedoke Creek. The following table describes the overflow details:

Table 1-2: HCS04 Overflow Summary

| Overflow Type | Elevation | Destination | Civil Drawing |
|----------------------------|-----------|---------------|---------------|
| Overflow Weir - Cell 1 & 2 | TBD | Cell 1 | TBD |
| CSO Tank Overflow Weir | TBD | Chedoke Creek | TBD |

1.1.6 Backup Power

There is no generator on site; however there is a hookup for a portable generator.

Refer to “Section 8.1 - Electrical Equipment and Standby Power” for detailed power information at this station.

This station has a CSO Maintenance Bypass Gate that connects the inlet chamber directly to the outfall channel which flows to Chedoke Creek. Opening this gate results in flow bypassing the pumping station and CSO tanks to discharge to the environment. This gate is to remain fully closed at all times and is locked out with the hand wheel chained to prevent it being opened. The only reason to alter the position of this gate is for emergency situations which would require the authorization of the ORO.

1.2 SCADA SYSTEM OVERVIEW

The station is monitored and can be controlled via the SCADA HMI from the Woodward WTP/WWTP, Dundas WWTP or other locations based on security access.

There is one (1) PAC control panel (HCS04CP001) which contains an Allen-Bradley ControlLogix PAC.

The controller is connected to Hamilton’s SCADA WAN via fibre optic Ethernet link.




Figure 1-1: HCS04 Simplified Network Layout

The controller details are shown in the following table:

Table 1-3: HCS04 Communications

| SCADA Tag | Equipment Description |
|-----------------|---|
| HCS04PAC0100000 | Wastewater CSO Tank PAC (Main/Master PAC) |
| HCS04OIT0100000 | Wastewater CSO Tank Panel Computer |

Refer to “Table 7-3: HCS04 Local Logging” for details on captured data points.

Local monitoring at the station is provided by a liquid crystal display (LCD) panel computer mounted on the control panel. From the panel computer, operators and maintenance personnel can monitor the operation of the station including equipment status, process information, etc. All equipment controlled by the PACs in this station can be operated from the panel computer.

Table 1-4: HCS04 Network Equipment Summary

| SCADA Tag | Equipment Description |
|-----------------|-----------------------------|
| HCS04NAC01NAS01 | WAN Panel Ethernet Switch |
| HCS04NWA0100000 | Network Work Area Outlet(s) |

Refer to DWG. 127207- C11-38-08-HCS04 I001, the SCADA system network diagram, for further information.

1.3 FACILITY DRAWINGS

The following drawings should be viewed in conjunction with this narrative:

- Instrumentation & Control: Procon CS2087 HCS04CP01 001-019, Procon CS2087 HCS04CP02 001-025
- Process: 127207-C11-38-08-HCS04 P001-P004

Refer to Appendix C for the P&ID drawings.

2 EQUIPMENT & INSTRUMENTATION

2.1 MECHANICAL EQUIPMENT

The facility includes the following major mechanical equipment connected to the SCADA system.

Table 2-1: HCS04 SCADA Mechanical Equipment Summary

| SCADA Tag | Equipment Description |
|-----------------|-----------------------------|
| HCS04SLP0100000 | Sewage Lift Pump No.1 |
| HCS04SLP0200000 | Sewage Lift Pump No.2 |
| HCS04SLP0300000 | Sewage Lift Pump No.3 |
| HCS04SAM0100000 | Influent Sampler |
| HCS04SAM0200000 | Overflow Sampler |
| HCS04SAP0100000 | Sample Pump No.1 |
| HCS04SAP0200000 | Sample Pump No.2 |
| HCS04SAM01VLV01 | Influent Backwash Valve |
| HCS04STN01IV001 | Wetwell Inlet Gate |
| HCS04STN01IV002 | CSO Tank Cells Inlet Gate |
| HCS04STN01OV001 | CSO Tank Cells Outlet Gate |
| HCS04STN01OV002 | CSO Maintenance Bypass Gate |
| HCS04VCH01IV001 | Chamber No.1 Gate |
| HCS04VCH04IV001 | Chamber No.4 Gate |

| SCADA Tag | Equipment Description |
|-----------------|--|
| HCS04VCH05IV001 | Chamber No.5 Gate |
| HCS04WWT01SOL01 | Cell No.1 Flush Valve No.1 |
| HCS04WWT01SOL02 | Cell No.1 Flush Valve No.2 |
| HCS04WWT01SOL03 | Cell No.1 Flush Valve No.3 |
| HCS04WWT01SOL04 | Cell No.1 Flush Valve No.4 |
| HCS04WWT01SOL05 | Cell No.1 Flush Valve No.5 |
| HCS04WWT01VLV01 | Main Flushing Water Line Shutoff Valve |
| HCS04WWT02SOL06 | Cell No.2 Flush Valve No.6 |
| HCS04WWT02SOL07 | Cell No.2 Flush Valve No.7 |
| HCS04WWT02SOL08 | Cell No.2 Flush Valve No.8 |
| HCS04WWT02SOL09 | Cell No.2 Flush Valve No.9 |
| HCS04WWT02SOL10 | Cell No.2 Flush Valve No.10 |
| HCS04WWT02SOL11 | Cell No.2 Flush Valve No.11 |
| HCS04WWT02SOL12 | Cell No.2 Flush Valve No.12 |
| HCS04WWT02SOL13 | Cell No.2 Flush Valve No.13 |
| HCS04WWT02SOL14 | Cell No.2 Flush Valve No.14 |
| HCS04WWT02SOL15 | Cell No.2 Flush Valve No.15 |
| HCS04WWT02SOL16 | Cell No.2 Trough Flush Valve No.16 |
| HCS04ATS0100000 | Automatic Transfer Switch |

The facility includes the following major mechanical equipment that is not connected to the SCADA system.

Table 2-2: HCS04 Mechanical Equipment Summary

| SCADA Tag | Equipment Description |
|-----------------|---------------------------------------|
| HCS04SLP01DV001 | Sewage Lift Pump No.1 Discharge Valve |
| HCS04SLP01CV001 | Sewage Lift Pump No.1 Check Valve |
| HCS04SLP02DV001 | Sewage Lift Pump No.2 Discharge Valve |
| HCS04SLP02CV001 | Sewage Lift Pump No.2 Check Valve |
| HCS04SLP03DV001 | Sewage Lift Pump No.3 Discharge Valve |
| HCS04SLP03CV001 | Sewage Lift Pump No.3 Check Valve |

The pump capacities are identified below:

Table 2-3: HCS04 Pump Capacity Summary

| Pump | Nominal Rate Capacity | Comments |
|------------------|-----------------------|----------------|
| Sample Pump No.1 | TBD | Constant Speed |
| Sample Pump No.2 | TBD | Constant Speed |

| Pump | Nominal Rate Capacity | Comments |
|-----------------------|-----------------------|----------------|
| Sewage Lift Pump No.1 | 375 L/s (4,949 GPM) | Constant Speed |
| Sewage Lift Pump No.2 | 375 L/s (4,949 GPM) | Constant Speed |
| Sewage Lift Pump No.3 | 375 L/s (4,949 GPM) | Constant Speed |

The Wetwell capacities are identified below:

Table 2-4: HCS04 Wetwell Capacity Summary

| Wetwell | Nominal Capacity | Comments |
|-----------------|-----------------------|-----------------------------|
| HCS04WWL0100000 | TBD m ³ | Wetwell Capacity |
| HCS04WWT0100000 | 22,000 m ³ | CSO Tank Cell No.1 Capacity |
| HCS04WWT0200000 | 53,000 m ³ | CSO Tank Cell No.2 Capacity |

2.2 INSTRUMENTATION

The following instruments are located in this station:

Table 2-5: HCS04 Instrumentation Summary

| SCADA Tag | Instrument Description | Analog / Discrete | Span |
|-----------------|--|-------------------|--------------|
| HCS04STN01FIT01 | Station Discharge Flow Transmitter | Analog | 0 – 1400 L/s |
| HCS04STN01LIT01 | Overflow Weir Level Transmitter | Analog | 0 – 2.7 m |
| HCS04STN01PIT01 | City Water Pressure Transmitter | Analog | 300 kPa |
| HCS04VCH01LIT01 | Chamber No. 1 Level Transmitter | Analog | 0 – 1.2 m |
| HCS04VCH04LIT01 | Chamber No. 4 Level Transmitter | Analog | 0 – 1.3 m |
| HCS04WWL01LIT01 | Wetwell Level Transmitter | Analog | 0 - 12.7 m |
| HCS04WWT01FIT01 | Main Flushing Water Line Flow Transmitter | Analog | 0 – 10 L/s |
| HCS04WWT01LIT01 | CSO Tank Cell No. 1 Level Transmitter | Analog | 0 - 11.0 m |
| HCS04WWT02LIT01 | CSO Tank Cell No. 2 Level Transmitter | Analog | 0 - 11.0 m |
| HCS04STN01IV001 | Wetwell Inlet Gate Position Transmitter | Analog | 0 – 100% |
| HCS04STN01IV002 | CSO Tank Cells Inlet Gate Position Transmitter | Analog | 0 – 100% |
| HCS04STN01OV001 | CSO Tank Cells Outlet Gate Position Transmitter | Analog | 0 – 100% |
| HCS04STN01OV002 | Influent Well Overflow Gate Position Transmitter | Analog | 0 – 100% |
| HCS04VCH01IV001 | Chamber No. 1 Gate Position Transmitter | Analog | 0 – 100% |
| HCS04VCH04IV001 | Chamber No. 4 Gate Position Transmitter | Analog | 0 – 100% |
| HCS04VCH05IV001 | Chamber No. 5 Gate Position Transmitter | Analog | 0 – 100% |
| HCS04STN01TIT01 | Building Temperature Transmitter | Analog | 0 – 100 °C |

2.3 I/O LISTING

Refer to the I/O listings in Appendices A and B. Appendix A provides an I/O listing grouped by device and can be cross-referenced to the facility loop diagrams. Appendix A also includes a comprehensive list of all the Networked I/O that communicates with the PAC from other communication protocols (e.g. Modbus or DeviceNet).

Appendix B provides an I/O listing grouped by PAC I/O card assignments, and can be cross-referenced to the facility I/O drawings.

3 COMPLIANCE WITH HAMILTON SCADA STANDARDS

All work was completed in accordance with the Hamilton SCADA standards v5.0 as of January 2017 with the exception of the following deviations:

Table 3-1: HCS04 Standards Deviation

| Deviation | Description |
|-----------|-------------|
| N/A | |

4 CONTROL MODES

The station is normally unattended and is continuously monitored via the SCADA HMI at the Woodward Avenue WTP/WWTP. Three (3) control modes are available for “normal” operation of the station equipment: local, SCADA manual, and SCADA auto.

The following table defines each of the three (3) control modes as generally applied to the City’s SCADA system.

Table 4-1: HCS04 Standard Control Modes

| Local Control Modes | Description |
|---------------------|---|
| LOCAL | <p>Local control mode is selected in the field at or near the device, MCC, control panel, etc. by means of physically selecting the local control mode, commonly by using a Local-Remote or Hand-Off-Auto selector switch.</p> <p>When a device is in local mode, the device can be controlled locally only. A device in local mode cannot be controlled via the SCADA System.</p> <p>Putting a device in local mode will bypass all software interlocks and in most cases, all hardwired interlocks. In addition, devices in local mode will typically <u>not</u> be operated by hardwired backup circuits, if existing.</p> |

| Remote Control Modes | Description |
|----------------------|---|
| SCADA MANUAL | <p>Prior to selecting the SCADA Manual mode of control on the SCADA HMI system, a device must be in remote control mode. Remote control mode is selected in the field at or near the device, MCC, control panel, etc., by means of physically selecting the remote control mode, commonly by using a Local-Remote or Hand-Off-Auto selector switch.</p> <p>When a device is in remote control mode, the SCADA Manual mode is selected by an Operator on the SCADA HMI system. Control of the device is then accomplished by an Operator via commands that are input into the SCADA HMI system.</p> <p>Putting a device in SCADA Manual mode will typically bypass all software interlocks only. Hardwired interlocks will not be bypassed. Devices that are being operated in SCADA Manual mode will typically be operated by hardwired backup circuits, if existing.</p> |
| SCADA AUTO | <p>Prior to selecting the SCADA Auto mode of control on the SCADA HMI system, a device must be in remote control mode. Remote control mode is selected in the field at or near the device, MCC, control panel, etc., by means of physically selecting the remote control mode, commonly by using a Local-Remote or Hand-Off-Auto selector switch.</p> <p>When a device is in remote control mode, the SCADA Auto mode is selected by an Operator on the SCADA HMI system. Control of the device is then accomplished automatically by control logic that is programmed into a PAC/PLC.</p> <p>Putting a device in SCADA Auto mode will not bypass software interlocks or hardwired interlocks. Devices that are being operated in SCADA Auto mode will typically be operated by hardwired backup circuits, if existing.</p> |

4.1.1 Station Control Mode

This station is equipped with a selector switch which determines how the station operates. The sewage lift pumps in the Wetwell are operated under three conditions. The following table describes the control modes available.

Table 4-2: HCS04 Station Control Modes

| Control Modes | Description |
|--------------------|---|
| NORMAL MODE | <p>In Normal mode, this station acts as a Wetwell station. The pump station is isolated from the CSO storage tank.</p> <p>The chamber gates are in the following positions:</p> <ul style="list-style-type: none"> • Chamber No.1 gate = 35% • Chamber No.4 gate = 100% • Chamber No.5 gate = 30% <p>The station gates are in the following position:</p> <ul style="list-style-type: none"> • PS Inlet Gate = 100% • CSO Inlet Gate = 50% • CSO Outlet Gate =100% <p>NOTE: Gate 1 should never be open more than 35%.</p> |

| Control Modes | Description |
|--------------------------|--|
| <p>FILL MODE</p> | <p>Fill mode is selected during significant storm events that would produce flows that exceed the capacity of the Woodward WWTP to treat. When Tank Fill mode is selected from SCADA, all running sewage lift pumps are automatically turned off to fill the CSO tank cells. The chamber gates divert substantial portions of wastewater flows into the HCS04 influent well and from there into CSO Cell No.1. Storm events producing flows that exceed the storage volume of CSO Cell No.1 overflow a weir into CSO Cell No.2. Flows exceeding the capacity of CSO Cell No.2 overflow a second weir in CSO Cell No.1 and discharge into Cootes Paradise at the mouth of Chedoke Creek via Chamber No.6B.</p> <p>The chamber gates are in the following positions:</p> <ul style="list-style-type: none"> • Chamber No.1 gate = 35% • Chamber No.4 gate = 7% • Chamber No.5 gate = 2% <p>The station gates are in the following position:</p> <ul style="list-style-type: none"> • PS Inlet Gate = 100% • CSO Inlet Gate = 100% • CSO Outlet Gate = 100% <p>NOTE: Gate 1 should never be open more than 35%.</p> |
| <p>EMPTY MODE</p> | <p>After the storm event has passed and the interceptor level has decreased, the stored storm water is released back to the WSIS and the Woodward WWTP. When Empty mode is selected from SCADA, the operating sequence of the chamber gates and sewage lift pumps are as follows:</p> <ol style="list-style-type: none"> 1. When the Wetwell level is higher than 10.3 m, the sewage lift pumps are shut off. The chamber gates are in the following positions: <ul style="list-style-type: none"> • Chamber No.1 gate = 35% • Chamber No.4 gate = 7% • Chamber No.5 gate = 2% 2. When the CSO tank level is decreasing (CSO tank draining by gravity) and the Wetwell level is higher than 9.9 m but less than 10.3 m, the sewage lift pumps remain off. The chamber gates are in the following positions: <ul style="list-style-type: none"> • Chamber No.1 gate = 35% • Chamber No.4 gate = 7% • Chamber No.5 gate = 10% 3. When the CSO tank level is decreasing (CSO tank draining by gravity) and the Wetwell level is higher than 9.7 m but less than 9.9 m, the sewage lift pumps remain off. The chamber gates are in the following positions: <ul style="list-style-type: none"> • Chamber No.1 gate = 35% • Chamber No.4 gate = 100% • Chamber No.5 gate = 10% |

| Control Modes | Description |
|---------------|--|
| | <p>4. When the Wetwell level falls to 9.05 m the system flips back to Normal Mode and the DUTY 1 and DUTY 2 sewage lift pumps are started to drain the Wetwell and CSO tank.</p> <p>The station gates are in the following position:</p> <ul style="list-style-type: none"> • PS Inlet Gate = 100% • CSO Inlet Gate = 50% • CSO Outlet Gate = 100% <p>NOTE: Gate 1 should never be open more than 35%.</p> |

5 STATION CONTROL

5.1 GENERAL DESCRIPTION

5.1.1 Main Process

Dry Weather

The CSO facility is operated as a wastewater pumping station during dry weather conditions. The three (3) sewage lift pumps are operated automatically, based on Wetwell levels and associated start and stop levels setpoints programmed in the PAC logic to pump sewage into the interceptor sewer.

Sewage lift pump duty is rotated automatically at the end of each cycle by the PAC, or manually by an Operator via the SCADA HMI.

In order for a sewage lift pump to produce flow, the associated discharge valve must be open. There is no monitoring or control of the sewage lift pump discharge.

Wet (Storm) Weather

During storm events and high flow conditions, chamber gates in the collection system are operated automatically to divert storm water from the WSIS (Western Sanitary Interceptor South) and sewers into the CSO Tank Wetwell. The sewage lift pumps are stopped and storm water is allowed to overflow the Wetwell into the CSO Tank. The CSO Tank is filled by partially closing Chamber control gates 4 and 5 causing water to be diverted to the CSO Tank Cells (or into the overflow when storm water volumes exceeds the Tank capacity) and away from the WSIS sewer and the Woodward WWTP.

After the storm event has passed and the WSIS level has decreased, the stored storm water is released back to the WSIS and the Woodward WWTP. As the WSIS level drops some of the CSO Tank contents are gravity fed back into the WSIS through Chamber gates 4 and 5. CSO Tank contents below the Chamber 5 weir crest elevation of 9.05 m must be pumped out using the sewage lift pumps located in the CSO Tank Wetwell. After the CSO Tank is dewatered, a tank flushing system comprised of a series of tipping flush buckets are filled with water and dumped sequentially to flush remaining solids from the Tank.

5.1.2 CSO Sampling System Description

Two (2) 24-hour composite flow proportional samplers and sample pumps provide sample collection of the storm water influent and overflow from the CSO Tank during each storm event or when the CSO Tank is in operation. Flow monitoring devices and recorders at the CSO Tank measure the quantity of sewage being conveyed by the sewage pumping station and the quantity of the combined sewer overflow emitted to Cootes Paradise/Hamilton Harbor via the 6B Chamber to Chedoke Creek.

Influent Sampler

The Influent sample pump starts when the Wetwell level reaches 5.4 meters.

The duration of each event is captured in the PAC. The influent event duration timer to accumulate, as long as the level of the Wetwell remains above 4.9 m.

Upon indication of 5.4 m level in the Wetwell, an influent event is activated and a 24-hour timer is started. The sample pump is initiated. When the pump’s run status is confirmed the sampler may start. Sampling is triggered with one digital signal sent from the PAC every 1 minute for 24 minutes. Once the first influent bottle is filled, the influent sampler is switched to volume paced mode. In volume paced mode the number of samples taken are based on the calculated volume in the CSO tanks. Samples are taken in even volume intervals as the volume in the CSO tanks increased. Indication of an influent event occurring appears on the sampler pop-up window.

See Calculated Variables for the volume equation.

The end of a sampling event is determined by time, i.e., T_0+24 hours. If a bottle is not completely full by $T = 24$, a forced bottle change occurs. This creates a full sample by cycling the contacts once per minute to simulate a full bottle.

The PAC monitors the sample number and keeps track of the bottle numbers filled. As each bottle is filled, the bottle number is trended so the Process Supervisor can inform the operator of the dates to label the bottles collected. When all 8 bottles become full, alarms (a pop-up display and an alarm generated on the alarm summary screen) are sent to SCADA and the program is shut down and will not send any more pulses until it is reset. The SCADA sampling program needs to be reset manually from the Sampler Setpoint popup. A hardwired general alarm from the sampler does not directly end the sampling sequence; only if the sampler fails to respond to repeated sample requests from the PAC will the sampling sequencing fault. Resetting of the sampling program within SCADA is performed manually from the Sampler Setpoint popup.

Parameters listed in Table 5-3: HCS04 Effluent Sampler Key Parameters as global variables are available at SCADA in order for adjustments to be made in the future. There may have to be a security level on global variables.

Table 5-1: HCS04 Influent Sampler Key Parameters

| Parameter | Amount | Type of Variable |
|------------------------------------|--|------------------|
| Sample trigger | Wetwell level detected and volume paced as described above | Global |
| Aliquot | 50 ml | ISCO Variable |
| Number of pulses per sample bottle | 24 | |
| Minimal water level for pump | 20 mm | Local |

Table 5-2: HCS04 Influent Sampler Programming Parameters

| Step | Action | Condition |
|------|---|---|
| 1 | <ul style="list-style-type: none"> A Wetwell Event is started. The influent sample pump is started. The influent 24-hour timer is started. Pulse 24 times at 1-minute intervals (until bottle change) | <ul style="list-style-type: none"> Wetwell Level of 5.4 m |
| | <ul style="list-style-type: none"> Confirm bottle change with bottle number update | <ul style="list-style-type: none"> Bottle change |
| 2 | <ul style="list-style-type: none"> Volume Paced Sampling is started. | <ul style="list-style-type: none"> Samples are taken every 4390 m³ of volume in CSO tanks |

| Step | Action | Condition |
|------|---|---|
| 3 | <ul style="list-style-type: none"> Finish Bottle | <ul style="list-style-type: none"> 24 hours has elapsed since start of influent sequence. |
| | <ul style="list-style-type: none"> Return to Step 1 start influent event | <ul style="list-style-type: none"> If Wetwell level is still above 5.4 m the sample pump will remain off until the level rate of change in the CSO tank is seen to increase above the rate of change setpoint. |

Influent Sampling Line – Backwash Valve

When the sampling system is operating in SCADA auto mode, the PAC opens the valve for two (2) minutes to flush out the influent sampling line after the sample pump has stopped.

Overflow Sampler

The Overflow sample pump starts when the overflow channel level reaches 0.1 meters and the CSO tank cell no.1 level is above 7.7 m (if CSO tank cell no.1 level is unavailable CSO tank cell no.2 is checked to be above 7.0).

(The existing calculation in the PAC is based on the Manning equation.)

For the Main / King CSO Tank overflow weir, the center point elevation is 0.109 m above the floor under the sensor. The sensor is set so that it shows a negative “head” of 0.109 m when the channel is dry (and floor clean).

See Calculated Variables for the equation. The overflow is totalized in the PAC.

The duration of each event is captured in the PAC. The overflow event time will accumulate as long as there is a level detected in the weir above the permissive.

Upon indication of 0.1m level in the overflow channel, an overflow event is activated and the 24-hour timer is reset to zero after the first Overflow bottle is filled. The sample pump is initiated. When the pump’s run status is confirmed the sampler may start. Sampling is triggered with one digital signal sent from the PAC every 3 minutes for 72 minutes provided there is still overflow in the channel. Once the first overflow bottle is filled, the influent sampler is pulsed for the balance of the 24 samples necessary to produce a bottle change so that influent and Overflow samplers are synchronized. The second of 2 sample bottles is filled via pulses from the PAC, 24 samples, one each hour for 24 hours together with the influent sampler. Indication of an overflow event occurring appears on the sampler pop-up window.

The Overflow sampler routine works in the same manner as the influent sampler. The same failures are reported to the HMI requiring the same steps necessary to reset. Note that an incorrect bottle number does not fault the sequence.

The end of a sampling event is determined solely by time, i.e., T_0+24 hours. If a bottle is not completely full by $T = 24$, a forced bottle change occurs. This creates a full sample by cycling the contacts once per three minutes to simulate a full bottle.

The PAC monitors the sample number and keeps track of the bottle numbers filled. As each bottle is filled, the bottle number is trended so the Process Supervisor can inform the operator of the dates to label the bottles collected. When all 8 bottles become full, alarms (a pop-up display and an alarm generated on the alarm summary screen) are sent to SCADA and the program is shut down and will not send any more pulses until it is reset. The SCADA sampling program needs to be reset manually. If the sampler generates a general alarm on SCADA, then the operator retrieving the samples will have to reset the sampler locally. A hardwired general alarm from the sampler does not directly end the sampling sequence; only if the sampler fails to respond to repeated sample requests from the PAC will the sampling sequencing fault. Resetting of the sampling program within SCADA is performed manually from the Sampler Setpoint popup.

Parameters listed in the Table 5-3: HCS04 Effluent Sampler Key Parameters as global variables are available at SCADA in order for adjustments to be made in the future. There may have to be a security level on global variables.

Table 5-3: HCS04 Effluent Sampler Key Parameters

| Parameter | Amount | Type of Variable |
|------------------------------------|--|------------------|
| Sample trigger | Overflow level detected and time-pace as described above | Global |
| Aliquot | 50 ml | ISCO Variable |
| Number of pulses per sample bottle | 24 | |
| Minimal water level for pump | 20 mm | Local |

Table 5-4: HCS04 Effluent Sampler Programming Parameters

| Step | Action | Condition |
|------|--|--|
| 1 | <ul style="list-style-type: none"> An Overflow Event is started. The effluent sample pump is started. The effluent 24-hour timer is started. Pulse 24 times at 3-minute intervals (until bottle change) | <ul style="list-style-type: none"> Level over weir of 0.1 m and Cell #1 above 7.7m (or if Cell #1 unavailable Cell #2 must be above 7.0m) |
| | <ul style="list-style-type: none"> Confirm bottle change with bottle number update | <ul style="list-style-type: none"> Bottle change |
| 2 | <ul style="list-style-type: none"> Synchronize the influent sampler by rolling over to new bottle, send pulses to influent sample at 1-minute intervals until bottle change. Influent sampler waits for overflow to complete its first 24 samples | <ul style="list-style-type: none"> New bottle effluent sampler New bottle influent sampler |
| 3 | <ul style="list-style-type: none"> Send a pulse to the overflow sampler and influent sampler simultaneously | <ul style="list-style-type: none"> Every hour for 24 hrs. (T+24) |
| | <ul style="list-style-type: none"> Return to Step 1 start Overflow event | <ul style="list-style-type: none"> Event-end 24 timed-out level is still above weir |

5.1.3 CSO Tank Flushing System

The CSO Tank Flushing System is activated after the CSO Tank has been used to flush away any solids that may remain on the floor of the tank cells. Wash water valves are opened in sequence to fill tipping flush buckets that then dump onto the tank floor, pushing residual waste towards the station Wetwell where it can be pumped towards the Woodward WWTP.

Wash Water Valves

There is one (1) dedicated wash water solenoid valve per pair of backwash tipping flush buckets. The solenoid valves open to fill the flush buckets with water. Valves no.1 to 5 are for washing CSO tank cell no.1, and valves no.6 to 15 are for washing CSO tank cell no.2. The wash water trough has a dedicated solenoid flush valve (no.16) and is located in CSO tank cell no.2. There is one shut-off valve on the main flushing water line that closes to stop water flow on the condition that any wash water solenoid valve fails to close when commended to.

Tipping Flush Buckets

There are 30 tipping flush buckets for backwashing the CSO tank. Flush buckets are numbered (TB01 to TB30). Ten buckets, no.1 to 10, are used to backwash CSO tank cell no.1, and 20 buckets, no.11 to 30, are used to backwash CSO tank cell no.2. The Solenoid-controlled flush bucket fill valves open to fill the flushing buckets with water. Solenoid valve no.1 fills buckets no.1 & 2; valve no.2 fills buckets no.3 & 4, and so on. After the tipping flush bucket is filled, gravity tips the pivoting bucket and the water spills into the CSO tank floor. CSO tank cells no.1 and 2 can be flushed independently.

5.1.4 CSO Tank Lighting System

The main CSO tank lighting system is activated from the SCADA HMI to provide visibility in the CSO tank. There is also an emergency lighting system which can be activated from the SCADA HMI during a power failure.

5.1.5 CSO Tank Supply Fan System

The CSO tank supply fan system is activated during a high combustible gas condition or when the CSO tank lighting system is active.

5.2 SUMMARY OF RELATED DEVICES

There are no additional devices from other controllers related to this station's operation.

Table 5-5: HCS04 Related Devices Summary

| SCADA Tag | Equipment Description |
|------------------|------------------------------|
| N/A | |

5.3 PROCESS CONTROL LOGIC

The following subsections describe the operation of the SCADA-connected major equipment. Refer to “Appendix G – Program Variables & Internal Software Parameters” for setpoint information.

5.3.1 Equipment Starting/Opening

In HAND/LOCAL position (Local Mode):

- Sewage lift pump (constant speed) is started by pressing the START button on the MCC unless prevented by an interlock or fault.
- Chamber gate (modulating) is opened by pressing and holding the OPEN button on the MCC until the desired position is obtained unless prevented by an interlock or fault.
- Sample pump (constant speed) is started by pressing the start button on the MCC unless prevented by an interlock or fault.
- There is no local control of the Flush valves.
- Gallery supply fan (constant speed) is started by pressing the START button on the MCC unless prevented by an interlock of fault.

In OFF position (Local Mode):

- Equipment in the OFF position cannot be started.

In AUTO/REMOTE position (SCADA Manual Mode):

- Sewage lift pump (constant speed) is started by clicking on the START button on the SCADA HMI unless prevented by an interlock or fault.
- Chamber gate (modulating) is opened by entering a position setpoint on the SCADA HMI unless prevented by an interlock or fault.
- Sample pump (constant speed) is started by clicking on the START button on the SCADA HMI unless prevented by an interlock or fault.
- Flush valve (discrete) is opened by clicking on the OPEN button on the SCADA HMI unless prevented by an interlock or fault.
- Gallery supply fan (constant speed) is started by clicking on the START button on the SCADA HMI unless prevented by an interlock or fault.

In AUTO/REMOTE position (SCADA Auto Mode):

- Sewage lift pump (constant speed) is started automatically based on setpoints programmed in the PAC, unless prevented by an interlock or fault.
- Chamber gate (modulating) is opened automatically based on setpoints programmed in the PAC, unless prevented by an interlock or fault.
- Sample pump (constant speed) is started automatically based on setpoints programmed in the PAC, unless prevented by an interlock or fault.
- Flush valve (discrete) is opened automatically based on setpoints programmed in the PAC, unless prevented by an interlock or fault.
- Gallery supply fan (constant speed) is started automatically based on setpoints programmed in the PAC, unless prevented by an interlock or fault.

5.3.2 Equipment Running/Positioning

In HAND/LOCAL position (Local Mode):

- Sewage lift pump (constant speed) runs at full speed. An interlock or fault will automatically shut down the pump.
- Chamber gate (modulating) maintains position.
- Sample pump (constant speed) runs at full speed. An interlock or fault will automatically shut down the pump.
- Flush valve (discrete) maintains position.
- Gallery supply fan (constant speed) runs at full speed. An interlock or fault will automatically shut down the pump.

In AUTO/REMOTE position (SCADA Manual Mode):

- Sewage lift pump (constant speed) runs at full speed. An interlock or fault will automatically shut down the pump.
- Chamber gate (modulating) maintains position. An interlock will automatically close the gate.
- Sample pump (constant speed) runs at full speed. An interlock or fault will automatically shut down the pump.
- Flush valve (discrete) maintains position. An interlock will automatically close the valve.

- Gallery supply fan (constant speed) runs at full speed. An interlock or fault will automatically shut down the pump.

In AUTO/REMOTE position (SCADA Auto Mode):

- Sewage lift pump (constant speed) runs at full speed. An interlock or fault will automatically shut down the pump.
- Chamber gate (modulating) maintains position. An interlock will automatically close the gate.
- Sample pump (constant speed) runs at full speed. An interlock or fault will automatically shut down the pump.
- Flush valve (discrete) maintains position. An interlock will automatically close the valve.
- Gallery supply fan (constant speed) runs at full speed. An interlock or fault will automatically shut down the pump.

5.3.3 Equipment Stopping/Closing

In HAND/LOCAL position (Local Mode):

- Sewage lift pump (constant speed) is stopped by pressing the STOP button on the MCC.
- Chamber gate (modulating) is closed by pressing and holding the CLOSE button on the MCC until the desired position is obtained.
- Sample pump (constant speed) is stopped by pressing the STOP button on the MCC.
- There is no local control of the Flush valves.
- Gallery supply fan (constant speed) is stopped by pressing the STOP button on the MCC.

In AUTO/REMOTE position (SCADA Manual Mode):

- Sewage lift pump (constant speed) is stopped by clicking on the STOP button on the SCADA HMI.
- Chamber gate (modulating) is closed by entering a position setpoint of zero on the SCADA HMI.
- Sample pump (constant speed) is stopped by clicking on the STOP button on the SCADA HMI.
- Flush valve (discrete) is closed by clicking on the CLOSE button on the SCADA HMI.
- Gallery supply fan (constant speed) is stopped by clicking on the STOP button on the SCADA HMI.

In AUTO/REMOTE position (SCADA Auto Mode):

- Sewage lift pump (constant speed) is stopped automatically based on setpoints programmed in the PAC.
- Chamber gate (modulating) is closed automatically based on setpoints programmed in the PAC.
- Sample pump (constant speed) is stopped automatically based on setpoints programmed in the PAC.
- Flush valve (discrete) is closed automatically based on setpoints programmed in the PAC.
- Gallery supply fan (constant speed) is stopped automatically based on setpoints programmed in the PAC.

5.4 MAJOR EQUIPMENT CONTROL LOGIC

5.4.1 Control Modes

Local control mode for a device is attained by placing the selector switch for the device in the LOCAL or HAND position. The selector switch is located on the MCC, by the equipment, or on the equipment control panel. In local mode, the equipment is controlled directly by switches or pushbuttons and all software interlocks are bypassed.

Equipment is transferred to remote mode by placing the selector switch for the device in the REMOTE or AUTO position. In remote mode, the equipment can be controlled in either SCADA manual or SCADA auto modes of control.

Hardwired backup control may be available for some equipment. When the selector switch for a piece of equipment is in the REMOTE or AUTO position, the equipment can be automatically operated by hardwired devices at the station.

The following table summarizes the control modes for the equipment:

Table 5-6: HCS04 Mechanical Equipment Modes of Operation

| SCADA Tag | Equipment Description | Local | SCADA Manual | SCADA Auto | Hardwired Backup Control |
|-----------------|-----------------------------|-------------------------------------|-------------------------------------|-------------------------------------|--------------------------|
| HCS04SLP0100000 | Sewage Lift Pump No.1 | <input checked="" type="checkbox"/> | <input checked="" type="checkbox"/> | <input checked="" type="checkbox"/> | |
| HCS04SLP0200000 | Sewage Lift Pump No.2 | <input checked="" type="checkbox"/> | <input checked="" type="checkbox"/> | <input checked="" type="checkbox"/> | |
| HCS04SLP0300000 | Sewage Lift Pump No.3 | <input checked="" type="checkbox"/> | <input checked="" type="checkbox"/> | <input checked="" type="checkbox"/> | |
| HCS04SAM0100000 | Influent Sampler | <input checked="" type="checkbox"/> | | <input checked="" type="checkbox"/> | |
| HCS04SAM01VLV01 | Influent Backwash Valve | <input checked="" type="checkbox"/> | <input checked="" type="checkbox"/> | <input checked="" type="checkbox"/> | |
| HCS04SAM0200000 | Overflow Sampler | <input checked="" type="checkbox"/> | | <input checked="" type="checkbox"/> | |
| HCS04SAP0100000 | Sample Pump No.1 | <input checked="" type="checkbox"/> | <input checked="" type="checkbox"/> | <input checked="" type="checkbox"/> | |
| HCS04SAP0200000 | Sample Pump No.2 | <input checked="" type="checkbox"/> | <input checked="" type="checkbox"/> | <input checked="" type="checkbox"/> | |
| HCS04STN01IV001 | Wetwell Inlet Gate | <input checked="" type="checkbox"/> | <input checked="" type="checkbox"/> | <input checked="" type="checkbox"/> | |
| HCS04STN01IV002 | CSO Tank Inlet Gate | <input checked="" type="checkbox"/> | <input checked="" type="checkbox"/> | <input checked="" type="checkbox"/> | |
| HCS04STN01OV001 | CSO Tank Outlet Gate | <input checked="" type="checkbox"/> | <input checked="" type="checkbox"/> | <input checked="" type="checkbox"/> | |
| HCS04STN01OV002 | Influent Well Overflow Gate | <input checked="" type="checkbox"/> | | | |
| HCS04VCH01IV001 | Chamber No.1 Gate | <input checked="" type="checkbox"/> | <input checked="" type="checkbox"/> | <input checked="" type="checkbox"/> | |
| HCS04VCH04IV001 | Chamber No.4 Gate | <input checked="" type="checkbox"/> | <input checked="" type="checkbox"/> | <input checked="" type="checkbox"/> | |
| HCS04VCH05IV001 | Chamber No.5 Gate | <input checked="" type="checkbox"/> | <input checked="" type="checkbox"/> | <input checked="" type="checkbox"/> | |
| HCS04WWT01SOL01 | Cell No.1 Flush Valve No.1 | <input checked="" type="checkbox"/> | <input checked="" type="checkbox"/> | <input checked="" type="checkbox"/> | |

| SCADA Tag | Equipment Description | Local | SCADA Manual | SCADA Auto | Hardwired Backup Control |
|-----------------|--|-------------------------------------|-------------------------------------|-------------------------------------|--------------------------|
| HCS04WWT01SOL02 | Cell No.1 Flush Valve No.2 | <input checked="" type="checkbox"/> | <input checked="" type="checkbox"/> | <input checked="" type="checkbox"/> | |
| HCS04WWT01SOL03 | Cell No.1 Flush Valve No.3 | <input checked="" type="checkbox"/> | <input checked="" type="checkbox"/> | <input checked="" type="checkbox"/> | |
| HCS04WWT01SOL04 | Cell No.1 Flush Valve No.4 | <input checked="" type="checkbox"/> | <input checked="" type="checkbox"/> | <input checked="" type="checkbox"/> | |
| HCS04WWT01SOL05 | Cell No.1 Flush Valve No.5 | <input checked="" type="checkbox"/> | <input checked="" type="checkbox"/> | <input checked="" type="checkbox"/> | |
| HCS04WWT01VLV01 | Main Flushing Water Line Shutoff Valve | <input checked="" type="checkbox"/> | <input checked="" type="checkbox"/> | <input checked="" type="checkbox"/> | |
| HCS04WWT02SOL06 | Cell No.2 Flush Valve No.6 | <input checked="" type="checkbox"/> | <input checked="" type="checkbox"/> | <input checked="" type="checkbox"/> | |
| HCS04WWT02SOL07 | Cell No.2 Flush Valve No.7 | <input checked="" type="checkbox"/> | <input checked="" type="checkbox"/> | <input checked="" type="checkbox"/> | |
| HCS04WWT02SOL08 | Cell No.2 Flush Valve No.8 | <input checked="" type="checkbox"/> | <input checked="" type="checkbox"/> | <input checked="" type="checkbox"/> | |
| HCS04WWT02SOL09 | Cell No.2 Flush Valve No.9 | <input checked="" type="checkbox"/> | <input checked="" type="checkbox"/> | <input checked="" type="checkbox"/> | |
| HCS04WWT02SOL10 | Cell No.2 Flush Valve No.10 | <input checked="" type="checkbox"/> | <input checked="" type="checkbox"/> | <input checked="" type="checkbox"/> | |
| HCS04WWT02SOL11 | Cell No.2 Flush Valve No.11 | <input checked="" type="checkbox"/> | <input checked="" type="checkbox"/> | <input checked="" type="checkbox"/> | |
| HCS04WWT02SOL12 | Cell No.2 Flush Valve No.12 | <input checked="" type="checkbox"/> | <input checked="" type="checkbox"/> | <input checked="" type="checkbox"/> | |
| HCS04WWT02SOL13 | Cell No.2 Flush Valve No.13 | <input checked="" type="checkbox"/> | <input checked="" type="checkbox"/> | <input checked="" type="checkbox"/> | |
| HCS04WWT02SOL14 | Cell No.2 Flush Valve No.14 | <input checked="" type="checkbox"/> | <input checked="" type="checkbox"/> | <input checked="" type="checkbox"/> | |
| HCS04WWT02SOL15 | Cell No.2 Flush Valve No.15 | <input checked="" type="checkbox"/> | <input checked="" type="checkbox"/> | <input checked="" type="checkbox"/> | |
| HCS04WWT02SOL16 | Cell No.2 Trough Flush Valve No.16 | <input checked="" type="checkbox"/> | <input checked="" type="checkbox"/> | <input checked="" type="checkbox"/> | |

5.4.2 Hardwired Interlocks

Hardwired interlocks are used for equipment and personnel safety or backup control. These will stop/close the equipment and prevent it from restarting, under specific control modes. All hardwired interlocks are also programmed into the controller to prevent the PAC from attempting to take control under a hardwired interlock condition. The following hardwired interlocks are installed:

Table 5-7: HCS04 Hardwired Interlocks by Device

| Device | Interlock | Action / Consequences | Interlock Active In | | | |
|---|---------------------------|--|-------------------------------------|-------------------------------------|-------------------------------------|-------------------------------------|
| | | | Local | SCADA Manual | SCADA Auto | Latching |
| HCS04SAP0100000 HCS04SAP0200000 | Sample Pump General Fault | Sample pump motor stops. The interlock is unlatched when the general fault is reset. | <input checked="" type="checkbox"/> | <input checked="" type="checkbox"/> | <input checked="" type="checkbox"/> | <input checked="" type="checkbox"/> |
| HCS04SFN0100000 HCS04SFN0200000 HCS04SFN0300000 HCS04SFN0400000 HCS04SFN0500000 | Supply Fan General Fault | Supply fan motor stops. The interlock is unlatched when the general fault is reset. | <input checked="" type="checkbox"/> | <input checked="" type="checkbox"/> | <input checked="" type="checkbox"/> | <input checked="" type="checkbox"/> |
| HCS04SLP0100000 HCS04SLP0200000 HCS04SLP0300000 | SLP General Fault | Sewage lift pump motor stops. The interlock is unlatched when the general fault is reset. | <input checked="" type="checkbox"/> | <input checked="" type="checkbox"/> | <input checked="" type="checkbox"/> | <input checked="" type="checkbox"/> |

5.4.3 Backup Control System

There is no hardwired backup control at this site.

5.4.4 Software Interlocks

Software interlocks are used to prevent the operation of equipment in SCADA auto and occasionally SCADA manual modes of control based on specific requirements. In the local mode, all PAC software interlocks are bypassed. Software interlocks are active in the following modes of control:

Table 5-8: HCS04 Software Interlocks By Device

| Device | Interlock | Action / Consequences | Interlock Active In | | | |
|---|--|--|---------------------|-------------------------------------|-------------------------------------|----------|
| | | | Local | SCADA Manual | SCADA Auto | Latching |
| HCS04SLP0100000 HCS04SLP0200000 HCS04SLP0300000 | Generator Running | When generator is running and two sewage lift pumps are running, the third sewage lift pump motor will be interlocked. | | <input checked="" type="checkbox"/> | <input checked="" type="checkbox"/> | |
| | Wetwell LIT General Fault / Signal Error | PAC will stop the SLP until the fault is cleared / the level signal is re-established. | | | <input checked="" type="checkbox"/> | |

| Device | Interlock | Action / Consequences | Interlock Active In | | | |
|---|--|--|---------------------|-------------------------------------|-------------------------------------|----------|
| | | | Local | SCADA Manual | SCADA Auto | Latching |
| HCS04SFN0100000 HCS04SFN0200000 HCS04SFN0300000 HCS04SFN0400000 HCS04SFN0500000 | 600V Power Supply Failed | PAC will stop the Gallery Supply Fan | | <input checked="" type="checkbox"/> | <input checked="" type="checkbox"/> | |
| HCS04STN01LHT01 HCS04STN01LHT02 HCS04STN01LHT03 HCS04STN01LHT04 HCS04STN01LHT05 HCS04STN01LHT06 HCS04STN01LHT07 | Area Lighting Contactors C7 Master Interlock | PAC will prevent the lights from turning on. | | <input checked="" type="checkbox"/> | <input checked="" type="checkbox"/> | |

5.4.5 Program Variables & Internal Software Parameters

Program variables are values within the PAC logic that are adjustable through the SCADA HMI based on security level authorization.

Internal software parameters are values are entered in the PAC programs that are set at the time of commissioning and not adjustable from the SCADA system.

Refer to “Appendix G – Program Variables and Internal Software Parameters” for a detailed table of program variables and internal software parameters.

5.4.6 Calculated Variables

The following parameters are calculated within the PAC logic:

Table 5-9: HCS04 Calculated Values

| Control Parameter | Calculation Description | Variables |
|--|--|---|
| Overflow Weir Flow HCS04STN01FIT02CV_ | $Q = CLH^{3/2}$ | <ul style="list-style-type: none"> Q = Flow (m³/s) C = Weir Flow Coefficient 1.83 L = Weir Crest Length 4.5 m H = “Head” on Weir 0.109 m (when the channel is dry) |
| CSO Tank Cell No.1 Volume (m ³) | = (Cell No.1 Level) * (Cell No.1 Area) | <ul style="list-style-type: none"> Cell No.1 Level (HCS04WWT01LIT01) Cell No.1 Area 2,890 m |

| Control Parameter | Calculation Description | Variables |
|---|--|--|
| CSO Tank Cell No.2 Volume (m ³) | = (Cell No.2 Level) * (Cell No.2 Area) | <ul style="list-style-type: none"> Cell No.2 Level (WWT01LIT02) Cell No.2 Area 6,890 m |
| CSO Tank Total Volume (m ³) | = (Cell No.1 Volume) + (Cell No.2 Volume) | <ul style="list-style-type: none"> Cell No.1 Volume (m³) Cell No.2 Volume (m³) |
| Volume Paced Required Samples | = (CSO Tank Volume) / (Sampler Trigger Volume) | <ul style="list-style-type: none"> CSO Tank Volume (m³) Influent Sampler Trigger Volume 3,060 m³ |

5.4.7 Normal Operating Conditions

During normal dry weather station operation, the Wetwell level signal is used by the PAC to control the sewage lift pumps. The PAC program automatically assigns individual sewage lift pump duties (Duty 1, Duty 2, and Standby) based on sewage lift pump availability and runtime. The PAC program also alternates sewage lift pump operation between each duty cycle.

Each sewage lift pump has an individual No Flow Setpoint which is adjustable from the pump pop-up. If a pump is running in SCADA-auto mode and the observed flow fails to exceed the No Flow Setpoint for a set time delay, the pump will stop and a No Flow alarm will be annunciated on the HMI. This alarm will need to be acknowledged before the pump will be allowed to restart under SCADA-auto mode. Note that a No Flow alarm will not stop a pump while operating in SCADA-manual mode but the No Flow alarm will still be annunciated on the HMI.

5.4.8 Normal Backwashing Sequence

For a backwash sequence to start, the level in both CSO tanks must be below 1m. Once the sequence is started the following sequence is followed.

Backwash CSO Tank Cell No.1:

12. Flush bucket fill valve no.1 is opened for a time period sufficient to tipping flush buckets no.1 & 2;
13. Flush buckets no.1 & 2 are full and tilted then flush bucket fill valve no.1 is closed;
14. Flush bucket fill valve 2 is opened for a time period sufficient to tipping flush buckets no.3 & 4;
15. Flush buckets no.3 & 4 are full and tilted then flush bucket fill valve no.2 is closed;
16. Flush bucket fill valve 3 is opened for a time period sufficient to tipping flush buckets no.5 & 6;
17. Flush buckets no.5 & 6 are full and tilted then flush bucket fill valve no.3 is closed;
18. Flush bucket fill valve 4 is opened for a time period sufficient to tipping flush buckets no.7 & 8;
19. Flush buckets no.7 & 8 are full and tilted then flush bucket fill valve no.4 is closed;
20. Flush bucket fill valve 5 is opened for a time period sufficient to tipping flush buckets no.9 & 10;
21. Flush buckets no.9 & 10 are full and tilted then flush bucket fill valve no.5 is closed.
22. CSO Tank Cell no.1 backwash is completed.

Backwash CSO Tank Cell No.2:

22. Flush bucket fill valve no.6 is opened for a time period sufficient to tipping flush buckets no.11 & 12;
23. Flush buckets no.11 & 12 are full and tilted then flush bucket fill valve no.6 is closed;
24. Flush bucket fill valve no.7 is opened for a time period sufficient to tipping flush buckets no.13 & 14;
25. Flush buckets no.13 & 14 are full and tilted then flush bucket fill valve no.7 is closed;
26. Flush bucket fill valve no.8 is opened for a time period sufficient to tipping flush buckets no.15 & 16;
27. Flush buckets no.15 & 16 are full and tilted then flush bucket fill valve no.8 is closed;
28. Flush bucket fill valve no.9 is opened for a time period sufficient to tipping flush buckets no.17 & 18;
29. Flush buckets no.17 & 18 are full and tilted then flush bucket fill valve no.9 is closed;
30. Flush bucket fill valve no.10 is opened for a time period sufficient to tipping flush buckets no.19 & 20;

31. Flush buckets no.19 & 20 are full and tilted then flush bucket fill valve no.10 is closed;
32. Flush bucket fill valve no.11 is opened for a time period sufficient to tipping flush buckets no.21 & 22;
33. Flush buckets no.21 & 22 are full and tilted then flush bucket fill valve no.11 is closed;
34. Flush bucket fill valve no.12 is opened for a time period sufficient to tipping flush buckets no.23 & 24;
35. Flush buckets no.23 & 24 are full and tilted then flush bucket fill valve no.12 is closed;
36. Flush bucket fill valve no.13 is opened for a time period sufficient to tipping flush buckets no.25 & 26;
37. Flush buckets no.25 & 26 are full and tilted then flush bucket fill valve no.13 is closed;
38. Flush bucket fill valve no.14 is opened for a time period sufficient to tipping flush buckets no.27 & 28;
39. Flush buckets no. 27 & 28 are full and tilted then flush bucket fill valve no.14 is closed;
40. Flush bucket fill valve no.15 is opened for a time period sufficient to tipping flush buckets no.29 & 30;
41. Flush buckets no.29 & 30 are full and tilted then flush bucket fill valve no.15 is closed.
42. CSO Tank Cell no.2 backwash is completed.

After the backwash cycle is complete, flush bucket fill valve no.16 is activated for two minutes to flush the trough. Should any flush bucket fill valve fail to open when commanded as determined by the city water pressure transmitter (no pressure drop), an alarm is annunciated on the SCADA HMI and the next tipping flush buckets fill in the sequence until the entire sequence is complete. Should three (3) or more flush bucket fill valves fail to close when commanded as determined by the city water pressure transmitter (no pressure increase) an alarm is annunciated on the SCADA HMI, the main flushing water line shut-off line is commanded to close and the flush sequence is terminated.

5.4.9 Demo Backwashing Sequence

The DEMO mode is a short cycle, used to demonstrate the backwashing process.

When the DEMO mode is selected from the SCADA HMI, flush bucket fill valve no.1 opens for a time period sufficient to fill tipping flush buckets no. 1 and 2. When full, the flush buckets tip, flush bucket fill valve no.1 closes, and flush bucket fill valve no.2 opens to fill tipping flush buckets no.3 and 4. When full, the flush buckets tip, flush bucket fill valve no.2 closes, and the cycle repeats until the timers set for both flush bucket fill valves time out.

5.4.10 Influent and Overflow Sampler Modes

Table 5-10: HCS04 Sampler Modes

| Sampler Mode | Description |
|--|---|
| 7. Inactive | No samples are taken and sampler pumps remain off |
| 8. Time Paced Sample | Time Paced Sampling begins when the level increases above the sampler pump start setpoint. Samples are taken at defined intervals until bottle change (24 samples). The influent sampler uses an intervals of 60 seconds while the overflow sampler uses and interval of 180 seconds. |
| 9. Volume Paced Sample (Influent Sampler only) | After 24 samples have been taken in time paced mode the Influent Sampler is put in volume paced sample mode. A sample is taken for every 4390 m ³ of volume in the CSO tanks. See Calculated Variables for volume paced calculations. |
| 10. Hourly Samples | After 24 samples have been taken by the Overflow Sampler, the Overflow Sampler is put into Hourly Samples mode. The Influent sample is issued a command to finish its current bottle and then sync with the Overflow Sampler. Once synchronized, samples are taken every hour for 24 hours. After 24 samples are taken both samplers are moved to the Inactive state. They will then move to Time Paced Mode if the start conditions are met. |

| Sampler Mode | Description |
|-------------------|--|
| 11. Finish Bottle | When in Finish Bottle mode, samples will be taken at the minimum allowed interval until the current bottle is finished (24 samples). The Influent Sampler has a minimum sample interval of 60 seconds while the Overflow Sampler has a minimum sample interval of 180 seconds. After the finish bottle sequence is complete the sample event ends. |
| 12. Overflow Sync | When Overflow Hourly Sample Mode begins it moves the Influent Sampler into Finish Bottle mode in order to synchronize the Influent Sampler with the Overflow Sampler. Once synchronized with the Overflow Sampler, the Influent sampler will remain in Overflow Sync Mode until the Overflow Sampler has completed its sequence. |

5.4.11 SCADA Auto Starting/Stopping Conditions

In SCADA auto mode the equipment is controlled by the PAC logic. The PAC operates the equipment as follows:

On Rising Wetwell Level:

- Sewage level rises above the Duty 1 start level. Duty 1 sewage lift pump starts.
- Sewage level rises above the Duty 2 start level. Duty 2 sewage lift pump starts.

On Falling Wetwell Level:

- All duty sewage lift pumps run when the sewage level is at or above the Duty 2 start level.
- Sewage level drops below the Duty 2 stop level. Duty 2 sewage lift pump stops.
- Sewage level drops below the Duty 1 stop level. Duty 1 sewage lift pump stops.

Refer to “Figure 5-1: HCS04 Normal Operating Levels” for normal operating levels of the Wetwell.




Figure 5-1: HCS04 Normal Operating Levels

5.4.12 Automatic Duty Rotation Modes

When in SCADA auto mode, five (5) automatic duty rotation modes are available.

Table 5-11: HCS04 Duty Rotation Modes

| Duty Rotation Mode | Description |
|--------------------------|--|
| 13. Cycle End* | Automatic duty rotation will occur after the completion of a pumping cycle, when the sewage lift pumps have stopped. Typically, it is City policy to set all duty stop setpoints at the same level. |
| 14. Cycle End & Runtime* | Automatic duty rotation will occur after the completion of a pumping cycle based on accumulated runtime. The pump with the least amount of runtime will always be placed in the Duty 1 position. |
| 15. Set Time* | Automatic duty rotation will occur at a preset time each day. |
| 16. Set Time & Runtime* | Automatic duty rotation will occur at a preset time, and the pump with the least amount of running time will always be placed in the Duty 1 or lead position. |
| 17. Manual | An operator rotates the sewage lift pump duty assignments via the SCADA HMI. |

*For duty rotation modes 1, 2, 3, and 4, automatic duty rotation will always occur if the Duty 1 pump is failed. The next available pump will be automatically rotated into the Duty 1 position.

An available pump is a pump that is in SCADA auto mode, and is not out of service or faulted.

Single Sewage Lift Pump Failure

On failure of the Duty 1 sewage lift pump, the pump will be unavailable and removed from the duty rotation. The Duty 2 sewage lift pump will be moved to the Duty 1 position and the standby sewage lift pump will be moved to the Duty 2 position. This rotation is bumpless if the Duty 2 pump is already running. Otherwise, the new Duty 1 pump will start as required by the PAC. A sewage lift pump that is faulted will not be included in the duty rotation. The pump will be put back into the duty rotation when the fault is cleared and the pump is put into SCADA auto mode.

All Sewage Lift Pumps Fail

Immediate action must be taken by Operations staff to prevent flooding of the station. Contact the process supervisor for further direction.

6 WASTEWATER EVENT MANAGEMENT

This following table describes critical events that present risk to the operation of this station and defines how these events are mitigated through systems and practices built into the SCADA system:

Table 6-1: HCS04 Wastewater Event Management

| Hazard and Effect | Risk Level | Critical Risk | Risk Mitigation | Processes & Procedures |
|--|------------|---------------|---|--|
| SCADA HMI Communications Failure. | Low | No | The Station is able to function without the SCADA HMI connection. | Additional operational resources may be required to monitor and/or operate the station locally while repairs are being made. |
| PAC Failure. Potential for Wetwell overflow and spillage into the environment. | Med | Yes | The PAC is monitored by SCADA. | Additional operational resources may be required to monitor and/or operate the station locally while repairs are being made. |
| Mechanical Failure of Sewage Lift Pump | Low | No | There are multiple pumps for redundancy. | Issue work order and follow policies and procedures to replace equipment. |
| Facility Power Failure | High | Yes | Backup generator power available. | Electrical or Equipment Failure Emergency procedure. |
| Sabotage - Damage to Equipment/Property. Possible loss of function. | Low | No | Facility is locked and has an alarm system. | Call police and process supervisor. |

7 FAULT RESPONSE AND ALARMS

7.1 FAULT RESPONSE OPERATION

7.1.1 Power Failure

Facility Power Failure

In the event of a station power failure, all equipment in the facility that is not backed up by UPS power will shut down.

There is an ATS located at this station for automatic transfer between hydro power and generator power. If hydro power fails, a portable generator can be connected to the station. Once the portable generator is running, the ATS will transfer to generator power. Upon restoration of hydro, the ATS will seamlessly transfer back to hydro power. The portable generator will then need to be shut down and removed from the station.

When power is restored, a sewage lift pump in LOCAL/HAND mode will need to be restarted with the start pushbutton. A sewage lift pump that was in SCADA manual mode prior to the power failure will need to be restarted manually via the SCADA HMI. A sewage lift pump that was in SCADA auto mode will operate based on the PAC control setpoints after a preset delay – no operator intervention is required.

Refer to “Section 8.1 - Electrical Equipment and Standby Power” for more information.

PAC Panel Power Failure

The PAC, instruments, backup control system, and network equipment are powered by a UPS. If power does not return or generator power is not available prior to the UPS battery draining to empty, the PAC and communications equipment will power down, and communications to the station will be lost. Refer to “Appendix C – SCADA HMI Screens and P&IDs” for the UPS pop up screen for status information that is available remotely from the UPS.

7.1.2 SCADA Communication Failure

The HMI and panel computer each send individual heartbeat signals to the PAC every 10 seconds. If no heartbeat signal is received for a period of 120 seconds, the HMI, panel computer, and PAC will set a communication alarm. In the event of an HMI or panel computer to PAC communication failure, the equipment will continue to operate in its last state and the PAC automatic logic will continue to operate equipment in SCADA auto mode of control.

Operations staff is to treat communication alarms as high priority. There is no way to remotely determine if the loss of communications is due to power failure, communication infrastructure failure, or catastrophic failure of the station. No remote alarming will be possible from the station during a communications failure.

7.1.3 PAC Failure

If the station PAC fails, the PAC will not be able to control the pumps or other station equipment. The station will operate on the hardwired backup control systems to control the sewage lift pumps while the PAC is unavailable. The pumps can also be operated manually at the station.

Upon PAC restart, the equipment in SCADA auto mode will restart as required.

7.1.4 Wetwell Level Transmitter Failure

If the Wetwell level transmitter fails, a transmitter fault will be annunciated on the SCADA HMI and any sewage lift pumps running in SCADA Auto mode will be commanded to stop; sewage lift pumps in SCADA Manual or local modes will continue to operate normally.

7.1.5 Flow Transmitter Failure

Upon failure of the station discharge flow transmitter, a transmitter fault will be annunciated on the SCADA HMI and operations will have to visit the site to determine the cause of failure. Until the discharge flow transmitter fault is corrected, the discharge flow will not be able to be accurately measured and the station's flow will remain unconfirmed.

7.1.6 Sluice Gate Failure

If a sluice gate is faulted, an alarm will be annunciated on the SCADA HMI indicating that the gate has failed. The sluice gate will not be able to be operated remotely in SCADA manual mode or SCADA auto mode, and in many cases, local mode.

Fault Conditions that will stop a Sluice Gate

- Torque/Overload Alarm

7.1.7 Sampler Unresponsive

If a sampler fails to annunciate that a sample has been taken after a sample is requested the sample event will end and the associated sampler pump will shut down. The sampler must be manually reset to clear the failure.

Fault Conditions that will stop a Sampler

- Maximum Bottle Limit Exceeded Alarm
- Sampler Failed to take sample – Sequence Error Detected Alarm

7.1.8 Sewage Lift Pump Failure

If a sewage lift pump is faulted, an alarm will be annunciated on the SCADA HMI indicating that the pump has failed. The sewage lift pump will not be able to be operated remotely in SCADA manual mode or SCADA auto mode, and in many cases, local mode. If a sewage lift pump failure occurs while the sewage lift pump is in SCADA auto mode, the PAC will repeatedly attempt to stop the sewage lift pump until the pump stops.

Fault Conditions that will shut down a Sewage Lift Pump

- General Fault
- Facility Power Failure

7.2 ALARMS

All alarms will be displayed on the SCADA HMI and local panel computer. Process setpoints can be changed and alarm setpoints are accessible from the SCADA HMI or local panel computer based on security clearance. Trending of process variables is provided from SCADA HMI or local panel computer.

Note that trends on the local panel computer are not tied to the Hamilton historical database; they are locally logged only. The panel computer is configured to automatically acknowledge all alarms at midnight every day. This clears alarms on the panel computer only. It does not clear alarms on the SCADA HMI system at the Woodward/Dundas Plants.

Appendix E contains a Table of alarms associated with this station and generated by the PAC. All alarms are of the Boolean Data Type and are recorded by the Historian as an alarm.

Note:

- The HMI alarm areas for this station/process area are: HCS04 and HAMC.

- The HMI security area for this process area is: CSOP.
- All pump no-flow alarms are conditioned for a pump only while it is running.
- All analog high high, high, low, and low low alarms are conditioned to only be active when there are no faults on the associated instrument.

7.2.1 Sewage Lift Pump Virtual Alarm Auto-Acknowledge

The PAC is programmed to auto-acknowledge sewage lift pump virtual alarms. When enabled, the PAC will auto-acknowledge all PAC generated virtual alarms after 60 seconds. Up to nine (9) virtual alarms will be auto-acknowledged within a one (1) hour period. If a tenth virtual alarm is triggered within the one (1) hour period, an alarm will be annunciated on the SCADA HMI and virtual alarms will no longer be auto-acknowledged until the Operator acknowledges this alarm.

7.2.2 HMI - Red Screen

Very critical processes in some facilities or areas require immediate attention and action. The City of Hamilton uses a 'Red Screen' on the SCADA HMI to annunciate these alarms. All conditions for a Red Screen are grouped under one (1) SCADA tag (HCS04STN0100000RS_) in the PAC program.

The conditions for the red screen are:

- Overflow Event in Progress OR Flushing Sequence Failed

Refer to the Alarm table in Appendix E for alarms at this station that will cause a Red Screen to be displayed.

7.2.3 Pilot Lights

'System OK' Pilot Light

Under normal conditions, the System OK pilot light is lit. The System OK pilot light is turned off by the PAC when there are any active alarms/faults (including equipment virtual alarms, but excluding SCADA system specific alarms) that are monitored by the PAC. The System OK pilot light will relight once all alarms/faults have been cleared.

'SCADA Alarm' Pilot Light

Under normal conditions, the SCADA Alarm pilot light is off. The 'SCADA alarm' pilot light is turned on by the PAC for SCADA specific set of faults, such as an I/O card fault, UPS fault, DC power supply fault, Ethernet switch fault, etc. Operations are to notify the SCADA Group in the event that this pilot light is lit.

7.2.4 Alarm Horn

There is an alarm horn present at this station; currently, the PAC program does not contain any logic to trigger it.

7.3 ENVIRONMENTAL COMPLIANCE APPROVAL OR OTHER REGULATORY REQUIREMENTS

Refer to Certificate of Approval No. 3-1455-94-956 issued January 6, 1995.

7.4 TRENDING OF INPUTS

The SCADA HMI trend screen uses chart group files to populate the trending configurations for each station. The trends are grouped by station.

The following points are captured from the Historian and trended by the SCADA HMI.

Table 7-1: HCS04 Trending Points

| SCADA Tag | Description |
|----------------------------------|--|
| Analog Trending | |
| HCS04STN01FIT01CV_ | Station Discharge Flow Indication |
| HCS04STN01IV001ZI_ | Wetwell Inlet Gate Position Feedback |
| HCS04STN01IV002ZI_ | CSO Tank Inlet Gate Position Feedback |
| HCS04STN01LIT01CV_ | Overflow Weir Level Indication |
| HCS04STN01OV001ZI_ | CSO Tank Outlet Gate Position Feedback |
| HCS04STN01PIT01CV_ | City Water Pressure Indication |
| HCS04STN01TIT01CV_ | Building Temperature Indication |
| HCS04VCH01IV001ZI_ | Chamber No.1 Gate Position Feedback |
| HCS04VCH01LIT01CV_ | Chamber No. 1 Level Indication |
| HCS04VCH04IV001ZI_ | Chamber No.4 Gate Position Feedback |
| HCS04VCH04LIT01CV_ | Chamber No. 4 Level Indication |
| HCS04VCH05IV001ZI_ | Chamber No.5 Gate Position Feedback |
| HCS04WWL01LIT01CV_ | Wetwell Level Indication |
| HCS04WWT01FIT01CV_ | Main Flushing Water Line Flow Indication |
| HCS04WWT01LIT01CV_ | CSO Tank Cell No. 1 Level Indication |
| HCS04WWT02LIT01CV_ | CSO Tank Cell No. 2 Level Indication |
| Digital Trending | |
| HCS04SLP0100000MN_ | Sewage Lift Pump No.1 Running Status |
| HCS04SLP0200000MN_ | Sewage Lift Pump No.2 Running Status |
| HCS04SLP0300000MN_ | Sewage Lift Pump No.3 Running Status |
| Calculated Value Trending | |
| HCS04SAM0100000BNC | Influent Sampler Bottle Count |
| HCS04SAM0100000HIS | Influent Sampler Pulses per Bottle |
| HCS04SAM0100000YX_ | Influent Event in Progress |
| HCS04SAM0200000BNC | Overflow Sampler Bottle Count |
| HCS04SAM0200000HIS | Overflow Sampler Pulses per Bottle |
| HCS04SAM0200000YX_ | Overflow Event in Progress |
| HCS04SLP0100000RT_ | Sewage Lift Pump No.1 Total Runtime |
| HCS04SLP0200000RT_ | Sewage Lift Pump No.2 Total Runtime |
| HCS04SLP0300000RT_ | Sewage Lift Pump No.3 Total Runtime |
| HCS04STN01FIT01TT_ | Station Discharge Flow Total Today |
| HCS04STN01FIT01TY_ | Station Discharge Flow Total Yesterday |

| SCADA Tag | Description |
|--|--|
| HCS04STN01FIT01MT_ | Station Discharge Flow Total This Month |
| HCS04STN01FIT01MY_ | Station Discharge Flow Total Last Month |
| HCS04STN01FIT02CV_ | Calculated Overflow Weir Flow Indication |
| HCS04STN01FIT02TT_ | Calculated Overflow Weir Flow Total Today |
| HCS04STN01FIT02TY_ | Calculated Overflow Weir Flow Total Yesterday |
| HCS04STN01FIT02MT_ | Calculated Overflow Weir Flow Total This Month |
| HCS04STN01FIT02MY_ | Calculated Overflow Weir Flow Total Last Month |
| HCS04STN01FIT03TT_ | Calculated Cells Inflow Total Today |
| HCS04STN01FIT03TY_ | Calculated Cells Inflow Total Yesterday |
| Communications Network I/O Trending | |
| N/A | |

7.5 REPORTING

The following points are captured from the Historian and are included in the station daily reports. A Sample Report can be found in Appendix D – Historian Report.

Table 7-2: HCS04 Reporting Variables List

| SCADA Tag | Parameter Description | Reporting Variables |
|--------------------|--------------------------------|---|
| Hourly | | |
| HCS04WWT01LIT01CV_ | CSO Tank Cell No.1 Level | <ul style="list-style-type: none"> Hourly Level (m) |
| HCS04WWT02LIT01CV_ | CSO Tank Cell No.2 Level | <ul style="list-style-type: none"> Hourly Level (m) |
| HCS04STN01LIT01CV_ | Overflow Weir Level | <ul style="list-style-type: none"> Hourly Level (m) |
| HCS04SLP0100000MN_ | Sewage Lift Pump No.1 | <ul style="list-style-type: none"> Hourly Runtime (min/hr) |
| HCS04SLP0200000MN_ | Sewage Lift Pump No.2 | <ul style="list-style-type: none"> Hourly Runtime (min/hr) |
| HCS04SLP0300000MN_ | Sewage Lift Pump No.3 | <ul style="list-style-type: none"> Hourly Runtime (min/hr) |
| HCS04STN01FIT01CV_ | Station Discharge Flow | <ul style="list-style-type: none"> Hourly Flow Rate (L/s) |
| HCS04STN01PIT01CV_ | City Water Pressure Indication | <ul style="list-style-type: none"> Hourly Pressure (kPa) |
| HCS04VCH01LIT01CV_ | Chamber No.1 Level Indication | <ul style="list-style-type: none"> Hourly Level (m) |
| HCS04VCH01IV001ZI_ | Chamber No. 1 Gate | <ul style="list-style-type: none"> Gate Position (%) |
| HCS04VCH04LIT01CV_ | Chamber No.4 Level Indication | <ul style="list-style-type: none"> Hourly Level (m) |

| SCADA Tag | Parameter Description | Reporting Variables |
|--------------------|-------------------------------|--|
| HCS04VCH04IV001ZI_ | Chamber No. 4 Gate | <ul style="list-style-type: none"> Gate Position (%) |
| HCS04VCH05IV001ZI_ | Chamber No. 5 Gate | <ul style="list-style-type: none"> Gate Position (%) |
| HCS04STN01IV001CV_ | Wetwell Inlet Gate | <ul style="list-style-type: none"> Gate Position (%) |
| HCS04STN01IV002CV_ | CSO Tank Inlet Gate | <ul style="list-style-type: none"> Gate Position (%) |
| HCS04STN01OV001CV_ | CSO Tank Outlet Gate | <ul style="list-style-type: none"> Gate Position (%) |
| HCS04WWL01LIT01CV_ | Wetwell Level | <ul style="list-style-type: none"> Hourly Level (m) |
| HCS04STN01FIT02CV_ | Calculated Overflow Weir Flow | <ul style="list-style-type: none"> Hourly Flow Rate (L/s) |
| Totals | | |
| HCS04SLP0100000RT_ | Sewage Lift Pump No.1 | <ul style="list-style-type: none"> Daily Runtime Total (hr) |
| HCS04SLP0200000RT_ | Sewage Lift Pump No.2 | <ul style="list-style-type: none"> Daily Runtime Total (hr) |
| HCS04SLP0300000RT_ | Sewage Lift Pump No.3 | <ul style="list-style-type: none"> Daily Runtime Total (hr) |
| HCS04STN01FIT01TY_ | Station Discharge Flow | <ul style="list-style-type: none"> Daily Flow Total (m³) |

7.6 LOCAL LOGGING

The following analog input point values are stored in an array on the PAC local RAM memory. Data is logged every minute. The data is stored for seven (7) days (10,080 records). Data is stored on a first in, first out basis; older data will be overwritten after seven (7) days.

Table 7-3: HCS04 Local Logging

| SCADA Tag | Description | Capture Frequency | Log Time |
|--------------------|--|-------------------|----------|
| HCS04STN01FIT01CV_ | Station Discharge Flow Indication | 1 minute | 7 days |
| HCS04STN01FIT02CV_ | Calculated Overflow Weir Flow | 1 minute | 7 days |
| HCS04STN01LIT01CV_ | Overflow Weir Level Indication | 1 minute | 7 days |
| HCS04STN01PIT01CV_ | City Water Pressure Indication | 1 minute | 7 days |
| HCS04STN01TIT01CV_ | Building Temperature Indication | 1 minute | 7 days |
| HCS04VCH01LIT01CV_ | Chamber No.1 Level Indication | 1 minute | 7 days |
| HCS04VCH04LIT01CV_ | Chamber No.4 Level Indication | 1 minute | 7 days |
| HCS04WWL01LIT01CV_ | Wetwell Level Indication | 1 minute | 7 days |
| HCS04WWT01FIT01CV_ | Main Flushing Water Line Flow Indication | 1 minute | 7 days |
| HCS04WWT01LIT01CV_ | CSO Tank Cell No.1 Level Indication | 1 minute | 7 days |

| SCADA Tag | Description | Capture Frequency | Log Time |
|--------------------|-------------------------------------|-------------------|----------|
| HCS04WWT02LIT01CV_ | CSO Tank Cell No.2 Level Indication | 1 minute | 7 days |

8 MISCELLANEOUS

8.1 ELECTRICAL EQUIPMENT AND STANDBY POWER

The incoming hydro service for this site is 600V, 3 phase, 4 wire.

An ATS is located at the station, as well as a connection for the portable generator. Once the generator is connected and running at speed, the ATS can be manually switched over to the emergency power position and power will return to the station. The City uses an ATS in manual mode at this station to protect the station equipment from the accidental connection of a generator of the wrong voltage, and to check phase rotation.

The portable generator that is used for this station is not large enough to run more than two (2) sewage lift pumps. When the PAC receives the ATS in Generator/Emergency Position status input, the PAC will automatically limit the number of pumps that can run.

Refer to “Table 8-2: HCS04 Generator Summary” for generator details.

The following major electrical equipment in the station is present and monitored by the SCADA system.

Table 8-1: HCS04 Electrical Equipment Summary

| SCADA Tag | Equipment Description |
|-----------------|---------------------------|
| HCS04CP001UPS01 | PAC Panel UPS |
| HCS04ATS0100000 | Automatic Transfer Switch |

The following table describes the generator:

Table 8-2: HCS04 Generator Summary

| Type | Rating | Fuel | | Approximate Run Time at Full Load with Full Fuel Tanks |
|--------------------|------------------|--------------|------------------|--|
| | | No. of Tanks | Total Volume (L) | |
| Portable Generator | 350kW, 600V, 3ph | 2 | 1970 | 16 hours |

8.2 HVAC

The following HVAC equipment is present at this station:

- There is a smoke detector (HCS04STN01SKD01) present inside the station that is connected to the SCADA system.
- There are two blower/heater units for heating the station, each with a built in thermostat. The blower/heaters are not monitored or controlled by the SCADA System.
- There is a SCADA monitored building exhaust fan at this station (HCS04STN01EXF01). The fan is controlled by a thermostat mounted on the wall near the fan. The fan is not controllable via the SCADA System.

- There are five (5) SCADA monitored and controlled supply fans at this station (HSC04SFN0100000, HSC04SFN0200000, HSC04SFN0300000, HSC04SFN0400000 and HSC04SFN0500000). These fans are controlled by the PAC to mitigate gas produced at the station.
 - HCS04SFN0100000 Gallery No.1 Supply Fan
 - HCS04SFN0200000 Gallery No.2 Supply Fan
 - HCS04SFN0300000 Gallery No.3 Supply Fan
 - HCS04SFN0400000 Pump/Gate Gallery No.4 Supply Fan
 - HCS04SFN0500000 Pump/Well Chamber Supply Fan
 - HCS04SFN0600000 Pump Well Chamber Supply Fan

8.3 HAZARDOUS GASES

A combustible gas detector is installed in the station Wetwell. The gas monitor monitors combustible gas and sends an analog gas concentration signal in ppm to the PAC. A high combustible gas level will also cause the gas monitor to send a digital High Combustible Gas concentration alarm to the PAC.

8.4 STATION FLOOD

A station flood float is installed at this station. In the event of a station flood, the alarm will be displayed on the SCADA HMI.

8.5 STATION SECURITY

There is a station security system that consists of door contacts (HCS04STN01ESW01) to monitor all doors, and a key-operated security switch (HCS04STN01HSW01) to enable and disable the security system. When a door is opened, an intrusion alarm will be displayed on the SCADA HMI. The person entering must use their key to disarm the security system by turning the security key switch to DISARM. A notification that a station door has opened will always be displayed on the SCADA HMI regardless of whether the security system is armed or disarmed.

To rearm the security system when leaving the station, the key switch should be turned to 'ARM' immediately before leaving the station. There will be a 45 second delay before the security system is re-armed to allow for safe exit of the station without tripping the intrusion alarm. Once the security system has been armed, the station has been exited, and all doors are closed and locked, the Process Supervisor is to be called to confirm that they can see the security system armed, the doors closed, and that the intrusion alarm has not been activated.

8.6 PRECIPITATION (RAINFALL) MONITORING

There is no precipitation monitoring at this site.

8.7 STATION LIGHTING

Lighting systems are installed in the West, East, and South galleries and in the West and South sections of the Tank. Emergency lights are powered by an AC emergency inverter system that is available for a prolonged power outage. The contactors for normal and emergency lights are as follows:

- HCS04STN01LHT01 Area C1 Gallery Lights West
- HCS04STN01LHT02 Area C2 Gallery Lights East
- HCS04STN01LHT03 Area C3 Gallery Lights South
- HCS04STN01LHT04 Area C4 Tank Flood Lights West

- HCS04STN01LHT05 Area C5 Tank Flood Lights South
- HCS04STN01LHT06 Area C6 Tank Flood Lights South
- HCS04STN01LHT07 Area C7 Emergency Lights

Controls for lighting areas C1 to C6 are operated through the HMI and interlocked when the station security keyswitch is armed. Emergency lights C7 are interlocked with the area lights when they are in “Auto.”

APPENDIX A – SCADA I/O LISTING BY DEVICE

I/O List

The following table details the I/O at this station arranged by major device type.

HCS04 I/O list by Device

| Type | SCADA Tag | Description |
|------|---------------------|---|
| DI | HCS04ATS010000XA_ | ATS General Alarm (Future) |
| DI | HCS04ATS010000YN_ | ATS in Remote (Future) |
| DI | HCS04ATS01JJSW01YX_ | ATS in Normal/Hydro Power Position |
| DI | HCS04ATS01JJSW02YX_ | ATS in Emergency/Generator Power Position |
| DI | HCS04ATS01LNE01YX_ | ATS Normal/Hydro Power Available |
| DI | HCS04ATS01LNE02YX_ | ATS Emergency/Generator Power Available |
| DI | HCS04CP001DCP01XA_ | PAC Panel DC Power Supply Fault |
| DO | HCS04CP001HRN01MH_ | Station Alarm Horn (Future) |
| DI | HCS04CP001JJSW01JA_ | PAC Panel Power Fail Alarm |
| DI | HCS04CP001UPS01MN_ | PAC Panel UPS Online |
| DI | HCS04CP001UPS01XA_ | PAC Panel UPS Fault/Low Battery |
| DO | HCS04GDS000000MH_ | Combustible Gas Alarm Beacon (Future) |
| DI | HCS04GEN010000MN_ | Generator Running (Future) |
| DI | HCS04GEN010000XA_ | Generator General Alarm (Future) |
| DI | HCS04GEN010000YN_ | Generator in Remote (Future) |
| DI | HCS04GEN01HSW01HAS | Generator E-Stop Activated (Future) |
| DI | HCS04NAC01NAS01XA_ | WAN Panel Ethernet Switch Minor Fault |
| DI | HCS04NAC01NAS01XA2 | WAN Panel Ethernet Switch Major Fault |
| DO | HCS04PAC010000XA_ | SCADA Alarm Pilot Light |
| DO | HCS04PAC010000YX_ | System OK Pilot Light |
| DI | HCS04SAM000000RES | Influent/Overflow Sampler Program Reset |
| DI | HCS04SAM010000BN_ | Influent Sampler Bottle Number |
| DO | HCS04SAM010000MH_ | Influent Sampler Take Sample Command |
| DI | HCS04SAM010000ST_ | Influent Sampler Sample Mark |
| DO | HCS04SAM01VLV01CE_ | Influent Backwash Close Command (Future) |
| DO | HCS04SAM01VLV01OP_ | Influent Backwash Open Command |
| DI | HCS04SAM01VLV01WA_ | Influent Backwash Valve Overtorque Alarm (Future) |
| DI | HCS04SAM01VLV01XA_ | Influent Backwash Valve General Fault (Future) |
| DI | HCS04SAM01VLV01YN_ | Influent Backwash Valve in Remote |
| DI | HCS04SAM01VLV01ZH_ | Influent Backwash Valve Opened Status |
| DI | HCS04SAM01VLV01ZL_ | Influent Backwash Valve Closed Status (Future) |
| DI | HCS04SAM020000BN_ | Effluent Sampler Bottle Number |
| DO | HCS04SAM020000MH_ | Effluent Sampler Take Sample |
| DI | HCS04SAM020000ST_ | Effluent Sampler Sample Mark |
| DO | HCS04SAP010000MB_ | Sample Pump No.1 Stop Command |
| DO | HCS04SAP010000MH_ | Sample Pump No.1 Start Command |
| DI | HCS04SAP010000MN_ | Sample Pump No.1 Running |
| DI | HCS04SAP010000XA_ | Sample Pump No.1 General Fault |
| DI | HCS04SAP010000YN_ | Sample Pump No.1 In Remote |

| | | |
|----|--------------------|---|
| DO | HCS04SAP020000MB_ | Sample Pump No.2 Stop Command |
| DO | HCS04SAP020000MH_ | Sample Pump No.2 Start Command |
| DI | HCS04SAP020000MN_ | Sample Pump No.2 Running |
| DI | HCS04SAP020000XA_ | Sample Pump No.2 General Fault |
| DI | HCS04SAP020000YN_ | Sample Pump No.2 In Remote |
| DO | HCS04SFN010000MB_ | Gallery No.1 Supply Fan Stop Command |
| DO | HCS04SFN010000MH_ | Gallery No.1 Supply Fan Start Command |
| DI | HCS04SFN010000MN_ | Gallery No.1 Supply Fan Running Status |
| DI | HCS04SFN010000XA_ | Gallery No.1 Supply Fan General Fault |
| DI | HCS04SFN010000YN_ | Gallery No.1 Supply Fan In Remote |
| DO | HCS04SFN020000MB_ | Gallery No.2 Supply Fan Stop Command |
| DO | HCS04SFN020000MH_ | Gallery No.2 Supply Fan Start Command |
| DI | HCS04SFN020000MN_ | Gallery No.2 Supply Fan Running Status |
| DI | HCS04SFN020000XA_ | Gallery No.2 Supply Fan General Fault |
| DI | HCS04SFN020000YN_ | Gallery No.2 Supply Fan In Remote |
| DO | HCS04SFN030000MB_ | Gallery No.3 Supply Fan Stop Command |
| DO | HCS04SFN030000MH_ | Gallery No.3 Supply Fan Start Command |
| DI | HCS04SFN030000MN_ | Gallery No.3 Supply Fan Running Status |
| DI | HCS04SFN030000XA_ | Gallery No.3 Supply Fan General Fault |
| DI | HCS04SFN030000YN_ | Gallery No.3 Supply Fan In Remote |
| DO | HCS04SFN040000MB_ | Pump/Gate Gallery Supply Fan Stop Command |
| DO | HCS04SFN040000MH | Pump/Gate Gallery Supply Fan Start Fast Command |
| DO | HCS04SFN040000MHL | Pump/Gate Gallery Supply Fan Start Slow Command |
| DI | HCS04SFN040000MNH | Pump/Gate Gallery Supply Fan Running Fast |
| DI | HCS04SFN040000MNL | Pump/Gate Gallery Supply Fan Running Slow |
| DI | HCS04SFN040000XA_ | Pump/Gate Gallery Supply Fan General Fault |
| DI | HCS04SFN040000YN_ | Pump/Gate Gallery Supply Fan In Remote |
| DO | HCS04SFN050000MB_ | Pump/Well Chamber Supply Fan Stop Command |
| DO | HCS04SFN050000MH_ | Pump/Well Chamber Supply Fan Start Command |
| DI | HCS04SFN050000MN_ | Pump/Well Chamber Supply Fan Running Status |
| DI | HCS04SFN050000XA_ | Pump/Well Chamber Supply Fan General Fault |
| DI | HCS04SFN050000YN_ | Pump/Well Chamber Supply Fan In Remote |
| DO | HCS04SLP010000MB_ | Sewage Lift Pump No.1 Stop Command |
| DO | HCS04SLP010000MH_ | Sewage Lift Pump No.1 Start Command |
| DI | HCS04SLP010000MN_ | Sewage Lift Pump No.1 Running |
| DI | HCS04SLP010000XA_ | Sewage Lift Pump No.1 General Fault |
| DI | HCS04SLP010000XLT | Sewage Lift Pump No.1 Temp/Leak Fault (Future) |
| DI | HCS04SLP010000YN_ | Sewage Lift Pump No.1 In Remote |
| DI | HCS04SLP01VFD01XA_ | Sewage Lift Pump No.1 VFD Fault (RTC Future) |
| DO | HCS04SLP020000MB_ | Sewage Lift Pump No.2 Stop Command |
| DO | HCS04SLP020000MH_ | Sewage Lift Pump No.2 Start Command |
| DI | HCS04SLP020000MN_ | Sewage Lift Pump No.2 Running |
| DI | HCS04SLP020000XA_ | Sewage Lift Pump No.2 General Fault |
| DI | HCS04SLP020000XLT | Sewage Lift Pump No.2 Temp/Leak Fault (Future) |

| | | |
|----|--------------------|--|
| DI | HCS04SLP020000YX_ | Sewage Lift Pump No.2 In Remote |
| DI | HCS04SLP02VFD01XA_ | Sewage Lift Pump No.2 VFD Fault (RTC Future) |
| DO | HCS04SLP030000MB_ | Sewage Lift Pump No.3 Stop Command |
| DO | HCS04SLP030000MH_ | Sewage Lift Pump No.3 Start Command |
| DI | HCS04SLP030000MN_ | Sewage Lift Pump No.3 Running |
| DI | HCS04SLP030000XA_ | Sewage Lift Pump No.3 General Fault |
| DI | HCS04SLP030000XLT | Sewage Lift Pump No.3 Temp/Leak Fault (Future) |
| DI | HCS04SLP030000YX_ | Sewage Lift Pump No.3 In Remote |
| DI | HCS04STN01ESW01ZSH | Door Contact |
| DI | HCS04STN01ESW02ZSH | Wetwell Hatch Contact (Future) |
| AI | HCS04STN01FIT01FI_ | Station Flow Indication |
| DI | HCS04STN01FIT01XA_ | Station Flow Transmitter General Fault (Future) |
| DI | HCS04STN01HSW01YX_ | Station Security Key Switch Status |
| DO | HCS04STN01IV001CE_ | Pump Station Inlet Gate Analog Override Close Command (Future) |
| DO | HCS04STN01IV001OP_ | Pump Station Inlet Gate Analog Override Open Command (Future) |
| DI | HCS04STN01IV001WA_ | Pump Station Inlet Gate Overtorque Alarm (Future) |
| DI | HCS04STN01IV001XA_ | Pump Station Inlet Gate General Fault (Future) |
| DI | HCS04STN01IV001YN_ | Pump Station Inlet Gate In Remote |
| AO | HCS04STN01IV001ZC_ | Pump Station Inlet Gate Position Setpoint |
| DI | HCS04STN01IV001ZH_ | Pump Station Inlet Gate Opened Status (Future) |
| AI | HCS04STN01IV001ZI_ | Pump Station Inlet Gate Position Indication |
| DI | HCS04STN01IV001ZL_ | Pump Station Inlet Gate Closed Status (Future) |
| DO | HCS04STN01IV002CE_ | Cells Inlet Gate Analog Override Close Command (Future) |
| DO | HCS04STN01IV002OP_ | Cells Inlet Gate Analog Override Open Command (Future) |
| DI | HCS04STN01IV002WA_ | Cells Inlet Gate Overtorque Alarm (Future) |
| DI | HCS04STN01IV002XA_ | Cells Inlet Gate General Fault (Future) |
| DI | HCS04STN01IV002YN_ | Cells Inlet Gate In Remote |
| AO | HCS04STN01IV002ZC_ | Cells Inlet Gate Position Setpoint |
| DI | HCS04STN01IV002ZH_ | Cells Inlet Gate Opened Status (Future) |
| AI | HCS04STN01IV002ZI_ | Cells Inlet Gate Position Indication |
| DI | HCS04STN01IV002ZL_ | Cells Inlet Gate Closed Status (Future) |
| DI | HCS04STN01JSW01JA_ | 600 VAC Power Supply Failed Alarm |
| DO | HCS04STN01LHT01LOK | Area Lighting Contactors C1 - C6 Master Interlock |
| DO | HCS04STN01LHT01MH_ | Area C1 Gallery Lights West On Command |
| DI | HCS04STN01LHT01MN_ | Area C1 Gallery Lights West On Status |
| DI | HCS04STN01LHT01YN_ | Area C1 Gallery Lights West In Remote (Future) |
| DO | HCS04STN01LHT02LOK | Area Lighting Contactor C7 Master Interlock |
| DO | HCS04STN01LHT02MH_ | Area C2 Gallery Lights East On Command |
| DI | HCS04STN01LHT02MN_ | Area C2 Gallery Lights East On Status |
| DI | HCS04STN01LHT02YN_ | Area C2 Gallery Lights East In Remote (Future) |
| DO | HCS04STN01LHT03MH_ | Area C3 Gallery Lights South On Command |
| DI | HCS04STN01LHT03MN_ | Area C3 Gallery Lights South On Status |
| DI | HCS04STN01LHT03YN_ | Area C3 Gallery Lights South In Remote (Future) |
| DO | HCS04STN01LHT04MH_ | Area C4 Tank Flood Lights West On Command |

| | | |
|----|--------------------|--|
| DI | HCS04STN01LHT04MN_ | Area C4 Tank Flood Lights West On Status |
| DI | HCS04STN01LHT04YN_ | Area C4 Tank Flood Lights West In Remote (Future) |
| DO | HCS04STN01LHT05MH_ | Area C5 Tank Flood Lights South On Command |
| DI | HCS04STN01LHT05MN_ | Area C5 Tank Flood Lights South On Status |
| DI | HCS04STN01LHT05YN_ | Area C5 Tank Flood Lights South In Remote (Future) |
| DO | HCS04STN01LHT06MH_ | Area C6 Tank Flood Lights South On Command |
| DI | HCS04STN01LHT06MN_ | Area C6 Tank Flood Lights South On Status |
| DI | HCS04STN01LHT06YN_ | Area C6 Tank Flood Lights South In Remote (Future) |
| DO | HCS04STN01LHT07MH_ | Area C7 Emergency Lights On Command |
| DI | HCS04STN01LHT07MN_ | Area C7 Emergency Lights On Status |
| DI | HCS04STN01LHT07YN_ | Area C7 Emergency Lights In Remote (Future) |
| AI | HCS04STN01LIT01LI_ | Overflow Weir Level Indication |
| DI | HCS04STN01LIT01XA_ | Overflow Weir Level Transmitter General Fault |
| DI | HCS04STN01LSH01LHH | Station Flood Alarm |
| DO | HCS04STN010V001CE_ | Cells Outlet Gate Analog Override Close Command (Future) |
| DO | HCS04STN010V0010P_ | Cells Outlet Gate Analog Override Open Command (Future) |
| DI | HCS04STN010V001WA_ | Cells Outlet Gate Overtorque Alarm (Future) |
| DI | HCS04STN010V001XA_ | Cells Outlet Gate General Fault (Future) |
| DI | HCS04STN010V001YN_ | Cells Outlet Gate In Remote |
| AO | HCS04STN010V001ZC_ | Cells Outlet Gate Position Setpoint |
| DI | HCS04STN010V001ZH_ | Cells Outlet Gate Opened Status (Future) |
| AI | HCS04STN010V001ZI_ | Cells Outlet Gate Position Indication |
| DI | HCS04STN010V001ZL_ | Cells Outlet Gate Closed Status (Future) |
| AI | HCS04STN01PIT01PI_ | City Water Pressure Indication |
| DI | HCS04STN01SKD01XA_ | Building Smoke/Fire Alarm |
| AI | HCS04STN01TIT01TI_ | Building Temperature Indication |
| DO | HCS04VCH01IV001CE_ | Chamber No.1 Gate Analog Override Close Command (Future) |
| DO | HCS04VCH01IV0010P_ | Chamber No.1 Gate Analog Override Open Command (Future) |
| DI | HCS04VCH01IV001WA_ | Chamber No.1 Gate Overtorque Alarm (Future) |
| DI | HCS04VCH01IV001XA_ | Chamber No.1 Gate General Fault (Future) |
| DI | HCS04VCH01IV001YN_ | Chamber No.1 Gate In Remote |
| AO | HCS04VCH01IV001ZC_ | Chamber No.1 Gate Position Setpoint |
| DI | HCS04VCH01IV001ZH_ | Chamber No.1 Gate Opened Status (Future) |
| AI | HCS04VCH01IV001ZI_ | Chamber No.1 Gate Position Indication |
| DI | HCS04VCH01IV001ZL_ | Chamber No.1 Gate Closed Status (Future) |
| AI | HCS04VCH01LIT01LI_ | Chamber No.1 Level Indication |
| DI | HCS04VCH01LIT01XA_ | Chamber No.1 Level Transmitter General Fault (Future) |
| DO | HCS04VCH04IV001CE_ | Chamber No.4 Gate Analog Override Close Command (Future) |
| DO | HCS04VCH04IV0010P_ | Chamber No.4 Gate Analog Override Open Command (Future) |
| DI | HCS04VCH04IV001WA_ | Chamber No.4 Gate Overtorque Alarm (Future) |
| DI | HCS04VCH04IV001XA_ | Chamber No.4 Gate General Fault (Future) |
| DI | HCS04VCH04IV001YN_ | Chamber No.4 Gate In Remote |
| AO | HCS04VCH04IV001ZC_ | Chamber No.4 Gate Position Setpoint |
| DI | HCS04VCH04IV001ZH_ | Chamber No.4 Gate Opened Status (Future) |

| | | |
|----|--------------------|--|
| AI | HCS04VCH04IV001ZI_ | Chamber No.4 Gate Position Indication |
| DI | HCS04VCH04IV001ZL_ | Chamber No.4 Gate Closed Status (Future) |
| AI | HCS04VCH04LIT01LI_ | Chamber No.4 Level Indication |
| DI | HCS04VCH04LIT01XA_ | Chamber No.4 Level Transmitter General Fault (Future) |
| DO | HCS04VCH05IV001CE_ | Chamber No.5 Gate Analog Override Close Command (Future) |
| DO | HCS04VCH05IV001OP_ | Chamber No.5 Gate Analog Override Open Command (Future) |
| DI | HCS04VCH05IV001WA_ | Chamber No.5 Gate Overtorque Alarm (Future) |
| DI | HCS04VCH05IV001XA_ | Chamber No.5 Gate General Fault (Future) |
| DI | HCS04VCH05IV001YN_ | Chamber No.5 Gate In Remote |
| AO | HCS04VCH05IV001ZC_ | Chamber No.5 Gate Position Setpoint |
| DI | HCS04VCH05IV001ZH_ | Chamber No.5 Gate Opened Status (Future) |
| AI | HCS04VCH05IV001ZI_ | Chamber No.5 Gate Position Indication |
| DI | HCS04VCH05IV001ZL_ | Chamber No.5 Gate Closed Status (Future) |
| AI | HCS04WWL01LIT01LI_ | Wetwell Level Indication |
| DI | HCS04WWL01LIT01XA_ | Wetwell Level Transmitter General Fault |
| AI | HCS04WWT01FIT01FI_ | Main Flushing Water Line Flow Indication |
| DI | HCS04WWT01FIT01XA_ | Main Flushing Water Line Flow Transmitter General Fault |
| AI | HCS04WWT01LIT01LI_ | Cell No.1 Level Indication |
| DI | HCS04WWT01LIT01XA_ | Cell No.1 Level Transmitter General Fault (Future) |
| DO | HCS04WWT01SOL01MH_ | Cell No.1 Flush Valve No.1 Open Command |
| DO | HCS04WWT01SOL02MH_ | Cell No.1 Flush Valve No.2 Open Command |
| DO | HCS04WWT01SOL03MH_ | Cell No.1 Flush Valve No.3 Open Command |
| DO | HCS04WWT01SOL04MH_ | Cell No.1 Flush Valve No.4 Open Command |
| DO | HCS04WWT01SOL05MH_ | Cell No.1 Flush Valve No.5 Open Command |
| DO | HCS04WWT01VLV01CE_ | Main Flushing Water Line Shutoff Valve Close Command |
| DO | HCS04WWT01VLV01OP_ | Main Flushing Water Line Shutoff Valve Open Command |
| DI | HCS04WWT01VLV01WA_ | Main Flushing Water Line Shutoff Valve Overtorque Alarm |
| DI | HCS04WWT01VLV01XA_ | Main Flushing Water Line Shutoff Valve General Fault |
| DI | HCS04WWT01VLV01YN_ | Main Flushing Water Line Shutoff Valve In Remote |
| DI | HCS04WWT01VLV01ZH_ | Main Flushing Water Line Shutoff Valve Opened Status |
| DI | HCS04WWT01VLV01ZL_ | Main Flushing Water Line Shutoff Valve Closed Status |
| AI | HCS04WWT02LIT01LI_ | Cell No.2 Level Indication |
| DI | HCS04WWT02LIT01XA_ | Cell No.2 Level Transmitter General Fault (Future) |
| DO | HCS04WWT02SOL06MH_ | Cell No.2 Flush Valve No.6 Open Command |
| DO | HCS04WWT02SOL07MH_ | Cell No.2 Flush Valve No.7 Open Command |
| DO | HCS04WWT02SOL08MH_ | Cell No.2 Flush Valve No.8 Open Command |
| DO | HCS04WWT02SOL09MH_ | Cell No.2 Flush Valve No.9 Open Command |
| DO | HCS04WWT02SOL10MH_ | Cell No.2 Flush Valve No.10 Open Command |
| DO | HCS04WWT02SOL11MH_ | Cell No.2 Flush Valve No.11 Open Command |
| DO | HCS04WWT02SOL12MH_ | Cell No.2 Flush Valve No.12 Open Command |
| DO | HCS04WWT02SOL13MH_ | Cell No.2 Flush Valve No.13 Open Command |
| DO | HCS04WWT02SOL14MH_ | Cell No.2 Flush Valve No.14 Open Command |
| DO | HCS04WWT02SOL15MH_ | Cell No.2 Flush Valve No.15 Open Command |
| DO | HCS04WWT02SOL16MH_ | Cell No.2 Trough Flush Valve No.16 Open Command |

APPENDIX B – SCADA I/O LISTING BY CARD ASSIGNMENT

I/O List

The following table details the I/O at this station arranged by card layout.

HCS04 I/O list by Card

Platform: ControlLogix
Processor: 1756-L73
Power Supply: 1756-PA75 x 3

| Rack | Slot | Pts | Card Type | Card Model |
|------|------|---------------|----------------|------------|
| 0 | 0 | N/A | CPU | 1756-L63 |
| | 1 | N/A | ETHERNET CARD | 1756-ENBT |
| | 2 | N/A | ETHERNET CARD | 1756-ENBT |
| | 3 | N/A | ETHERNET CARD | 1756-ENBT |
| | 4 | N/A | SPARE | N/A |
| | 5 | 16 | DIGITAL OUTPUT | 1756-OW16I |
| | 6 | 16 | DIGITAL OUTPUT | 1756-OW16I |
| | 7 | 16 | DIGITAL OUTPUT | 1756-OW16I |
| | 8 | 16 | DIGITAL OUTPUT | 1756-OW16I |
| | 9 | 16 | DIGITAL OUTPUT | 1756-OW16I |
| | 10 | 16 | DIGITAL OUTPUT | 1756-OW16I |
| | 11 | N/A | SPARE | N/A |
| | 12 | N/A | SPARE | N/A |
| | 13 | 6 | ANALOG OUTPUT | 1756-OF6CI |
| | 14 | 6 | ANALOG OUTPUT | 1756-OF6CI |
| | 15 | N/A | SPARE | N/A |
| 16 | N/A | SPARE | N/A | |
| 1 | 0 | N/A | ETHERNET CARD | 1756-ENBT |
| | 1 | N/A | SPARE | N/A |
| | 2 | 16 | DIGITAL INPUT | 1756-IV16 |
| | 3 | 16 | DIGITAL INPUT | 1756-IV16 |
| | 4 | 16 | DIGITAL INPUT | 1756-IV16 |
| | 5 | 16 | DIGITAL INPUT | 1756-IV16 |
| | 6 | 16 | DIGITAL INPUT | 1756-IV16 |
| | 7 | 16 | DIGITAL INPUT | 1756-IV16 |
| | 8 | 16 | DIGITAL INPUT | 1756-IV16 |
| | 9 | 16 | DIGITAL INPUT | 1756-IV16 |
| | 10 | 16 | DIGITAL INPUT | 1756-IV16 |
| | 11 | 16 | DIGITAL INPUT | 1756-IV16 |
| | 12 | 16 | DIGITAL INPUT | 1756-IV16 |
| | 13 | 16 | DIGITAL INPUT | 1756-IV16 |
| 14 | 16 | DIGITAL INPUT | 1756-IV16 | |

| | | | | |
|---|----|-----|---------------|-----------|
| | 15 | 16 | DIGITAL INPUT | 1756-IV16 |
| | 16 | 16 | DIGITAL INPUT | 1756-IV16 |
| 2 | 0 | N/A | ETHERNET CARD | 1756-ENBT |
| | 1 | N/A | SPARE | N/A |
| | 2 | 16 | DIGITAL INPUT | 1756-IV16 |
| | 3 | 16 | DIGITAL INPUT | 1756-IV16 |
| | 4 | 16 | DIGITAL INPUT | 1756-IV16 |
| | 5 | N/A | SPARE | N/A |
| | 6 | N/A | SPARE | N/A |
| | 7 | N/A | SPARE | N/A |
| | 8 | 6 | ANALOG INPUT | 1756-IF6I |
| | 9 | 6 | ANALOG INPUT | 1756-IF6I |
| | 10 | 6 | ANALOG INPUT | 1756-IF6I |
| | 11 | 6 | ANALOG INPUT | 1756-IF6I |
| | 12 | 6 | ANALOG INPUT | 1756-IF6I |
| | 13 | 6 | ANALOG INPUT | 1756-IF6I |
| | 14 | 6 | ANALOG INPUT | 1756-IF6I |
| | 15 | 6 | ANALOG INPUT | 1756-IF6I |
| | 16 | N/A | SPARE | N/A |

| Rack | Slot | Pt | SCADA Tag | Description |
|------|------|----|--------------------|--|
| 0 | 0 | | | Processor |
| 0 | 1 | | | Ethernet Card |
| 0 | 2 | | | Ethernet Card |
| 0 | 3 | | | Ethernet Card |
| 0 | 4 | | | Spare |
| 0 | 5 | 0 | HCS04STN01IV0010P_ | Pump Station Inlet Gate Analog Override Open Command (Future) |
| DO | 1 | | HCS04STN01IV001CE_ | Pump Station Inlet Gate Analog Override Close Command (Future) |
| | 2 | | HCS04VCH01IV0010P_ | Chamber No.1 Gate Analog Override Open Command (Future) |
| | 3 | | HCS04VCH01IV001CE_ | Chamber No.1 Gate Analog Override Close Command (Future) |
| | 4 | | HCS04SLP0100000MH_ | Sewage Lift Pump No.1 Start Command |
| | 5 | | HCS04SLP0100000MB_ | Sewage Lift Pump No.1 Stop Command |
| | 6 | | HCS04SAM0100000MH_ | Influent Sampler Take Sample Command |
| | 7 | | HCS04SAM01VLV01CE_ | Influent Backwash Close Command (Future) |
| | 8 | | HCS04SAM01VLV010P_ | Influent Backwash Open Command |
| | 9 | | | |
| | 10 | | | |
| | 11 | | | |
| | 12 | | HCS04STN01LHT01LOK | Area Lighting Contactors C1 - C6 Master Interlock |
| | 13 | | HCS04STN01LHT01MH_ | Area C1 Gallery Lights West On Command |
| | 14 | | HCS04SFN0100000MH_ | Gallery No.1 Supply Fan Start Command |
| | 15 | | HCS04SFN0100000MB_ | Gallery No.1 Supply Fan Stop Command |

| | | | | |
|---|----|--------------------|---|--|
| 0 | 6 | 0 | HCS04STN010V0010P_ | Cells Outlet Gate Analog Override Open Command (Future) |
| | DO | 1 | HCS04STN010V001CE_ | Cells Outlet Gate Analog Override Close Command (Future) |
| | | 2 | HCS04SAP010000MH_ | Sample Pump No.1 Start Command |
| | | 3 | HCS04SAP010000MB_ | Sample Pump No.1 Stop Command |
| | | 4 | HCS04SLP020000MH_ | Sewage Lift Pump No.2 Start Command |
| | | 5 | HCS04SLP020000MB_ | Sewage Lift Pump No.2 Stop Command |
| | | 6 | HCS04WWT01SOL01MH_ | Cell No.1 Flush Valve No.1 Open Command |
| | | 7 | HCS04WWT01SOL02MH_ | Cell No.1 Flush Valve No.2 Open Command |
| | | 8 | HCS04WWT01SOL03MH_ | Cell No.1 Flush Valve No.3 Open Command |
| | | 9 | HCS04WWT02SOL06MH_ | Cell No.2 Flush Valve No.6 Open Command |
| | | 10 | HCS04WWT02SOL07MH_ | Cell No.2 Flush Valve No.7 Open Command |
| | | 11 | HCS04WWT02SOL08MH_ | Cell No.2 Flush Valve No.8 Open Command |
| | | 12 | HCS04STN01LHT02L0K | Area Lighting Contactor C7 Master Interlock |
| | | 13 | HCS04STN01LHT02MH_ | Area C2 Gallery Lights East On Command |
| | | 14 | HCS04SFN020000MH_ | Gallery No.2 Supply Fan Start Command |
| | 15 | HCS04SFN020000MB_ | Gallery No.2 Supply Fan Stop Command | |
| 0 | 7 | 0 | HCS04STN01IV0020P_ | Cells Inlet Gate Analog Override Open Command (Future) |
| | DO | 1 | HCS04STN01IV002CE_ | Cells Inlet Gate Analog Override Close Command (Future) |
| | | 2 | HCS04SAP020000MH_ | Sample Pump No.2 Start Command |
| | | 3 | HCS04SAP020000MB_ | Sample Pump No.2 Stop Command |
| | | 4 | HCS04SLP030000MH_ | Sewage Lift Pump No.3 Start Command |
| | | 5 | HCS04SLP030000MB_ | Sewage Lift Pump No.3 Stop Command |
| | | 6 | HCS04SAM020000MH_ | Effluent Sampler Take Sample |
| | | 7 | HCS04WWT01SOL04MH_ | Cell No.1 Flush Valve No.4 Open Command |
| | | 8 | HCS04WWT01SOL05MH_ | Cell No.1 Flush Valve No.5 Open Command |
| | | 9 | HCS04WWT02SOL09MH_ | Cell No.2 Flush Valve No.9 Open Command |
| | | 10 | HCS04WWT02SOL10MH_ | Cell No.2 Flush Valve No.10 Open Command |
| | | 11 | HCS04WWT02SOL11MH_ | Cell No.2 Flush Valve No.11 Open Command |
| | | 12 | HCS04WWT02SOL12MH_ | Cell No.2 Flush Valve No.12 Open Command |
| | | 13 | HCS04STN01LHT03MH_ | Area C3 Gallery Lights South On Command |
| | | 14 | HCS04SFN030000MH_ | Gallery No.3 Supply Fan Start Command |
| | 15 | HCS04SFN030000MB_ | Gallery No.3 Supply Fan Stop Command | |
| 0 | 8 | 0 | | |
| | DO | 1 | | |
| | | 2 | HCS04VCH04IV0010P_ | Chamber No.4 Gate Analog Override Open Command (Future) |
| | | 3 | HCS04VCH04IV001CE_ | Chamber No.4 Gate Analog Override Close Command (Future) |
| | | 4 | HCS04WWT01VLV01CE_ | Main Flushing Water Line Shutoff Valve Close Command |
| | | 5 | HCS04WWT01VLV010P_ | Main Flushing Water Line Shutoff Valve Open Command |
| | | 6 | | |
| | | 7 | HCS04WWT02SOL13MH_ | Cell No.2 Flush Valve No.13 Open Command |
| | | 8 | HCS04WWT02SOL14MH_ | Cell No.2 Flush Valve No.14 Open Command |
| | | 9 | HCS04WWT02SOL15MH_ | Cell No.2 Flush Valve No.15 Open Command |
| | 10 | HCS04WWT02SOL16MH_ | Cell No.2 Trough Flush Valve No.16 Open Command | |

| | | | | |
|---|----|----|--------------------|--|
| | | 11 | | |
| | | 12 | | |
| | | 13 | HCS04STN01LHT04MH_ | Area C4 Tank Flood Lights West On Command |
| | | 14 | HCS04SFN050000MH_ | Pump/Well Chamber Supply Fan Start Command |
| | | 15 | HCS04SFN050000MB_ | Pump/Well Chamber Supply Fan Stop Command |
| 0 | 9 | 0 | | |
| | DO | 1 | | |
| | | 2 | HCS04VCH05IV001OP_ | Chamber No.5 Gate Analog Override Open Command (Future) |
| | | 3 | HCS04VCH05IV001CE_ | Chamber No.5 Gate Analog Override Close Command (Future) |
| | | 4 | | |
| | | 5 | | |
| | | 6 | | |
| | | 7 | | |
| | | 8 | | |
| | | 9 | HCS04SFN040000MHH | Pump/Gate Gallery Supply Fan Start Fast Command |
| | | 10 | HCS04SFN040000MHL | Pump/Gate Gallery Supply Fan Start Slow Command |
| | | 11 | HCS04SFN040000MB_ | Pump/Gate Gallery Supply Fan Stop Command |
| | | 12 | | |
| | | 13 | HCS04STN01LHT05MH_ | Area C5 Tank Flood Lights South On Command |
| | | 14 | | |
| | | 15 | | |
| 0 | 10 | 0 | HCS04GDS000000MH_ | Combustible Gas Alarm Beacon (Future) |
| | DO | 1 | HCS04CP001HRN01MH_ | Station Alarm Horn (Future) |
| | | 2 | | |
| | | 3 | | |
| | | 4 | | |
| | | 5 | | |
| | | 6 | | |
| | | 7 | | |
| | | 8 | HCS04PAC010000YX_ | System OK Pilot Light |
| | | 9 | HCS04PAC010000XA_ | SCADA Alarm Pilot Light |
| | | 10 | | |
| | | 11 | | |
| | | 12 | | |
| | | 13 | HCS04STN01LHT06MH_ | Area C6 Tank Flood Lights South On Command |
| | | 14 | HCS04STN01LHT07MH_ | Area C7 Emergency Lights On Command |
| | | 15 | | |
| 0 | | 11 | | Spare |
| 0 | | 12 | | Spare |
| 0 | | 13 | 0 | HCS04VCH01IV001ZC_ Chamber No.1 Gate Position Setpoint |
| | AO | 1 | | |
| | | 2 | HCS04VCH05IV001ZC_ | Chamber No.5 Gate Position Setpoint |

| | | | | |
|---|----|----|--------------------|---|
| | | 3 | HCS04STN01IV001ZC_ | Pump Station Inlet Gate Position Setpoint |
| | | 4 | HCS04STN01IV002ZC_ | Cells Inlet Gate Position Setpoint |
| | | 5 | | |
| 0 | | 14 | 0 | |
| | AO | 1 | HCS04VCH04IV001ZC_ | Chamber No.4 Gate Position Setpoint |
| | | 2 | | |
| | | 3 | HCS04STN010V001ZC_ | Cells Outlet Gate Position Setpoint |
| | | 4 | | |
| | | 5 | | |
| 0 | | 15 | | Spare |
| 0 | | 16 | | Spare |
| 1 | | 0 | | Ethernet Card |
| | | 1 | | Spare |
| | | 2 | 0 | HCS04VCH01IV001YN_ Chamber No.1 Gate In Remote |
| | DI | 1 | HCS04VCH01IV001XA_ | Chamber No.1 Gate General Fault (Future) |
| | | 2 | HCS04VCH01IV001WA_ | Chamber No.1 Gate Overtorque Alarm (Future) |
| | | 3 | HCS04VCH01IV001ZH_ | Chamber No.1 Gate Opened Status (Future) |
| | | 4 | HCS04VCH01IV001ZL_ | Chamber No.1 Gate Closed Status (Future) |
| | | 5 | | |
| | | 6 | | |
| | | 7 | HCS04STN01FIT01XA_ | Station Flow Transmitter General Fault (Future) |
| | | 8 | HCS04SLP0100000YN_ | Sewage Lift Pump No.1 In Remote |
| | | 9 | HCS04SLP0100000XA_ | Sewage Lift Pump No.1 General Fault |
| | | 10 | HCS04SLP0100000MN_ | Sewage Lift Pump No.1 Running |
| | | 11 | HCS04SLP0100000XLT | Sewage Lift Pump No.1 Temp/Leak Fault (Future) |
| | | 12 | HCS04SLP01VFD01XA_ | Sewage Lift Pump No.1 VFD Fault (RTC Future) |
| | | 13 | | |
| | | 14 | HCS04VCH01LIT01XA_ | Chamber No.1 Level Transmitter General Fault (Future) |
| | | 15 | | |
| 1 | | 3 | 0 | HCS04VCH04IV001YN_ Chamber No.4 Gate In Remote |
| | DI | 1 | HCS04VCH04IV001XA_ | Chamber No.4 Gate General Fault (Future) |
| | | 2 | HCS04VCH04IV001WA_ | Chamber No.4 Gate Overtorque Alarm (Future) |
| | | 3 | HCS04VCH04IV001ZH_ | Chamber No.4 Gate Opened Status (Future) |
| | | 4 | HCS04VCH04IV001ZL_ | Chamber No.4 Gate Closed Status (Future) |
| | | 5 | | |
| | | 6 | | |
| | | 7 | | |
| | | 8 | HCS04SLP0200000YN_ | Sewage Lift Pump No.2 In Remote |
| | | 9 | HCS04SLP0200000XA_ | Sewage Lift Pump No.2 General Fault |
| | | 10 | HCS04SLP0200000MN_ | Sewage Lift Pump No.2 Running |
| | | 11 | HCS04SLP0200000XLT | Sewage Lift Pump No.2 Temp/Leak Fault (Future) |
| | | 12 | HCS04SLP02VFD01XA_ | Sewage Lift Pump No.2 VFD Fault (RTC Future) |

| | | | | |
|---|----|----|--------------------|--|
| | | 13 | HCS04VCH04LIT01XA_ | Chamber No.4 Level Transmitter General Fault (Future) |
| | | 14 | | |
| | | 15 | | |
| 1 | | 4 | 0 | HCS04VCH05IV001YN_ Chamber No.5 Gate In Remote |
| | DI | 1 | 1 | HCS04VCH05IV001XA_ Chamber No.5 Gate General Fault (Future) |
| | | 2 | 2 | HCS04VCH05IV001WA_ Chamber No.5 Gate Overtorque Alarm (Future) |
| | | 3 | 3 | HCS04VCH05IV001ZH_ Chamber No.5 Gate Opened Status (Future) |
| | | 4 | 4 | HCS04VCH05IV001ZL_ Chamber No.5 Gate Closed Status (Future) |
| | | 5 | | |
| | | 6 | | |
| | | 7 | | |
| | | 8 | 8 | HCS04SLP0300000YN_ Sewage Lift Pump No.3 In Remote |
| | | 9 | 9 | HCS04SLP0300000XA_ Sewage Lift Pump No.3 General Fault |
| | | 10 | 10 | HCS04SLP0300000MN_ Sewage Lift Pump No.3 Running |
| | | 11 | 11 | HCS04SLP0300000XLT Sewage Lift Pump No.3 Temp/Leak Fault (Future) |
| | | 12 | | |
| | | 13 | | |
| | | 14 | | |
| | | 15 | | |
| 1 | | 5 | 0 | HCS04STN01IV001YN_ Pump Station Inlet Gate In Remote |
| | DI | 1 | 1 | HCS04STN01IV001XA_ Pump Station Inlet Gate General Fault (Future) |
| | | 2 | 2 | HCS04STN01IV001WA_ Pump Station Inlet Gate Overtorque Alarm (Future) |
| | | 3 | 3 | HCS04STN01IV001ZH_ Pump Station Inlet Gate Opened Status (Future) |
| | | 4 | 4 | HCS04STN01IV001ZL_ Pump Station Inlet Gate Closed Status (Future) |
| | | 5 | 5 | HCS04SAP0100000YN_ Sample Pump No.1 In Remote |
| | | 6 | 6 | HCS04SAP0100000XA_ Sample Pump No.1 General Fault |
| | | 7 | 7 | HCS04SAP0100000MN_ Sample Pump No.1 Running |
| | | 8 | 8 | HCS04WWT01LIT01XA_ Cell No.1 Level Transmitter General Fault (Future) |
| | | 9 | | |
| | | 10 | 10 | HCS04WWT01VLV01WA_ Main Flushing Water Line Shutoff Valve Overtorque Alarm |
| | | 11 | 11 | HCS04WWT01VLV01XA_ Main Flushing Water Line Shutoff Valve General Fault |
| | | 12 | 12 | HCS04WWT01VLV01YN_ Main Flushing Water Line Shutoff Valve In Remote |
| | | 13 | 13 | HCS04WWT01VLV01ZH_ Main Flushing Water Line Shutoff Valve Opened Status |
| | | 14 | 14 | HCS04WWT01VLV01ZL_ Main Flushing Water Line Shutoff Valve Closed Status |
| | | 15 | 15 | HCS04WWT01FIT01XA_ Main Flushing Water Line Flow Transmitter General Fault |
| 1 | | 6 | 0 | HCS04STN01IV002YN_ Cells Inlet Gate In Remote |
| | DI | 1 | 1 | HCS04STN01IV002XA_ Cells Inlet Gate General Fault (Future) |
| | | 2 | 2 | HCS04STN01IV002WA_ Cells Inlet Gate Overtorque Alarm (Future) |
| | | 3 | 3 | HCS04STN01IV002ZH_ Cells Inlet Gate Opened Status (Future) |
| | | 4 | 4 | HCS04STN01IV002ZL_ Cells Inlet Gate Closed Status (Future) |
| | | 5 | 5 | HCS04SAP0200000YN_ Sample Pump No.2 In Remote |
| | | 6 | 6 | HCS04SAP0200000XA_ Sample Pump No.2 General Fault |
| | | 7 | 7 | HCS04SAP0200000MN_ Sample Pump No.2 Running |

| | | | | |
|---|----|----|--------------------|--|
| | | 8 | HCS04WWT02LIT01XA_ | Cell No.2 Level Transmitter General Fault (Future) |
| | | 9 | | |
| | | 10 | | |
| | | 11 | | |
| | | 12 | | |
| | | 13 | | |
| | | 14 | | |
| | | 15 | | |
| 1 | | 7 | 0 | HCS04STN010V001YN_ Cells Outlet Gate In Remote |
| | DI | 1 | | HCS04STN010V001XA_ Cells Outlet Gate General Fault (Future) |
| | | 2 | | HCS04STN010V001WA_ Cells Outlet Gate Overtorque Alarm (Future) |
| | | 3 | | HCS04STN010V001ZH_ Cells Outlet Gate Opened Status (Future) |
| | | 4 | | HCS04STN010V001ZL_ Cells Outlet Gate Closed Status (Future) |
| | | 5 | | |
| | | 6 | | |
| | | 7 | | |
| | | 8 | | |
| | | 9 | | |
| | | 10 | | |
| | | 11 | | |
| | | 12 | | |
| | | 13 | | |
| | | 14 | | |
| | | 15 | | |
| 1 | | 8 | 0 | |
| | DI | 1 | | |
| | | 2 | | |
| | | 3 | | |
| | | 4 | | |
| | | 5 | | |
| | | 6 | | |
| | | 7 | | |
| | | 8 | | |
| | | 9 | | |
| | | 10 | | |
| | | 11 | | |
| | | 12 | | |
| | | 13 | | |
| | | 14 | | |
| | | 15 | | |
| 1 | | 9 | 0 | - - |
| | DI | 1 | | - |
| | | 2 | | - |

| | | | | |
|---|----|----|---|---|
| | | 3 | | - |
| | | 4 | | - |
| | | 5 | | - |
| | | 6 | | - |
| | | 7 | | - |
| | | 8 | | - |
| | | 9 | | - |
| | | 10 | | - |
| | | 11 | | - |
| | | 12 | | - |
| | | 13 | | - |
| | | 14 | | - |
| | | 15 | | - |
| 1 | 10 | 0 | - | - |
| | DI | 1 | | - |
| | | 2 | | - |
| | | 3 | | - |
| | | 4 | | - |
| | | 5 | | - |
| | | 6 | | - |
| | | 7 | | - |
| | | 8 | | - |
| | | 9 | | - |
| | | 10 | | - |
| | | 11 | | - |
| | | 12 | | - |
| | | 13 | | - |
| | | 14 | | - |
| | | 15 | | - |
| 1 | 11 | 0 | - | - |
| | DI | 1 | | - |
| | | 2 | | - |
| | | 3 | | - |
| | | 4 | | - |
| | | 5 | | - |
| | | 6 | | - |
| | | 7 | | - |
| | | 8 | | - |
| | | 9 | | - |
| | | 10 | | - |
| | | 11 | | - |
| | | 12 | | - |
| | | 13 | | - |

| | | | | |
|---|----|----|--------------------|--|
| | | 14 | | - |
| | | 15 | - | - |
| 1 | 12 | 0 | HCS04SFN0100000YN_ | Gallery No.1 Supply Fan In Remote |
| | DI | 1 | HCS04SFN0100000XA_ | Gallery No.1 Supply Fan General Fault |
| | | 2 | HCS04SFN0100000MN_ | Gallery No.1 Supply Fan Running Status |
| | | 3 | HCS04STN01LHT01YN_ | Area C1 Gallery Lights West In Remote (Future) |
| | | 4 | HCS04STN01LHT01MN_ | Area C1 Gallery Lights West On Status |
| | | 5 | HCS04STN01LHT02YN_ | Area C2 Gallery Lights East In Remote (Future) |
| | | 6 | HCS04STN01LHT02MN_ | Area C2 Gallery Lights East On Status |
| | | 7 | | |
| | | 8 | HCS04STN01LIT01XA_ | Overflow Weir Level Transmitter General Fault |
| | | 9 | HCS04WWL01LIT01XA_ | Wetwell Level Transmitter General Fault |
| | | 10 | | |
| | | 11 | | |
| | | 12 | | |
| | | 13 | | |
| | | 14 | | |
| | | 15 | | |
| 1 | 13 | 0 | HCS04SFN0200000YN_ | Gallery No.2 Supply Fan In Remote |
| | DI | 1 | HCS04SFN0200000XA_ | Gallery No.2 Supply Fan General Fault |
| | | 2 | HCS04SFN0200000MN_ | Gallery No.2 Supply Fan Running Status |
| | | 3 | HCS04STN01LHT03YN_ | Area C3 Gallery Lights South In Remote (Future) |
| | | 4 | HCS04STN01LHT03MN_ | Area C3 Gallery Lights South On Status |
| | | 5 | HCS04STN01LHT04YN_ | Area C4 Tank Flood Lights West In Remote (Future) |
| | | 6 | HCS04STN01LHT04MN_ | Area C4 Tank Flood Lights West On Status |
| | | 7 | | |
| | | 8 | | |
| | | 9 | | |
| | | 10 | | |
| | | 11 | | |
| | | 12 | | |
| | | 13 | | |
| | | 14 | | |
| | | 15 | | |
| 1 | 14 | 0 | HCS04SFN0300000YN_ | Gallery No.3 Supply Fan In Remote |
| | DI | 1 | HCS04SFN0300000XA_ | Gallery No.3 Supply Fan General Fault |
| | | 2 | HCS04SFN0300000MN_ | Gallery No.3 Supply Fan Running Status |
| | | 3 | HCS04STN01LHT05YN_ | Area C5 Tank Flood Lights South In Remote (Future) |
| | | 4 | HCS04STN01LHT05MN_ | Area C5 Tank Flood Lights South On Status |
| | | 5 | HCS04STN01LHT06YN_ | Area C6 Tank Flood Lights South In Remote (Future) |
| | | 6 | HCS04STN01LHT06MN_ | Area C6 Tank Flood Lights South On Status |
| | | 7 | | |
| | | 8 | | |

| | | | | |
|---|----|----|--------------------|--|
| | | 9 | | |
| | | 10 | | |
| | | 11 | | |
| | | 12 | | |
| | | 13 | | |
| | | 14 | | |
| | | 15 | | |
| 1 | 15 | 0 | HCS04SFN0500000YN_ | Pump/Well Chamber Supply Fan In Remote |
| | DI | 1 | HCS04SFN0500000XA_ | Pump/Well Chamber Supply Fan General Fault |
| | | 2 | HCS04SFN0500000MN_ | Pump/Well Chamber Supply Fan Running Status |
| | | 3 | HCS04STN01LHT07YN_ | Area C7 Emergency Lights In Remote (Future) |
| | | 4 | HCS04STN01LHT07MN_ | Area C7 Emergency Lights On Status |
| | | 5 | HCS04STN01JSW01JA_ | 600 VAC Power Supply Failed Alarm |
| | | 6 | HCS04GDS01GIT01XA_ | Control Room Combustible Gas Monitor General Fault (Future) |
| | | 7 | HCS04GDS03GIT01XA_ | West Stairs Combustible Gas Monitor General Fault (Future) |
| | | 8 | HCS04GDS05GIT01XA_ | East Stairs Combustible Gas Monitor General Fault (Future) |
| | | 9 | HCS04GDS07GIT01XA_ | Pump Room Fumes Combustible Gas Monitor General Fault (Future) |
| | | 10 | HCS04GDS09GIT01XA_ | West Stairs Oxygen Monitor General Fault (Future) |
| | | 11 | | |
| | | 12 | | |
| | | 13 | | |
| | | 14 | | |
| | | 15 | | |
| 1 | 16 | 0 | | |
| | DI | 1 | | |
| | | 2 | | |
| | | 3 | | |
| | | 4 | | |
| | | 5 | | |
| | | 6 | | |
| | | 7 | | |
| | | 8 | HCS04GDS02GIT01XA_ | Pump Room Combustible Gas Monitor General Fault (Future) |
| | | 9 | HCS04GDS04GIT01XA_ | Access 1 Combustible Gas Monitor General Fault (Future) |
| | | 10 | HCS04GDS06GIT01XA_ | Access 3 Combustible Gas Monitor General Fault (Future) |
| | | 11 | HCS04GDS08GIT01XA_ | Control Room Oxygen Monitor General Fault (Future) |
| | | 12 | HCS04GDS10GIT01XA_ | East Stairs Oxygen Monitor General Fault (Future) |
| | | 13 | | |
| | | 14 | | |
| | | 15 | | |
| 2 | 0 | | | Ethernet Card |
| 2 | 1 | | | Spare |
| 2 | 2 | 0 | HCS04SFN0400000YN_ | Pump/Gate Gallery Supply Fan In Remote |

| | | | | | |
|---|----|----|--------------------|---|------------------------------------|
| | DI | 1 | HCS04SFN040000MNH | Pump/Gate Gallery Supply Fan Running Fast | |
| | | 2 | HCS04SFN040000MNL | Pump/Gate Gallery Supply Fan Running Slow | |
| | | 3 | HCS04SFN040000XA_ | Pump/Gate Gallery Supply Fan General Fault | |
| | | 4 | | | |
| | | 5 | HCS04SAM010000BN_ | Influent Sampler Bottle Number | |
| | | 6 | HCS04SAM010000ST_ | Influent Sampler Sample Mark | |
| | | 7 | HCS04SAM01VLV01YN_ | Influent Backwash Valve in Remote | |
| | | 8 | HCS04SAM01VLV01ZH_ | Influent Backwash Valve Opened Status | |
| | | 9 | HCS04SAM01VLV01ZL_ | Influent Backwash Valve Closed Status (Future) | |
| | | 10 | HCS04SAM01VLV01XA_ | Influent Backwash Valve General Fault (Future) | |
| | | 11 | HCS04SAM01VLV01WA_ | Influent Backwash Valve Overtorque Alarm (Future) | |
| | | 12 | HCS04SAM020000BN_ | Effluent Sampler Bottle Number | |
| | | 13 | HCS04SAM020000ST_ | Effluent Sampler Sample Mark | |
| | | 14 | HCS04SAM000000RES | Influent/Overflow Sampler Program Reset | |
| | | 15 | | | |
| 2 | | 3 | 0 | HCS04ATS010000YN_ | ATS in Remote (Future) |
| | DI | 1 | HCS04ATS010000XA_ | ATS General Alarm (Future) | |
| | | 2 | HCS04ATS01LNE01YX_ | ATS Normal/Hydro Power Available | |
| | | 3 | HCS04ATS01LNE02YX_ | ATS Emergency/Generator Power Available | |
| | | 4 | HCS04ATS01JSW01YX_ | ATS in Normal/Hydro Power Position | |
| | | 5 | HCS04ATS01JSW02YX_ | ATS in Emergency/Generator Power Position | |
| | | 6 | | | |
| | | 7 | | | |
| | | 8 | HCS04GEN010000YN_ | Generator in Remote (Future) | |
| | | 9 | HCS04GEN01HSW01HAS | Generator E-Stop Activated (Future) | |
| | | 10 | HCS04GEN010000XA_ | Generator General Alarm (Future) | |
| | | 11 | HCS04GEN010000MN_ | Generator Running (Future) | |
| | | 12 | | | |
| | | 13 | | | |
| | | 14 | | | |
| | | 15 | | | |
| 2 | | 4 | 0 | HCS04STN01HSW01YX_ | Station Security Key Switch Status |
| | DI | 1 | HCS04STN01ESW01ZSH | Door Contact | |
| | | 2 | HCS04STN01ESW02ZSH | Wetwell Hatch Contact (Future) | |
| | | 3 | HCS04STN01SKD01XA_ | Building Smoke/Fire Alarm | |
| | | 4 | HCS04STN01LSH01LHH | Station Flood Alarm | |
| | | 5 | HCS04CP001JSW01JA_ | PAC Panel Power Fail Alarm | |
| | | 6 | HCS04CP001UPS01MN_ | PAC Panel UPS Online | |
| | | 7 | HCS04CP001UPS01XA_ | PAC Panel UPS Fault/Low Battery | |
| | | 8 | HCS04NAC01NAS01XA_ | WAN Panel Ethernet Switch Minor Fault | |
| | | 9 | HCS04NAC01NAS01XA2 | WAN Panel Ethernet Switch Major Fault | |
| | | 10 | HCS04CP001DCP01XA_ | PAC Panel DC Power Supply Fault | |
| | | 11 | | | |


| | | | | |
|---|----|----|----|--|
| | | | 12 | |
| | | | 13 | |
| | | | 14 | |
| | | | 15 | |
| 2 | | 5 | | Spare |
| 2 | | 6 | | Spare |
| 2 | | 7 | | Spare |
| 2 | | 8 | 0 | HCS04VCH01IV001ZI_ Chamber No.1 Gate Position Indication |
| | AI | | 1 | |
| | | | 2 | |
| | | | 3 | |
| | | | 4 | |
| | | | 5 | HCS04VCH01LIT01LI_ Chamber No.1 Level Indication |
| 2 | | 9 | 0 | HCS04VCH04IV001ZI_ Chamber No.4 Gate Position Indication |
| | AI | | 1 | |
| | | | 2 | HCS04VCH04LIT01LI_ Chamber No.4 Level Indication |
| | | | 3 | |
| | | | 4 | HCS04WWT01FIT01FI_ Main Flushing Water Line Flow Indication |
| | | | 5 | HCS04STN01PIT01PI_ City Water Pressure Indication |
| 2 | | 10 | 0 | HCS04VCH05IV001ZI_ Chamber No.5 Gate Position Indication |
| | AI | | 1 | |
| | | | 2 | |
| | | | 3 | |
| | | | 4 | |
| | | | 5 | |
| 2 | | 11 | 0 | HCS04STN01IV001ZI_ Pump Station Inlet Gate Position Indication |
| | AI | | 1 | HCS04STN01IV002ZI_ Cells Inlet Gate Position Indication |
| | | | 2 | |
| | | | 3 | |
| | | | 4 | |
| | | | 5 | HCS04WWT01LIT01LI_ Cell No.1 Level Indication |
| 2 | | 12 | 0 | HCS04STN01OV001ZI_ Cells Outlet Gate Position Indication |
| | AI | | 1 | |
| | | | 2 | |
| | | | 3 | |
| | | | 4 | |
| | | | 5 | HCS04WWT02LIT01LI_ Cell No.2 Level Indication |
| 2 | | 13 | 0 | HCS04STN01LIT01LI_ Overflow Weir Level Indication |
| | AI | | 1 | HCS04WWL01LIT01LI_ Wetwell Level Indication |
| | | | 2 | |
| | | | 3 | HCS04STN01FIT01FI_ Station Flow Indication |
| | | | 4 | |

| | | | |
|---|----|--|--|
| | 5 | HCS04STN01TIT01TI_ Building Temperature Indication | |
| 2 | 14 | 0 | |
| | AI | 1 | |
| | | 2 | |
| | | 3 | |
| | | 4 | |
| | | 5 | |
| 2 | 15 | 0 | |
| | AI | 1 | |
| | | 2 | |
| | | 3 | |
| | | 4 | |
| | | 5 | |
| 2 | 16 | Spare | |


APPENDIX C – SCADA HMI SCREENS AND P&IDs

HMI Screens


Below are screen captures of the HMI screens at this station. For detailed SCADA HMI screen information, Refer to the HCS04 Operations and Maintenance Manual.




HCS04 HMI Screen – Main Overview




HCS04 HMI Screen – Wetwell



HCS04 HMI Screen – CSO Tank Overview



HCS04 HMI Screen – Environmental



HCS04 HMI Screen – Power

The 'HCS04 - SETPOINTS' popup window is divided into several sections:

- PUMP DUTIES:** Includes radio buttons for 'AUTOMATIC ALTERNATION' (selected), 'ALTERNATION @ TIME:', 'ALTERNATE @ TIME, IF RUNTIME HIGHER:' (with input 'Every 1 days at 00 : 00' and 'Last Alternation was 0 days ago'), 'ALTERNATE ON STOP IF RUNTIME HIGHER', and 'MANUAL:'.
- LEVEL SETPOINTS TABLE:** A table with 'Current' values:

| | Current |
|--------------|---------|
| DUTY 1 START | 4.50 |
| DUTY 1 STOP | 3.00 |
| DUTY 2 START | 4.80 |
| DUTY 2 STOP | 3.00 |
- PUMPS RUN STATUS:** Lists 'SLP01: STOPPED', 'SLP02: STOPPED', and 'SLP03: STOPPED'.
- CELL FLUSHING SETPOINTS:** Includes 'FLUSH:' and 'DEMO:' buttons (START/STOP), and 'CELL 1 FLUSH:' and 'CELL 2 FLUSH:' both set to 'Enabled'.

An 'UPDATE' button is located below the manual duty table. A version number 'HCS04_SP - ver: 5.0 (Upd: Jan 20, 2017)' is in the bottom right corner.

HCS04 HMI Screen – Setpoints Popup

HCS04 - SAMPLING SETPOINTS

INFLUENT SAMPLING SETPOINTS TABLE (SAM01)
INFLUENT EVENT IN PROGRESS

BOTTLE LIMIT EXCEEDED
SEQUENCE ERROR DETECTED
INFLUENT SAMPLER FAULT

Influent Sampling Pump Cells Start Level: 5.4 m
Max No. Of Event Marks Per Bottle (Pulses): 24
No. of Pulses Counted: 0
Bottle Number In Sequence (Calculated): 1
Bottle Number In Sequence (Received): 1
Maximum Bottle Limit: 8
Trigger Volume: 3060 m3
Current Influent Duration: 0 hrs 0 mins
No. of Pulses Received: 0
No. of Pulses Sent: 0
Wet Well Level Rate of Change Time Delay Timer Setpoint: 30 sec
Wet Well Level Rate of Change Difference Setpoint: 0.10 m

OVERFLOW SAMPLING SETPOINTS TABLE (SAM02)
OVERFLOW EVENT IN PROGRESS

BOTTLE LIMIT EXCEEDED
SEQUENCE ERROR DETECTED
OVERFLOW SAMPLER FAULT

Overflow Sampl. Pump Ovflw Weir Start Level: 0.1 m
Max No. Of Event Marks Per Bottle (Pulses): 24
No. of Pulses Counted: 0
Bottle Number In Sequence (Calculated): 1
Bottle Number In Sequence (Received): 1
Maximum Bottle Limit: 8
Current Overflow Duration: 0 hrs 0 mins
No. of Pulses Received: 0
No. of Pulses Sent: 0

HCS04_SAM - ver. 5.0 (Upd. Jan 19, 2017)

HCS04 HMI Screen – Sampling Popup

HCS04 - MAIN / KING CSO Tank

CSO OVERFLOWING!

Refer to the CSO Overflow Notification list in BCOS
to contact the appropriate personnel.

AT LEAST THREE FLUSH VALVES FAILED TO CLOSE!
Operator to be sent to the station to check the valves!

HCS04_RS - ver. 5.0 (Upd. Jan 19, 2017)

HCS04 HMI Screen – Red Screen Popup

EATON
Eaton 5PX 1000

| | | |
|---------------------|-----------------------------------|-------|
| Input Voltage | <input type="text" value="116"/> | V |
| Input Frequency | <input type="text" value="59.9"/> | Hz |
| Output Voltage | <input type="text" value="115"/> | V |
| Output Current | <input type="text" value="1.0"/> | A |
| Output Frequency | <input type="text" value="59.9"/> | Hz |
| Output Power | <input type="text" value="60"/> | W |
| Output Load | <input type="text" value="11"/> | % |
| Battery Charge | <input type="text" value="100"/> | % |
| Runtime Remaining | <input type="text" value="135"/> | min |
| Battery Temperature | <input type="text" value="0"/> | Deg C |

| | |
|----------------------|-------|
| Running On Battery | ALARM |
| Battery Low | ALARM |
| Battery Fault | ALARM |
| Battery Need Replace | ALARM |
| Battery Charge Fault | ALARM |
| UPS Output Overload | ALARM |
| UPS High Temperature | ALARM |
| UPS General Alarm | ALARM |

UPS_POPUP / ver. 4.3

HMI Screen – SNMP UPS Popup

Piping and Instrumentation Diagram

The following is the P&ID for this station

APPENDIX D – HISTORIAN REPORT

Historian Report

Below is the e.RIS report for this station.

HCS04 - Main/King St. Combined Sewer Overflow Tank

Daily Report: Sunday, November 27, 2016
 <Sewage>

Rep: 154 HC: 05
 Index: 184



The City of Hamilton

| Time | MPS Wet Well Level (m) | MPS Flow East (ML/d) | MPS Flow West (ML/d) | Cell 1 Level (m) | Cell 2 Level (m) | Overflow Level (m) | SLP01 Runtime (min) | SLP02 Runtime (min) | SLP03 Runtime (min) | Pumping Rate (m³) | PS Flow Rate (L/s) | PS Flow Total (m³) | Pot. Water Pressure (kPa) |
|---------|------------------------|----------------------|----------------------|------------------|------------------|--------------------|---------------------|---------------------|---------------------|-------------------|--------------------|--------------------|---------------------------|
| 00:00 | 65.50 | 110.21 | 127.78 | 0.04 | 0.07 | 0.00 | 0.00 | 0.00 | 39.00 | 877.50 | 158.57 | 433.12 | 18.18 |
| 01:00 | 65.83 | 109.17 | 126.71 | 0.04 | 0.07 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 1.05 | 574.77 | 18.21 |
| 02:00 | 65.94 | 110.66 | 129.09 | 0.05 | 0.07 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 1.05 | 578.55 | 18.23 |
| 03:00 | 65.91 | 100.82 | 145.33 | 0.05 | 0.07 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 1.05 | 582.33 | 18.26 |
| 04:00 | 65.33 | 87.51 | 168.34 | 0.05 | 0.08 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 1.05 | 586.11 | 18.29 |
| 05:00 | 65.10 | 86.71 | 106.16 | 0.05 | 0.08 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 1.05 | 589.92 | 18.33 |
| 06:00 | 65.15 | 71.17 | 91.27 | 0.05 | 0.08 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 1.05 | 593.76 | 18.34 |
| 07:00 | 65.10 | 86.82 | 106.20 | 0.05 | 0.08 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 1.05 | 597.54 | 18.35 |
| 08:00 | 65.21 | 82.02 | 97.02 | 0.05 | 0.08 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 1.05 | 601.32 | 18.40 |
| 09:00 | 65.14 | 103.15 | 116.46 | 0.05 | 0.08 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 1.05 | 605.10 | 18.41 |
| 10:00 | 65.31 | 100.16 | 110.88 | 0.05 | 0.08 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 1.05 | 608.88 | 18.43 |
| 11:00 | 65.77 | 101.10 | 112.84 | 0.05 | 0.08 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 1.05 | 612.66 | 18.45 |
| 12:00 | 65.98 | 145.25 | 160.82 | 0.05 | 0.07 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 1.05 | 616.44 | 18.45 |
| 13:00 | 65.94 | 155.12 | 150.46 | 0.05 | 0.07 | 0.00 | 0.00 | 59.00 | 0.00 | 1327.50 | 313.84 | 1259.47 | 18.45 |
| 14:00 | 65.93 | 154.80 | 166.92 | 0.05 | 0.06 | 0.00 | 0.00 | 60.00 | 0.00 | 1350.00 | 300.51 | 2373.42 | 18.45 |
| 15:00 | 66.01 | 155.59 | 169.61 | 0.05 | 0.06 | 0.00 | 0.00 | 8.00 | 0.00 | 180.00 | 39.23 | 2971.80 | 18.42 |
| 16:00 | 66.04 | 155.35 | 151.07 | 0.05 | 0.06 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 1.05 | 2975.57 | 18.40 |
| 17:00 | 65.99 | 154.76 | 132.39 | 0.05 | 0.06 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 1.05 | 2979.35 | 18.38 |
| 18:00 | 65.95 | 152.35 | 124.22 | 0.05 | 0.06 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 1.05 | 2983.13 | 18.32 |
| 19:00 | 65.97 | 152.11 | 127.94 | 0.05 | 0.06 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 1.05 | 2986.91 | 18.35 |
| 20:00 | 65.95 | 150.79 | 129.53 | 0.05 | 0.06 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 1.05 | 2990.69 | 18.42 |
| 21:00 | 65.88 | 146.10 | 145.14 | 0.05 | 0.06 | 0.00 | 0.00 | 0.00 | 58.00 | 1305.00 | 256.52 | 3518.79 | 18.45 |
| 22:00 | 65.82 | 139.60 | 132.75 | 0.05 | 0.06 | 0.00 | 0.00 | 0.00 | 60.00 | 1350.00 | 253.99 | 4452.46 | 18.49 |
| 23:00 | 65.77 | 134.65 | 136.35 | 0.05 | 0.05 | 0.00 | 0.00 | 0.00 | 39.00 | 877.50 | 157.24 | 5259.85 | 18.53 |
| Average | 65.69 | 122.75 | 131.89 | 0.05 | 0.07 | 0.00 | 0.00 | 5.29 | 8.17 | 302.81 | 62.41 | 1763.83 | 18.37 |
| Minimum | 65.10 | 71.17 | 91.27 | 0.04 | 0.05 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 1.05 | 433.12 | 18.18 |
| Maximum | 66.04 | 155.59 | 169.61 | 0.05 | 0.08 | 0.00 | 0.00 | 60.00 | 60.00 | 1350.00 | 313.84 | 5259.85 | 18.53 |
| Total | | | | | | | | | | 7267.50 | | | |

| | SLP01 Runtime (h) | SLP02 Runtime (h) | SLP03 Runtime (h) | Total Flow (m³) |
|-------------|-------------------|-------------------|-------------------|-----------------|
| 28Nov 00:00 | 3222.09 | 1284.73 | 3656.72 | 5398.24 |

HCS04 - Main/King St. Combined Sewer Overflow Pumping Station

Daily Report: Sunday, November 27, 2016
<Sewage>

Rep: 155 HC: 06
Index: 185



The City of Hamilton

| Time | MPS Wet Well Level (m) | MPS Flow East (ML/d) | MPS Flow West (ML/d) | Chamber 1 Level (m) | Chamber 1 Gate Pos. (%) | Chamber 4 Level (m) | Chamber 4 Gate Pos. (%) | Chamber 5 Gate Pos. (%) | Cells Out Gate Pos. (%) | Inf Well OF Gate Pos. (%) | Wet Well Level (m) | Stn Inlet Gate Pos. (%) | Cells Inlet Gate Pos. (%) | Overflow Flow (L/s) |
|---------|------------------------|----------------------|----------------------|---------------------|-------------------------|---------------------|-------------------------|-------------------------|-------------------------|---------------------------|--------------------|-------------------------|---------------------------|---------------------|
| 00:00 | 65.50 | 110.21 | 127.78 | 0.91 | 33.73 | 0.00 | 8.53 | 28.76 | 100.00 | 4.71 | 3.22 | 99.40 | 47.81 | 0.00 |
| 01:00 | 65.83 | 109.17 | 126.71 | 0.87 | 33.73 | 0.00 | 8.53 | 28.76 | 100.00 | 4.71 | 3.15 | 99.39 | 47.81 | 0.00 |
| 02:00 | 65.94 | 110.66 | 129.09 | 0.80 | 33.73 | 0.00 | 8.53 | 28.76 | 100.00 | 4.70 | 3.26 | 99.38 | 47.80 | 0.00 |
| 03:00 | 65.91 | 100.82 | 145.33 | 0.69 | 33.73 | 0.00 | 8.53 | 28.76 | 100.00 | 4.70 | 3.33 | 99.38 | 47.80 | 0.00 |
| 04:00 | 65.33 | 87.51 | 168.34 | 0.70 | 33.73 | 0.00 | 8.53 | 28.76 | 100.00 | 4.69 | 3.38 | 99.37 | 47.80 | 0.00 |
| 05:00 | 65.10 | 86.71 | 106.16 | 0.58 | 33.73 | 0.00 | 8.53 | 28.76 | 100.00 | 4.70 | 3.43 | 99.37 | 47.80 | 0.00 |
| 06:00 | 65.15 | 71.17 | 91.27 | 0.71 | 33.73 | 0.00 | 8.53 | 28.76 | 100.00 | 4.74 | 3.46 | 99.42 | 47.81 | 0.00 |
| 07:00 | 65.10 | 86.82 | 106.20 | 0.56 | 33.73 | 0.00 | 8.53 | 28.76 | 100.00 | 4.76 | 3.53 | 99.45 | 47.82 | 0.00 |
| 08:00 | 65.21 | 82.02 | 97.02 | 0.62 | 33.73 | 0.00 | 8.53 | 28.76 | 100.00 | 4.74 | 3.59 | 99.42 | 47.81 | 0.00 |
| 09:00 | 65.14 | 103.15 | 116.46 | 0.81 | 33.72 | 0.00 | 8.53 | 28.76 | 100.00 | 4.73 | 3.63 | 99.41 | 47.81 | 0.00 |
| 10:00 | 65.31 | 100.16 | 110.88 | 0.89 | 33.73 | 0.00 | 8.53 | 28.76 | 100.00 | 4.72 | 3.72 | 99.40 | 47.81 | 0.00 |
| 11:00 | 65.77 | 101.10 | 112.84 | 0.97 | 33.73 | 0.00 | 8.53 | 28.76 | 100.00 | 4.72 | 4.01 | 99.40 | 47.81 | 0.00 |
| 12:00 | 65.98 | 145.25 | 160.82 | 0.96 | 33.73 | 0.00 | 8.53 | 28.76 | 100.00 | 4.72 | 4.36 | 99.39 | 47.81 | 0.00 |
| 13:00 | 65.94 | 155.12 | 150.46 | 0.96 | 33.73 | 0.00 | 8.53 | 28.76 | 100.00 | 4.72 | 4.26 | 99.40 | 47.81 | 0.00 |
| 14:00 | 65.93 | 154.80 | 166.92 | 0.96 | 33.73 | 0.00 | 8.53 | 28.76 | 100.00 | 4.72 | 3.59 | 99.40 | 47.81 | 0.00 |
| 15:00 | 66.01 | 155.59 | 169.61 | 0.95 | 33.73 | 0.00 | 8.53 | 28.76 | 100.00 | 4.71 | 3.19 | 99.39 | 47.81 | 0.00 |
| 16:00 | 66.04 | 155.35 | 151.07 | 0.93 | 33.73 | 0.00 | 8.53 | 28.76 | 100.00 | 4.71 | 3.57 | 99.39 | 47.81 | 0.00 |
| 17:00 | 65.99 | 154.76 | 132.39 | 0.93 | 33.73 | 0.00 | 8.53 | 28.76 | 100.00 | 4.71 | 3.82 | 99.38 | 47.81 | 0.00 |
| 18:00 | 65.95 | 152.35 | 124.22 | 0.93 | 33.73 | 0.00 | 8.53 | 28.76 | 100.00 | 4.72 | 4.02 | 99.40 | 47.81 | 0.00 |
| 19:00 | 65.97 | 152.11 | 127.94 | 0.95 | 33.73 | 0.00 | 8.53 | 28.76 | 100.00 | 4.75 | 4.23 | 99.45 | 47.82 | 0.00 |
| 20:00 | 65.95 | 150.79 | 129.53 | 0.94 | 33.73 | 0.00 | 8.53 | 28.76 | 100.00 | 4.74 | 4.43 | 99.43 | 47.82 | 0.00 |
| 21:00 | 65.88 | 146.10 | 145.14 | 0.95 | 33.73 | 0.00 | 8.53 | 28.76 | 100.00 | 4.73 | 4.32 | 99.42 | 47.81 | 0.00 |
| 22:00 | 65.82 | 139.60 | 132.75 | 0.94 | 33.73 | 0.00 | 8.53 | 28.76 | 100.00 | 4.72 | 3.86 | 99.40 | 47.81 | 0.00 |
| 23:00 | 65.77 | 134.65 | 136.35 | 0.93 | 33.73 | 0.00 | 8.53 | 28.76 | 100.00 | 4.71 | 3.21 | 99.40 | 47.81 | 0.00 |
| Average | 65.69 | 122.75 | 131.89 | 0.85 | 33.73 | 0.00 | 8.53 | 28.76 | 100.00 | 4.72 | 3.69 | 99.40 | 47.81 | 0.00 |
| Minimum | 65.10 | 71.17 | 91.27 | 0.56 | 33.72 | 0.00 | 8.53 | 28.76 | 100.00 | 4.69 | 3.15 | 99.37 | 47.80 | 0.00 |
| Maximum | 66.04 | 155.59 | 169.61 | 0.97 | 33.73 | 0.00 | 8.53 | 28.76 | 100.00 | 4.76 | 4.43 | 99.45 | 47.82 | 0.00 |

APPENDIX E – ALARM TABLE

Alarms

All alarms are of the Boolean type and can be acknowledged at the SCADA HMI by any operator, supervisor or administrator security level.

HCS04 Alarms

| SCADA Tag | Alarm Description | Units | Priority | Sig. Digits | Default | Delay Timer (sec) | MOE (Y/N) |
|---------------------------|---|-------|----------|-------------|---------|-------------------|-----------|
| Station / Building | | | | | | | |
| HCS04STN01SKD01XA_ | Station Smoke Alarm | N/A | H | N/A | N/A | 10 | N |
| HCS04STN01LSH01LHH | Station Flood Alarm | N/A | H | N/A | N/A | 0 | N |
| HCS04STN01ESW01XA_ | Station Illegal Entry | sec | L | N/A | N/A | 45 | N |
| HCS04STN01TIT01AHH | Station Temperature HIHI | °C | L | 4 | 40.0 | 10 | N |
| HCS04STN01TIT01AAH | Station Temperature HI | °C | L | 4 | 35.0 | 10 | N |
| HCS04STN01TIT01AAL | Station Temperature LO | °C | L | 4 | 10.0 | 10 | N |
| HCS04STN01TIT01ALL | Station Temperature LOLO | °C | L | 4 | 5.0 | 10 | N |
| HCS04STN01TIT01ER_ | Station Temperature Signal Error | N/A | L | N/A | N/A | 10 | N |
| Power | | | | | | | |
| HCS04STN01JSW01XA_ | Station 600 VAC Power Failure | N/A | HH | N/A | N/A | 60 | N |
| HCS04ATS010000XA2 | ATS Position Error | N/A | L | N/A | N/A | 60 | N |
| HCS04GEN010000SF_ | Portable Generator Fail to Start | N/A | L | N/A | N/A | 60 | N |
| HCS04GEN010000XF_ | Portable Generator Fail to Stop | N/A | L | N/A | N/A | 3600 | N |
| HCS04GEN010000XA_ | Portable Generator Diesel Fuel Low | N/A | L | N/A | N/A | 0 | N |
| WAN Panel | | | | | | | |
| HCS04NAC01NAS01XA_ | WAN Panel Ethernet Switch Minor Fault | N/A | HH | N/A | N/A | 0 | N |
| HCS04NAC01NAS01XA2 | WAN Panel Ethernet Switch Major Fault | N/A | HH | N/A | N/A | 0 | N |
| PAC Control Panel | | | | | | | |
| HCS04PAC010000COM | PAC to HMI Communication Failure | N/A | HH | N/A | N/A | 120 | N |
| HCS04PAC01OIT01COM | PAC to Panel Computer Communication Failure | N/A | HH | N/A | N/A | 60 | N |
| HCS04PAC010000XAM | PAC I/O Fault | N/A | HH | N/A | N/A | 0 | N |
| HCS04PAC010000PXF | PAC Major Fault | N/A | HH | N/A | N/A | 0 | N |
| HCS04PAC010000MXB | PAC Battery Low | N/A | HH | N/A | N/A | 0 | N |

| SCADA Tag | Alarm Description | Units | Priority | Sig. Digits | Default | Delay Timer (sec) | MOE (Y/N) |
|--|---|-------|----------|-------------|---------|-------------------|-----------|
| HCS04PAC0100000MXP | PAC Minor Fault | N/A | HH | N/A | N/A | 0 | N |
| HCS04PAC0100000MXI | PAC Minor I/O Fault | N/A | HH | N/A | N/A | 0 | N |
| HCS04PAC0100000OVF | PAC Overflow Fault | N/A | HH | N/A | N/A | 0 | N |
| HCS04CP001JSW01JA_ | PAC Panel AC Power Failure | N/A | HH | N/A | N/A | 10 | N |
| HCS04CP001DCP01XA_ | PAC Panel DC Power Fault | N/A | HH | N/A | N/A | 10 | N |
| HCS04CP001UPS01MN_ | UPS Offline | N/A | HH | N/A | N/A | 0 | N |
| HCS04CP001UPS01XA_ | UPS General Fault / Low Battery | N/A | HH | N/A | N/A | 0 | N |
| Sewage Lift Pumps (No.1-3) | | | | | | | |
| HCS04SLP0100000SF_ To HCS04SLP0300000SF_ | Sewage Lift Pump Failed To Start | N/A | L | N/A | N/A | 30 | N |
| HCS04SLP0100000XF_ To HCS04SLP0300000XF_ | Sewage Lift Pump Failed To Stop | N/A | L | N/A | N/A | 30 | N |
| HCS04SLP0100000SU_ To HCS04SLP0300000SU_ | Sewage Lift Pump Uncommanded Start | N/A | L | N/A | N/A | 0 | N |
| HCS04SLP0100000XU_ To HCS04SLP0300000XU_ | Sewage Lift Pump Uncommanded Stop | N/A | L | N/A | N/A | 0 | N |
| HCS04SLP0100000XAF To HCS04SLP0300000XAF | Sewage Lift Pump General Fault | N/A | M | N/A | N/A | 0 | N |
| HCS04SLP0100000NF_ To HCS04SLP0300000NF_ | Sewage Lift Pump No Flow | N/A | M | N/A | N/A | 45 | N |
| HCS04SLP0100000AAA To HCS04SLP0300000AAA | Sewage Lift Pump Auto Acknowledge Alarm | N/A | L | N/A | N/A | 0 | N |
| Sample Pumps | | | | | | | |
| HCS04SAP0100000SF_ HCS04SAP0200000SF_ | Sample Pump Failed To Start | N/A | L | N/A | N/A | 30 | N |
| HCS04SAP0100000XF_ HCS04SAP0200000XF_ | Sample Pump Failed To Stop | N/A | L | N/A | N/A | 30 | N |

| SCADA Tag | Alarm Description | Units | Priority | Sig. Digits | Default | Delay Timer (sec) | MOE (Y/N) |
|--|--------------------------------------|-------|----------|-------------|---------|-------------------|-----------|
| HCS04SAP0100000SU_ HCS04SAP0200000SU_ | Sample Pump Uncommanded Start | N/A | L | N/A | N/A | 0 | N |
| HCS04SAP0100000XU_ HCS04SAP0200000XU_ | Sample Pump Uncommanded Stop | N/A | L | N/A | N/A | 0 | N |
| HCS04SAP0100000XAF HCS04SAP0200000XAF | Sample Pump General Fault | N/A | M | N/A | N/A | 0 | N |
| HCS04SAP0100000AAA HCS04SAP0200000AAA | Sample Pump Auto Acknowledge Alarm | N/A | L | N/A | N/A | 0 | N |
| Fans | | | | | | | |
| HCS04SFN0100000SF_ To HCS04SFN0300000SF_ HCS04SFN0500000SF_ | Supply Fan Failed To Start | N/A | L | N/A | N/A | 30 | N |
| HCS04SFN0100000XF_ To HCS04SFN0300000XF_ HCS04SFN0500000XF_ | Supply Fan Failed To Stop | N/A | L | N/A | N/A | 30 | N |
| HCS04SFN0100000SU_ To HCS04SFN0300000SU_ HCS04SFN0500000SU_ | Supply Fan Uncommanded Start | N/A | L | N/A | N/A | 0 | N |
| HCS04SFN0100000XU_ To HCS04SFN0300000XU_ HCS04SFN0500000XU_ | Supply Fan Uncommanded Stop | N/A | L | N/A | N/A | 0 | N |
| HCS04SFN0100000XAF To HCS04SFN0300000XAF HCS04SFN0500000XAF | Supply Fan General Fault | N/A | M | N/A | N/A | 0 | N |
| HCS04SFN0100000AAA To HCS04SFN0300000AAA HCS04SFN0500000AAA | Supply Fan Auto Acknowledge Alarm | N/A | L | N/A | N/A | 0 | N |
| HCS04SFN0100000SFH | Supply Fan No.4 Failed To Start Fast | N/A | L | N/A | N/A | 30 | N |

| SCADA Tag | Alarm Description | Units | Priority | Sig. Digits | Default | Delay Timer (sec) | MOE (Y/N) |
|--|---|-------|----------|-------------|---------|-------------------|-----------|
| HCS04SFN010000SFL | Supply Fan No.4 Failed To Start Slow | N/A | L | N/A | N/A | 30 | N |
| HCS04SFN010000XF_ | Supply Fan No.4 Failed To Stop | N/A | L | N/A | N/A | 30 | N |
| HCS04SFN010000SUH | Supply Fan No.4 Uncommanded Start Fast | N/A | L | N/A | N/A | 0 | N |
| HCS04SFN010000SUI | Supply Fan No.4 Uncommanded Start Slow | N/A | L | N/A | N/A | 0 | N |
| HCS04SFN010000XU_ | Supply Fan No.4 Uncommanded Stop | N/A | L | N/A | N/A | 0 | N |
| HCS04SFN010000XAF | Supply Fan No.4 General Fault | N/A | M | N/A | N/A | 0 | N |
| Samplers | | | | | | | |
| HCS04SAM01VLV01FO_ | Influent Backwash Valve Fail to Open | N/A | L | N/A | N/A | 30 | N |
| HCS04SAM01VLV01CF_ | Influent Backwash Valve Fail to Close | N/A | L | N/A | N/A | 30 | N |
| HCS04SAM01VLV01OU_ | Influent Backwash Valve Uncommanded Open | N/A | L | N/A | N/A | 0 | N |
| HCS04SAM01VLV01CU_ | Influent Backwash Valve Uncommanded Close | N/A | L | N/A | N/A | 0 | N |
| HCS04SAM010000XA2 HCS04SAM020000XA2 | Sampler Sequence Failed | N/A | | N/A | N/A | 0 | N |
| HCS04SAM010000XA3 HCS04SAM020000XA3 | Sampler Bottle Limit Reached | N/A | | N/A | N/A | 0 | N |
| Gates | | | | | | | |
| HCS04STN01IV001ZA_ HCS04STN01IV002ZA_ HCS04STN01OV001ZA_ HCS04STN01OV002ZA_ HCS04VCH01IV001ZA_ HCS04VCH04IV001ZA_ | Gate Position Deviation | N/A | L | N/A | N/A | 120 | N |
| HCS04VCH05IV001ZA_ | Chamber No.5 Gate Position Deviation | N/A | L | N/A | N/A | 390 | N |

| SCADA Tag | Alarm Description | Units | Priority | Sig. Digits | Default | Delay Timer (sec) | MOE (Y/N) |
|--|--|-------|----------|-------------|---------|-------------------|-----------|
| HCS04STN01IV001ZIA HCS04STN01IV002ZIA HCS04STN01OV001ZIA HCS04VCH01IV001ZIA HCS04VCH04IV001ZIA | Gate Position Signal Error | N/A | L | N/A | N/A | 10 | N |
| HCS04VCH05IV001ZIA | Chamber No.5 Gate Position Signal Error | N/A | L | N/A | N/A | 5 | N |
| Valves | | | | | | | |
| HCS04WWT01VLV01FO_ | Main Flushing Water Line Shutoff Valve Failed to Open | N/A | L | N/A | N/A | 10 | N |
| HCS04WWT01VLV01CF_ | Main Flushing Water Line Shutoff Valve Failed to Close | N/A | L | N/A | N/A | 10 | N |
| HCS04WWT01VLV01OU_ | Main Flushing Water Line Shutoff Valve Uncommanded Open | N/A | L | N/A | N/A | 0 | N |
| HCS04WWT01VLV01CU_ | Main Flushing Water Line Shutoff Valve Uncommanded Close | N/A | L | N/A | N/A | 0 | N |
| HCS04WWT01VLV01XA_ | Main Flushing Water Line Shutoff Valve General Fault | N/A | M | N/A | N/A | 0 | N |
| HCS04WWT01VLV01WA_ | Main Flushing Water Line Shutoff Valve Over-Torque | N/A | L | N/A | N/A | 0 | N |
| HCS04WWT01SOL01FO_ To HCS04WWT01SOL05FO_ HCS04WWT02SOL06FO_ To HCS04WWT02SOL15FO_ | Flushing Valve Fail to Open | N/A | L | N/A | N/A | 30 | N |
| HCS04WWT01SOL01CF_ To HCS04WWT01SOL05CF_ HCS04WWT02SOL06CF_ To HCS04WWT02SOL15CF_ | Flushing Valve Fail to Close | N/A | L | N/A | N/A | 30 | N |
| Level | | | | | | | |
| HCS04WWL01LIT01AHH | Wetwell Level HIHI | m | L | 3 | 10.0 | 10 | N |
| HCS04WWL01LIT01AAH | Wetwell Level HI | m | L | 3 | 8.0 | 10 | N |
| HCS04WWL01LIT01AAL | Wetwell Level LO | m | L | 3 | 2.9 | 10 | N |

| SCADA Tag | Alarm Description | Units | Priority | Sig. Digits | Default | Delay Timer (sec) | MOE (Y/N) |
|--|---|-------|----------|-------------|---------|-------------------|-----------|
| HCS04WWL01LIT01ALL | Wetwell Level LOLO | m | L | 3 | 2.0 | 10 | N |
| HCS04WWL01LIT01XAF | Wetwell Level Transmitter General Fault | N/A | L | N/A | N/A | 0 | N |
| HCS04WWL01LIT01ER_ | Wetwell Level Transmitter Signal Error | N/A | L | N/A | N/A | 10 | N |
| HCS04WWT01LIT01AHH HCS04WWT02LIT01AHH | CSO Tank Cell Level HIHI | m | L | 3 | 10.0 | 10 | N |
| HCS04WWT01LIT01AAH HCS04WWT02LIT01AAH | CSO Tank Cell Level HI | m | L | 3 | 8.0 | 10 | N |
| HCS04WWT01LIT01AAL HCS04WWT02LIT01AAL | CSO Tank Cell Level LO | m | L | 3 | 0.0 | 10 | N |
| HCS04WWT01LIT01ALL HCS04WWT02LIT01ALL | CSO Tank Cell Level LOLO | m | L | 3 | 0.0 | 10 | N |
| HCS04WWT01LIT01ER_ HCS04WWT02LIT01ER_ | CSO Tank Cell Level Transmitter Signal Error | N/A | L | N/A | N/A | 10 | N |
| HCS04STN01LIT01AHH | Overflow Weir Level HIHI | m | L | 3 | 0.1 | 10 | N |
| HCS04STN01LIT01AAH | Overflow Weir Level HI | m | L | 3 | 0.1 | 10 | N |
| HCS04STN01LIT01AAL | Overflow Weir Level LO | m | L | 3 | 0.0 | 10 | N |
| HCS04STN01LIT01ALL | Overflow Weir Level LOLO | m | L | 3 | 0.0 | 10 | N |
| HCS04STN01LIT01XAF | Overflow Weir Level Transmitter General Fault | N/A | L | N/A | N/A | 0 | N |
| HCS04STN01LIT01ER_ | Overflow Weir Level Transmitter Signal Error | N/A | L | N/A | N/A | 10 | N |
| HCS04VCH01LIT01AHH | Chamber No.1 Level HIHI | m | L | 3 | 1.08 | 10 | N |
| HCS04VCH01LIT01AAH | Chamber No.1 Level HI | m | L | 3 | 1.05 | 10 | N |
| HCS04VCH01LIT01AAL | Chamber No.1 Level LO | m | L | 3 | 0.0 | 10 | N |
| HCS04VCH01LIT01ALL | Chamber No.1 Level LOLO | m | L | 3 | 0.0 | 10 | N |
| HCS04VCH01LIT01ER_ | Chamber No.1 Level Transmitter Signal Error | N/A | L | N/A | N/A | 10 | N |
| HCS04VCH04LIT01AHH | Chamber No.4 Level HIHI | m | L | 3 | 1.17 | 10 | N |
| HCS04VCH04LIT01AAH | Chamber No.4 Level HI | m | L | 3 | 0.90 | 10 | N |
| HCS04VCH04LIT01AAL | Chamber No.4 Level LO | m | L | 3 | 0.0 | 10 | N |
| HCS04VCH04LIT01ALL | Chamber No.4 Level LOLO | m | L | 3 | 0.0 | 10 | N |

| SCADA Tag | Alarm Description | Units | Priority | Sig. Digits | Default | Delay Timer (sec) | MOE (Y/N) |
|---------------------------------------|---|-------|----------|-------------|---------|-------------------|-----------|
| HCS04VCH04LIT01ER_ | Chamber No.4 Level Transmitter Signal Error | N/A | L | N/A | N/A | 10 | N |
| Flow | | | | | | | |
| HCS04STN01FIT01AHH | Station Flow HIHI | L/s | L | 3 | 950 | 10 | N |
| HCS04STN01FIT01AAH | Station Flow HI | L/s | L | 3 | 750 | 10 | N |
| HCS04STN01FIT01AAL | Station Flow LO | L/s | L | 3 | 150 | 10 | N |
| HCS04STN01FIT01ALL | Station Flow LOLO | L/s | L | 3 | 100 | 10 | N |
| HCS04STN01FIT01ER_ | Station Flow Transmitter Signal Error | N/A | L | N/A | N/A | 10 | N |
| HCS04WWT01FIT01AHH | Main Flushing Water Line Flow HIHI | L/s | L | 3 | 9.0 | 10 | N |
| HCS04WWT01FIT01AAH | Main Flushing Water Line Flow HI | L/s | L | 3 | 7.0 | 10 | N |
| HCS04WWT01FIT01AAL | Main Flushing Water Line Flow LO | L/s | L | 3 | 3.0 | 10 | N |
| HCS04WWT01FIT01ALL | Main Flushing Water Line Flow LOLO | L/s | L | 3 | 1.0 | 10 | N |
| HCS04WWT01FIT01ER_ | Main Flushing Water Line Flow Transmitter Signal Error | N/A | L | N/A | N/A | 10 | N |
| HCS04WWT01FIT01XAF | Main Flushing Water Line Flow Transmitter General Fault | N/A | L | N/A | N/A | 0 | N |
| Pressure | | | | | | | |
| HCS04STN01PIT01AHH | City Water Pressure HIHI | kPa | L | 3 | 260 | 10 | N |
| HCS04STN01PIT01AAH | City Water Pressure HI | kPa | L | 3 | 245 | 10 | N |
| HCS04STN01PIT01AAL | City Water Pressure LO | kPa | L | 3 | 180 | 10 | N |
| HCS04STN01PIT01ALL | City Water Pressure LOLO | kPa | L | 3 | 150 | 10 | N |
| HCS04STN01PIT01ER_ | City Water Pressure Transmitter Signal Error | N/A | L | N/A | N/A | 10 | N |
| Red Screen (HCS04STN010000RS_) | | | | | | | |
| HCS04BWS010000XA_ | Flushing Sequence Failed | N/A | HH | N/A | N/A | 0 | N |
| HCS04STN01LIT01XA2 | Overflow Event in Progress | N/A | HH | N/A | N/A | 0 | N |

APPENDIX F – MESSAGE TABLE

Message Table

There is no messaging for this site.

APPENDIX G – PROGRAM VARIABLES & INTERNAL SOFTWARE PARAMETERS

Program Variables

These variables are adjustable at the SCADA HMI or panel computer based on security level.

HCS04 Program Variables

| SCADA Tag | Description | Data Type | Units | Sig. Digits | Input Range | | Default | Security Level |
|--------------------|--------------------------------|-----------|-------|-------------|-------------|-----|---------|----------------|
| | | | | | MIN | MAX | | |
| HCS04STN0100000MOD | Tank Mode | INT | N/A | 1 | 1 | 3 | 1 | CSOP |
| HCS04STN01LHT01CMH | C1 Gallery Lights West On | BOOL | N/A | N/A | OFF | ON | OFF | CSOP |
| HCS04STN01LHT01CMB | C1 Gallery Lights West Off | BOOL | N/A | N/A | OFF | ON | OFF | CSOP |
| HCS04STN01LHT02CMH | C2 Gallery Lights East On | BOOL | N/A | N/A | OFF | ON | OFF | CSOP |
| HCS04STN01LHT02CMB | C2 Gallery Lights East Off | BOOL | N/A | N/A | OFF | ON | OFF | CSOP |
| HCS04STN01LHT03CMH | C3 Gallery Lights South On | BOOL | N/A | N/A | OFF | ON | OFF | CSOP |
| HCS04STN01LHT03CMB | C3 Gallery Lights South Off | BOOL | N/A | N/A | OFF | ON | OFF | CSOP |
| HCS04STN01LHT04CMH | C4 Tank Flood Lights West On | BOOL | N/A | N/A | OFF | ON | OFF | CSOP |
| HCS04STN01LHT04CMB | C4 Tank Flood Lights West Off | BOOL | N/A | N/A | OFF | ON | OFF | CSOP |
| HCS04STN01LHT05CMH | C5 Tank Flood Lights South On | BOOL | N/A | N/A | OFF | ON | OFF | CSOP |
| HCS04STN01LHT05CMB | C5 Tank Flood Lights South Off | BOOL | N/A | N/A | OFF | ON | OFF | CSOP |
| HCS04STN01LHT06CMH | C6 Tank Flood Lights South On | BOOL | N/A | N/A | OFF | ON | OFF | CSOP |
| HCS04STN01LHT06CMB | C6 Tank Flood Lights South Off | BOOL | N/A | N/A | OFF | ON | OFF | CSOP |
| HCS04STN01LHT07CMH | C7 Emergency Lights On | BOOL | N/A | N/A | OFF | ON | OFF | CSOP |
| HCS04STN01LHT07CMB | C7 Emergency Lights Off | BOOL | N/A | N/A | OFF | ON | OFF | CSOP |
| HCS04SLPDY00000MOD | Duty Rotation Mode Selection | INT | N/A | N/A | 0 | 5 | 0 | CSOP |
| HCS04SLPDY00000P1_ | DUTY 1 Selection | INT | N/A | 1 | 1 | 3 | 1 | CSOP |

| SCADA Tag | Description | Data Type | Units | Sig. Digits | Input Range | | Default | Security Level |
|--------------------|---|-----------|----------------|-------------|-------------|-------|---------|----------------|
| | | | | | MIN | MAX | | |
| HCS04SLPDY00000P2_ | DUTY 2 Selection | INT | N/A | 1 | 1 | 3 | 2 | CSOP |
| HCS04SLPDY00000P3_ | STANDBY Selection | INT | N/A | 1 | 1 | 3 | 3 | CSOP |
| HCS04SLPDY00000DTU | Duty Rotation Table Update | BOOL | N/A | N/A | OFF | ON | OFF | CSOP |
| HCS04SLPDY00000DYH | Duty Rotation Set Time Hours | INT | hr | 2 | 0 | 23 | 2 | CSOP |
| HCS04SLPDY00000DYM | Duty Rotation Set Time Minutes | INT | min | 2 | 0 | 59 | 0 | CSOP |
| HCS04SLPDY00000NDR | Duty Rotation Days before Rotation | INT | day | 3 | 1 | 365 | 1 | CSOP |
| HCS04BWS0100000CMH | Flushing Sequence Start Request | BOOL | N/A | N/A | OFF | ON | OFF | CSOP |
| HCS04BWS0100000CMB | Flushing Sequence Stop Request | BOOL | N/A | N/A | OFF | ON | OFF | CSOP |
| HCS04BWS0200000CMH | Demo Mode Flushing Sequence Start Request | BOOL | N/A | N/A | OFF | ON | OFF | CSOP |
| HCS04BWS0200000CMB | Demo Mode Flushing Sequence Stop Request | BOOL | N/A | N/A | OFF | ON | OFF | CSOP |
| HCS04WWT0100000ENA | Cell No.1 Flushing Enable | BOOL | N/A | N/A | OFF | ON | OFF | CSOP |
| HCS04WWT0200000ENA | Cell No.2 Flushing Enable | BOOL | N/A | N/A | OFF | ON | OFF | CSOP |
| HCS04SAP0100000SP_ | Influent Sampling Pump Start Level | REAL | m | 4 | 0 | 12.70 | 5.40 | CSOP |
| HCS04SAM0100000HIS | Influent Number of Event Marks per Bottle | INT | N/A | 3 | 0 | 100 | 24 | SUPER |
| HCS04SAM0100000BLT | Influent Max Bottle Limit | DINT | N/A | 3 | 0 | 100 | 8 | CSOP |
| HCS04SAM0100000VC_ | Trigger Volume | REAL | m ³ | 5 | 0 | 10000 | 3060 | CSOP |
| HCS04SAM0100000AK2 | Influent Reset | BOOL | N/A | N/A | OFF | ON | OFF | SUPER |
| HCS04SAM0100000SMR | Wetwell Level ROC Time Delay | DINT | sec | 3 | 0 | 600 | 30 | CSOP |

| SCADA Tag | Description | Data Type | Units | Sig. Digits | Input Range | | Default | Security Level |
|--------------------|---|-----------|-------|-------------|-------------|-------|---------|----------------|
| | | | | | MIN | MAX | | |
| HCS04SAM0100000SP_ | Wetwell Level ROC Difference | REAL | m | 4 | 0 | 12.70 | 0.10 | CSOP |
| HCS04SAP0200000SP_ | Overflow Sampling Pump Start Level | REAL | m | 3 | 0 | 2.70 | 0.10 | CSOP |
| HCS04SAM0200000HIS | Overflow Number of Event Marks per Bottle | INT | N/A | 3 | 0 | 100 | 24 | SUPER |
| HCS04SAM0200000BLT | Overflow Max Bottle Limit | DINT | N/A | 3 | 0 | 100 | 8 | CSOP |
| HCS04SAM0200000AK2 | Overflow Reset | BOOL | N/A | N/A | OFF | ON | OFF | SUPER |
| HCS04GEN0100000TO_ | Portable Generator Fuel Consumption Time Setpoint | REAL | hr | 2 | 0 | 1000 | 25 | CSOP |

For all analog alarms found in the Alarm Table, there are accompanying alarm setpoints and alarm enable/disable program variables.

The input range for these alarms is based on the span of the instrument associated with the alarm; the instruments associated with this site can be found in Table 2-5: HCS04 Instrumentation Summary.

The tagging for the analogs is as follows:

HCS04 Analog Alarm Program Variables

| Analog Alarm Description | SCADA Tag - Fragment 8 | | Program Variable Security Level |
|--------------------------|-------------------------------|-----------------------|---------------------------------|
| | Analog Alarm Enable / Disable | Analog Alarm Setpoint | |
| High High | HHE | HHS | ADM |
| High | HAE | HIS | SUP |
| Low | LAE | LAS | SUP |
| Low Low | LLE | LLS | ADM |

Internal Software Parameters

These variables are set at the time of commissioning and are not adjustable at the SCADA HMI or panel computer.

HCS04 Internal Software Parameters

| SCADA Tag | Description | Data Type | Units | Sig. Digits | Input Range | | Default |
|--------------------|-----------------------|-----------|-------|-------------|-------------|------|---------|
| | | | | | MIN | MAX | |
| HCS04SLPDY00000D1T | DUTY 1 Start Setpoint | REAL | m | 3 | 0 | 12.7 | 4.50 |
| HCS04SLPDY00000D1P | DUTY 1 Stop Setpoint | REAL | m | 3 | 0 | 12.7 | 3.00 |
| HCS04SLPDY00000D2T | DUTY 2 Start Setpoint | REAL | m | 3 | 0 | 12.7 | 4.80 |
| HCS04SLPDY00000D2P | DUTY 2 Stop Setpoint | REAL | m | 3 | 0 | 12.7 | 3.00 |

HCS04 Internal Software Delay Parameters

| Parameter | Value | Description |
|----------------------------|------------|--|
| Pump Minimum On Timer | 30 seconds | Minimum time a pump must run once started before it will accept a pump auto stop command. A manual stop command will override this interlock and will issue a pump stop command immediately. This feature is used to prevent rapid starting/stopping of the pumps. |
| Pump Minimum Off Timer | 30 seconds | Minimum time a pump must remain off after stopping before it will accept a pump auto start command. A manual start command will override this interlock and will issue a pump start command immediately. This feature is used to prevent rapid starting/stopping of the pumps. |
| Valve Open Timer Delay | 2 seconds | Minimum time required for the open condition of a valve to be true before the auto open command is issued to the valve AOI. |
| Valve Close Timer Delay | 2 seconds | Minimum time required for the close condition of a valve to be true before the auto close command is issued to the valve AOI. |
| Valve Minimum Opened Timer | 10 seconds | Minimum time a valve must remain opened after opening before it will accept a valve auto close command. |
| Valve Minimum Closed Timer | 10 seconds | Minimum time a valve must remain closed after closing before it will accept a valve auto open command. |
| Pump Duty Start Delay Time | 10 seconds | Minimum time required for the starting condition of a pump to be true before the auto start command is issued to the pump AOI. For example, if a five (5) second pump on timer delay is used at a wet well the level in the wet well must be above the duty 1 start level setpoint for five (5) seconds before the auto start command is issued. |
| Pump Stop Delay Time | 10 seconds | Minimum time required for the stopping condition of a pump to be true before the auto stop command is issued to the pump AOI. |
| Non-Concurrent Start Delay | 10 seconds | Delay between the starting of pumps to prevent unnecessary current draw. |

| Parameter | Value | Description |
|--|--------------|--|
| Backup System Remote Interrupt Time | 2 seconds | Timer that remote interrupts are latched on before unlatching. |
| Disable Backup System Remote Interrupt Time | 24 hours | The Backup System Remote Interrupt can be disabled for up to 24 hours before it is re-enabled. |
| Wetwell Level Differential Alarm Debounce Time | 10 seconds | Time delay to ensure a proper Wetwell level differential alarm signal is transmitted. |
| Debounce Timer(s) | 5 seconds | Time delay to ensure a proper low pressure, high pressure, low flow, high flow and heat trace alarm signal is transmitted. |
| Door Contact Vibration Filter | 2 seconds | Timer during which the door contact has to be enabled before registering. |

APPENDIX H – REFERENCE SITE PHOTOS

Site Reference Photos

These photos show the general layout of the station and where the major equipment is located.



HCS04 - Station Exterior Layout




HCS04 - Station Interior Layout No.1



HCS04 - Station Interior Layout No.2



HCS04 - Electrical Equipment Layout



HCS04 - PAC Panel CP001 Interior Layout



HCS04 - PAC Panel CP001 Exterior Layout



HCS04 - PAC Panel CP002 Exterior Layout



HCS04 - PAC Panel CP002 Interior Layout



HCS04 - WAN Panel Layout



HCS04 – Sewage Lift Pump Nameplate

APPENDIX I – FLOOR PLAN

Station Floor Plan

The floor plan shows the general layout of the station and where the major equipment is located.

