# 15.6 MID RISE RESIDENTIAL – LARGE SCALE (R4a) ZONE

**Explanatory Note:** The intent of the R4s Zone is to permit a range of mid rise residential housing types, including multiple dwellings, and multiple dwelling townhouses as part of a comprehensive development, along arterial roads at the periphery of neighbourhoods. Local commercial uses are permitted to serve the residents of mixed use buildings and the surrounding neighbourhoods.

No person shall erect, or use any building in whole or in part, or use any land in whole or in part, within a Mid Rise Residential (R4a) Zone for any purpose other than one or more of the following uses or uses accessory thereto. Such erection or use shall also comply with the prescribed regulations:

## 15.6.1 PERMITTED USES

Artist Studio

Commercial School

Community Garden

Craftsperson Shop

**Child Care Centre** 

Financial Establishment

**Lodging House** 

Medical Clinic

Multiple Dwelling

Multiple Dwelling Townhouse

Office

Personal Service

Place of Worship

Repair Service

Restaurant

Retail

Residential Care Facility

Retirement Home

Social Services Establishment

Tradesperson's Shop

Urban Farm

Veterinary Service

#### 15.6.1.1 RESTRICTED USES

In addition to Section 15.6.1, the following uses shall be permitted in accordance

with the following restrictions:

- i) The following uses shall only be permitted as a Secondary use to a Lodging House, Multiple Dwelling, Residential Care Facility, or Retirement Home and shall only be permitted within the ground floor of a building:
  - i. Art Gallery
  - ii. Commercial School
  - iii. Craftsperson Shop
  - iv. Child Care Centre
  - v. Financial Establishment
  - vi. Medical Clinic
  - vii. Office
  - viii. Personal Service
  - ix. Place of Worship
  - x. Repair Service
  - xi. Restaurant
  - xii. Retail
  - xiii. Studio
  - xiv. Social Services Establishment
  - xv. Tradesperson's Shop
  - xvi. Veterinary Service
- ii) An Office shall be limited to a maximum Gross Floor Area of 500.0 square metres per individual building.
- iii) Multiple Dwelling Townhouse
  - 1) A Multiple Dwelling Townhouse shall only be permitted on a lot which contains a Lodging House, Multiple Dwelling, Residential Care Facility, or Retirement Home which is greater than or equal to 18.0 metres in height, subject to the following regulations:
    - A) The aggregate Gross Floor
      Area of all Multiple Dwelling
      Townhouses shall not
      exceed 40% of the
      aggregate Gross Floor Area
      of all uses on the lot.

2) Section 15.6.1.1 iii) 1) A) shall not apply to a Multiple Dwelling Townhouse existing at the date of passing of the By-law (October 8, 2025), provided there is no increase in the number of Dwelling Units within an existing Multiple Dwelling Townhouse building.

#### 15.6.1.2 PROHIBITED USES

Notwithstanding Section 15.6.1, a Drive-Through Facility shall be prohibited, even as an accessory use.

#### 15.6.2 REGULATIONS

# 15.6.2.1 LODGING HOUSE, MULTIPLE DWELLING, RESIDENTIAL CARE FACILITY, AND RETIREMENT HOME REGULATIONS

a) Minimum Lot Frontage

30.0 metres.

- b) Minimum Setback from a Street Line
- i) 4.5 metres;
- ii) Notwithstanding Section 15.6.2.1 b)
  i), for lots identified on Figure 46 of
  Schedule "F" Special Figures of
  this By-law, the minimum setback
  from a Street Line shall be 3.0
  metres.
- c) Minimum Setback from a Side Lot Line
- i) 4.5 metres;
- ii) Notwithstanding Section 15.6.2.1 c)
  i), for lots identified on Figure 46
  Schedule "F" Special Figures of
  this By-law, the minimum setback
  from a side lot line shall be 3.0
  metres and a minimum aggregate of
  7.5 metres;
- iii) Notwithstanding Section 15.6.2.1 c)
  i) and ii), where windows of a
  Habitable Room face a side lot line:
  - A) 7.5 metres; and,

- B) 10.0 metres for any portion of a building exceeding 14.0 metres in height.
- iv) Notwithstanding Section 15.6.2.1 c)
  i) and ii), where the lot line abuts a
  lot in a Low Density Residential
  (R1), Low Density Residential –
  Small Lot (R1a), or Low Density
  Residential Large Lot (R2) Zone:
  - A) 7.5 metres; and,
  - B) 10.0 metres for any part of the building exceeding 14.0 metres in height.
- d) Minimum Setback from the Rear Lot Line
- i) 10.0 metres;
- ii) Notwithstanding Section 15.6.2.1 d)
  i), when the rear lot line abuts a laneway, the minimum setback from the rear lot line shall be 7.5 metres; and.
- iii) In addition to Section 15.6.2.1 d) i) and ii), the minimum setback from the rear lot line shall be 14.0 metres for any portion of a building exceeding 14.0 metres in height.
- e) Maximum Building Height
- i) 40.0 metres; and,
- ii) In addition to the definition of Building Height in Section 3: Definitions, any wholly enclosed or partially enclosed amenity area, or any portion of a building designed to provide access to a rooftop amenity area shall be permitted to project above the uppermost point of the building, subject to the following regulations:

- A) The total floor area of the wholly enclosed or partially enclosed structure belonging to an amenity area, or portion of a building designed to provide access to a rooftop amenity area shall not exceed 10% of the floor area of the storey directly beneath;
- B) The wholly enclosed or partially enclosed amenity area, or portion of a building designed to provide access to a rooftop amenity area shall be setback a minimum of 3.0 metres from the exterior walls of the storey directly beneath; and,
- C) The wholly enclosed or partially enclosed amenity area, or portion of a building designed to provide access to a rooftop amenity area shall not be greater than 3.0 metres in vertical distance from the uppermost point of the building to the uppermost point of the rooftop enclosure.
- f) Minimum Distance Between Buildings on a Lot
- Between two exterior walls which contain no windows to a Habitable Room: 6.0 metres;
- ii) Between two exterior walls, at least one of which contains windows to a Habitable Room:
  - A) For any portion of the building equal to or less than 14.0 metres in height: 15.0 metres.
  - B) For any portion of the building exceeding 14.0 metres in height: 20.0 metres.

g) Built Form for New Development

In the case of buildings constructed after the effective date of this By-law or additions to buildings existing as of the effective date of this By-law:

- Rooftop mechanical equipment shall be located and/or screened from view of any abutting street.
- ii) No parking or aisles shall be located between the building façade and a Street Line.
- iii) All principal entrances shall face the street and be accessible from the building façade with direct access from the public sidewalk.
- iv) Notwithstanding the definition of Planting Strip, a sidewalk shall be permitted where required by Section iii) above.
- v) A minimum of 50% of the area of the ground floor façade containing a use permitted in Section 15.6.1.1 i) shall be comprised of clear glazed windows and doors. Window and door frames, clear glazed transoms and sidelights, doors with at least 50% clear glazing, and a sill up to 0.6m in height are permitted to be included in the calculation of the clear glazed area. Signage and opaque/spandrel glazing shall not be included in the calculation of the clear glazed area.
- vi) Within the interior side yard, a walkway with a minimum width of 1.5 metres leading to a street shall be required.

h) Minimum Amenity Area for a Multiple Dwelling

On a lot containing more than 10 Dwelling Units, the following minimum Amenity Area requirements shall be provided exclusively for the residential use and shall be functionally separated from public areas associated with any non-residential use:

- 5.0 square metres per Dwelling Unit, subject to the following regulations:
  - A) 3.0 square metres shall be outdoors on or above the ground, at least 50% of which shall be a contiguous area; and,
  - B) 2.0 square metres shall be indoors.

i) Planting Strip

- i) Where a property lot line abuts a property lot line within a Low Density Residential (R1), Low Density Residential Small Lot (R1a), Low Density Residential Large Lot (R2), Neighbourhood Institutional (I1) or Community Institutional (I2) Zone, a minimum 3.0 metre wide Planting Strip shall be provided and maintained, except:
- ii) Notwithstanding Section 15.6.2.1 h)
  i), for lots identified on Figure 46 of
  Schedule "F" Special Figures of
  this By-law, where a property lot line
  abuts a property lot line within a Low
  Density Residential (R1), Low
  Density Residential Small Lot
  (R1a), Low Density Residential –
  Large Lot (R2), Neighbourhood
  Institutional (I1), or a Community
  Institutional (I2) Zone, a minimum
  2.0 metre wide Planting Strip shall
  be provided and maintained.

i) Visual Barriers

A visual barrier shall be required along any lot line abutting a Residential Zone, Institutional Zone, or Downtown (D5) Zone line in accordance with the requirements of Section 4.19 of this By-law.

- k) Minimum Landscaped Area
- i) 30% of the Lot Area:
- ii) Within the Landscaped Area, the requirements of Section 4.35.2 of this By-law shall apply.
- iii) Notwithstanding Section 15.6.2.1 k)
   i), for lots identified on Figure 46 of Schedule "F" Special Figures of this By-law, the minimum
   Landscaped Area shall be 15% of the Lot Area.
- I) Maximum Number of Vehicular Accesses on a Lot
- i) Two access driveways; and,
- ii) In addition to Section 15.6.2.1 I) i), one additional access driveway shall be permitted for every 150.0 metres of cumulative portions of any lot line abutting a street.

m) Waste Storage

Outdoor waste storage shall be fully enclosed and shall not be located in the front yard.

## 15.6.2.2 MULTIPLE DWELLING TOWNHOUSE REGULATIONS

a) Unit Arrangement – Multiple Dwelling Townhouse

Not more than eight (8) Dwelling Units shall be attached in a continuous row.

- b) Minimum Unit Width for each Dwelling Unit
- i) 6.0 metres where the Dwelling Unit contains a garage; and,
- ii) 5.0 metres where the Dwelling Unit does not contain a garage.
- c) Minimum Setback from a Street Line
- i) 4.0 metres;

- ii) Notwithstanding Section 15.6.2.2 c)
  i), for lots identified on Figure 46 of
  Schedule "F" Special Figures of
  this By-law, a building may be
  erected closer to the street line in
  accordance with the following:
  - A) Within 10 percent of the average Street Line setback of the two adjacent dwellings, or in the case of a corner lot, within 10 percent of the setback from the Street Line of the adjacent dwelling sharing a common lot line; and,
  - B) In no case shall the setback from the Street Line be less than 0.5 metres.
- d) Minimum Setback from a Side or Rear Lot Line
- i) Where the lot line abuts a lot in a Low Density Residential (R1), Low Density Residential Small Lot (R1a), Low Density Residential Large Lot (R2), Neighbourhood Institutional (I1), or Community Institutional (I2) Zone:
  - A) For the first 25.0 metres measured from the intersection of the lot line and a street: 1.2 metres if the wall contains no windows to a Habitable Room and 7.5 metres if the wall contains windows to a Habitable Room; and,
  - B) Beyond 25.0 metres measured from the intersection of the lot line and a street: 7.5 metres;
- ii) In all other cases:
  - A) 1.5 metres where the wall contains no windows to a Habitable Room; and,
  - B) 4.5 metres where the wall

contains windows to a Habitable Room.

- e) Minimum Distance Between Buildings on a Lot
- i) Between two exterior walls which contain no windows to a Habitable Room: 3.0 metres;
- ii) Between two exterior walls, at least one of which contains windows to a Habitable Room: 6.0 metres; and,
- iii) Between two exterior walls, both of which contain windows to a Habitable Room: 12.0 metres.
- f) Maximum Building Height
- i) 13.5 metres;
- ii) Notwithstanding Section 15.6.2.2 f)
  i), portions of a building used
  exclusively for providing access to a
  rooftop amenity area and privacy
  screens associated with a rooftop
  amenity area may project above the
  maximum permitted height by 3.0
  metres, provided that any enclosed
  access is located a minimum of 3.0
  metres from the exterior walls of the
  storey directly beneath.
- g) Built Form for New Development

In the case of buildings constructed after the effective date of this By-law:

 Rooftop mechanical equipment shall be located and/or screened from view of any abutting street;

- h) Minimum Landscaped Area
- i) 30% of the Lot Area;
- ii) Notwithstanding Section 15.6.2.2 h)
  i), for lots identified on Figure 46 of
  Schedule "F" Special Figures of
  this By-law, the minimum
  Landscaped Area shall be 15% of
  the Lot Area; and,
- iii) Within the Landscaped Area, the requirements of Section 4.35.2 of this By-law shall apply.
- i) Minimum Amenity Area per Dwelling Unit
- 5.0 square metres per Dwelling Unit, which may be provided in a communal area, exclusive to the Dwelling Unit or a combination of both;
- ii) In addition to the definition of Amenity Area, an Amenity Area satisfying Section 15.6.2.2 i) i) located outdoors shall be unobstructed and shall be located at or above the surface, and exposed to light and air and may include balconies and patios; and,
- iii) In addition to Section 15.6.2.2 i) i),
  4.0 square metres per Dwelling Unit
  which is located above another
  Dwelling Unit or has a rear wall
  attached to the rear wall of another
  Dwelling Unit must be provided in
  one or more communal areas each
  having a minimum area of 20.0
  square metres and which is located
  entirely outdoors and on the surface
  of the ground.
- j) Location of Parking

No parking spaces shall be located between a Façade and the Front Lot Line or between the Façade and a Flankage Lot Line, except that parking shall be permitted on individual driveways leading to garages forming part of a Dwelling Unit.

- k) Maximum number of Vehicular Accesses on a Lot
- i) Two access driveways; and,
- ii) In addition to Section 15.6.2.2 k) i), one additional access driveway shall be permitted for every 150.0 metres of cumulative portions of any lot line abutting a street.
- Pedestrian Accesses

Any Dwelling Unit adjacent to a yard abutting a street must have a minimum of one pedestrian entrance which is located in a Façade.

m) Maximum Height of a Principal Pedestrian Entrance The height of the floor level of any principal pedestrian entrance shall be a maximum of 1.2 metres above Grade.

n) Waste Storage

Outdoor waste storage shall be fully enclosed and shall not be located in the front yard.

- 15.6.3 SINGLE DETACHED, SEMI-DETACHED, DUPLEX, TRIPLEX, FOURPLEX AND STREET TOWNHOUSE DWELLINGS EXISTING AT THE DATE OF THE PASSING OF THE BY-LAW (October 8, 2025)
- i) In addition to Section 4.12 j) and in accordance with Section 34(10) of the Planning Act, R.S.O., 1990, c.P.13, an addition or alteration to a Single Detached, Semi-Detached, Duplex, Triplex, Fourplex and Street Townhouse Dwelling, not permitted by the By-Law but legally existing at the date of the passing of the By-Law, that increases the volume or size of the building shall be permitted as follows:

Nothing in this section shall prevent the enlargement, extension, or alteration of an existing building or structure, provided that:

The increase shall not exceed a maximum of 10% of the Gross Floor Area of the building existing at the date of passing of the By-law; and,

The existing side yard and front yard setbacks are maintained for the addition.

# **SECTION 15: RESIDENTIAL ZONES**

# 15.6.4 REGULATIONS FOR COMMUNITY GARDENS AND URBAN FARMS AS ACCESSORY USES

a) Urban Farms

- i) In accordance with the requirements of Subsection 4.26 (c) of this Bylaw.
- ii) In addition to i) above, an Urban Farm shall only be permitted in the Rear Yard or on the roof-top of the principal building.
- b) Community Gardens
- i) In accordance with the requirements of Section 4.27 of this By-law.
- ii) In addition to i) above, a Community Garden shall only be permitted in the Rear Yard or on the roof-top of the principal building.

(NOT FINAL & BINDING: By-law No. 25-189, October 08, 2025)